

11/03/2019

CU-11280731-7368

TO: KEYSTONE RV COMPANY

P.O. Box 2000

Goshen, IN 46527-2000

INFORMATION REDACTED PURSUANT TO THE FREEDOM
OF INFORMATION ACT (FOIA), 5 U.S.C. 552(B)(6)

From: [REDACTED]
[REDACTED]
[REDACTED]

Garden City, Idaho [REDACTED]

To whom it may concern, back in January 15th, of 2018 I received this notice for recall of my RV's Fire Extinguishers. I have not had the time to respond but am doing so now.

I am sending photographs of the two fire extinguishers that I have in my 2017 Keystone Outback RV 324-CG. Also included is a copy of my RV name plate.

The VIN : 4YDT32423HB [REDACTED]

The serial Number of the fire extinguishers are as follows:

(1.) B71098690

(2.) B13254617

If, these two fire extinguishers are on your Safety Recall list, please send me two new ones, to the following address.

[REDACTED]
[REDACTED]
Garden City, Idaho [REDACTED]
[REDACTED]

11/03/2019

EA
11.14.19
UD

12



**Keystone RV
Company**

Recreational Vehicle Safety Recall Notice

Safety Recall: 17V-755

Safety Advisory: 17-307

January 15, 2018

IMPORTANT SAFETY RECALL

This notice applies to your vehicle: 4YDT32423HB

GARDEN CITY, ID

Dear

This notice is sent to you in accordance with the requirements of the National Traffic and Motor Vehicle Safety Act. Following a November 2017 recall announced by Kidde, Keystone RV Company has decided that a defect which relates to motor vehicle safety exists in certain 2003 - 2018 Keystone, Dutchmen, and Crossroads recreational vehicles. As a result, Keystone is conducting a safety recall. We apologize for any inconvenience this action may cause you; however your safety and continued satisfaction are of the utmost importance to us.

REASON FOR THIS RECALL

The vehicles subject to this recall may have an affected Kidde portable fire extinguisher installed in them. Kidde has determined that certain fire extinguishers can become clogged or require excessive force to activate, posing a risk of failure to discharge. In addition, the nozzle can detach with enough force to pose an impact hazard. In the event that the fire extinguisher does not operate properly, injury or fatality may result.

Two models of Kidde fire extinguishers are impacted by this recall:

1. Fire Extinguishers with Plastic Handles:



2. Indicator/Push Button Fire Extinguishers:



If the fire extinguisher experiences one of the conditions described above, it may not function properly, creating an increased risk of injury in the event of a fire.

INSPECTION:

INSPECT THE EXTINGUISHER MONTHLY, OR AT MORE FREQUENT INTERVALS. EXAMINE NOZZLE FOR OBSTRUCTION. CHECK THAT TAMPER SEAL IS INTACT. **CHECK PRESSURE BY PRESSING IN GREEN INDICATOR BUTTON. IF BUTTON DOES NOT SPRING BACK, EXTINGUISHER IS INOPERABLE, DISCARD AND REPLACE.**

MAINTENANCE:

INSTALL, MAINTAIN AND TEST IN ACCORDANCE WITH NFPA NO. 10 OR THE NATIONAL FIRE CODE OF CANADA. INSPECT THE EXTINGUISHER MONTHLY, OR AT MORE FREQUENT INTERVALS. EXAMINE NOZZLE FOR OBSTRUCTIONS. CHECK THAT TAMPER SEAL IS INTACT. FILLED WITH PLUS-FIFTY® C SODIUM BICARBONATE DRY CHEMICAL POWDER. HMIS 1-0-0. TALC, MAGNESIUM ALUMINUM SILICATE. NUISANCE DUST. IRRITANT.

RECORD INSTRUCTIONS:

RECORD INSPECTION AND MAINTENANCE DATES ON ATTACHED TAG.

CAUTION: THIS EXTINGUISHER IS NONREFILLABLE. AFTER USE DISCHARGE COMPLETELY AND DISCARD. ANY USE REQUIRES DISCARDING. IMMEDIATELY AFTER USE CLEAN ALL SURFACES CONTACTED BY DRY CHEMICAL AGENT.

WARNING: IMPROPER USE OF THIS EXTINGUISHER COULD CAUSE SERIOUS BODILY INJURY OR PROPERTY DAMAGE. DO NOT DISCHARGE AT A PERSON'S FACE.

CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE. DO NOT EXPOSE TO TEMPERATURES OVER 49C (120F). TESTED TO 2,070 kPa (300 psi).
GROSS WEIGHT 2lb. 7.75 oz. $\pm$ 1.793 oz. (1.127 kg. $\pm$ 0.051 kg.) ACCEPTABLE
Agent Weight 1.38 lb. + 1oz. (0.625 kg. + 0.028 kg.)
FOR USE AT TEMPERATURES FOR -40C (-40F) TO 49C (120F)
MODEL KFE2S5



LISTED

Dry Chemical Fire Extinguisher
Extincteur A Feu A Poudre Chimique
Rated 5-B:C
Tested to ANSI / UL 711, ANSI / UL 299
and CAN4-S508, CAN4-S504



LISTED

NO.

B71098690



MANUFACTURED BY/FABRIQUÉ PAR: Keystone RV Company DATE: 4/21/2016
2642 Hackberry Drive
Goshen, IN 46526

GVWR/PNBV 4763 KG (10500 LB)

GAWR (EACH AXLE)/PNBE(CHAQUE ESSIEU) 2304 KG (5080 LB)

TIRE/PNEU ST225/75R15D RIMS/JANTE 15x6

COLD INFL. PRESS/PRESS. DE GONFL. À FROID 448 KPA (65 PSI/LPC)-SINGLE

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE. THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. - CE VEHICULE EST CONFORME À TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU RÈGLEMENT SUR LA SÉCURITÉ DES VÉHICULES AUTOMOBILES DU CANADA EN VIGUEUR À LA DATE DE SA FABRICATION.

V.I.N./N.I.V.: 4YDT32423HB [REDACTED] TYPE/TYPE: TRAILER TRA/REM: OB324CG17

CARGO-CARRYING CAPACITY: 1002 KG
CALCULATED WITH THE FRESH WATER
TANKS FULL (COLD 178 KG.
HOT 23 KG.)

AND THE WASTE WATER TANKS EMPTY

MASS OF WASTE WATER
TANKS FULL 431 KG

CAPACITÉ DE CHARGEMENT: 1002 KG
CALCULÉE AVEC LES RÉSERVOIRS D'EAU
DOUCE PLEINS (FROID 178 KG.
CHAUD 23 KG.)

ET LES RÉSERVOIRS D'EAUX USÉES VIDES

MASSE DES RÉSERVOIRS D'EAUX
USÉES PLEINS: 431 KG.



TIRE AND LOADING INFORMATION RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should never exceed 1152 KG
or 2540 LBS. Le poids de chargement ne devrait
jamais excéder 1152 KG ou 2540 LBS.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS À FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
FRONT AVANT	ST225/75R15D	448 KPA /65 PSI	
REAR ARRIÈRE	ST225/75R15D	448 KPA /65 PSI	
SPARE DE SECOURS	ST225/75R15D	448 KPA /65 PSI	

This vehicle contains composite wood products
that comply with the applicable California Code of
Regulations Section 93120.2(a) Phase 2 (P2)
formaldehyde emission standards specified on the
date of manufacture.

Garden City, ID

SALT LAKE CITY UT 840

04 NOV 2019 PM 3 L



ADMINISTRATOR
NATIONAL HIGHWAY Traffic Safety Administration
1200 New Jersey Avenue
SE, Washington, DC 20590

20590-

