



U.S. Department
of Transportation
National Highway
Traffic Safety
Administration

Auto Safety Hotline

Vehicle Owner's Questionnaire

NATIONWIDE 1-800-424-9393
DC METRO AREA (202) 366-0123

FOR AGENCY USE ONLY

Date Received

DEFECTS DIVISION

560039

Day Time Telephone Number

OWNER INFORMATION (Type or Print)

Name
Street
City

Do you authorize NHTSA to provide a copy of this report to the manufacturer of your vehicle? ☒ YES ☐ NO
In the absence of an authorization, NHTSA WILL NOT provide your name and address to the vehicle manufacturer.

Signature of Owner _____ Date 1/30/01

VEHICLE INFORMATION

Vehicle Ident. No. (VIN) (Located at bottom of windshield on driver's side) 1GCHK39R0W1057481 Vehicle Make Chevrolet Vehicle Model G3500 Vehicle Year 1998 Current Odometer Reading 36300

Purchase Date
3-25-98

Dealer's Name Murray ChevroletCity Gresham State OR Zip Code 97000

Engine Size (CID/CC/L) 5.7L ☐ Turbo ☒ Diesel
No. Cylinders 8 ☐ Gas ☒ Fuel Injection

Transmission Type

☐ Manual
☒ Automatic

Antilock Brakes

☒ Yes
☐ No

Restraint System

☒ Driverside Airbag ☐ Motorbelt
☐ Passengerside Airbag ☐ 2-Point Belt
☒ 3-Point Belt

Cruise Control

☒ Yes
☐ No

Drivetrain

☐ Front
☒ Rear
☐ 4-Wheel

Body Style

☐ Hatch Back
☒ Van
☐ Pick Up Truck
☐ Other

FAILED COMPONENT(S)/PART(S) INFORMATION

Component

Tire

Part Name(s)

Firestone

Location

☐ Left ☐ Right
☐ Front ☐ Rear

Failed Part(s)

☒ Original
☐ Replacement

No of Failures

1Date(s) of Failure(s) Jan. 8, 2001Mileage at Failure(s) 36300Vehicle Speed at Failure(s) discovered during rebalance

Manufacturer Contacted?

☐ Yes ☒ No

NHTSA Previously Contacted?

☒ Yes ☐ No

APPLICABLE ACCIDENT INFORMATION

(Use reverse side for more detailed information)

Accident

☐ Yes ☒ No

Fire

☐ Yes ☒ No

Number Persons Injured

0

Number of Fatalities

0

Estimated Property Damage

\$ 0

Reported to Police

☐ Yes ☒ No

INFORMATION ON TIRE FAILURE(S) (IF APPLICABLE)

To report defective or failed tires provide the following: DOT Number, Tire Manufacturer, Tire Name, Tire Size (Include all numbers and letters).
Note: This information not required for normal operation tires.

DOT

Manufacturer

Firestone

Tire Name

R4S

Size

245/5R16E

TIRE SIZE

TIRE NAME



TIRE MANUFACTURER

U.S. DOT safety standard code

The number may be on the inner side of the tire and have up to 11 letters and numbers. Usually located near rim flange on side opposite whitewall or on either side of blackwall tire.

The Privacy Act of 1974—Public Law 93-579 This information is requested pursuant to authority vested in the National Highway Traffic Safety Act and subsequent amendments. You are under no obligation to respond to this questionnaire. Your response may be used to assist the NHTSA in determining whether a manufacturer should take appropriate action to correct a safety defect. If the NHTSA proceeds with administrative enforcement or litigation against a manufacturer, your response, or a statistical summary thereof, may be used in support of the agency's action.

Narrative Description of Failure(s), Accident(s), and Injury(ies)

Observed tread separation blister on the tread area
as tire was being spun on balancing machine.

Fold to show Return Address (no stamp needed) Fasten with tape or staple and mail

U.S. Department
of Transportation
**National Highway
Traffic Safety
Administration**

400 Seventh St., S.W.
Washington, D.C. 20590

Official Business
Penalty for Private Use \$300

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 73173 WASHINGTON, D.C.

POSTAGE WILL BE PAID BY NATL. HWY. TRAFFIC SAFETY ADMIN.

U.S. Department of Transportation
National Highway Traffic Safety Administration
Auto Safety Hotline, NEF-11 HL
400 7th Street, SW.
Washington, DC 20590



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES



**NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES**