

VEHICLE OWNER'S QUESTIONNAIRE

FOR AGENCY USE ONLY

DATE RECEIVED _____

od.or _____
 rt.dt _____
 od.rt _____
 up.ltr _____

OWNER INFORMATION (TYPE OR PRINT)

NAME & ADDRESS



609118

REFERENCE NO.

DAY TIME TELEPHONE NO. (AREA CODE) _____

Do you authorize NHTSA to provide a copy of this report to the manufacturer of your vehicle? YES NO

In the absence of an authorized representative, please provide the name or address to the vehicle manufacturer.

SIGNATURE OF OWNER _____ DATE 1.11.99

VEHICLE INFORMATION

VEHICLE IDENTIFICATION NO. JT8BH28F2WD111257 VEHICLE MAKE LEXUS VEHICLE MODEL LS 400 MODEL YEAR 1998

* LOCATED AT BOTTOM OF WINDSHIELD ON DRIVER'S SIDE

CURRENT ODOMETER READING _____ DATE PURCHASED _____ DEALER'S NAME, CITY, & STATE _____ ENGINE SIZE (CID/CC/L) _____ TURBO DIESEL GAS FUEL INJECTION

NEW USED NO. CYLINDERS _____

TRANSMISSION TYPE MANUAL AUTOMATIC

ANTILOCK BRAKES YES NO

RESTRAINT SYSTEM DRIVER SIDE AIRBAG MOTOR BELT PASSENGER SIDE AIRBAG 3-POINT BELT 2-POINT BELT

CRUISE CONTROL YES NO

DRIVETRAIN FRONT REAR 4-WHEEL

BODY STYLE STAWAG HATCH BK 2 DOOR VAN 4 DOOR PK UP TRK OTHER

FAILED COMPONENT(S)/PART(S) INFORMATION

COMPONENT	PART NAME(S)	LOCATION	FAILED PART(S)
		<input type="checkbox"/> LEFT <input type="checkbox"/> RIGHT <input type="checkbox"/> FRONT <input type="checkbox"/> REAR	<input type="checkbox"/> ORIGINAL <input type="checkbox"/> REPLACEMENT
NO. OF FAILURES	DATE(S) OF FAILURE(S) _____ MILEAGE AT FAILURE(S) _____ VEHICLE SPEED AT FAILURE(S) _____	MANUFACTURER CONTACTED POSTED <input type="checkbox"/> YES <input type="checkbox"/> NO	NHTSA PREVIOUSLY CONTACTED <input type="checkbox"/> YES <input type="checkbox"/> NO

APPLICABLE ACCIDENT INFORMATION

ACCIDENT YES NO FIRE Yes No

NUMBER OF PERSONS INJURED 2 NUMBER OF FATALITIES _____ PROPERTY DAMAGE EST \$ _____ POLICE REPORT FILED YES NO

FAILED TIRE INFORMATION ONLY

TIRE IDENTIFICATION NO.* _____ MANUFACTURER TIRE NAME _____ SIZE _____

DOT _____

* The identification number consists of 7 to 10 letters and numerals following the letters DOT. It is usually located near the rim flange on the side opposite the whitewall or on either side of a blackwall tire.

NARRATIVE DESCRIPTION OF FAILURE(S), ACCIDENT(S), INJURY(IES) ON THE BACK

The Privacy Act of 1974 Public Law 93-579

This information is requested pursuant to authority vested in the National Highway Traffic Safety Act and subsequent amendments. You are under no obligation to respond to this questionnaire. Your response may be used to assist the NHTSA in determining whether a manufacturer should take appropriate action to correct a safety defect. If the NHTSA proceeds with administrative enforcement or litigation against a manufacturer, your response, or a statistical summary thereof, may be used in support of the agency's action.

NUMBER

609118

CHANGED

TO

6901208