



U.S. Department
of Transportation
**National Highway
Traffic Safety
Administration**

Auto Safety Hotline

Vehicle Owner's Questionnaire

NATIONWIDE 1-800-424-9393
DC METRO AREA (202) 366-0123
INTERNET: <http://www.nhtsa.dot.gov>

FOR AGENCY USE ONLY 258

Date Received

03-FEB-2002

Od_or _____
rt_dt _____
od_rt _____
ip_lr _____

Reference No.

757693

Do you authorize NHTSA to provide a copy of report to the manufacturer of your vehicle? ☐ YES ☐ NO
In the absence of an authorization, NHTSA WILL NOT provide your name and address to the vehicle manufacturer.

Signature of Owner _____ Date ____/____/____

VEHICLE INFORMATION

Vehicle Ident. No. (VIN) (Locate at bottom of windshield or driver's side door)	Vehicle Make	Vehicle Model	Vehicle Year	Current Odometer Reading
4C3AU52N2YE021559	CHRYSLER	SEBRING	2000	

Purchase Date 01-APR-2001	Dealer's Name _____	Engine Size (CID/CC/L) _____	☐ Turbo ☐ Diesel ☐ Gas ☒ Fuel Injection
☐ New ☒ Used	City _____ State _____ Zip Code _____	No Cylinders _____	

Transmission Type ☐ Manual ☐ Automatic	Antilock Brakes ☒ Yes ☐ No	Restraint System ☐ 3-Point Belt ☐ Driverside Airbag ☐ Passengerside Airbag ☐ Motorbelt ☐ 2-Point Bel	Cruise Control ☒ Yes ☐ No	Drive Train ☒ Front ☐ Rear ☐ 4-Wheel	Vehicle Type ☐ Car ☐ Van ☐ Minivan ☐ Other _____ ☐ Sport Utl ☐ Truck ☐ Motorcycle	Body Style ☒ 2-Door ☐ 4-Door ☐ Stationwagon ☐ Pick Up Truck ☐ Other _____
--	---	--	--	---	---	--

FAILED COMPONENT(S)/PART(S) INFORMATION

Component 02700000	Part Name(s) TIRES	Location ☐ Left ☐ Right ☐ Front ☐ Rear	Failed Part(s) ☐ Original ☐ Replacement
No of Failure 3	Date(s) of Failure(s) 01-DEC-2001 Mileage at Failure(s) 10989 Vehicle Speed at Failure(s) 0	Failed Part(s) ☐ Yes ☐ No	NHTSA Previously ☐ Yes ☐ No

APPLICATION INCIDENT INFORMATION

(Please describe in detail the incident(s), Failure(s), Crash(es), and injury(ies) on the back of this form)

Crash ☐ Yes ☐ No	Fire ☐ Yes ☒ No	Number of Persons Injured	Number of Fatalities	Estimated Property Damag	Reported to Police ☐ Yes ☒ No
---	---	---------------------------	----------------------	--------------------------	---

NARRATIVE DESCRIPTION OF FAILURE(S), INCIDENT(S), INJURY(IES)

BOTH FRONT TIRES HAVE GONE COMPLETELY FLAT. TIRE DEALER STATED THAT THIS IS DUE TO ALLOY RIMS CONTRACTING WITH THE LOW PROFILE TIRES. ONE WAS A NEWLY REPLACED TIRE, THE OTHER TIRE HAD 11,00 MILES ON IT. THE RIGHT WHEEL IS SLIGHTLY BENT, AND I AM TOLD THAT THIS CANNOT BE REPAIRED AND THIS COULD CAUSE AN INCOMPLETE SEAL AROUND THE BEAD/RIM. I AM CURRENTLY CHECKING TIRE PRESSURE EVERY TWO WEEKS, AND MOST RECENTLY HAD PRESSURE AS LOW AS 10 PSI ON REAR RIGHT, AND 15-25 ON ALL OTHERS. TIRE DEALER STATED THIS PROBLEM IS DUE TO COMBINATION OF ALUMINUM RIMS AND LOW PROFILE TIRES. THIS APPEARS TO BE QUITE AN UNSAFE COMBINATION IF HE IS CORRECT. I CANNOT BELIEVE THAT I NEED TO REINFLATE MY TIRES EVERY THREE

COPIES OF THIS FORM ARE:

The Privacy Act of 1974-Public Law 93-579 This information is requested pursuant to authority vested in the National Highway Traffic Safety Act and subsequent amendments. You are under no obligation to respond to this questionnaire. Your response may be used to assist the NHTSA in determining whether a manufacturer should take appropriate action to correct a safety defect. If the NHTSA proceeds with administrative enforcement or litigation against a manufacturer, your response, or a statistical summary thereof, may be used in support of the agency's action.



U.S. Department
of Transportation
**National Highway
Traffic Safety
Administration**

Auto Safety Hotline

Vehicle Owner's Questionnaire

NATIONWIDE 1-800-424-9393
DC METRO AREA (202) 366-0123
INTERNET: <http://www.nhtsa.dot.gov>

FOR AGENCY USE ONLY 258

Date Received

03-FEB-2002

Od_or _____
rt_dt _____
od_rt _____
ip_lr _____

Reference No.

757693

Do you authorize NHTSA to provide a copy of report to the manufacturer of your vehicle? ☐ YES ☐ NO
In the absence of an authorization, NHTSA WILL NOT provide your name and address to the vehicle manufacturer.

Signature of Owner _____ Date ____/____/____

VEHICLE INFORMATION

Vehicle Ident. No. (VIN) (Locate at bottom of windshield or driver's side door)	Vehicle Make	Vehicle Model	Vehicle Year	Current Odometer Reading
4C3AU52N2YE021559	FIRESTONE	FIRESTONE	1900	

Purchase Date 01-APR-2001	Dealer's Name _____	Engine Size (CID/CC/L) _____	☐ Turbo ☐ Diesel ☐ Gas ☒ Fuel Injection
☐ New ☒ Used	City _____ State _____ Zip Code _____	No Cylinders _____	

Transmission Type ☐ Manual ☐ Automatic	Antilock Brakes ☒ Yes ☐ No	Restraint System ☐ 3-Point Belt ☐ Motorbelt ☐ Driverside Airbag ☐ 2-Point Bel ☐ Passengerside Airbag	Cruise Control ☒ Yes ☐ No	Drive Train ☒ Front ☐ Rear ☐ 4-Wheel	Vehicle Type ☐ Car ☐ Sport Util ☐ Van ☐ Truck ☐ Minivan ☐ Motorcycle ☐ Other _____	Body Style ☒ 2-Door ☐ 4-Door ☐ Stationwagon ☐ Pick Up Truck ☐ Other _____
--	---	--	--	---	---	--

FAILED COMPONENT(S)/PART(S) INFORMATION

Component 02700000	Part Name(s) TIRES	Location ☐ Left ☐ Right ☐ Front ☐ Rear	Failed Part(s) ☐ Original ☐ Replacement
No of Failure 3	Date(s) of Failure(s) _____ Mileage at Failure(s) _____ Vehicle Speed at Failure(s) _____	Failed Part(s) ☐ Yes ☐ No	NHTSA Previously ☐ Yes ☐ No

APPLICATION INCIDENT INFORMATION

(Please describe in detail the incident(s), Failure(s), Crash(es), and injury(ies) on the back of this form)

Crash ☐ Yes ☐ No	Fire ☐ Yes ☒ No	Number of Persons Injured	Number of Fatalities	Estimated Property Damag	Reported to Police ☐ Yes ☒ No
---	---	---------------------------	----------------------	--------------------------	---

NARRATIVE DESCRIPTION OF FAILURE(S), INCIDENT(S), INJURY(IES)

BOTH FRONT TIRES HAVE GONE COMPLETELY FLAT. TIRE DEALER STATED THAT THIS IS DUE TO ALLOY RIMS CONTRACTING WITH THE LOW PROFILE TIRES. ONE WAS A NEWLY REPLACED TIRE, THE OTHER TIRE HAD 11,00 MILES ON IT. THE RIGHT WHEEL IS SLIGHTLY BENT, AND I AM TOLD THAT THIS CANNOT BE REPAIRED AND THIS COULD CAUSE AN INCOMPLETE SEAL AROUND THE BEAD/RIM. I AM CURRENTLY CHECKING TIRE PRESSURE EVERY TWO WEEKS, AND MOST RECENTLY HAD PRESSURE AS LOW AS 10 PSI ON REAR RIGHT, AND 15-25 ON ALL OTHERS. TIRE DEALER STATED THIS PROBLEM IS DUE TO COMBINATION OF ALUMINUM RIMS AND LOW PROFILE TIRES. THIS APPEARS TO BE QUITE AN UNSAFE COMBINATION IF HE IS CORRECT. I CANNOT BELIEVE THAT I NEED TO REINFLATE MY TIRES EVERY THREE

CONTINUE ON REVERSE

The Privacy Act of 1974-Public Law 93-579 This information is requested pursuant to authority vested in the National Highway Traffic Safety Act and subsequent amendments. You are under no obligation to respond to this questionnaire. Your response may be used to assist the NHTSA in determining whether a manufacturer should take appropriate action to correct a safety defect. If the NHTSA proceeds with administrative enforcement or litigation against a manufacturer, your response, or a statistical summary thereof, may be used in support of the agency's action.