

CERTAIN 2005 AND 2006 MODEL YEAR FREESTAR AND MONTEREY VEHICLES EQUIPPED WITH POWER LIFTGATE — POWER LIFTGATE MODULE REPROGRAMMING

REPROGRAMMING THE POWER LIFTGATE MODULE

1. Verify that the scan tool (WDS or VCM) is updated to software **version B42.1 P1 or later**.
- NEW** 2. Reprogram the power liftgate (PLG) module (also called the liftgate/trunk [LTM] module) to the latest software version using one of the following methods:
 - a) Worldwide Diagnostic System (WDS).
 - b) Vehicle Communication Module (VCM) and Integrated Diagnostic System (IDS) software with appropriate hardware.
 - If unable to reprogram the PLG module:
 - prior to disconnecting the scan tool and closing the session, call the Special Service Support Center at 1-800-325-5621 for further instructions.
3. Power open the liftgate by using either the key fob or the overhead console switch.
 - If the liftgate remains open, power close the liftgate using either the key fob or overhead console switch. Service is complete. Release the vehicle.
 - Once open, if the liftgate freely falls or goes into “power close” mode (**accompanied by an audible alert that sounds four [4] times per second**) without activating either the key fob or overhead switch, contact the Special Service Support Center at 1-800-325-5621 for further instruction.

