











TEST VEHICLES ONLY

NO PARKING ANY TIME

ELECTRIC VEHICLE ONLY

MFD. BY FORD MOTOR CO.

DATE: 04/04

FRONT GAWR: 1353KG/2985LB

GVWR: 2639KG /5820LB

REAR GAWR: 1292KG /2850LB

THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY AND THEFT PREVENTION STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 2MRDA20274[REDACTED] TYPE: MPV

MAXIMUM LOAD = OCCUPANTS + LUGGAGE = 544KG/1200LB
OCCUPANTS = 7 TOTAL; 2 FRONT, 2 2ND, 3 REAR

TIRE (FR): P235/60R16

(RR): P235/60R16

RIMS (FR): 16X7.0J

(RR): 16X7.0J

PRESSURE (FR): 240 kPa/35 PSI COLD

(RR): 240 kPa/35 PSI COLD



2MRDA20274[REDACTED]

TRAILER TOWING - SEE OWNER GUIDE

EXT PNT: C2

RC: 45

DSO:

F0053

T0127

INT TR

TP/PS

R

AXLE

TR

SPR

L7

V

24

N

BH

CBU

2U5A-5420472-AA

LATERAL POSE
LESIONES.

1USA-1425











NO PARKING ANY TIME

Customer Clinic
ENTER
←













DATE: 01/06

FRONT GAWR: 1350KG/2977LB

GAWR: 2050KG/4525LB
REAR GAWR: 1315KG/2900LB

THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR
VEHICLE SAFETY AND THEFT PREVENTION STANDARDS
IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 2FMZA522X6B [REDACTED] TYPE: MPV

MAXIMUM LOAD = OCCUPANTS + LUGGAGE = 544KG/1200LB
OCCUPANTS = 7 TOTAL; 2 FRONT, 5 REAR

TIRE (FR): P235/55R17
(RR): P235/55R17

RIMS (FR): 17x7.0J
(RR): 17x7.0J

PRESSURE (FR): 240 kPa/ 35 PSI COLD (RR): 240 kPa/ 35 PSI COLD



2FMZA522X6B [REDACTED]

TRAILER TOWING - SEE OWNER GUIDE

EXT PNT: FS

RC: 48 | DSO:

INT TR

TP/PS

R

AXLE

TR

SPR

6A41V

F0085

R0129

M7

S

24

N

AAHH

AOA

CBU

5U5A-5420472-AA













