

DP14-004

CHRYSLER

9/15/2014

Legals and Cust Complaints

PUBLIC

PROD BY CHRYSLER GROUP LLC

DATE OF MFG: 4-11

GRAB FRONT:

GRAB REAR:

	WEIGHT	HGT	WT	HT	TRES
GRAB FRONT:	1339 KG	2890 LB	235/69R15	230 MM (9 1/8")	230
GRAB REAR:	1407 KG	3100 LB	235/69R15	230 MM (9 1/8")	230
	1506.5		235/69R15	230 MM (9 1/8")	230
			235/69R15	230 MM (9 1/8")	230

THIS VEHICLE COMPLIES IN ALL APPROPRIATE U.S.A. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE.

VIN: 2C4AC5L56K[REDACTED]

VEHICLE MADE IN CANADA



DATE OF MFG: 4-11
GRAB FRONT: 1339 KG 2890 LB
GRAB REAR: 1407 KG 3100 LB
WEIGHT: 1506.5
HT: 235/69R15
WT: 230 MM (9 1/8")
TRES: 230

PROD BY CHRYSLER GROUP LLC

DATE OF MFR: 4-11

GRAND FRONT: 1339 KG 2950 LB WITH RIMS AT

GRAND REAR: 1407 KG 3100 LB WITH RIMS AT

GRAND FRONT: 1876.5 KG 4140 LB WITH RIMS AT

GRAND REAR: 1576.5 KG 3470 LB WITH RIMS AT

GRAND:

2745 KG 6050 LB

235/60R16

250 MPH (36 PSI) COLD

235/60R16

250 MPH (36 PSI) COLD

TIRES

TIRES

TIRES

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.A. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 2D4R5U058B [REDACTED]

VEHICLE MADE IN CANADA

TYPE:

PAINT: 952

MPV

1971-1971

MSR:042700 12764

DATE: 03/20/2011
TIME: 10:00 AM
LOCATION: [REDACTED]
OPERATOR: [REDACTED]
VEHICLE: [REDACTED]

PROD BY CHRYSLER GROUP LLC

DATE OF MFR: 4-11

DRY WEIGHT	1339 KG	2950 LB	WITH	2745 KG	6053 LB
WET WEIGHT	1407 KG	3125 LB	WITH	250 KPA (36 PSI)	TIRES
	16X6.5		RIMS AT	235/60R16	
			RIMS AT	250 KPA (36 PSI)	COLD

DRY WEIGHT	1339 KG	2950 LB	WITH	2745 KG	6053 LB
WET WEIGHT	1407 KG	3125 LB	WITH	250 KPA (36 PSI)	TIRES
	16X6.5		RIMS AT	235/60R16	
			RIMS AT	250 KPA (36 PSI)	COLD

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.A. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 2D4RSD059E [REDACTED] TYPE: MPV

VEHICLE MADE IN CHINA PAINT: 952 TRIM: HVAL

DOB: 042700 127AA



ALL SPS (M) 18101-0411
 MADE IN AMSTERDAM, NETHERLANDS
 CHRYSLER GROUP LLC
 18101-0411

PFD BY CHRYSLER GROUP LLC

DATE OF MFR: 4-11

1333 KG	2950 LB	WITH	RIMS AT
18X6.5	31	B	WITH
1407 KG	31	B	RIMS AT
18X6.5			

GRADE:

2745 KG	6050 LB		
235/60R16			
250 KPA (36 PSI)	COLD	TIRES	
235/60R16			
250 KPA (36 PSI)	COLD		

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.A. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 2D4RNSD35B8 [REDACTED]

TYPE: MPV

VEHICLE MADE IN CANADA PAINT: 952 TRIM: HVAL



PLANT: BSA
 MODEL: 1407
 GRADE: 18X6.5
 TRIM: HVAL
 VIN: 2D4RNSD35B8 [REDACTED]

MFD BY CHRYSLER GROUP LLC
 DATE OF MFR: 4-11
 GAWR FRONT: 1339 KG 2955 LB WITH 235/69R15 TIRRES
 1506.5
 250 09K (35 910) CALJ
 GAWR REAR: 1407 KG 3100 LB WITH 235/69R15 TIRRES
 1506.5
 250 09K (35 910) CALJ
 THIS SPECIAL CHARGES TO ALL APPROPRIATE U.S. FEDERAL, STATE AND LOCAL AGENCIES
 STRONGER IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE
 VIN: 2G4NSC355[REDACTED] P9V 08H14C2704 12704
 RETIRED MADE IN CHINA

1804 2
 1404 10 2100 19 010
 1506.5
 235/69R15
 250 09K (35 910) CALJ

08H14C2704 12704
 2G4NSC355[REDACTED] P9V
 08H14C2704 12704

OTHER KEYS: 10X8"2 0112 W1 S20 10V 1 3E
 1403 KG 3160 TB 411W S20V80R16
 10X8"2 0112 W1 S20 10V 1 3E
 1403 KG 3160 TB 411W S20V80R16
 OTHER KEYS: 10X8"2 0112 W1 S20 10V 1 3E
 1403 KG 3160 TB 411W S20V80R16

FED BY CHRYSLER GROUP LLC

DATE OF MFR: 4-11 GWR: 2745 KG 6050 LB
 CURR FRONT: 1339 KG 2900 LB WITH 235/60R16 TIRES
 16X6.5 16X6.5 250 KPA (36 PSI) COLD
 CURR REAR: 1407 KG 3100 LB WITH 235/60R16 TIRES
 16X6.5 16X6.5 250 KPA (36 PSI) COLD



THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.A. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 2D4RNSU65B [REDACTED] TYPE: MPV
 VEHICLE MADE IN CANADA PAINT: P52 TRIM: H7X1
 H0H:042700 12744

MFD BY CHRYSLER GROUP LLC

DATE OF MFR: 4-11

GAIR FRONT:

1339 KG 2900 LB WITH

18X6.5 RIMS AT

GAIR REAR:

1407 KG 3100 LB WITH

18X6.5 RIMS AT

GAIR:

2745 KG 6050 LB

235/60R16 TIRES

250 KPA (36 PSI) COLD

235/60R16 TIRES

250 KPA (36 PSI) COLD



THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.A. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.
VIN: 2D4RNSD658B [REDACTED]
VEHICLE MADE IN CANADA
PRINT: P92
TYPE: MPV
TRIM: H7X1
MDH: 042700 127AA

18X6.5 2900 LB WITH
18X6.5 3100 LB WITH
2745 KG 6050 LB
235/60R16 TIRES
250 KPA (36 PSI) COLD
235/60R16 TIRES
250 KPA (36 PSI) COLD

13111 4321
040104252506 152AA
18X6.5
235/60R16 TIRES
250 KPA (36 PSI) COLD
235/60R16 TIRES
250 KPA (36 PSI) COLD

8-16
NEXT
PM
DUE
17603

Form 3107 5/89

8-16
NEXT
PM
DUE
17603

8-16
NEXT
PM
DUE
17603





























































D O D G E

GRAND
CARAVAN



D O D G E

GRAND
CARAVAN



D O D G E

GRAND
CARAVAN



















FD BY CHRYSLER GROUP LLC
DATE OF MFG: 4-11
GROSS WEIGHT: 1328 KG, 2950 LB
GROSS VOLUME: 1806.5
GROSS HEIGHT: 1467 KG, 3100 LB
NET WEIGHT: 1096.5 KG, 2418 LB
NET VOLUME: 1328 KG, 2950 LB
NET HEIGHT: 1467 KG, 3100 LB
GROSS WEIGHT: 2745 KG, 6050 LB
GROSS VOLUME: 230780.16
GROSS HEIGHT: 230780.16
NET WEIGHT: 259094.1 KG, 57100 LBS
NET VOLUME: 259094.16
NET HEIGHT: 259094.1 KG, 57100 LBS
THIS VEHICLE COMPLIES WITH ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY REGULATIONS. SEE THE OWNER'S MANUAL FOR MORE INFORMATION.
VIN: 2C4RS12S2C[REDACTED]
MODEL: [REDACTED]
YEAR: 2011
COUNTRY OF ORIGIN: CHINA
DATE OF MANUFACTURE: 04/11/11
FLOOR PLAN: 08P42700 12734

















PUSH TO
RELEASE

BE
BE
BE



PUSH TO
RELEASE

BET







Small white tag with illegible text.













3.6L VVT

Check for correct engine oil level. If low, add oil. Do not overfill. If you are unsure, consult your owner's manual.
 1278A



3.6L VVT

WARNING: ENGINE & ACCESSORIES ARE HOT!
CAUTION: HOT SURFACES!
DO NOT TOUCH!
DO NOT OPEN THE HOOD WHEN THE ENGINE IS RUNNING!
DO NOT OPEN THE HOOD WHEN THE ENGINE IS HOT!
DO NOT OPEN THE HOOD WHEN THE ENGINE IS HOT!
DO NOT OPEN THE HOOD WHEN THE ENGINE IS HOT!

[REDACTED]



WARNING
Always use proper technique when lifting or carrying heavy objects to avoid back injury. Do not lift or carry heavy objects that are too heavy for you. Do not lift or carry heavy objects in a way that could cause you to lose your balance. Do not lift or carry heavy objects in a way that could cause you to trip or fall. Do not lift or carry heavy objects in a way that could cause you to strain your muscles. Do not lift or carry heavy objects in a way that could cause you to become dizzy or lightheaded. Do not lift or carry heavy objects in a way that could cause you to become short of breath. Do not lift or carry heavy objects in a way that could cause you to become fatigued. Do not lift or carry heavy objects in a way that could cause you to become overexerted. Do not lift or carry heavy objects in a way that could cause you to become injured. Do not lift or carry heavy objects in a way that could cause you to become disabled. Do not lift or carry heavy objects in a way that could cause you to become hospitalized. Do not lift or carry heavy objects in a way that could cause you to become killed.



Icon of a battery and a fuse box.

Icon of a battery and a fuse box.



144AG
VIN: 1G1G221M1G144AG
144AG 144AG 144AG

VEHICLE EMISSION CONTROL INFORMATION
CALIFORNIA: 060 24 2 241 240000 1 00000
CALIFORNIA: 060 24 2 241 240000 1 00000

SLVVT

14410
MS14240111877M
RHH 14410 14404 14410 14410



Chrysler



DO NOT PRY VENTS

Chrysler Group LLC
Anderson Hills, MI 48225



PART NO. 050233389AA
CCA 700
RC 140
RECYCLED MATERIALS
VENDOR CODE 44949F

MSDS
1-800-451-7233
www.3m.com

ADANGER/POISON

NO FLAMING
NO REACTIVE
NO CORROSIVE
NO TOXIC

HAZARDOUS MATERIALS
HAZARDOUS WASTE
HAZARDOUS SOLID WASTE
HAZARDOUS LIQUID WASTE
HAZARDOUS GAS WASTE
HAZARDOUS DUST WASTE
HAZARDOUS SLAG WASTE
HAZARDOUS SLURRY WASTE
HAZARDOUS OTHER WASTE

HAZARDOUS MATERIALS
HAZARDOUS WASTE
HAZARDOUS SOLID WASTE
HAZARDOUS LIQUID WASTE
HAZARDOUS GAS WASTE
HAZARDOUS DUST WASTE
HAZARDOUS SLAG WASTE
HAZARDOUS SLURRY WASTE
HAZARDOUS OTHER WASTE



▲ DANGER/POISON

SPILLS FROM
EXPOSED BATTERIES
CAN DAMAGE PLACES
OR WEAR SURFACES

CAUTION: DO NOT
SHORT-CIRCUIT THE
TERMINALS OR
DISPOSE OF IN
FIRE

RECYCLE
SULFURIC ACID
CAN CAUSE ACID
BURNING AND
OTHER INJURY





8 101 120 021
15 AMP 15A
051407E AD
(90) MEXICO

05184162



 05184162AF-A

34671
1081






05184162AF-A

SAE APPROVED
SAE J1995







ATTENTION  **WARNING**  **MISE EN GARDE**  **ADVERTENCIA**

**R-134A A/C REFRIGERANT
FACTORY CHARGE**
USUAL CHARGE: 1.0 L (1.1 U.S. qt.) 0.81 kg
MAX. CHARGE: 1.2 L (1.3 U.S. qt.) 1.0 kg
PART NO. 822001-10

COMPRESSOR OIL:
MOBIL PUL PART NO. 82200-102

RECHARGEZ LE RÉFRIGÉRANT R-134A À LA MANÈRE SUIVANTE:
1. Vérifiez la pression de la conduite d'admission et de la conduite de retour.
2. Vérifiez la teneur en huile de la conduite d'admission et de la conduite de retour.
3. Vérifiez la teneur en huile de la conduite de retour et de la conduite d'admission.
4. Vérifiez la teneur en huile de la conduite d'admission et de la conduite de retour.
5. Vérifiez la teneur en huile de la conduite de retour et de la conduite d'admission.

3.6LVVT

ATTENTION
WARNING: HOT SURFACES & MOVING PARTS
CAUTION: HOT SURFACES & MOVING PARTS
DO NOT TOUCH. BURNING OIL OR FLUIDS MAY BE PRESENT.
DO NOT OPEN THE HOOD OR REAR TRUNK LID WHEN THE ENGINE IS RUNNING.
DO NOT OPEN THE HOOD OR REAR TRUNK LID WHEN THE ENGINE IS HOT.
DO NOT OPEN THE HOOD OR REAR TRUNK LID WHEN THE ENGINE IS RUNNING.
DO NOT OPEN THE HOOD OR REAR TRUNK LID WHEN THE ENGINE IS HOT.
DO NOT OPEN THE HOOD OR REAR TRUNK LID WHEN THE ENGINE IS RUNNING.
DO NOT OPEN THE HOOD OR REAR TRUNK LID WHEN THE ENGINE IS HOT.



04677621AB



ATTENTION

R-134a A/C REFRIGERANT FACTORY CHARGE:

SINGLE UNIT: 29 oz. (1.81 lb - 0.82 kg)

DUAL UNIT: 40.5 oz. (2.53 lb - 1.15 kg)

PART NO. 83200101

COMPRESSOR OIL:

ND8 PAG PART NO. 82300102

WARNING ▲ MISE EN GARDE ▲ ADVERTENCIA

HIGH-PRESSURE REFRIGERANT SYSTEM TO BE SERVICED BY QUALIFIED PERSONNEL ONLY.
CONSULT SERVICE MANUAL. IMPROPER SERVICE METHODS MAY CAUSE PERSONAL INJURY.
SYSTEM MEETS SAFETY REQUIREMENTS OF SAE STANDARD J639.

SYSTÈME DE CLIMATISATION SOUS HAUTE PRESSION DEVANT ÊTRE RÉPARÉ PAR UN TECHNICIEN QUALIFIÉ.
CONSULTEZ LE MANUEL D'ENTRETIEN. DES BLESSURES CORPORELLES SONT POSSIBLES SI NON RÉPARÉ
CORRECTEMENT. SYSTÈME CONFORME AUX CRITÈRES DE SÉCURITÉ DE LA NORME SAE J639.

SISTEMA DE REFRIGERANTE DE ALTA PRESIÓN SÓLO DEBE SER REPARADO POR PERSONAL CALIFICADO.
CONSULTE EL MANUAL DE SERVICIO. MÉTODOS INADECUADOS DE REPARACIÓN PODRÍAN CAUSAR LESIONES
PERSONALES. EL SISTEMA CUMPLE LAS NORMAS DE SEGURIDAD ESTÁNDAR SAE J639

4AG
#T144AG11118777#
11118
10401



Chrysler Group LLC

VEHICLE EMISSION CONTROL INFORMATION

CONFORMS TO REGULATIONS:
2011 MY FFV

U.S. EPA: T2 B4 LDV OBD: CA II FUEL: GASOLINE / ETHANOL

CALIFORNIA: OBD: CA II FUEL: GASOLINE / ETHANOL
CERTIFIED FOR SALE ULEV II QUALIFIED.

NO ADJUSTMENTS NEEDED

GROUP: BCRXJ03.6UPA ENGINE: 3.6L
EVAP: BCRXR0150RKA

TWC, HO2S, SFI

68085 127AA



VT



144AG

05005 144AG			S4204			1111B		
05005 144AG			S4204			18:46:21		



SAFETY INFORMATION
SEE USER MANUAL FOR
DETAILED INFORMATION
ON THIS PRODUCT

SAFETY INFORMATION
SEE USER MANUAL FOR
DETAILED INFORMATION
ON THIS PRODUCT

SAFETY INFORMATION
SEE USER MANUAL FOR
DETAILED INFORMATION
ON THIS PRODUCT

VT





ATTENTION: NE TÔUCHEZ PAS LA BATTERIE AVANT D'ÊTRE DÉBRAYÉ. ATTENTION: NE TÔUCHEZ PAS LA BATTERIE AVANT D'ÊTRE DÉBRAYÉ. ATTENTION: NE TÔUCHEZ PAS LA BATTERIE AVANT D'ÊTRE DÉBRAYÉ.

DO NOT PERMIT

Chrysler Group LLC
Warren, MI 48090

RECYCLED MATERIALS

PART NO. 05033389AA

CCA 700

MC 140

VERSION CODE 44049F

Pb

KEEP AWAY FROM CHILDREN
KEEP AWAY FROM CHILDREN
KEEP AWAY FROM CHILDREN

ATTENTION - NETTOYER LE BORDJON DE REMPLISSAGE AVANT DE L'ENLEVER
WARNING - CLEAN FILLER CAP BEFORE REMOVING
ATTENTION - NETTOYER LE BORDJON DE REMPLISSAGE AVANT DE L'ENLEVER

DO NOT PLY VENTS



Chrysler Group LLC
Auburn Hills, MI 48326

Pd

PART NO.

05033389

CCA 700

RECICLE



RECYCLE

REC 140

VENDOR CODE 44949F























