

DP14-004

CHRYSLER

9/15/2014

Legals and Cust Complaints

PUBLIC





DODGE

21722602X



CHRYSLER

Dodge

217226CDX

12/25/2012

SF



21122602

SF

SUNGLASS

CHRISLER

ge



2172682

SF

Brad Zook



TEST POINT

45

PREPARED BY



68P3700

CHRIS...



04-1226809

CHRYSLER

ST 1/24

54

8



21722602x

ST
7/24/12

526

















DUNLOP









Minnesota



5/24/12

No edo

σ







 	ATTENTION	WARNING ▲ MISE EN GARDE ▲ ADVERTENCIA
	<p>R-134a A/C REFRIGERANT FACTORY CHARGE SINGLE UNIT: 29 oz. (1.01 lb - 5.82 kg) DUAL UNIT: 43.5 oz. (1.52 lb - 1.19 kg) PART NO. 82306101</p>	<p>HAUT-PRESSION ▲ REFRIGÉRANT DESTINÉ À SE Remplir DE TOUTES PRESSIONS DANS CERTAINES SITUATIONS. ÉVITER LES CHOCS MÉCANIQUES. NE PAS EXPOSER À DES CHOCQUES MÉCANIQUES NI À DES FROTTEMENTS.</p> <p>PREVENIR LES ÉLÉMENTS EN FLAMME ÉLOIGNÉS ÉLOIGNÉS DE LA ZONE DE TRAVAIL ÉLOIGNER LE SÉRIEUR, L'ÉTANCHÉITÉ, LES SÉRIEURS CHARGÉS DE TRAVAIL EN LA ZONE ÉLOIGNÉE. NE PAS COMPARTIR AVEC D'AUTRES ÉLÉMENTS DE LA ZONE DE TRAVAIL.</p> <p>PREVENIR LES ÉLÉMENTS EN FLAMME ÉLOIGNÉS ÉLOIGNÉS DE LA ZONE DE TRAVAIL ÉLOIGNER LE SÉRIEUR, L'ÉTANCHÉITÉ, LES SÉRIEURS CHARGÉS DE TRAVAIL EN LA ZONE DE TRAVAIL.</p> <p>PREVENIR LES ÉLÉMENTS EN FLAMME ÉLOIGNÉS ÉLOIGNÉS DE LA ZONE DE TRAVAIL ÉLOIGNER LE SÉRIEUR, L'ÉTANCHÉITÉ, LES SÉRIEURS CHARGÉS DE TRAVAIL EN LA ZONE DE TRAVAIL.</p>
	<p>COMPRESSOR OIL NEW P&D PART NO. 82300102</p>	









No Odo

21722602X



no one
8199900X



X80266818 060 04



X60J66R18

06004

2767L

MPD BY CHRYSLER LLC

DATE OF MFR 11-07

GVWR 2745 KG(6050 LB)

GVWR FRONT

WITH TIRES

RIMS AT

COLD

1339 KG(2950 LB)

P225/65R17

1706.5

250 KPH(36 PS1)

GVWR REAR

WITH TIRES

RIMS AT

COLD

1497 KG(3100 LB)

P225/65R17

1706.5

250 KPH(36 PS1)

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.A. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 248HRC64X

[REDACTED]

1199

[REDACTED]

MODEL SINGLE X BULK

MDH: 110809 01648 M172H

VEHICLE MAKE: [REDACTED]

VEHICLE MODEL: [REDACTED]

365



TIRE AND LOADING INFORMATION

5

REAR

2

FRONT

7

SEATING CAPACITY - TOTAL

THE COMBINED WEIGHT OF OCCUPANTS AND CARGO SHOULD NEVER EXCEED

521 KG OR 1150 LB



TIRE	FRONT	REAR	SPARE
ORIGINAL TIRE SIZE	P225/65R17	P225/65R17	T145/90D16
COLD TIRE INFLATION PRESSURE	250 kPa / 36 PSI	250 kPa / 36 PSI	420 kPa / 60 PSI



SEE OWNERS MANUAL FOR ADDITIONAL INFORMATION

8R631921















PUSH TO
RELEASE

TOWING & LOADING



PUSH TO
RELEASE

PUSH TO
RELEASE

















Hudson
Hearing Center
Hearing Aids
(701) 746-8421
800-669-8421
www.hudsonhearing.com

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45	46	47	48
49	50	51	52	53	54	55	56	57	58	59	60

TOWN & COUNTRY



AudioCare
Hearing Center
1011 S. Main St.
(701) 746-8421
800-869-8421
@audiocare

MON	TUE	WED	THUR	FRI	SAT	SUN
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30	31				

TOWN & COUNTRY