





































[REDACTED]

2C4RC1BG [REDACTED]

GROUP LLC

2000	2745 KG	6050 LB
2000 LB 417H	225/65R17	TIRES
417H 417H	250 104 1 36 PSI	COLD
2000 LB 417H	225/65R17	TIRES
417H 417H	250 104 1 36 PSI	COLD

STANDARDS IN EFFECT AS THE DATE OF MANUFACTURE SHOWN ABOVE.
VIN: 2C4RC1BG6
VEHICLE MADE IN CHINA

TYPE: PAR
MPV
TRIM: MPV
RPM: 040214 05000

































The image shows a battery label with the following details:

- Top Section:** A row of six safety icons: a triangle with a sunburst (corrosion), a circle with a book (manual), a triangle with a lightning bolt (high voltage), a circle with a person falling (no heavy lifting), a circle with a person wearing a mask (respiratory protection), and a circle with a crossed-out person (no smoking).
- Technical Specifications:**
 - 12V
 - 56029635AC
 - PART NO.
 - CCA 730
 - Alt 80
 - RC 140
 - EN 630
- Chemical and Material Markings:**
 - Pb (Lead)
 - Caution L.A.O.
 - Acidic Electrolyte, see inside
- Bottom Section:** A row of four icons: a triangle with a sunburst, a circle with a book, a triangle with a lightning bolt, and a circle with a crossed-out person.

1001 W. North Ave., Johnson Controls Battery Group, Inc., Milwaukee, WI 53209





WARNING: CLEAN FILTER CAP BEFORE REMOVING. USE ONLY DOT 3 FLUID FROM A SEALED CONTAINER.
AVERTISSEMENT: NETTOYER LE CAP DU FILTRE AVANT DE LE RETIRER. UTILISER SEULEMENT DU LIQUIDE DOT 3 PROVENANT D'UN CONTENAINEAU SCELLE.

04779659AA















































































P.M. App'D
PTA-01-115













RAD
MEXICO



1029435AC
80
EN 630

Controls Battery Group, Inc. Milwaukee, WI 53209







MIKE EN GARDE - NETTOYER
AVANT DE LE RETIRER, D'UN
CÔTÉ À L'AUTRE ATTENTION
DANGER - NE PAS TOUCHER
L'ÉLÉMENT CHAUFFANT
DANGER - NE PAS TOUCHER
L'ÉLÉMENT CHAUFFANT

ENGINE OIL

SAFETY

SAFETY

























