KNOX install cheat sheet

Rear-facing Installation: *Lap/Shoulder belt*

- Place car seat in rear-facing direction, adjust recline and make sure bottom of seat has full contact.
- Make sure seat is level, so ball indicator lines up with the weight of the child.
- Remove crotch buckle cover & unzip seat fabric to reveal the BLUE TENSION PLATE.
- Route the lap/shoulder belt up through BLUE BELT PATH.
- Route lap belt **only** behind the BLUE TENSION PLATE and buckle the seat belt.
- Tighten the slack behind the plate.
- Apply pressure and pull slack until indicator goes from RED to GREEN. *Pro tip: push toward seat back.
- Lock the seat belt and then feed shoulder belt into the tensioner. *It's helpful to remember that *the shoulder belt should be under the BLUE TENSION CLIP furthest from the buckle.*
- Attach tether. -Always *recommended. R*oute around the back of the car seat on side furthest from the car door for easy access to the child.

Rear-facing Installation: *LATCH*

- Place car seat in rear-facing direction, adjust recline and make sure bottom of seat has full contact.
- Make sure seat is level, so ball indicator lines up with the weight of the child.
- Remove crotch buckle cover & unzip seat fabric panel.
- Remove Lower Anchor Connectors from front section of car seat.
- Slide through BLUE BELT PATH. *Make sure it's not twisted.
- Route the connector belt under the BLUE TENSION PLATE. -There will be some slack. This is normal.
- Attach anchors with ORANGE button facing up, listen for a click.
- Apply pressure into the bottom of the car seat and pull up on anchor adjustor until indicator goes from RED to GREEN. *Pro tip: Push toward seat back.
- Attach tether. *Always recommended. R*oute around the back of the car seat on side furthest from the car door for easy access to the child.

Forward-Facing Installation: *Lap/Shoulder*

- Place car seat in forward facing direction, adjust recline and make sure bottom of seat has full contact.
- Make sure seat is level, so ball indicator lines up with the weight of the child.
- Raise headrest to allow access to RED TENSION PLATE.
- Remove crotch buckle cover & unzip seat fabric panel.
- Route the belt through the RED BELT PATH and buckle.
- Place the lap belt **only** behind RED TENSION PLATE.
- Apply pressure and pull the slack until indicator goes from RED to GREEN. *Pro tip: push toward seat back.
- Route the belt under the RED TENSION CLIP *furthest from the buckle.*
- Attach tether. -Always *recommended.*

Forward-Facing Installation: *LATCH*

- Place car seat in forward facing direction, adjust recline and make sure bottom of seat has full contact.
- Make sure seat is level, so ball indicator lines up with the weight of the child.
- Raise headrest to allow access to RED TENSION PLATE.
- Remove crotch buckle cover & unzip seat fabric panel.
- Slide Lower anchors towards the RED BELT PATH. *Make sure belt isn't twisted.
- Route the belt behind the RED TENSION PLATE.
- Route each side through the RED BELT PATH and attach with ORANGE button facing up.
- Apply pressure into the bottom of the car seat and pull up on belt until indicator goes from RED to GREEN. *Pro tip: Push toward seat back.
- Attach tether. -*Always recommended.*