

This file represents a consolidation of multiple files sent by the manufacturer. Please use the bookmarks to navigate to each file. (Each bookmark label is the name of the original file.)



VEHICLE SCAN REPORT

Vehicle 2021 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN [REDACTED]

Odometer 8885.7 miles
Publication Date Aug 31, 2021, 3:49:34 PM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	PART #
PCM	Powertrain Control Module	CAN-C	68499122AD	68499122AD
PLGM	Power Liftgate	CAN-I	68466171AF	68466171AF
ICS	Integrated Center Stack	CAN-I	7AS341X8AA	7AS341X8AA
RFH	Radio Frequency Hub	CAN-C	68500152AA	68500152AA
ESM	Electronic Shifter	CAN-C	68240089AM	68240089AM
ORC	Occupant Restraint	CAN-C	68480710AC	68480710AC
EPS	Electric Power Steering	CAN-C	68460392AA	68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68493454AE	68493454AE
DDM	Driver Door Module	CAN-I	68496461AB	68496461AB
PDM	Passenger Door Module	CAN-I	68496460AB	68496460AB
DMRL	Door Module Rear Left	CAN-I	68508894AB	68508894AB
DMRR	Door Module Rear Right	CAN-I	68508894AB	68508894AB
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD	68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD	68369596AD
MSM	Memory Seat Module	CAN-I	68321862AC	68321862AC
CSWM	Comfort Seat Wheel Module	CAN-I	68517013AB	68517013AB
AMP	Amplifier	CAN-I	68448067AA	68448067AA
IPC	Instrument Panel Cluster	CAN-C	68434960AE	68434960AE
PTS	Parktronics	CAN-C	68485862AA	68485862AA

SCCM	Steering Column Control Module	CAN-C	68360889AD	68360889AD
BCM	Body Controller	CAN-C	68491085AG	68491085AG
ACC	Adaptive Cruise Control	CAN-C	68540436AA	68540436AA
RADIO	Radio	CAN-I	68465292AC	68465292AC
OCM	Occupant Classification	CAN-C	68403127AA	68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB	68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AB	04672786AB
RBSS	Right Blind Spot Sensor	CAN-I	04672786AB	04672786AB
FFCM	Forward Facing Camera Module	CAN-C	68493395AA	68493395AA
APM	Accessory Power Module	CAN-C	05185046AB	05185046AB
BPCM	Battery Pack Control Module	CAN-C	05193183AE	05193183AE
HCP	Hybrid Control Processor	CAN-C	05185116AF	05185116AF
OBCM	On Board Charging Module	CAN-C	05185047AE	05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC	68321862AC
DSM	Display Screen Module	CAN-I	68437339AD	68437339AD
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA	6WL30DX9AA
CVPM	Central vision processing module	CAN-I	56029920AB	56029920AB
EAC	Electric A/C Compressor	CAN-C	68237995AG	68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05185117AF	05185117AF
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB	68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68471122AD	68471122AD
SGW	Security Gateway Module	CAN-C	68488429AB	68488429AB
TBM2	Telematic Box Module 2	CAN-C	68546266AB	68546266AB

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	CVNS
PCM	USA	1B 47	75 00 01	4422	941DFC50
PLGM	USA	0	5269	000200000031	
ICS	USA	0F 0C 00	13 31 01	4700	

RFH	USA / USA	10 17 00	13 26 00	4A00	
ESM	USA / USA	0F 24 00	12 28 FF	4402	
ORC	USA / USA	12 1A 00	13 2E 00	4301	
EPS	USA / USA	12 2A 00	12 1E 01	4502	
HVAC	USA	0E 09 00	14 2F 01	4401	
DDM	USA	11 07 00	14 07 00	4202	
PDM	USA	11 07 00	14 07 00	4202	
DMRL	USA / USA	10 0B 00	14 08 00	4201	
DMRR	USA / USA	10 0B 00	14 08 00	4201	
PSDML	USA / USA	10 17 00	14 10 12	4001	
PSDMR	USA / USA	10 17 00	14 10 12	4001	
MSM	USA	0F 2B 00	10 27 03	4101	
CSWM	USA	11 2A 00	14 25 00	4302	
AMP	USA	0F 06 01	12 2E 01	4021	
IPC	USA / USA	12 06 00	14 2B 00	4705	
PTS	USA	0E 32 00	14 07 00	4311	
SCCM	USA	13 28 00	13 29 00	4301	
BCM	USA	0D 11 00	14 26 90	4420	
ACC	USA / USA	14 12 01	14 26 01	4400	
RADIO		65	5175	000200000008	
OCM	USA / USA	11 1F 01	0E 2F 02	4030	
HVACR	USA	0E 09 00	10 03 02	4301	
LBSS	USA / USA	11 30 02	12 0D 00	4202	
RBSS	USA / USA	11 30 02	12 0D 00	4202	
FFCM	USA / USA	11 06 00	13 1E 00	4102	
APM	USA / USA	11 32 00	11 32 00	4001	
BPCM	Not programmed / COUNTRY_SNA	0E 03 00	14 2C 00	4005	79855957
HCP	USA	11 1F 04	0F 2D 00	4006	FE120BB2 29C5A4AB 050DC953
OBCM	USA	0F 0D 00	12 02 00	4002	
MSMP	USA	0F 2B 00	10 27 03	4001	
DSM	USA / USA	14 0C 00	14 28 00	4300	
RCCC	USA	0F 1D 00	13 04 00	4000	
CVPM	USA / USA	11 27 01	14 0C 01	4004	
EAC	USA	0E 34 00	12 0F 00	4102	
AHCP	USA	11 1F 04	0F 2D 00	4000	
EBBM	USA	0E 19 02	14 0D 18	4000	E5898FA5
ABSO	USA	0E 15 02	14 1B 26	4201	4F158D1B
SGW		5	969	4103	
TBM2	USA	13 0E 02	14 2A 5C	4104	

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
PLGM	B1971-00	Power Liftgate Latch Cinch - Ratchet Primary Switch Performance-	Stored

PLGM	B1975-00	Power Liftgate Latch Cinch - Ratchet Secondary Switch Performance-	Stored
BCM	U151A-87	Hybrid Control Processor Secret Code-Missing Message	Stored
ACC	C14A4-00	Sensor Adjustment Required-	Stored
HCP	P0513-00	Invalid SKIM Key-	Stored
HCP	P0A43-00	Drive Motor "A" Position Sensor Circuit Intermittent-	Stored
DSM	B156D-00	Low Voltage Differential Signal (LVDS) Video Cable-	Stored
CVPM	U0265-00	Lost Communication with Front Camera-	Stored
CVPM	B23C5-92	Front Camera-Performance or Incorrect Operation	Stored

ENVIRONMENTAL DATA SUMMARY

PLGM | B1971-00 | Stored | Power Liftgate Latch Cinch - Ratchet Primary Switch Performance-

NAME	VALUE	UNITS
------	-------	-------

PLGM | B1975-00 | Stored | Power Liftgate Latch Cinch - Ratchet Secondary Switch Performance-

NAME	VALUE	UNITS
------	-------	-------

BCM | U151A-87 | Stored | Hybrid Control Processor Secret Code-Missing Message

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	ERROR	
Original Odometer Value	7268	miles
Most Recent Odometer Value	8799	miles
Frequency Counter	4	
Ignition Cycle Counter	15	

ACC | C14A4-00 | Stored | Sensor Adjustment Required-

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	

Occurrence flag	ERROR	
Original Odometer Value	8669	miles
Most Recent Odometer Value	8669	miles
Frequency Counter	1	
Operation Cycle Counter	33	
Vehicle Speed	31	MPH
Engine RPM	1760	rpm
ACC Set Speed	73	MPH
Object of Interest Distance	830	FEET
Engine Torque Request	SNA	Ft-Lbs
PRNDL Status	D range	
Ignition Voltage	13.9	
System Voltage	14.2	Volts

HCP | P0513-00 | Stored | Invalid SKIM Key-

NAME	VALUE	UNITS
DTC	05 13 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Occurrence	
Original Odometer Value	8176.9	miles
Most Recent Odometer Value	8800.4	miles
Frequency Counter	3	
Ignition Cycle Counter	37	
Real time clock	21600032	sec
RAM stamps keyOn	0	sec
RAM Stamps	43002	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Applied	
Engine Speed	0	rpm
HV Battery SOC	26	%
Ignition State	Ignition Off/ACC	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Motor A Temp Sensor	144	°F
Motor B Temp Sensor	153	°F
Barometric Pressure	14	PSI

Engine Coolant Temperature	172	°F
Internal EPS Voltage Sense A	8.208	Volts
Internal EPS Voltage Sense B	8.136	Volts
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.000	Ft-Lbs
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.000	Ft-Lbs
Available Motor Torque - Motor A	43.603	Ft-Lbs
Available Motor Torque - Motor B	116.150	Ft-Lbs
Available Regen Torque - Motor A	-43.603	Ft-Lbs
Available Regen Torque - Motor B	-116.150	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor A - Inverter Current - phase A	0	AMP
Motor A - Inverter Current - phase B	-4	AMP
Motor A - Inverter Current - phase C	-4	AMP
Motor B - Inverter Current - phase A	-4	AMP
Motor B - Inverter Current - phase B	0	AMP
Motor B - Inverter Current - phase C	-4	AMP
Motor B Resolver Angle	104	Degree
Motor A Resolver Angle	350	Degree
Electric Motor A Speed	0.0	rpm
Electric Motor B Speed	0.0	rpm
PIM DC Link Voltage - A	359	Volts
PIM DC Link Voltage - B	358	Volts
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
HCP System Shutdown Command	Default	
HV Battery Voltage from BPCM	358.90	Volts
SW Build Release Version	PIM_21B_2007B0_RU_HCP__	
HCP SW Version	21B	
EPT LOC Diag Enable	Disable LOC Daignostic	
HV Contactor Status	Closed	
APM Status	Buck CV	
Impact Event	False	
Outside Air Temperature	93.2	°F
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Battery Feed Voltage 1 Sense	12.456	Volts
Battery Feed Voltage 2 Sense	12.456	Volts
Battery Feed Voltage 3 Sense	12.384	Volts
Hybrid System State	High Voltage Enabled	
Inverter A IGBT Temperature for phase A	129	°F

Inverter A IGBT Temperature for phase B	129	°F
Inverter A IGBT Temperature for phase C	127	°F
Inverter B IGBT Temperature for phase A	129	°F
Inverter B IGBT Temperature for phase B	129	°F
Inverter B IGBT Temperature for phase C	129	°F
PHEV Charging Status	No Charging	
Distance Travelled with Light ON	6	miles
GPS Date - Year	2021	Year
GPS Date - Month	8	
GPS Date - Day	29	Days
UTC Time - Hours	20	Hours
UTC Time - Minutes	36	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	256	ms

HCP | P0A43-00 | Stored | Drive Motor "A" Position Sensor Circuit Intermittent-

NAME	VALUE	UNITS
DTC	0A 43 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Occurrence	
Original Odometer Value	8794.5	miles
Most Recent Odometer Value	8794.5	miles
Frequency Counter	1	
Ignition Cycle Counter	5	
Real time clock	21595438	sec
RAM stamps keyOn	1755	sec
RAM Stamps	42929	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
PHEV Charging Status	No Charging	
Engine Speed	2086	rpm
HV Battery SOC	25	%
Ignition State	Reserved	
PRND Position Display	D	
Propulsion System Active	False	
Vehicle Speed	57.1370	MPH
Motor A Temp Sensor	180	°F

Motor B Temp Sensor	180	°F
Barometric Pressure	14	PSI
Engine Coolant Temperature	198	°F
Motor A Resolver Offset Learn Erase	not requested	
Motor A Resolver Offset Learning Status Flag	Applied	
Motor B Resolver Offset Learning Status Flag	Applied	
Motor A Resolver Angle Offset	2.40	Degree
Motor B Resolver Angle Offset	2.80	Degree
Motor A Resolver Supply Voltage Value	15.75	Volts
Motor B Resolver Supply Voltage Value	15.75	Volts
Motor A Resolver to Digital Low Level Driver Faults	No fault	
Motor B Resolver to Digital Low Level Driver Faults	No fault	
Battery Feed Voltage 2 Sense	14.184	Volts
Internal EPS Voltage Sense A	8.208	Volts
Internal EPS Voltage Sense B	8.064	Volts
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	24.797	Ft-Lbs
Available Motor Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor B	111.726	Ft-Lbs
Available Regen Torque - Motor A	0.000	Ft-Lbs
Available Regen Torque - Motor B	-111.726	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	21.755	Ft-Lbs
Electric Motor A Speed	816.0	rpm
Electric Motor B Speed	6280.5	rpm
Battery Feed Voltage 1 Sense	14.184	Volts
Battery Feed Voltage 3 Sense	14.184	Volts
Hybrid System State	Reserved	
Motor A - Inverter Current - phase A	0	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	0	AMP
Motor B - Inverter Current - phase A	-8	AMP
Motor B - Inverter Current - phase B	-40	AMP
Motor B - Inverter Current - phase C	40	AMP
Outside Air Temperature	93.2	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	Off	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Closed	
HV Battery Voltage from BPCM	335.40	Volts
PIM DC Link Voltage - A	337	Volts
PIM DC Link Voltage - B	336	Volts
Inverter A IGBT Temperature for phase A	127	°F
Inverter A IGBT Temperature for phase B	122	°F

Inverter A IGBT Temperature for phase C	124	°F
Inverter B IGBT Temperature for phase A	113	°F
Inverter B IGBT Temperature for phase B	113	°F
Inverter B IGBT Temperature for phase C	115	°F
APM Status	Buck CV	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	0	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	24.797	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Motor B Resolver Offset Learn Erase	not requested	
GPS Date - Year	2021	Year
GPS Date - Month	8	
GPS Date - Day	29	Days
UTC Time - Hours	19	Hours
UTC Time - Minutes	20	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	37	ms

DSM | B156D-00 | Stored | Low Voltage Differential Signal (LVDS) Video Cable-

NAME	VALUE	UNITS
DTC	95 6D 00	
Test Failed	False	
Pending DTC	False	
Test Failed This Operation Cycle	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	Occurrence	
Original Odometer Value	8828	miles
Most Recent Odometer Value	8828	miles
Frequency Counter	1	
Ignition Cycle Counter	10	

CVPM | U0265-00 | Stored | Lost Communication with Front Camera-

NAME	VALUE	UNITS
DTC	C2 65 00	
Test Failed	False	

Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	ERROR	
Original Odometer Value	8630	miles
Most Recent Odometer Value	8630	miles
Frequency Counter	1	
Ignition Cycle Counter	31	
DTC Extended Data Record Number 2	2	
ECU Failure – Internal Voltage	Off	
ECU Failure – ECU Memory	Off	
ECU Failure – Internal Communication Error	Off	
ECU Failure – Video Subsystem Error	Off	
ECU Failure – Watchdog Error	Off	
Calibration Failure - Calibration not Executed	Off	
Calibration Failure - Calibration Data Inconsistent	Off	
Battery Voltage	14.2	V
ECU Voltage	13.9	V
Vehicle Speed	20.723700	MPH
Ignition Status	Ignition Status: Running	
Steering Wheel Angle	6.5	Deg
Steering Wheel Angle Status	Steering Wheel Status: Okay	
Driver Door Ajar	Inactive	
Rear Left Door Ajar	Inactive	
Passenger Door Ajar	Inactive	
Rear Right Door Ajar	Inactive	
Reverse Gear	Inactive	
Liftgate Ajar	Inactive	
Touch Screen Status	Touch Screen Status: Not Pressed	
Touch Screen X Coordinate	0000	
Touch Screen Y Coordinate	0000	
Radio Display Status	Display Status: Off	

CVPM | B23C5-92 | Stored | Front Camera-Performance or Incorrect Operation

NAME	VALUE	UNITS
DTC	A3 C5 92	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	

Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	ERROR	
Original Odometer Value	5985	miles
Most Recent Odometer Value	8630	miles
Frequency Counter	17	
Ignition Cycle Counter	31	
DTC Extended Data Record Number 2	2	
ECU Failure – Internal Voltage	Off	
ECU Failure – ECU Memory	Off	
ECU Failure – Internal Communication Error	Off	
ECU Failure – Video Subsystem Error	Off	
ECU Failure – Watchdog Error	Off	
Calibration Failure - Calibration not Executed	Off	
Calibration Failure - Calibration Data Inconsistent	Off	
Battery Voltage	14.4	V
ECU Voltage	14.1	V
Vehicle Speed	18.908131	MPH
Ignition Status	Ignition Status: Running	
Steering Wheel Angle	113.5	Deg
Steering Wheel Angle Status	Steering Wheel Status: Okay	
Driver Door Ajar	Inactive	
Rear Left Door Ajar	Inactive	
Passenger Door Ajar	Inactive	
Rear Right Door Ajar	Inactive	
Reverse Gear	Inactive	
Liftgate Ajar	Inactive	
Touch Screen Status	Touch Screen Status: Not Pressed	
Touch Screen X Coordinate	0000	
Touch Screen Y Coordinate	0000	
Radio Display Status	Display Status: Off	

SNAPSHOT DATA SUMMARY

No Snapshot Data available for B1971-00

No Snapshot Data available for B1975-00

No Snapshot Data available for U151A-87

No Snapshot Data available for C14A4-00

No Snapshot Data available for P0513-00

No Snapshot Data available for P0A43-00

No Snapshot Data available for B156D-00

No Snapshot Data available for U0265-00

No Snapshot Data available for B23C5-92



