

This file represents a consolidation of multiple files sent by the manufacturer. Please use the bookmarks to navigate to each file. (Each bookmark label is the name of the original file.)



CONFIGURATION REPORT

Vehicle 2020 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN [REDACTED]

Odometer 21379.5 miles
Publication Date Nov 5, 2021, 4:00:59 PM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	PART #
PCM	Powertrain Control Module	CAN-C	68444229AD	68444229AD
ICS	Integrated Center Stack	CAN-I	6UX601X8AA	6UX601X8AA
RFH	Radio Frequency Hub	CAN-C	68453559AB	68453559AB
ESM	Electronic Shifter	CAN-C	68240089AM	68240089AM
ORC	Occupant Restraint	CAN-C	68405567AC	68405567AC
EPS	Electric Power Steering	CAN-C	68460392AA	68460392AA
ANC	Active Noise Cancellation	CAN-I	68440556AB	68440556AB
HVAC	Heat, Ventilation and A/C	CAN-I	68447893AC	68447893AC
DDM	Driver Door Module	CAN-I	68424451AC	68424451AC
PDM	Passenger Door Module	CAN-I	68424450AC	68424450AC
DMRL	Door Module Rear Left	CAN-I	68225096AG	68225096AG
DMRR	Door Module Rear Right	CAN-I	68225096AG	68225096AG
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD	68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD	68369596AD
PLGM	Power Liftgate	CAN-I	68316094AF	68316094AF
CSWM	Comfort Seat Wheel Module	CAN-I	68434910AC	68434910AC
IPC	Instrument Panel Cluster	CAN-C	68434956AC	68434956AC
PTS	Parktronics	CAN-C	68193772AJ	68193772AJ
SCCM	Steering Column Control Module	CAN-C	68360889AD	68360889AD
BCM	Body Controller	CAN-C	68424601AD	68424601AD
RADIO	Radio	CAN-I	68461768AD	68461768AD

OCM	Occupant Classification	CAN-C	68403127AA		68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB		68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AB		04672786AB
RBSS	Right Blind Spot Sensor	CAN-I	04672786AB		04672786AB
APM	Accessory Power Module	CAN-C	05185046AB		05185046AB
BPCM	Battery Pack Control Module	CAN-C	05193166AD		05193166AD
HCP	Hybrid Control Processor	CAN-C	05190265AE		05190265AE
OBCM	On Board Charging Module	CAN-C	05185047AE		05185047AE
DSM	Display Screen Module	CAN-I	68316175AC		68316175AC
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA		6WL30DX9AA
EAC	Electric A/C Compressor	CAN-C	68237995AG		68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05190266AE		05190266AE
EBBM	Electronic Brake Booster Module	CAN-C	68461813AA		68461813AA
ABSO	Anti Lock Brakes OBD	CAN-C	68461812AA		68461812AA
SGW	Security Gateway Module	CAN-C	68447193AB		68447193AB

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	CVNS
PCM	USA	1B 47	46 02 06	4419	
ICS	USA	0F 0C 00	12 25 00	4400	
RFH	USA / USA	10 17 00	13 09 00	4A00	
ESM	USA / USA	0F 24 00	12 28 FF	4402	
ORC	USA / USA	11 1F 00	12 2B 00	4301	
EPS	USA / USA	12 2A 00	12 1E 01	4502	
ANC	USA	0F 05 01	12 2C 01	4210	
HVAC	USA	0E 09 00	13 05 01	4401	
DDM	USA	11 07 00	13 0B 00	4202	
PDM	USA	11 07 00	13 0B 00	4202	
DMRL	USA / USA	10 0B 00	12 0C 00	4201	
DMRR	USA / USA	10 0B 00	12 0C 00	4201	
PSDML	USA / USA	10 17 00	14 10 12	4001	
PSDMR	USA / USA	10 17 00	14 10 12	4001	
PLGM	USA	17 19 00	18 22 00	4202	
CSWM	USA	11 2A 00	13 2C 00	4302	
IPC	USA / USA	12 06 00	13 27 00	4704	

PTS	USA	0E 32 00	12 1F 00	4311	
SCCM	USA	13 28 00	13 29 00	4301	
BCM	USA	0D 11 00	13 0C 90	4415	
RADIO	USA	13 31 14	13 31 14	8205	
OCM	USA / USA	11 1F 01	0E 2F 02	4030	
HVACR	USA	0E 09 00	10 03 02	4301	
LBSS	USA / USA	11 30 02	12 0D 00	4202	
RBSS	USA / USA	11 30 02	12 0D 00	4202	
APM	USA / USA	11 32 00	11 32 00	4001	
BPCM	Not programmed / COUNTRY_SNA	0E 03 00	13 18 03	4005	
HCP	USA	11 1D 07	13 05 03	4005	C6F23FD5 E84E843F 050DC953
OBCM	USA	0F 0D 00	12 02 00	4002	
DSM	USA / USA	13 29 00	12 23 00	4000	
RCCC	USA	0F 1D 00	13 04 00	4000	
EAC	USA	0E 34 00	12 0F 00	4102	
AHCP	USA	11 1D 07	13 05 03	4000	
EBBM	USA	0E 19 02	12 31 17	4000	AD6A1E22
ABSO	USA	0E 15 02	12 2E 1E	4201	73EEDB6B
SGW		5	779	4103	

CONFIGURATION

PCM CONFIGURATION

NAME	VALUE	UNITS
Secondary Mass Airflow Sensor Equipped	—	
Active Exhaust Pressure Sensor Equipped	—	
Electronic Parking Brake Equipped	—	
Active Exhaust Valve(s) Equipped	—	
High Side Port Tumble Valve Equipped	—	
Aux Coolant Pump Heater Equipped	—	
Heater Temp Control Valve Equipped	—	
Mechanical Coolant Pump Equipped	—	
Wastegate HBridge Equipped	—	
Remote Start Present	—	
2.0 Liter I4 Direct Injection Engine	—	
Coolant On-Off Pump Equipped	—	
1.0 Liter I3 Engine	—	
Primary Lin Alternator Equipped	—	
Variable Valve Lift Equipped	—	
Dual Fuel Tank Equipped	—	
Auxillary Coolant Pump Equipped	—	
Cooled EGR Equipped	—	
Dual Alternator Gen1 Capable	—	
A/C Relay Powered from Engine Switched Battery	—	

Supercharger Equipped	—	
Low Temp Radiator Coolant Pump Equipped	—	
PTO System Equipped	—	
CNG Large Gas Tank Equipped	—	
HPT 6-Speed Trans Equipped	—	
Hybrid MEC Shifter Equipped	—	
Engine Idle Shutoff Equipped	—	
ZF 9-Speed Trans Equipped	—	
MDS Equipped	—	
Variable Speed Fuel Pump Equipped	—	
ERS Equipped Indicator	—	
O2 Sensor Bank 1 Sensor 1 Equipped	—	
GPEC2 Equipped	—	
ESIM Equipped	—	
Intake Cam 2 Equipped	—	
Engine Stop Start Equipped	—	
Trans Skip Shift Equipped	—	
VFS Actuators Available Indicator	—	
Transmission Oil Heater Equipped	—	
Secondary Air Equipped	—	
3.5 Liter V6 Engine	—	
O2 Sensor Bank 2 Sensor 2 Equipped	—	
PWM Fan Motor System Equipped	—	
1 Speed Fan Mechanical Relay System Equipped	—	
Vehicle Speed Sensor #1 Calculated from CAN	—	
4.0 Liter I6 Engine	—	
6.1 Liter V8 Engine	—	
Active Engine Mount Equipped	—	
Primary Lin Alternator Equipped	—	
Auxiliary Heater Electric Water Pump Equipped	—	
Sensorless FFV Enabled	—	
Throttle Inlet Temp Sensor Equipped	—	
Electronic Automatic Transmission (EATX) Equipped	—	
WI4 Intake Flow Control Valve Equipped	—	
Wide Range O2 Sensor 1/1 Equipped	—	
2.7 Liter V6 Engine	—	
GPEC2A Equipped	—	
Auxiliary Coolant Pump Heater Equipped	—	
Active Grille Shutter Equipped	—	
Cooled EGR Equipped	—	
GPEC4 Equipped	—	
Unleaded diesel fuel	—	
PTO System Equipped	—	
Supercharger Equipped	—	

WI4 Variable Valve Timing Equipped	—	
Oil Pressure Sensor Enabled	—	
Low Temperature Radiator Coolant Pump Equipped	—	
High Side Port Tumble Valve Equipped	—	
Fiat VIN Learning Strategy Equipped	—	
ICC Cruise Equipped	—	
Starter Relay 2 Equipped	—	
ZF 9-Speed Transmission Equipped	—	
Next Gen Bus Equipped	—	
Humidity, Temperature and Pressure Sensor (LIN) Equipped	—	
3.0 Liter V6 Engine	—	
3.6 Liter V6 Engine	—	
Mechanical Coolant Pump Heater Equipped	—	
Active Exhaust Pressure Sensor Equipped	—	
VMM Equipped	—	
Dual Fuel Pressure Sensor Equipped	—	
Air Shutoff Valve Bank 1 Control Solenoid 2 Equipped	—	
Exhaust Cam 1 Equipped	—	
Trans Reverse Lockout Equipped	—	
Fan Wake Up Relay System Equipped	—	
66RFE / 68RFE	—	
Wastegate H-Bridge Equipped	—	
Brake Pedal Sensor Equipped	—	
Viscosity Sensor Equipped	—	
Coolant On-Off Pump Equipped	—	
AC Equipped	—	
6.4 Liter V8 Engine	—	
Secondary Fuel Pump Equipped	—	
3.7 Liter V6 Engine	—	
Linear PWM Fan Relay System Equipped	—	
CMCV H-Bridge Equipped	—	
Operator Idle Speed Request Equipped	—	
Tumble Generator Valve Equipped	—	
Electric Thermostat Heater Equipped	—	
CUSW PROXI Write Programming Support Enabled	—	
Electronic Throttle Control Equipped	—	
VLP Is Learnable Indicator	—	
AC Equipped Over Bus	—	
2.0 Liter WI4 engine	—	
1.0 Liter I3 Engine	—	
Electric Coolant Valve Equipped	—	
Engine Software In Package	—	
Adaptive Cruise Control Hardware Equipped	—	
Duty Cycle Purge Valve Equipped	—	

GPEC3 Equipped	—	
Air Shutoff Valve Bank 1 Control Solenoid 1 Equipped	—	
40TE / 41TE / 41TEA	—	
45RFE / 545RFE / 65RFE	—	
Coolant On-Off Valve Equipped	—	
Turbocharger Equipped	—	
EMAT (Getrag DCT transmission) Equipped	—	
Adaptive Cruise Control Equipped	—	
Dual Stage Oil Pump Equipped	—	
2.4 Liter I4 engine	—	
Power Steering Switch Equipped	—	
O2 Sensor Bank 2 Sensor 1 Equipped	—	
Police Package Equipped	—	
3 Speed Fan Mechanical Relay System Equipped	—	
Engine Idle Shutoff Equipped	—	
Fixed displacement AC Equipped	—	
Clutch Interlock Switch Equipped	—	
Intake Cam 1 Equipped	—	
3.8 Liter V6 Engine	—	
Electronic Coolant Pump Equipped	—	
TIP Equipped	—	
Aisin 6-Speed RWD Transmission Equipped	—	
4 Speed Automatic Transmission Equipped	—	
Variable Displacement AC Equipped	—	
Active Exhaust Valve Equipped	—	
Exhaust Cam 2 Equipped	—	
Turbine Volute Valve Actuator Equipped	—	
TOOLCONFIG_OIL_PRESS_ABS_EQUIPPED	—	
Buffered Crank Output for PHEV Engine Pulse Calculation Equipped	—	
Constant Heater Temperature Control Valve Equipped	—	
Continuous Variable Transmission Equipped	—	
3.3 Liter V6 Engine	—	
Brushless PWM Fan Equipped	—	
Electric Water Pump Equipped	—	
1.8 Liter I4 engine	—	
4.7 Liter V8 Engine	—	
Compressed Natural Gas Equipped	—	
3.2 Liter V6 Engine	—	
Vehicle Speed Sensor #1 Calculated by ECU	—	
SRV Equipped	—	
62TE	—	
Battery Temp Sensor Equipped	—	
HPT 6-Speed Transmission Equipped	—	
DUAL_ALTERNATOR_GEN1_LEARNEDCOPY	—	

CUSW (29-Bit) Equipped	—	
Inrush Current Reduction Relay Equipped	—	
Dual Speed Fuel Pump Equipped	—	
CUSW (11-Bit) Equipped	—	
Shift Indicator Lamp Equipped	—	
VLP Equipped Indicator	—	
2 Speed Fan PWM Relay System Equipped	—	
4 Button Integrated Cruise Control	—	
Direct Injection Equipped	—	
Electronic Vacuum Pump Equipped	—	
Air Shutoff Valve Bank 2 Control Solenoid 2 Equipped	—	
Hybrid Electric Vehicle Equipped	—	
6.2 Liter V8 Engine	—	
5.7 Liter V8 Engine	—	
Wide Range O2 Sensor 2/1 Equipped	—	
Cummins Equipped	—	
Fiat 940 Compact Equipped	—	
A/C Equipped	—	
Knock Sensor 1 Equipped	—	
Yaw Rate Sensor ESC Equipped	—	
Unleaded Gasoline Fuel	—	
Port Flap Valve Equipped	—	
Barometric Sensor Equipped	—	
Auxiliary Coolant Pump Equipped	—	
O2 Sensor Bank 1 Sensor 2 Equipped	—	
42RLE	—	
MTV Solenoid Equipped	—	
Rear Heater Equipped	—	
Transmission Software Included	—	
O2 Sensor Bank 1 Sensor 3 Equipped	—	
ETC Cruise equipped	—	
Dual Fuel Tank Equipped	—	
2 Speed Fan 3 Driver 3 Relay System Equipped	—	
MultiAir Equipped	—	
Linear EGR Equipped	—	
Powernet Equipped	—	
Linear Purge Equipped	—	
Buffered Crank Output for ANC (Active Noise Cancellation) Equipped	—	
2 Speed Fan Mechanical Relay System Equipped	—	
Knock Sensor 2 Equipped	—	
Engine Oil Heater Cooler Equipped	—	
Bi-Directional Crank Sensor Equipped	—	
Dual Fuel Pressure Sensor Equipped	—	
CUSW 4-Button Cruise Equipped	—	

Make Up Air Sensor Equipped	—	
Cylinder Pressure Sensor Equipped	—	
Throttle Inlet Temp Sensor Equipped	—	
5 Button Cruise (LIN) Equipped	—	
Brake Pedal Sensor Equipped	—	
Power Steering Angle Sensor Mandatory	—	
INTAKE O2 SENSOR EQUIPPED	—	
LIN Humidity, Temp, and Pressure Sensor Equipped	—	
Operator Idle Speed Request Equipped	—	
SWAP HARDWIRED BRAKE SWITCH INPUTS	—	
Clutch Sensor Equipped	—	
Mass Airflow System Equipped	—	
Engine Oil Pressure Sensor Type	—	None

ICS CONFIGURATION

NAME	VALUE	UNITS
Display Type (Mid)	False	
Display Type (Base)	True	
Display Type (High)	False	

RFH CONFIGURATION

NAME	VALUE	UNITS
Hardware Configuration: Trunk Door Handle H/W	Simple Switch AP	
Hardware Configuration: Remote Start Antenna	Present	
Hardware Configuration: Front Right Door Handle H/W	Serial AP	
Hardware Configuration: Front Left Door Handle H/W	Serial AP	
Hardware Configuration: Rear Right Door Handle H/W	No AP	
Hardware Configuration: Rear Left Door Handle H/W	No AP	
Valid Key In Ignition	No	
Fob Location #3 Successfully Programmed	Yes	
Fob Location #5 Key sense status	Fob is NOT Key Sense	
Secret Key Sent to Body Controller - Original attempt	Yes	
Fob Location #7 Key sense status	Fob is NOT Key Sense	
Fob Location #3 Key sense status	Fob is Key Sense	
Fob Location #7 Successfully Programmed	No	
Fob Location #6 Successfully Programmed	No	
Fob Location #5 Successfully Programmed	No	
Fob Location #8 Key sense status	Fob is NOT Key Sense	
PIN Successfully Programmed	Yes	
RFHub Locked	RFHUB Locked after IAC write	
Fob Location #1 Key sense status	Fob is NOT Key Sense	
Fob Location #4 Key sense status	Fob is NOT Key Sense	
Fob Location #6 Key sense status	Fob is NOT Key Sense	
Fob Location #1 Successfully Programmed	Yes	

Secret Key Sent to Body Controller - Most recent attempt	Yes	
Fob Location #2 Successfully Programmed	Yes	
Fob Location #4 Successfully Programmed	No	
Fob Location #2 Key sense status	Fob is NOT Key Sense	
VIN Successfully Programmed	Yes	
Fob Location #8 Successfully Programmed	No	
Base TPM	False	
Auto Park Present	True	
e-shifter present	True	
Secret Codes Programmed	True	
KeySense Configuration	True	
Ignition system type connected	KIN system	
RKE	True	
Remote Start Present	True	
\$0214 Programmed by	Programmed by Supplier EOL	
TPM Auto-Locate Enabled	True	
Keyless Go	True	
Passive Entry	True	
Hybrid Type	PHEV	
Module Configuration Status	True	
Premium TPM	True	
Back Up ECU Configuration 16	True	
Back Up ECU Configuration 14	True	
Back Up ECU Configuration 7	True	
Back Up Vehicle Config 1	True	
Back Up ECU Configuration 10	True	
Back Up ECU Configuration 11	True	
Back Up Vehicle Config 4	True	
Back Up Vehicle Config 3	True	
Back Up Customer Settings Menu 1 (CSM1)	True	
Back Up ECU Configuration 2	True	
Back Up ECU Configuration 1	True	
Back Up ECU Configuration 9	True	
Back Up Programmed ECUs: Cabin Network	True	
Back Up Vehicle Config 5	True	
Back Up ECU Configuration 3	True	
Back Up Customer Settings Menu 2 (CSM2)	True	
Back Up Vehicle Config 6	True	
Back Up ECU Configuration 12	True	
Back Up Programmed ECUs: P/T Chassis Network	True	
Back Up ECU Configuration 4	True	
Back Up ECU Configuration 17	True	
Back Up ECU Configuration 8	True	
Back Up ECU Configuration 13	True	

Back Up Vehicle Config 7	True	
Back Up ECU Configuration 5	True	
Back Up Vehicle Config 2	True	
Back Up ECU Configuration 15	True	
Back Up ECU Configuration 6	True	

ORC CONFIGURATION

NAME	VALUE	UNITS
First Row Driver Seatbelt Buckle Switch	—	
Driver Seat Track Position Sensor	—	
Second Row Left Seat Side Airbag	—	
Rollover Sensing	—	
Passenger Seatbelt Retractor Pretensioner	—	
Passenger Seatbelt Anchor Pretensioner	—	
Driver Seatbelt Anchor Pretensioner	—	
Left Side Seat Squib 1	—	
Driver Frontal Squib 3	—	
Passenger Seatbelt Load Limiter	—	
Passenger Occupant Detection Sensor	—	
Passenger Seatbelt Buckle Pretensioner	—	
Second Row Left seat belt Switch	—	
Left B-Pillar Impact Acceleration Sensor	—	
Right Up-Front Acceleration Sensor	—	
Configuration Column Identifier	—	
Passenger Airbag Disable Indicator	—	
Passenger Frontal Squib 1	—	
Driver Frontal Squib 1	—	
Passenger Frontal Squib 3	—	
Right Side Seat Squib 1	—	
Second Row Right seat belt Switch	—	
Left Up-Front Acceleration Sensor	—	
Right Curtain Squib 1	—	
Left C-Pillar Impact Acceleration Sensor	—	
Passenger Seat Track Position Sensor	—	
Driver Knee Bolster Squib	—	
Occupant Classification (OCM)	—	
Passenger Frontal Squib 2	—	
Driver Frontal Squib 4	—	
Second Row Center seat belt Switch	—	
Left Curtain Squib 1	—	
Right Side Door Pressure Sensor	—	
First Row Passenger Seatbelt Buckle Switch	—	
Right B-Pillar Impact Acceleration Sensor	—	
Left D-Pillar Impact Acceleration Sensor	—	

Right D-Pillar Impact Acceleration Sensor	—	
Right C-Pillar Impact Acceleration Sensor	—	
Driver Seatbelt Load Limiter	—	
Driver Seatbelt Retractor Pretensioner	—	
Second Row Right Seat Side Airbag	—	
Passenger Frontal Squib 4	—	
Passenger Airbag Disable Switch	—	
Passenger Knee Bolster Squib	—	
Driver Frontal Squib 2	—	
Left Side Door Pressure Sensor	—	
EPPM	—	
Driver Seatbelt Buckle Pretensioner	—	

EPS CONFIGURATION

NAME	VALUE	UNITS
Stop/Start Feature Active	—	
Parallel Park Assist Feature Active	—	
Dynamic Steering Torque Feature Active	—	
Lane Feedback Feature Active	—	

ANC CONFIGURATION

NAME	VALUE	UNITS
Premuim - 2 (12 Channel)	False	
Premuim - 1 (8 channel)	False	
Premium - 3 (SRT8)	True	
Door Module - Left Rear	Present	
NetCFG Stat AT, I, PT	Request Data	
Door Module - Right Front	Present	
Door Module - Right Rear	Present	
Door Module - Left Front	Present	
Current ANC Calibration ID - Service	Harman ANC Module 3.6L	
ANC Calibration Date - Year	18	
ANC Calibration Date - Patch	4	
ANC Calibration Date - Week	45	
Left/Right Hand Drive	SNA / Not Programmed	
ANC Status	Off - Microphone Fault	

HVAC CONFIGURATION

NAME	VALUE	UNITS
HVAC Configuration	Dual Zone ATC + Rear	
Dual Zone MTC Control (BB)	False	
MTC With EBL (3Knob)	False	
MTC heater only (3Knob)	False	
Single Zone MTC Control (BB)	False	

MTC Without EBL (3Knob)	False	
DualZone ATC Control (Factory) (BB)	False	
DualZone ATC Control (BB)	False	

PDM CONFIGURATION

NAME	VALUE	UNITS
Frameless Window	False	

PSDML CONFIGURATION

NAME	VALUE	UNITS
VSIM Status	False	

PSDMR CONFIGURATION

NAME	VALUE	UNITS
UPFM Status (Present = True, Absent = False)	False	

CSWM CONFIGURATION

NAME	VALUE	UNITS
EC - Seat A	—	
EC - Seat B	—	
Vehicle Line W-Series	—	
Vehicle Line P-Series	—	
Vehicle Line L-Series	—	
Vehicle Line R-Series	—	
Heated Steering Wheel	—	
Vehicle Line M-Series	—	
Vehicle Line D-Series	—	
Vehicle Line U-Series	—	
Vehicle Line J-Series	—	

IPC CONFIGURATION

NAME	VALUE	UNITS
PHEV	True	
Rear Fog Lamp	False	

PTS CONFIGURATION

NAME	VALUE	UNITS
Front License Plate Configuration	—	
Front System with 6 Rear Sensors	—	
Rear System with 6 Front Sensors	—	

SCCM CONFIGURATION

NAME	VALUE	UNITS
------	-------	-------

Rear Wiper	True	
Paddle Shifter	False	
Cruise Control / ACC	True	
Tilt Telescope	False	

BCM CONFIGURATION

NAME	VALUE	UNITS
Number of Reprogramming Attempts - Counter #0	0	
Vehicle Configuration Programmed Status	True	
Last Programmed Status	Manufacturing	
ECU Configuration 10	5	
Vehicle Config CSM1	5	
ECU Configuration 11	5	
ECU Configuration 6 (Brake)	5	
ECU Configuration 5 (Wireless)	5	
Programmed ECUs: P/T Chassis Network	5	
ECU Configuration 15 (Suspension)	5	
Programmed ECUs: Hybrid LAN Network	0	
ECU Configuration 8 (LIN and Miscellaneous)	5	
ECU Configuration 9A	5	
Vehicle Configuration 2 - Write Counter	5	
Vehicle Configuration 7 - Write Counter	5	
ECU Configuration 6 (Safety)	5	
ECU Configuration 2 (CBC Features)	5	
Vehicle Configuration 5 - Write Counter	5	
Programmed ECUs: Cabin Network	5	
Vehicle Configuration Auto Write Counter	1	
ECU Configuration 3	5	
ECU Configuration 7 (CBC Exterior Lighting Calibrations)	5	
ECU Configuration 12	5	
ECU Configuration 9 (ITM)	5	
ECU Configuration 1 (CBC Configurable Inputs and Outputs)	5	
ECU Configuration 14	5	
Vehicle Configuration 6 - Write Counter	5	
ECU Configuration 13	5	
ECU Configuration 5 (Memory)	5	
Vehicle Config CSM2	5	
ECU Configuration 15 (CBC Features)	5	
Programmed Network Configuration - Audio / Telematics Network	0	
Vehicle Configuration 4 - Write Counter	5	
ECU Configuration 6 (Powertrain)	5	
ECU Configuration 6 (Suspension)	5	
ECU Configuration 5 (Doors)	5	
ECU Configuration 4	5	

Vehicle Configuration 3 - Write Counter	5	
Last Configuration Odometer	0	miles
Vehicle Configuration 1 - Write Counter	5	
Emode Present	Not Set	
PTS Configuration	Rear / REAR	
Model Year	2020	
Vehicle Line	RU	
Hill Descent Feature Present	Not Set	
Body Style	Station Wagon	
Shifter Type	5 Position Rotary Eshifter PRNDL / Type RS5L	
Auto Highbeam	Not Set	
Drive Configuration	2WD Front	
Country Code	USA	
Special Packages	74	
Remote Start Present	Set	
Select Speed Control Feature Present	Not Set	
Left/Right Hand Drive	Left Hand Drive	
Performance Pages Present	Not Present	
Maximum Vehicle Speed	0	MPH
Max Load Inflation Pressure Rear Tire	36.0	PSI
Special Packages IC	Pacifica	
Power Inverter Type	No Power Inverter	
Cruise Feature is Present	Set	
Max Load Inflation Pressure Front Tire	36.0	PSI
Off Road Capable	Not Set	
Air Conditioning Present	Not Set	
Rain Sensor Present	Not Set	
Flipper Glass Present	Not Set	
SKIM System Present	Not Set	
Full Size Spare	Not Set	
Thatcham Present	Not Set	
Display Outside Temperature Present	Set	
Keyless Go Present	Set	
Vehicle is an SRT	Not Set	
Two Fuel Sending Units Present	Not Set	
Display Compass Heading Present	Set	
Wheel Base	Wheel base not programmed / WB_NP	
Auto Headlamp Feature Present	Set	
Premium TPM system present	Set	
Police Lighting Feature	Not Set	
Window Express Feature Configuration	Front windows express only	
Vehicle Brand	Chrysler	
Auto Park Present	Set	

T-Case Type	Not Present / Not Present	
Adjustable Pedal Feature Present (non-Memory)	Not Set	
Forward Collision Warning present	Not Set	
Paddle Shift Feature Present	Not Set	
Power Right Sliding Door Present	Set	
Disable Display of Radio Clock	Not Set	
FOBIK Safe Enable	Set	
Chassis Type	Type 9	
Fuel Capacity	17	gallons
ELV Present	Not Set	
Door Alert Feature Present	Not Set	
Passive Entry Present	Set	
RKE System Present	Set	
Secondary Lock Present	Not Set	
HVAC Configuration	Dual Zone ATC + Rear	
Sport Mode Present	Not Set	
ESCL system present	Not Set	
High Intensity Discharge Head Lamps	Not Set	
Collision Mitigation System present	Not Set	
Power Left Sliding Door Present	Set	
Liftgate/Trunk Type	Power Liftgate	
Base TPM system present	Not Set	
Transfer Case High Ratio	1.000	No Unit
Transfer Case Low Range Reduction Ratio	0.000	
Dynamic Tire Circumference (All or Rear)	89	inch
Axle Ratio	3.251	
Analog Door Sensor Configuration	Driver Door Only Analog Sensor	
Air Quality System Present	Not Set	
Steering Ratio at Negative Angle 1	0.0	No Unit
Connector E Pin 29: Rear Wiper Motor Park Signal Present	Set	
Connector D Pin 11: Stop/Turn Trailer Tow Left Output Present	Not Set	
Connector E Pin 9: Run-ACC Y Relay #2 Output Present	Set	
Connector G Pin 9: Ambient Light Dimmer Wheel Input Present	Set	
Connector E Pin 5: PHEV Fuel Door Switch Input	Set	
Connector G Pin 24 (Internally tied to Connector F Pin 7): Ambient Lighting Output	Not Set	
Connector F Pin 6: Fuel Door Motor Output Signal Present	Set	
Connector D Pin 15: Left Dedicated DRL Lamps Output Present	Set	
Connector A Pin 11: Hood Ajar Switch Input Present	Set	
Connector E Pin 4/Connector F Pin 32: Rear Park Lamps Output Present	Set	
Connector A Pin 3/Connector D Pin 2: Low Beam Output Present	Set	
Connector E Pin 8: PHEV HCP Hardwire Wakeup	Set	
Connector E Pin 7: Left HID Relay Control Output Present	Not Set	
Connector D Pin 10: Trailer Tow Tail Lamp Output Present	Not Set	
Connector G Pin 15: UGDO Feed Output Present	Set	

Connector F Pin 29: Horn Switch Present	Set	
Connector A Pin 1 and Connector D Pin 13: Front Fog Lamps Output Present	Set	
Connector E Pin 3/Connector F Pin 42: Rear Turn Lamps Output Present	Not Set	
Connector E Pin 48 (Tied internally to Connector A Pin16): Rear Wiper Motor Control Output Present	Set	
Connector G Pin 22: VTA Warning LED Output Present	Set	
Connector F Pin 9: Analog Door Ajar Signal Front Driver Present	Set	
Connector E Pin 11: Vacuum Switch Input	Not Set	
Connector A Pin 10/Connector D Pin 5: Side Markers Output Present	Set	
Connector E Pin 42: Charge Port Lock Output Present	Set	
Connector E Pin 41: Charge Port Unlock Output Present	Set	
Connector A Pin 22: Right Dedicated DRL Lamp Output Present	Set	
Connector F Pin 8 : Liftgate Release Outside Handle Switch Present	Not Set	
Connector E Pin 34: Vacuum Cleaner Relay Output Present	Not Set	
Connector D Pin 12: PHEV ECM Hardwire Wake Up Output Present	Set	
Connector F Pin 23: Door Lock Switch Signal Front Passenger Present	Set	
Connector D Pin 7: Stop/Turn Trailer Tow Right Output Present	Not Set	
Connector D Pin 22/ Connector D Pin 23: Ambient Temperature Signal/Return Present	Set	
Connector D Pin 9: Trailer Tow Backup Output Present	Not Set	
Connector E Pin 39/Connector F Pin 5: Rear Fog Lamps Output Present	Not Set	
Connector F Pin 4: Liftgate Release Present	Not Set	
Connectro E Pin 37: Right HID Control Output Present	Not Set	
Connector F Pin 35: Inverter Enable Relay Output Present	Not Set	
LED Rear Turn Lamps Present	Not Set	
Front Wiper Wipes After Wash	2 Wipes	
Fuel Door Release Enabled	Not Present	
Quad Headlamps Enable	Set	
Reversible Washer Pump Enable	Set	
DRL Dropout Enable	Set	
Park Lamp Loadshed Enable	Set	
LED Stop Lamps Present	Not Set	
Headlamp Washer Low Fluid Shut-Off Enable	Set	
Hazard Lamp Configuration	Latching Switch	
LED Tail Lamps Present	Set	
Bi Xenon Headlamps Enable	Not Set	
Front Fog Lamp Dropout Enable	Set	
LED Low Beam Lamps Present	Not Set	
Headlamp Wash Interval	wash cycle#11	
LED Dedicated DRL Present	Set	
Wiper Service Position Enabled	Not Set	
Illuminated approach Enabled	Not Set	
Front Wiper Park Enable	Set	
LED License Lamps Present	Set	
Horn Chirp Allowed	Set	

Fuel Door Present	Not Set	
Combined Front Park/Turn Feature Enable	Not Set	
DRL Configuration	No DRL	
DRL Lamp Location	Dedicated	
Rear Wiper Park Enable	Set	
Combined Rear Lighting Enable	Set	
LED Reverse Lamps Present	Not Set	
Intermittent Wiper States	4 Intermittent Wiper position Switch	
Headlamp Wash Shot	double	
LED Rear Fog Lamps Present	Not Set	
Trailer Tow Present	Not Set	
Tip Start Enabled	Set	
LED Front Turn Lamps Present	Not Set	
Side Repeaters Enable	Not Set	
LED Front Park/Marker Lamps Present	Set	
Headlamp Wash Spray Duration (at 100 ms intervals)	1100ms	
One Touch Lane Change	Set	
Tunnel Detection	Not Set	
Dual Start Relay System Present	Not Set	
Exterior Light Loadshed Enable	Set	
LED Front Fog Lamps Present	Not Set	
LED CHMSL Lamp Present	Set	
LED High Beam Lamps Present	Not Set	
Destination	United States of America	
Surround Sound Feature Present	Not Set	
Power Door Locks Present	Set	
Microphone Type	Peiker 300 mv	
Heated Steering Wheel Present	Set	
Power Inverter Present	Not Set	
Disable CD Eject	Not Set	
Cabin Equilization Curve Number	6 Speaker Base (RU)	
Antenna Type	Active Primary and no secondary antenna	
Splashscreen Type	Vehicle Brand	
Microphone Configuration	2 Microphones	
External Port Type	AUX + USB	
Microphone Tuning Parameter	Absent [Not Used]	
Front Park Assist Present	Set	
Front Heated Seats Present	Set	
Rear Camera Present	Set	
Fleet Vehicle Content	Not Set	
AP5 Trunk Lock	Simple Switch	
AP2 Right Front	Smart Switch	
Vehicle Variant	Undefined	
Tip Start Present	Set	

AP4 Right Rear	CAN	
Airport Scenario Trunk	Not Set	
AP1 Left Front	Smart Switch	
AP3 Left Rear	CAN	
AP5 Trunk Unlock	CAN	
Heated Mirrors Present	Set	
Blindspot Mirror Present	Set	
Frameless Window Present	Not Set	
Sun Shade	Not Set	
Global Up	Not Set	
Folding mirrors present	Not Set	
Electro-chromatic passenger mirror present	Not Set	
Window Motor Type	Not Set	
Global Down	Not Set	
Passenger Window Lockout	Not Set	
Tow Mirror Present	Not Set	
Passenger Memory Mirror Present	Not Set	
Rear Door Pre Short Drop	Not Set	
Electro-chromatic driver mirror present	Not Set	
Driver Memory Mirrors Present	Not Set	
Window Hall Sensors Present	Not Set	
Mirror turn signals present	Not Set	
Puddle Lamp Present	Not Set	
Heated Steering Wheel Present	Present	
Tilt/Telescope Steering Present	Not Set	
Memory Adjustable Pedals Present	Not Set	
Driver Memory Seat Present	Not Set	
Heated Seat Material Type	Perforated Leather	
Stow 'n Assist Present - Driver	Not Set	
Stow 'n Assist Present - Passenger	Not Set	
Rear Heated Seats Present	Not Present	
Front Vented Seats Present	Not Present	
Heated Wheel Material Type	Full Leather	
Brake System ECU Configuration A	value 0	
ECO Mode Configuration	Remember Previous State with Ignition Key Cycle	
Dual Alternator Present	Not Set	
Connector F Pin 13: Left Sliding Door Switch Input (B-Pillar)	Left B-Pillar sliding Door Switch	
License Plate Lamp Disable	Not Set	
Connector G Pin 2: Fog Lamp Switch Input	Fog Lamp Switch	
Connector F Pin 34: Spare HSD	Not Present	
Connector F Pin 16: Passenger Door Lock Switch Input	Not Present	
Auto High Beam Module Location	None	
Engine Off Clear Time	180	Time

Connector F Pin 30: Fuel Door Lock (BUX)	Not Present	
Heatsoak Speed	15	Counter
Connector D Pin 8: Digital Spare Input #2	Not Present	
Ambient Stable Counter Limit	40	Counter
Max Engine Off Time	220	Time
Connector F Pin 29: Horn Switch Present	Horn Switch Input	
Connector F Pin 37: Vacuum Cleaner Power Saver Indicator	Not Present	
Connector E Pin 48 (Tied internally to Connector A Pin16): Rear Wiper Motor Control Output Present	Rear Wiper (0)	
Humidy Sensor Long Present	Set	
Connector E Pin 3: Left Rear Turn Signal	Left Rear Turn Signal	
Connector F Pin 14: Right Sliding Door Switch Input (B-Pillar)	Right B-Pillar Sliding Door Switch	
Connector G Pin11/Connector G Pin 12: Not Used	ERS	
Connector E Pin 28: Secondary Door Ajar Switch Present - PIN E-28	Set	
Manual Door Locks Present	Not Set	
Heatsoak Flush Time	105	Time
Rain Sensor Module #2 Present	Not Set	
CHMSL Lamp Output Disable	Not Set	
Connctor F Pin 33: Fuel Door Unlock (BUX)	Not Present	
Connector E Pin 39: Right Rear Turn Signal	Right Rear Turn Signal	
Connector F Pin 15: Driver Door Lock Switch Input	Not Present	
Connector D Pin 4: Digital Spare Input #1	Not Present	
Heatsoak Set Time	15	Time
Steering Smoothing Factor	Filter Off	
Nose Dive Threshold	Filter Off	
Brake Smoothing Factor	Filter Off	
Average Last Longitudinal Acceleration Values	No Averaging	
Excess Lateral Acceleration Factor	Filter Off	
Brake Smoothing Duration	Filter Off	
Steering Smoothing Duration	Filter Off	
Maximum Lateral Change	Filter Off	
Acceleration Threshold	Filter Off	
Nose Dive Factor	Filter Off	
Excess Longitudinal Acceleration Factor	Filter Off	
Brake Smoothing Threshold	Filter Off	
Acceleration Factor	Filter Off	
Average Last Lateral Acceleration Values	No Averaging	
Steering Smoothing Threshold	Filter Off	
Maximum Longitudinal Change	Filter Off	
VTA Hood Ajar Monitoring	Not Set	
RKE Auto-Relock Feature Enable	Not Set	
PE Auto-Relock Feature Enable	Set	
Auto High Beam ON Threshold	25 km/hr	
Auto High Beam OFF Threshold	20 km/hr	
Interior Lighting Night Threshold	4.45147	Volt

Interior Lighting Day Threshold	4.27498	Volt
Headlamp Soak Delay	1.0 sec	
Horn Chirp Duration	Short	
Parking Light Enable	Not Set	
Smart Alternator Present	Not Set	
Temperature Display Resolution	HaLF	
TPMS Configuration	Logic 1 NHTSA Enable Warning	
Sunroof Present	Not Set	
ANC Calibration Parameter Data Set	Non Amplified 3.6L PHEV	
Radio Speaker Open Circuit Disable (RF)	Set	
Drive Mode Version	Version 1	
Auto Dimming Mirror Hard Button Present	Set	
Radio Speaker Open Circuit Disable (LF)	Set	
Radio Speaker Open Circuit Disable (LR)	Set	
Radio Speaker Open Circuit Disable (RR)	Set	
Automatic Crash Notification Feature Present	Undefined	
Show Phone Information in Cluster	01	
Surround View Camera On/Off Softkey Present	Not Set	
Park Assist Tuning Set	Sahara	
3rd Row Lock CSO	Not Set	
Siren	Not Set	
Ultrasonics	Not Set	
Tilt	Not Set	
ESC	Set	
HCP	Set	
AHCP	Set	
ESM	Set	
ORC	Set	
APM	Set	
ECM	Set	
BPCM	Set	
OBCM	Set	
EAC	Set	
EBCM	Set	
CVPM	Not Set	
VRM	Not Set	
MSMP	Not Set	
AMP	Not Set	
HVAC	Set	
PDM	Set	
VTM	Not Set	
DDM	Set	
EOMR	Set	
EDM	Not Set	

ITM	Not Set	
DMRR	Set	
MSM	Not Set	
HVACR	Set	
EAM	Not Set	
ICS	Set	
DSM	Set	
PSDML	Set	
ANC	Set	
BCM (Interior Bus)	Set	
DTV	Not Set	
FSM	Not Set	
DMRL	Set	
PLGM	Set	
HSM	Set	
PSDMR	Set	
Radio	Set	
Compass Mounting Angle	0	Degree
IBS Present	Set	
Auto Relock Time	60	seconds
Fobik Safe Alerts Per Ignition Cycle	2	
Illuminated Approach Headlamp Target Percentage	125 (62.5%)	
Humidity Sensor Present	Set	
Illuminated Approach Taillamp Target Percentage	125 (62.5%)	
Illuminated Approach Interior Lighting Ramp Up Time	130(2600ms)	
Alert no Reply	Set	
Alert On Search Timeout	Set	
Alert On System Fault	Set	
Illuminated Approach Interior Lighting Target Percentage	100(50%)	
OHC Module Present	Set	
Washer Fluid Level Voltage Threshold	4.46 volts	
EVIC SWS Module Present	Set	
CRVMM Present	Set	
HFRM Present	Not Set	
VTA System Present	VTA	
Panic Enable	Set	
Compass Mounting Orientation	Rightside up	
Connector F Pin 41: Backup-Reverse lamp Left	Set	
Connector E Pin 7: Left HID Relay Control	Left HID Lamp Relay	
Connector D Pin 12: PHEV ECM Hardwire Wake Up	Engine Control Module Wake up (PHEV only)	
Connector D Pin 11: Stop/Turn Trailer Tow Left Output Present	Reserved	
Connector A Pin 11: Hood Ajar Switch Signal	500 ohm series and 500 ohm parallel resistors	
Connector D Pin 21: Brake Fluid Level Switch	no parallel resistor	

Connector E Pin 1: Backup-Reverse lamp Right	Set	
Connector E Pin 37: Right HID Relay Control	Right HID Lamp Relay	
Connector F Pin 5: Left Rear Fog Lamp	Output Disable	
Connector E Pin 3: Left Rear Turn Signal	Left Rear Turn Signal	
Connector F Pin 31: Right Sliding Door Ajar	Right Sliding Door Ajar	
Connector F Pin 28: Right Rear Turn Lamp Fault Sense	Disable	
Connector F Pin 4: Liftgate Release	Trunk/Liftgate Release	
Connector F Pin 42: Right Rear Turn Signal	Right Rear Turn Signal	
Connector F Pin 25: Left Rear Turn Lamp Fault Sense	Disable	
Stop/Start Enable Switch Present	Not Set	
Connector A Pin 2: Right High Beam Feed	Right High Beam (0)	
Connector D Pin 1: Left High Beam Feed	Left High Beam (0)	
Connector F Pin 27: Left Sliding Door Ajar	Left Sliding Door Ajar	
Connector E Pin 5: E-5 PHEV Fuel Door Switch Input	PHEV Fuel Door Switch	
Connector E Pin 39: Right Rear Fog Lamp	Output Disable	
Connector E Pin 29: Rear Wiper Motor Park Signal	Reserved	
Connector F Pin 29: Horn Switch Input	Horn Switch Input	
Passive Ped Pro Present	False	
Tow Hooks Present	False	
1st Row Seat Side Airbags Present	True	
Passenger Kneebag Present	True	
BUX Market	False	
ODS Present	False	
Curtain Airbags Present	True	
Driver Kneebag Present	True	
Integrated EPP Present	False	
IPC	Set	
ESM	Set	
ORC	Set	
BCM (PT)	Set	
SCCM	Set	
ACC	Not Set	
PCM	Set	
PTS	Set	
EPS	Set	
RFH	Set	
AHLM	Not Set	
ESL	Not Set	
FFCM	Not Set	
ABSO	Set	
OCM	Set	
ABS	Not Set	
TCM	Not Set	
HCP	Set	

Accessory Delay Time	45	seconds
Sliding Door Chime Enable	Set	
Sliding Door Alert	Not Set	
Auto Unlock	Set	
Headlamps on with Wipers	Set	
Flash Lamps on Lock	Set	
Daytime Running Lamps	Set	
Auto Wipers	Not Set	
Sound Horn On Lock Status	Chirp on 1st press/FIRST	
Hands Free Sliding Door Enable	Set	
Sound Horn on Remote Start	Set	
Auto Lock	Set	
Unlock all doors on 1st press	Set	
Sound Horn on Lock	Set	
Illuminated Approach Time	30	seconds
Headlamp Delay Time	30	seconds
Auto Highbeam	Not Set	
IBS Quiescence Current Limit	-250	mA
IBS Minimal Charge Limit	10	AmpHrs
IBS Minimum Voltage Limit	5.0	Volts
Battery Type II	255	
Battery Types	SNA	
IBS Activate MWU	Not Set	
IBS Minimum Charge Limit	600	mA
Front Park/Turn Voltage	Park to Turn ratio 55 Percent	
Left Front Corner Voltage	13.2 Volts	
Left Low Beam Voltage Regulation	13.6 Volts	
Right High Beam Voltage Regulation	13.8 Volts	
Left Rear Corner Voltage	14 Volts	
Left High Beam Voltage Regulation	13.6 Volts	
Right Rear Corner Voltage	14 Volts	
Right Low Beam Voltage Regulation	14 Volts	
Auto Headlamp On Threshold	3.31409	Volt
Auto Headlamp Off Threshold	2.54930	Volt
Right Front Corner Voltage	13.4 Volts	
Rear View Camera Static Grid Lines Enabled	Not Set	
Rear View Camera Dynamic Grid Lines Enabled	Set	

RADIO CONFIGURATION

NAME	VALUE	UNITS
Compass on the bus messaging Authorization	Allowed	
GPS on the Bus messaging Authorization	Allowed	
Satellite Subscription Suspend Day	—	
Satellite Subscription Reason Code	—	

Satellite Subscription Suspend Year	—	
Satellite Subscription Suspend Month	—	
Satellite Subscription Status	—	
Satellite Subscription ID	—	
Aux Jack	—	
USB Hubs Detected	—	No Unit
SD Card Readers Detected	—	No Unit
Enumerated USB Devices	—	No Unit
DTV Short Term Configuration	—	
911 Button	—	
SDARS	—	
Internal CD Player	—	
Application Framework	—	
Bluetooth	—	
Navigation Active	—	
FM Diversity	—	
Cellular	—	
Wi-Fi	—	
Splash Screen	—	
Anti-Theft Enable Status	—	
Automated Loudness	—	
Front Seat Video Playback	—	
Clock Defeat	—	
Cabin EQ Curve Number Currently Used by Radio	—	
12/24 Time Selection	—	

HVACR CONFIGURATION

NAME	VALUE	UNITS
Dual Zone MTC Control (BB)	False	
MTC heater only (3Knob)	False	
DualZone ATC Control (BB)	False	
MTC w EBL (3Knob)	False	
MTC wo EBL (3Knob)	False	
Single Zone MTC Control (BB)	False	
DualZone ATC Control (Factory) (BB)	False	

RCCC CONFIGURATION

NAME	VALUE	UNITS
MTC with EBL	False	
DualZone ATC Control	True	
MTC Heater Only	False	
Single Zone MTC Control	False	
Dual Zone MTC Control	False	
DualZone ATC Control	False	

MTC without EBL	False
-----------------	-------

ABSO CONFIGURATION

NAME	VALUE	UNITS
Engine Displacement	3.6	No Unit
ESC BLA Enabled	False	
PN ESC Byte2	0	
PN ESC Byte1	0	
Drive Configuration	2WD Front	
Dynamic Tire Circumference	89	inch
VC Chassis Type	Type 9	
Axle Ratio	3.251	No Unit
Hardwired VSO	True	
ACC	True	
Multiple Pressure Sensors	True	
Rear Directional Sensors	True	
Feature PIN	False	
Front Directional Sensors	False	
EPB	True	



VEHICLE SCAN REPORT

Vehicle 2020 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN [REDACTED]

Odometer 21379.5 miles
Publication Date Nov 5, 2021, 4:00:24 PM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	PART #
PCM	Powertrain Control Module	CAN-C	68444229AD	68444229AD
ICS	Integrated Center Stack	CAN-I	6UX601X8AA	6UX601X8AA
RFH	Radio Frequency Hub	CAN-C	68453559AB	68453559AB
ESM	Electronic Shifter	CAN-C	68240089AM	68240089AM
ORC	Occupant Restraint	CAN-C	68405567AC	68405567AC
EPS	Electric Power Steering	CAN-C	68460392AA	68460392AA
ANC	Active Noise Cancellation	CAN-I	68440556AB	68440556AB
HVAC	Heat, Ventilation and A/C	CAN-I	68447893AC	68447893AC
DDM	Driver Door Module	CAN-I	68424451AC	68424451AC
PDM	Passenger Door Module	CAN-I	68424450AC	68424450AC
DMRL	Door Module Rear Left	CAN-I	68225096AG	68225096AG
DMRR	Door Module Rear Right	CAN-I	68225096AG	68225096AG
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD	68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD	68369596AD
PLGM	Power Liftgate	CAN-I	68316094AF	68316094AF
CSWM	Comfort Seat Wheel Module	CAN-I	68434910AC	68434910AC
IPC	Instrument Panel Cluster	CAN-C	68434956AC	68434956AC
PTS	Parktronics	CAN-C	68193772AJ	68193772AJ
SCCM	Steering Column Control Module	CAN-C	68360889AD	68360889AD
BCM	Body Controller	CAN-C	68424601AD	68424601AD
RADIO	Radio	CAN-I	68461768AD	68461768AD

OCM	Occupant Classification	CAN-C	68403127AA		68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB		68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AB		04672786AB
RBSS	Right Blind Spot Sensor	CAN-I	04672786AB		04672786AB
APM	Accessory Power Module	CAN-C	05185046AB		05185046AB
BPCM	Battery Pack Control Module	CAN-C	05193166AD		05193166AD
HCP	Hybrid Control Processor	CAN-C	05190265AE		05190265AE
OBCM	On Board Charging Module	CAN-C	05185047AE		05185047AE
DSM	Display Screen Module	CAN-I	68316175AC		68316175AC
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA		6WL30DX9AA
EAC	Electric A/C Compressor	CAN-C	68237995AG		68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05190266AE		05190266AE
EBBM	Electronic Brake Booster Module	CAN-C	68461813AA		68461813AA
ABSO	Anti Lock Brakes OBD	CAN-C	68461812AA		68461812AA
SGW	Security Gateway Module	CAN-C	68447193AB		68447193AB

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	CVNS
PCM	USA	1B 47	46 02 06	4419	
ICS	USA	0F 0C 00	12 25 00	4400	
RFH	USA / USA	10 17 00	13 09 00	4A00	
ESM	USA / USA	0F 24 00	12 28 FF	4402	
ORC	USA / USA	11 1F 00	12 2B 00	4301	
EPS	USA / USA	12 2A 00	12 1E 01	4502	
ANC	USA	0F 05 01	12 2C 01	4210	
HVAC	USA	0E 09 00	13 05 01	4401	
DDM	USA	11 07 00	13 0B 00	4202	
PDM	USA	11 07 00	13 0B 00	4202	
DMRL	USA / USA	10 0B 00	12 0C 00	4201	
DMRR	USA / USA	10 0B 00	12 0C 00	4201	
PSDML	USA / USA	10 17 00	14 10 12	4001	
PSDMR	USA / USA	10 17 00	14 10 12	4001	
PLGM	USA	17 19 00	18 22 00	4202	
CSWM	USA	11 2A 00	13 2C 00	4302	
IPC	USA / USA	12 06 00	13 27 00	4704	

PTS	USA	0E 32 00	12 1F 00	4311	
SCCM	USA	13 28 00	13 29 00	4301	
BCM	USA	0D 11 00	13 0C 90	4415	
RADIO	USA	13 31 14	13 31 14	8205	
OCM	USA / USA	11 1F 01	0E 2F 02	4030	
HVACR	USA	0E 09 00	10 03 02	4301	
LBSS	USA / USA	11 30 02	12 0D 00	4202	
RBSS	USA / USA	11 30 02	12 0D 00	4202	
APM	USA / USA	11 32 00	11 32 00	4001	
BPCM	Not programmed / COUNTRY_SNA	0E 03 00	13 18 03	4005	
HCP	USA	11 1D 07	13 05 03	4005	C6F23FD5 E84E843F 050DC953
OBCM	USA	0F 0D 00	12 02 00	4002	
DSM	USA / USA	13 29 00	12 23 00	4000	
RCCC	USA	0F 1D 00	13 04 00	4000	
EAC	USA	0E 34 00	12 0F 00	4102	
AHCP	USA	11 1D 07	13 05 03	4000	
EBBM	USA	0E 19 02	12 31 17	4000	AD6A1E22
ABSO	USA	0E 15 02	12 2E 1E	4201	73EEDB6B
SGW		5	779	4103	

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
HVAC	B10EB-00	Blower Power Module-	Stored
RADIO	B280B-00	NTSC Video Input-	Stored
HCP	P0A3F-00	Drive Motor A Position Sensor 1 Circuit-	Active
HCP	P0A40-00	Drive Motor A Position Sensor 1 Circuit Range/Performance-	Stored
HCP	P0C01-00	Drive Motor A Current High-	Stored
HCP	P0C19-00	Drive Motor A Torque Delivered Performance-	Active
ABSO	C2222-00	Improper Powerdown-	Stored

ENVIRONMENTAL DATA SUMMARY

HVAC | B10EB-00 | Stored | Blower Power Module-

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	True	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	

Original Odometer Value	21375	miles
Most Recent Odometer Value	21375	miles
Frequency Counter	4	
Ignition Cycle Counter	1	

RADIO | B280B-00 | Stored | NTSC Video Input-

NAME	VALUE	UNITS
DTCTable	A8 0B 00	
TestFailed	False	
TestFailedThisMonitoringCycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed This Monitoring Cycle	False	
Warning Indicator Requested	False	
DTCExtendedDataRecordNumber	FF	
Occurance Flag	Occurrence	
Reserved	Reserved	
Original Odometer Value	0	miles
Most Recent Odometer Value	21375	miles
Frequency Counter	255	
Ignition Counter	1	
RDI \$6080	60 80	
Event Counter	63	

HCP | P0A3F-00 | Active | Drive Motor A Position Sensor 1 Circuit-

NAME	VALUE	UNITS
DTC	0A 3F 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	Occurrence	
Original Odometer Value	21379.5	miles
Most Recent Odometer Value	21379.5	miles
Frequency Counter	11	
Ignition Cycle Counter	0	
Real time clock	39387368	sec
RAM stamps keyOn	0	sec
RAM Stamps	146588	Min
Accelerator Pedal Position	0	%

Brake Switch Status	Applied	
PHEV Charging Status	No Charging	
Engine Speed	431	rpm
HV Battery SOC	23	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Motor A Temp Sensor	52	°F
Motor B Temp Sensor	50	°F
Barometric Pressure	15	PSI
Engine Coolant Temperature	52	°F
Motor A Resolver Offset Learn Erase	not requested	
Motor A Resolver Offset Learning Status Flag	Applied	
Motor B Resolver Offset Learning Status Flag	Applied	
Motor A Resolver Angle Offset	3.20	Degree
Motor B Resolver Angle Offset	2.00	Degree
Motor A Resolver Supply Voltage Value	15.75	Volts
Motor B Resolver Supply Voltage Value	15.75	Volts
Motor A Resolver to Digital Low Level Driver Faults	Resolver Loss of Signal	
Motor B Resolver to Digital Low Level Driver Faults	No fault	
Battery Feed Voltage 2 Sense	13.536	Volts
Internal EPS Voltage Sense A	8.136	Volts
Internal EPS Voltage Sense B	8.136	Volts
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	39.086	Ft-Lbs
Available Motor Torque - Motor A	74.576	Ft-Lbs
Available Motor Torque - Motor B	232.485	Ft-Lbs
Available Regen Torque - Motor A	-1.936	Ft-Lbs
Available Regen Torque - Motor B	-232.485	Ft-Lbs
Commanded Torque - Motor A	23.875	Ft-Lbs
Commanded Torque - Motor B	30.973	Ft-Lbs
Electric Motor A Speed	818.5	rpm
Electric Motor B Speed	2.5	rpm
Battery Feed Voltage 1 Sense	13.608	Volts
Battery Feed Voltage 3 Sense	13.464	Volts
Hybrid System State	SNA	
Motor A - Inverter Current - phase A	-112	AMP
Motor A - Inverter Current - phase B	-28	AMP
Motor A - Inverter Current - phase C	136	AMP
Motor B - Inverter Current - phase A	-8	AMP
Motor B - Inverter Current - phase B	-28	AMP
Motor B - Inverter Current - phase C	24	AMP
Outside Air Temperature	57.2	°F

HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
EPT LOC Diag Enable	Enable Limited LOC Diagnostic	
HV Contactor Status	Closed	
HV Battery Voltage from BPCM	343.30	Volts
PIM DC Link Voltage - A	344	Volts
PIM DC Link Voltage - B	343	Volts
Inverter A IGBT Temperature for phase A	54	°F
Inverter A IGBT Temperature for phase B	55	°F
Inverter A IGBT Temperature for phase C	57	°F
Inverter B IGBT Temperature for phase A	57	°F
Inverter B IGBT Temperature for phase B	52	°F
Inverter B IGBT Temperature for phase C	54	°F
APM Status	Off	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	0	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	39.086	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Motor B Resolver Offset Learn Erase	not requested	
GPS Date - Year	0	Year
GPS Date - Month	1	
GPS Date - Day	1	Days
UTC Time - Hours	0	Hours
UTC Time - Minutes	0	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	0	ms

HCP | P0A40-00 | Stored | Drive Motor A Position Sensor 1 Circuit Range/Performance-

NAME	VALUE	UNITS
DTC	0A 40 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Occurrence	
Original Odometer Value	21379.5	miles

Most Recent Odometer Value	21379.5	miles
Frequency Counter	2	
Ignition Cycle Counter	0	
Real time clock	39206504	sec
RAM stamps keyOn	0	sec
RAM Stamps	146567	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Applied	
PHEV Charging Status	No Charging	
Engine Speed	600	rpm
HV Battery SOC	23	%
Ignition State	Ignition Off/ACC	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Motor A Temp Sensor	77	°F
Motor B Temp Sensor	90	°F
Barometric Pressure	13	PSI
Engine Coolant Temperature	93	°F
Motor A Resolver Offset Learn Erase	not requested	
Motor A Resolver Offset Learning Status Flag	Applied	
Motor B Resolver Offset Learning Status Flag	Applied	
Motor A Resolver Angle Offset	3.20	Degree
Motor B Resolver Angle Offset	2.00	Degree
Motor A Resolver Supply Voltage Value	15.75	Volts
Motor B Resolver Supply Voltage Value	15.75	Volts
Motor A Resolver to Digital Low Level Driver Faults	Resolver Loss of Track	
Motor B Resolver to Digital Low Level Driver Faults	No fault	
Battery Feed Voltage 2 Sense	12.024	Volts
Internal EPS Voltage Sense A	8.136	Volts
Internal EPS Voltage Sense B	8.136	Volts
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.092	Ft-Lbs
Available Motor Torque - Motor A	70.151	Ft-Lbs
Available Motor Torque - Motor B	233.868	Ft-Lbs
Available Regen Torque - Motor A	0.000	Ft-Lbs
Available Regen Torque - Motor B	-233.868	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Electric Motor A Speed	1697.0	rpm
Electric Motor B Speed	-3.0	rpm
Battery Feed Voltage 1 Sense	12.096	Volts
Battery Feed Voltage 3 Sense	12.024	Volts
Hybrid System State	SNA	

Motor A - Inverter Current - phase A	-16	AMP
Motor A - Inverter Current - phase B	132	AMP
Motor A - Inverter Current - phase C	-124	AMP
Motor B - Inverter Current - phase A	-8	AMP
Motor B - Inverter Current - phase B	-4	AMP
Motor B - Inverter Current - phase C	0	AMP
Outside Air Temperature	60.8	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
EPT LOC Diag Enable	Disable LOC Daignostic	
HV Contactor Status	Closed	
HV Battery Voltage from BPCM	344.10	Volts
PIM DC Link Voltage - A	344	Volts
PIM DC Link Voltage - B	344	Volts
Inverter A IGBT Temperature for phase A	32	°F
Inverter A IGBT Temperature for phase B	32	°F
Inverter A IGBT Temperature for phase C	32	°F
Inverter B IGBT Temperature for phase A	32	°F
Inverter B IGBT Temperature for phase B	32	°F
Inverter B IGBT Temperature for phase C	32	°F
APM Status	Off	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	0	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.092	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Motor B Resolver Offset Learn Erase	not requested	
GPS Date - Year	0	Year
GPS Date - Month	1	
GPS Date - Day	1	Days
UTC Time - Hours	0	Hours
UTC Time - Minutes	0	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	0	ms

HCP | P0C01-00 | Stored | Drive Motor A Current High-

NAME	VALUE	UNITS
DTC	0C 01 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	

Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	True	
Warning Indicator Requested	True	
Occurrence flag	Occurrence	
Original Odometer Value	21379.5	miles
Most Recent Odometer Value	21379.5	miles
Frequency Counter	5	
Ignition Cycle Counter	0	
Real time clock	39295508	sec
RAM stamps keyOn	0	sec
RAM Stamps	146583	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Applied	
PHEV Charging Status	No Charging	
Engine Speed	464	rpm
HV Battery SOC	23	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Barometric Pressure	15	PSI
Engine Coolant Temperature	43	°F
Actual Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor A	71.995	Ft-Lbs
Inverter A Input DC Current	0.0	AMP
Electric Motor A Speed	672.5	rpm
Motor A - Inverter Current - phase A	48	AMP
Motor A - Inverter Current - phase B	-148	AMP
Motor A - Inverter Current - phase C	96	AMP
Motor A Phase U Short Fault - High-Side	False	
Motor A Phase U Cross Conduction Fault - High-Side	False	
Motor A Phase U Over Current Fault - High-Side	True	
Motor A Phase U Thermal Warning Fault - High-Side	False	
Motor A Phase U Thermal Shutdown Fault - High-Side	False	
Motor A Phase U Comm Error High Voltage Regulator Fault - High-Side	False	
Motor A Phase U Comm Error Low Voltage Regulator Fault - High-Side	False	
Motor A Phase U SPI Error Fault - High-Side	False	
Motor A Phase U Hardware Error Fault - High-Side	False	
Motor A Phase U Short Fault - Low-Side	False	
Motor A Phase U Cross Conduction Fault - Low-Side	False	
Motor A Phase U Over Current Fault - Low-Side	True	
Motor A Phase U Thermal Warning Fault - Low-Side	False	

Motor A Phase U Thermal Shutdown Fault - Low-Side	False	
Motor A Phase U SPI Error Fault - Low-Side	False	
Motor A Phase U Hardware Error Fault - Low-Side	False	
Motor A Phase V Short Fault - High-Side	False	
Motor A Phase V Cross Conduction Fault - High-Side	False	
Motor A Phase V Over Current Fault - High-Side	False	
Motor A Phase V Thermal Warning Fault - High-Side	False	
Motor A Phase V Thermal Shutdown Fault - High-Side	False	
Motor A Phase V Comm Error High Voltage Regulator Fault - High-Side	False	
Motor A Phase V Comm Error Low Voltage Regulator Fault - High-Side	False	
Motor A Phase V SPI Error Fault - High-Side	False	
Motor A Phase V Hardware Error Fault - High-Side	False	
Motor A Phase V Short Fault - Low-Side	False	
Motor A Phase V Cross Conduction Fault - Low-Side	False	
Motor A Phase V Over Current Fault - Low-Side	False	
Motor A Phase V Thermal Warning Fault - Low-Side	False	
Motor A Phase V Thermal Shutdown Fault - Low-Side	False	
Motor A Phase V SPI Error Fault - Low-Side	False	
Motor A Phase V Hardware Error Fault - Low-Side	False	
Motor A Phase W Short Fault - High-Side	False	
Motor A Phase W Over Current Fault - High-Side	False	
Motor A Phase W Thermal Warning Fault - High-Side	False	
Motor A Phase W Thermal Shutdown Fault - High-Side	False	
Motor A Phase W Comm Error Low Voltage Regulator Fault - High-Side	False	
Motor A Phase W SPI Error Fault - High-Side	False	
Motor A Phase W Hardware Error Fault - High-Side	False	
Motor A Phase W Short Fault - Low-Side	False	
Motor A Phase W Cross Conduction Fault - Low-Side	False	
Motor A Phase W Over Current Fault - Low-Side	False	
Motor A Phase W Thermal Warning Fault - Low-Side	False	
Motor A Phase W Thermal Shutdown Fault - Low-Side	False	
Motor A Phase W Comm Error Low Voltage Regulator Fault - Low-Side	False	
Motor A Phase W SPI Error Fault - Low-Side	False	
Motor A Phase W Hardware Error Fault - Low-Side	False	
Motor A Resolver Supply Voltage Value	15.75	Volts
Battery Feed Voltage 2 Sense	13.680	Volts
Battery Feed Voltage 3 Sense	13.536	Volts
Internal EPS Voltage Sense A	8.136	Volts
Internal EPS Voltage Sense B	8.136	Volts
Hybrid System State	SNA	
PIM DC Link Voltage - A	344	Volts
PIM DC Link Voltage - B	344	Volts
Passive Pump Coolant Temp In Sensor	48	°F
Low Temp Active Pump Speed	0	rpm

High Temp Aux Pump - Actual Speed	1272	rpm
Outside Air Temperature	51.8	°F
HV Contactor Status	Closed	
Inverter B Status Feedback	Normal Off with HV Request	
Battery Feed Voltage 1 Sense	13.680	Volts
Actual Torque - Motor B	0.461	Ft-Lbs
Available Motor Torque - Motor B	234.698	Ft-Lbs
Available Regen Torque - Motor A	0.000	Ft-Lbs
Available Regen Torque - Motor B	-234.698	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor B - Inverter Current - phase A	0	AMP
Motor B - Inverter Current - phase B	0	AMP
Motor B - Inverter Current - phase C	-4	AMP
Motor B Resolver Angle	316	Degree
Motor B Temp Sensor	77	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
EPT LOC Diag Enable	Disable LOC Daignostic	
HV Battery Voltage from BPCM	344.20	Volts
Electric Motor B Speed	-11.5	rpm
Inverter A IGBT Temperature for phase A	32	°F
Inverter A IGBT Temperature for phase B	32	°F
Inverter A IGBT Temperature for phase C	32	°F
Inverter B IGBT Temperature for phase A	32	°F
Inverter B IGBT Temperature for phase B	32	°F
Inverter B IGBT Temperature for phase C	32	°F
APM Status	Off	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	0	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.461	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Commanded Inverter A State	Inverter Disabled	
Inverter Status Feedback	Inverter Faulted	
Motor A Phase U Over Voltage Fault VH - High-Side	False	
Motor A Phase U Under Voltage Fault VH - High-Side	False	
Motor A Phase U Over Voltage Fault VL - High-Side	False	
Motor A Phase U Under Voltage Fault VL - High-Side	False	
Motor A Phase U Over Voltage Fault VDD - High-Side	False	
Motor A Phase U Under Voltage Fault VDD - High-Side	False	

Motor A Phase U Over Voltage Fault VH - Low-Side	False	
Motor A Phase U Under Voltage Fault VH - Low-Side	False	
Motor A Phase U Over Voltage Fault VL - Low-Side	False	
Motor A Phase U Under Voltage Fault VL - Low-Side	False	
Motor A Phase U Over Voltage Fault VDD - Low-Side	False	
Motor A Phase U Under Voltage Fault VDD - Low-Side	False	
Motor A Phase U Comm Error High Voltage Regulator Fault - Low-Side	False	
Motor A Phase U Comm Error Low Voltage Regulator Fault - Low-Side	False	
Motor A Phase V Over Voltage Fault VH - High-Side	False	
Motor A Phase V Under Voltage Fault VH - High-Side	False	
Motor A Phase V Over Voltage Fault VL - High-Side	False	
Motor A Phase V Under Voltage Fault VL - High-Side	False	
Motor A Phase V Over Voltage Fault VDD - High-SideSide	False	
Motor A Phase V Under Voltage Fault VDD - High-Side	False	
Motor A Phase V Over Voltage Fault VH - Low-Side	False	
Motor A Phase V Under Voltage Fault VH - Low-Side	False	
Motor A Phase V Over Voltage Fault VL - Low-Side	False	
Motor A Phase V Under Voltage Fault VL - Low-Side	False	
Motor A Phase V Over Voltage Fault VDD - Low-Side	False	
Motor A Phase V Under Voltage Fault VDD - Low-Side	False	
Motor A Phase V Comm Error High Voltage Regulator Fault - Low-Side	False	
Motor A Phase V Comm Error Low Voltage Regulator Fault - Low-Side	False	
Motor A Phase W Cross Conduction Fault - High-Side	False	
Motor A Phase W Over Voltage Fault VH - High-Side	False	
Motor A Phase W Under Voltage Fault VH - High-Side	False	
Motor A Phase W Over Voltage Fault VL - High-Side	False	
Motor A Phase W Under Voltage Fault VL - High-Side	False	
Motor A Phase W Over Voltage Fault VDD - High-Side	False	
Motor A Phase W Under Voltage Fault VDD - High-Side	False	
Motor A Phase W Comm Error High Voltage Regulator Fault - High-Side	False	
Motor A Phase W Over Voltage Fault VH - Low-Side	False	
Motor A Phase W Under Voltage Fault VH - Low-Side	False	
Motor A Phase W Over Voltage Fault VL - Low-Side	False	
Motor A Phase W Under Voltage Fault VL - Low-Side	False	
Motor A Phase W Over Voltage Fault VDD - Low-Side	False	
Motor A Phase W Under Voltage Fault VDD - Low-Side	False	
Motor A Phase W Comm Error High Voltage Regulator Fault - Low-Side	False	
Inverter A Status Feedback	Inverter Faulted	
GPS Date - Year	0	Year
GPS Date - Month	1	
GPS Date - Day	1	Days
UTC Time - Hours	0	Hours
UTC Time - Minutes	0	
UTC Time - Seconds	0	seconds

ECU Time - Milliseconds

0

ms

HCP | P0C19-00 | Active | Drive Motor A Torque Delivered Performance-

NAME	VALUE	UNITS
DTC	0C 19 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	Occurrence	
Original Odometer Value	21379.5	miles
Most Recent Odometer Value	21379.5	miles
Frequency Counter	14	
Ignition Cycle Counter	0	
Real time clock	39387368	sec
RAM stamps keyOn	0	sec
RAM Stamps	146588	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Applied	
PHEV Charging Status	No Charging	
Engine Speed	431	rpm
HV Battery SOC	23	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Barometric Pressure	15	PSI
Engine Coolant Temperature	52	°F
Actual Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor A	75.313	Ft-Lbs
Inverter A Input DC Current	0.0	AMP
Electric Motor A Speed	811.0	rpm
Motor A - Inverter Current - phase A	-128	AMP
Motor A - Inverter Current - phase B	144	AMP
Motor A - Inverter Current - phase C	-20	AMP
Motor A Phase U Short Fault - High-Side	False	
Motor A Phase U Cross Conduction Fault - High-Side	False	
Motor A Phase U Over Current Fault - High-Side	True	
Motor A Phase U Thermal Warning Fault - High-Side	False	
Motor A Phase U Thermal Shutdown Fault - High-Side	False	

Motor A Phase U Comm Error High Voltage Regulator Fault - High-Side	False	
Motor A Phase U Comm Error Low Voltage Regulator Fault - High-Side	False	
Motor A Phase U SPI Error Fault - High-Side	False	
Motor A Phase U Hardware Error Fault - High-Side	False	
Motor A Phase U Short Fault - Low-Side	False	
Motor A Phase U Cross Conduction Fault - Low-Side	False	
Motor A Phase U Over Current Fault - Low-Side	True	
Motor A Phase U Thermal Warning Fault - Low-Side	False	
Motor A Phase U Thermal Shutdown Fault - Low-Side	False	
Motor A Phase U SPI Error Fault - Low-Side	False	
Motor A Phase U Hardware Error Fault - Low-Side	False	
Motor A Phase V Short Fault - High-Side	False	
Motor A Phase V Cross Conduction Fault - High-Side	False	
Motor A Phase V Over Current Fault - High-Side	False	
Motor A Phase V Thermal Warning Fault - High-Side	False	
Motor A Phase V Thermal Shutdown Fault - High-Side	False	
Motor A Phase V Comm Error High Voltage Regulator Fault - High-Side	False	
Motor A Phase V Comm Error Low Voltage Regulator Fault - High-Side	False	
Motor A Phase V SPI Error Fault - High-Side	False	
Motor A Phase V Hardware Error Fault - High-Side	False	
Motor A Phase V Short Fault - Low-Side	False	
Motor A Phase V Cross Conduction Fault - Low-Side	False	
Motor A Phase V Over Current Fault - Low-Side	False	
Motor A Phase V Thermal Warning Fault - Low-Side	False	
Motor A Phase V Thermal Shutdown Fault - Low-Side	False	
Motor A Phase V SPI Error Fault - Low-Side	False	
Motor A Phase V Hardware Error Fault - Low-Side	False	
Motor A Phase W Short Fault - High-Side	False	
Motor A Phase W Over Current Fault - High-Side	False	
Motor A Phase W Thermal Warning Fault - High-Side	False	
Motor A Phase W Thermal Shutdown Fault - High-Side	False	
Motor A Phase W Comm Error Low Voltage Regulator Fault - High-Side	False	
Motor A Phase W SPI Error Fault - High-Side	False	
Motor A Phase W Hardware Error Fault - High-Side	False	
Motor A Phase W Short Fault - Low-Side	False	
Motor A Phase W Cross Conduction Fault - Low-Side	False	
Motor A Phase W Over Current Fault - Low-Side	False	
Motor A Phase W Thermal Warning Fault - Low-Side	False	
Motor A Phase W Thermal Shutdown Fault - Low-Side	False	
Motor A Phase W Comm Error Low Voltage Regulator Fault - Low-Side	False	
Motor A Phase W SPI Error Fault - Low-Side	False	
Motor A Phase W Hardware Error Fault - Low-Side	False	
Motor A Resolver Supply Voltage Value	15.75	Volts
Battery Feed Voltage 2 Sense	13.536	Volts

Battery Feed Voltage 3 Sense	13.464	Volts
Internal EPS Voltage Sense A	8.136	Volts
Internal EPS Voltage Sense B	8.136	Volts
Hybrid System State	SNA	
PIM DC Link Voltage - A	344	Volts
PIM DC Link Voltage - B	343	Volts
Passive Pump Coolant Temp In Sensor	55	°F
Low Temp Active Pump Speed	0	rpm
High Temp Aux Pump - Actual Speed	312	rpm
Outside Air Temperature	57.2	°F
HV Contactor Status	Closed	
Inverter B Status Feedback	Normal On	
Battery Feed Voltage 1 Sense	13.608	Volts
Actual Torque - Motor B	43.326	Ft-Lbs
Available Motor Torque - Motor B	232.393	Ft-Lbs
Available Regen Torque - Motor A	-2.581	Ft-Lbs
Available Regen Torque - Motor B	-232.393	Ft-Lbs
Commanded Torque - Motor A	27.747	Ft-Lbs
Commanded Torque - Motor B	35.398	Ft-Lbs
Motor B - Inverter Current - phase A	64	AMP
Motor B - Inverter Current - phase B	-24	AMP
Motor B - Inverter Current - phase C	-52	AMP
Motor B Resolver Angle	256	Degree
Motor B Temp Sensor	50	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
EPT LOC Diag Enable	Enable Limited LOC Diagnostic	
HV Battery Voltage from BPCM	343.30	Volts
Electric Motor B Speed	2.0	rpm
Inverter A IGBT Temperature for phase A	54	°F
Inverter A IGBT Temperature for phase B	55	°F
Inverter A IGBT Temperature for phase C	57	°F
Inverter B IGBT Temperature for phase A	57	°F
Inverter B IGBT Temperature for phase B	52	°F
Inverter B IGBT Temperature for phase C	54	°F
APM Status	Off	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	0	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	43.326	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days

Commanded Inverter A State	Torque Control	
Inverter Status Feedback	Inverter Faulted	
Motor A Phase U Over Voltage Fault VH - High-Side	False	
Motor A Phase U Under Voltage Fault VH - High-Side	False	
Motor A Phase U Over Voltage Fault VL - High-Side	False	
Motor A Phase U Under Voltage Fault VL - High-Side	False	
Motor A Phase U Over Voltage Fault VDD - High-Side	False	
Motor A Phase U Under Voltage Fault VDD - High-Side	False	
Motor A Phase U Over Voltage Fault VH - Low-Side	False	
Motor A Phase U Under Voltage Fault VH - Low-Side	False	
Motor A Phase U Over Voltage Fault VL - Low-Side	False	
Motor A Phase U Under Voltage Fault VL - Low-Side	False	
Motor A Phase U Over Voltage Fault VDD - Low-Side	False	
Motor A Phase U Under Voltage Fault VDD - Low-Side	False	
Motor A Phase U Comm Error High Voltage Regulator Fault - Low-Side	False	
Motor A Phase U Comm Error Low Voltage Regulator Fault - Low-Side	False	
Motor A Phase V Over Voltage Fault VH - High-Side	False	
Motor A Phase V Under Voltage Fault VH - High-Side	False	
Motor A Phase V Over Voltage Fault VL - High-Side	False	
Motor A Phase V Under Voltage Fault VL - High-Side	False	
Motor A Phase V Over Voltage Fault VDD - High-SideSide	False	
Motor A Phase V Under Voltage Fault VDD - High-Side	False	
Motor A Phase V Over Voltage Fault VH - Low-Side	False	
Motor A Phase V Under Voltage Fault VH - Low-Side	False	
Motor A Phase V Over Voltage Fault VL - Low-Side	False	
Motor A Phase V Under Voltage Fault VL - Low-Side	False	
Motor A Phase V Over Voltage Fault VDD - Low-Side	False	
Motor A Phase V Under Voltage Fault VDD - Low-Side	False	
Motor A Phase V Comm Error High Voltage Regulator Fault - Low-Side	False	
Motor A Phase V Comm Error Low Voltage Regulator Fault - Low-Side	False	
Motor A Phase W Cross Conduction Fault - High-Side	False	
Motor A Phase W Over Voltage Fault VH - High-Side	False	
Motor A Phase W Under Voltage Fault VH - High-Side	False	
Motor A Phase W Over Voltage Fault VL - High-Side	False	
Motor A Phase W Under Voltage Fault VL - High-Side	False	
Motor A Phase W Over Voltage Fault VDD - High-Side	False	
Motor A Phase W Under Voltage Fault VDD - High-Side	False	
Motor A Phase W Comm Error High Voltage Regulator Fault - High-Side	False	
Motor A Phase W Over Voltage Fault VH - Low-Side	False	
Motor A Phase W Under Voltage Fault VH - Low-Side	False	
Motor A Phase W Over Voltage Fault VL - Low-Side	False	
Motor A Phase W Under Voltage Fault VL - Low-Side	False	
Motor A Phase W Over Voltage Fault VDD - Low-Side	False	
Motor A Phase W Under Voltage Fault VDD - Low-Side	False	

Motor A Phase W Comm Error High Voltage Regulator Fault - Low-Side	False	
Inverter A Status Feedback	Inverter Faulted	
GPS Date - Year	0	Year
GPS Date - Month	1	
GPS Date - Day	1	Days
UTC Time - Hours	0	Hours
UTC Time - Minutes	0	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	0	ms

ABS0 | C2222-00 | Stored | Improper Powerdown-

NAME	VALUE	UNITS
DTC	62 22 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	False	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	
Controller Event	No	
Mirror Memory	No	
Undervoltage Suspected	No	
Original Odometer Value	0	miles
Most Recent Odometer Value	0	miles
Frequency Counter	1	
Ignition Cycle Counter	0	
Fault Time	0.00	S
Current System Mode	CAN active	
Previous System Mode	CAN active	
System Condition	OK	
Supply Voltage Valves	12.3	V
Brake Pedal Status	Released	
Supply voltage Pump	10.0	V
Brake Pedal Travel Sensor Position	0	%
Ignition Unfiltered	0.0	V
Wheel Speed Left Front	0.000	MPH
Rotation Direction Left Front	Forward	
Wheel Speed Right Front	0.000	MPH
Rotation Direction Right Front	Forward	
Wheel Speed Left Rear	0.000	MPH
Rotation Direction Left Rear	Forward	

Wheel Speed Right Rear	0.000	MPH
Rotation Direction Right Rear	Forward	
Steering Wheel Angle	0.00	°
Longitudinal Acceleration	0.00	m/s^2
Lateral Acceleration	0.00	m/s^2
Yaw Rate	0.000	°/s
Primary Circuit Pressure	0.00	PSI
Engine Speed	0.0	rpm
Accelerator Pedal Position	0.0	%
ABS control	Not Active	
ASR control	Not Active	
MSR control	Not Active	
EBV control	Not Active	
ESP Control	Not Active	
HSA control	Not Active	
HBA control	Not Active	
Hold	No	
Braking assistance system	No assistance system is braking	
Plant Mode	No	
EPB Mode Status	Limp Home	
BLS High	No	
BLS Low	Yes	
Park Brake	Not Activated	
ESP-OFF mode	No	
Clutch	Not Activated	
Stop Coordinator Active	No	
Actual Gear	N	
Transmission selector lever setting	P	
Status Parking Brake Left	Brake is in an Unknown State	
Status Parking Brake Right	Brake is in an Unknown State	
EPB Switch Status	Idle	
Supplier Internal Code	140	

SNAPSHOT DATA SUMMARY

No Snapshot Data available for B10EB-00

No Snapshot Data available for B280B-00

No Snapshot Data available for P0A3F-00

No Snapshot Data available for P0A40-00

No Snapshot Data available for P0C01-00

No Snapshot Data available for P0C19-00

No Snapshot Data available for C2222-00

