

This file represents a consolidation of multiple files sent by the manufacturer. Please use the bookmarks to navigate to each file. (Each bookmark label is the name of the original file.)



CONFIGURATION REPORT

Vehicle 2021 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN [REDACTED]

Odometer 97.9 miles
Publication Date Apr 5, 2022, 11:57:27 AM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
PCM	Powertrain Control Module	CAN-C	68499122AF	[REDACTED]	[REDACTED]	68499122AF
PLGM	Power Liftgate	CAN-I	68466171AI	[REDACTED]	—	68466171AI
ICS	Integrated Center Stack	CAN-I	7AS341X8AA	[REDACTED]	[REDACTED]	7AS341X8AA
RFH	Radio Frequency Hub	CAN-C	68500152AA	[REDACTED]	[REDACTED]	68500152AA
ESM	Electronic Shifter	CAN-C	68240089AN	[REDACTED]	[REDACTED]	68240089AN
ORC	Occupant Restraint	CAN-C	68526665AB	[REDACTED]	[REDACTED]	68526665AB
EPS	Electric Power Steering	CAN-C	68460392AA	[REDACTED]	[REDACTED]	68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68493454AE	[REDACTED]	[REDACTED]	68493454AE
DDM	Driver Door Module	CAN-I	68496463AB	[REDACTED]	[REDACTED]	68496463AB
PDM	Passenger Door Module	CAN-I	68496462AB	[REDACTED]	[REDACTED]	68496462AB
DMRL	Door Module Rear Left	CAN-I	68508894AB	[REDACTED]	[REDACTED]	68508894AB
DMRR	Door Module Rear Right	CAN-I	68508894AB	[REDACTED]	[REDACTED]	68508894AB
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD	[REDACTED]	[REDACTED]	68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD	[REDACTED]	[REDACTED]	68369596AD
MSM	Memory Seat Module	CAN-I	68321862AC	[REDACTED]	[REDACTED]	68321862AC
CSWM	Comfort Seat Wheel Module	CAN-I	68517013AB	[REDACTED]	[REDACTED]	68517013AB
AMP	Amplifier	CAN-I	68547722AB	[REDACTED]	[REDACTED]	68547722AB
IPC	Instrument Panel Cluster	CAN-C	68434960AF	[REDACTED]	[REDACTED]	68434960AF
PTS	Parktronics	CAN-C	68485862AB	[REDACTED]	[REDACTED]	68485862AB

SCCM	Steering Column Control Module	CAN-C	68531525AA			68531525AA
BCM	Body Controller	CAN-C	68491085AG			68491085AG
ACC	Adaptive Cruise Control	CAN-C	68540436AC			68540436AC
RADIO	Radio	CAN-I	68465292AE			68465292AE
OCM	Occupant Classification	CAN-C	68403127AA			68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB			68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AC			04672786AC
RBSS	Right Blind Spot Sensor	CAN-I	04672786AC			04672786AC
FFCM	Forward Facing Camera Module	CAN-C	68551091AA			68551091AA
EDM	External Disc Module	CAN-I	68499745AA			68499745AA
APM	Accessory Power Module	CAN-C	05185046AB			05185046AB
BPCM	Battery Pack Control Module	CAN-C	68487194AA			68487194AA
HCP	Hybrid Control Processor	CAN-C	05185116AJ			05185116AJ
OBCM	On Board Charging Module	CAN-C	05185047AE			05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC			68321862AC
DSM	Display Screen Module	CAN-I	68437339AF			68437339AF
VRM	Video Routing Module	CAN-I	68493702AD			68493702AD
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA			6WL30DX9AA
CVPM	Central vision processing module	CAN-I	56029920AB			56029920AB
EAC	Electric A/C Compressor	CAN-C	68237995AG			68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05185117AJ			05185117AJ
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB			68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68471122AD			68471122AD
SGW	Security Gateway Module	CAN-C	68488429AB			68488429AB
TBM2	Telematic Box Module 2	CAN-C	68444865AH			68444865AH

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	CVNS
-----	--------------	------------------	------------------	-------	------

PCM	USA	1B 47	75 02 00	4422	7DC2E312
PLGM	USA	0	5084	000200000034	
ICS	USA	0F 0C 00	13 31 01	4700	
RFH	USA / USA	10 17 00	13 26 00	4A00	
ESM	USA / USA	13 02 00	14 23 FF	4402	
ORC	USA / USA	14 06 00	14 12 00	4301	
EPS	USA / USA	12 2A 00	12 1E 01	4502	
HVAC	USA	0E 09 00	14 2F 01	4401	
DDM	USA	11 07 00	14 07 00	4202	
PDM	USA	11 07 00	14 07 00	4202	
DMRL	USA / USA	10 0B 00	14 08 00	4201	
DMRR	USA / USA	10 0B 00	14 08 00	4201	
PSDML	USA / USA	10 17 00	14 10 12	4001	
PSDMR	USA / USA	10 17 00	14 10 12	4001	
MSM	USA	0F 2B 00	10 27 03	4101	
CSWM	USA	11 2A 00	14 25 00	4302	
AMP	USA	0F 06 01	15 0F 01	4021	
IPC	USA / USA	12 06 00	14 34 00	4705	
PTS	USA	0E 32 00	15 05 00	4311	
SCCM	USA	13 28 00	13 29 00	4301	
BCM	USA	0D 11 00	14 26 90	4420	
ACC	USA / USA	14 2A 01	15 23 02	4400	
RADIO		65	5671	000200000008	
OCM	USA / USA	11 1F 01	0E 2F 02	4030	
HVACR	USA	0E 09 00	10 03 02	4301	
LBSS	USA / USA	11 30 02	15 08 00	4202	
RBSS	USA / USA	11 30 02	15 08 00	4202	
FFCM	USA / USA	11 06 00	15 0C 00	4102	
EDM	USA	12 0A 00	11 08 00	4000	
APM	USA / USA	11 32 00	11 32 00	4001	
BPCM		0E 03 00	13 12 00	4005	D3037C3A
HCP	USA	11 1F 04	0F 2D 00	4006	5D31A9B9 16AACD23 050DC953
OBCM	USA	0F 0D 00	12 02 00	4002	
MSMP	USA	0F 2B 00	10 27 03	4001	
DSM	USA / USA	14 0C 00	15 06 00	4300	
VRM	USA / USA	0F 1C 00	15 0E 12	4001	
RCCC	USA	0F 1D 00	13 04 00	4000	
CVPM	USA / USA	11 27 01	14 0C 01	4004	
EAC	USA	0E 34 00	12 0F 00	4102	
AHCP	USA	11 1F 04	0F 2D 00	4000	
EBBM	USA	0E 19 02	14 0D 18	4000	E5898FA5
ABSO	USA	0E 15 02	14 1B 26	4201	4F158D1B
SGW		5	969	4103	

TBM2	USA	13 0E 02	14 2A 5F	4104	
------	-----	----------	----------	------	--

CONFIGURATION

PCM CONFIGURATION

NAME	VALUE	UNITS
Secondary Mass Airflow Sensor Equipped	False	
Active Exhaust Pressure Sensor Equipped	False	
Active Exhaust Valve(s) Equipped	False	
Electronic Parking Brake Equipped	True	
Heater Temp Control Valve Equipped	False	
Wastegate HBridge Equipped	False	
Aux Coolant Pump Heater Equipped	False	
Mechanical Coolant Pump Equipped	False	
High Side Port Tumble Valve Equipped	False	
Direct Injection Equipped	False	
Brake Pedal Sensor Equipped	False	
Active Engine Mount Equipped	False	
SRV Equipped	False	
Clutch Interlock Switch Equipped	False	
Mechanical Coolant Pump Heater Equipped	False	
2.0 Liter I4 engine	False	
Transmission Software Included	False	
Sensorless FFV Enabled	False	
TIP Equipped	False	
5.7 Liter V8 Engine	False	
62TE	False	
Adaptive Cruise Control Hardware Equipped	False	
MDS Equipped	False	
Electric Thermostat Heater Equipped	False	
Rear Heater Equipped	False	
Unleaded Gasoline Fuel	True	
Knock Sensor 2 Equipped	True	
ETC Cruise equipped	False	
3.8 Liter V6 Engine	False	
ZF 9-Speed Transmission Equipped	False	
AC Equipped Over Bus	False	
VLP Is Learnable Indicator	False	
Power Steering Switch Equipped	False	
Primary Lin Alternator Equipped	False	
Tumble Generator Valve Equipped	False	
Fiat 940 Compact Equipped	False	
CUSW PROXI Write Programming Support Enabled	False	
Engine Software In Package	True	
Dual Fuel Pressure Sensor Equipped	False	

Wide Range O2 Sensor 1/1 Equipped	False	
66RFE / 68RFE	False	
A/C Equipped	True	
4 Speed Automatic Transmission Equipped	False	
Electronic Throttle Control Equipped	True	
O2 Sensor Bank 2 Sensor 2 Equipped	True	
Secondary Air Equipped	False	
High Side Port Tumble Valve Equipped	Undefined	
Shift Indicator Lamp Equipped	False	
3.3 Liter V6 Engine	False	
4.0 Liter I6 Engine	False	
Turbocharger Equipped	False	
45RFE / 545RFE / 65RFE	False	
3 Speed Fan Mechanical Relay System Equipped	False	
GPEC3 Equipped	False	
O2 Sensor Bank 2 Sensor 1 Equipped	True	
Constant Heater Temperature Control Valve Equipped	False	
Air Shutoff Valve Bank 1 Control Solenoid 2 Equipped	False	
Secondary Fuel Pump Equipped	False	
Aisin 6-Speed RWD Transmission Equipped	False	
Fixed displacement AC Equipped	True	
Air Shutoff Valve Bank 2 Control Solenoid 2 Equipped	False	
PTO System Equipped	False	
VMM Equipped	False	
O2 Sensor Bank 1 Sensor 2 Equipped	True	
Viscosity Sensor Equipped	False	
Transmission Oil Heater Equipped	False	
Electronic Vacuum Pump Equipped	False	
MultiAir Equipped	False	
6.2 Liter V8 Engine	False	
Auxiliary Coolant Pump Equipped	False	
Police Package Equipped	False	
Linear Purge Equipped	False	
DUAL_ALTERNATOR_GEN1_LEARNEDCOPY	False	
2.7 Liter V6 Engine	False	
Oil Pressure Sensor Enabled	True	
Exhaust Cam 1 Equipped	True	
MTV Solenoid Equipped	False	
GPEC4 Equipped	False	
Active Exhaust Valve Equipped	False	
WI4 Variable Valve Timing Equipped	True	
Exhaust Cam 2 Equipped	True	
Supercharger Equipped	False	
Adaptive Cruise Control Equipped	True	

Continuous Variable Transmission Equipped	False	
Powernet Equipped	True	
Low Temperature Radiator Coolant Pump Equipped	False	
TOOLCONFIG_OIL_PRESS_ABS_EQUIPPED	True	
3.7 Liter V6 Engine	False	
Port Flap Valve Equipped	False	
O2 Sensor Bank 1 Sensor 1 Equipped	True	
WI4 Intake Flow Control Valve Equipped	False	
GPEC2A Equipped	True	
Trans Skip Shift Equipped	False	
42RLE	False	
4 Button Integrated Cruise Control	False	
Yaw Rate Sensor ESC Equipped	False	
Vehicle Speed Sensor #1 Calculated by ECU	False	
GPEC2 Equipped	False	
Buffered Crank Output for ANC (Active Noise Cancellation) Equipped	True	
Engine Idle Shutoff Equipped	False	
Brushless PWM Fan Equipped	NOT_FAN_PWM_BOSCH_BRUSHLESS_CNFG	
3.0 Liter V6 Engine	False	
Operator Idle Speed Request Equipped	False	
Auxiliary Heater Electric Water Pump Equipped	False	
3.2 Liter V6 Engine	False	
Electronic Coolant Pump Equipped	False	
HPT 6-Speed Transmission Equipped	False	
Dual Fuel Tank Equipped	False	
Wide Range O2 Sensor 2/1 Equipped	False	
Engine Oil Heater Cooler Equipped	True	
Active Grille Shutter Equipped	True	
Coolant On-Off Valve Equipped	False	
Cummins Equipped	False	
Electronic Automatic Transmission (EATX) Equipped	False	
Fan Wake Up Relay System Equipped	False	
Linear EGR Equipped	False	
Barometric Sensor Equipped	False	
40TE / 41TE / 41TEA	False	
CMCV H-Bridge Equipped	Undefined	
Intake Cam 2 Equipped	True	
O2 Sensor Bank 1 Sensor 3 Equipped	False	
AC Equipped	False	
1 Speed Fan Mechanical Relay System Equipped	False	
Battery Temp Sensor Equipped	False	
Dual Stage Oil Pump Equipped	True	
Dual Speed Fuel Pump Equipped	False	
Next Gen Bus Equipped	False	

EMAT (Getrag DCT transmission) Equipped	False	
Air Shutoff Valve Bank 1 Control Solenoid 1 Equipped	False	
Active Exhaust Pressure Sensor Equipped	False	
Buffered Crank Output for PHEV Engine Pulse Calculation Equipped	True	
Throttle Inlet Temp Sensor Equipped	False	
Starter Relay 2 Equipped	False	
Electric Coolant Valve Equipped	False	
Cooled EGR Equipped	False	
Duty Cycle Purge Valve Equipped	True	
Turbine Volute Valve Actuator Equipped	Undefined	
Vehicle Speed Sensor #1 Calculated from CAN	False	
Linear PWM Fan Relay System Equipped	False	
Knock Sensor 1 Equipped	True	
Humidity, Temperature and Pressure Sensor (LIN) Equipped	False	
VLP Equipped Indicator	False	
VFS Actuators Available Indicator	False	
Engine Stop Start Equipped	False	
1.0 Liter I3 Engine	False	
Variable Speed Fuel Pump Equipped	True	
Compressed Natural Gas Equipped	False	
ICC Cruise Equipped	False	
Coolant On-Off Pump Equipped	False	
3.6 Liter V6 Engine	True	
Unleaded diesel fuel	False	
2 Speed Fan 3 Driver 3 Relay System Equipped	False	
ESIM Equipped	False	
Variable Displacement AC Equipped	False	
4.7 Liter V8 Engine	False	
PWM Fan Motor System Equipped	True	
ERS Equipped Indicator	False	
Fiat VIN Learning Strategy Equipped	False	
Inrush Current Reduction Relay Equipped	False	
Intake Cam 1 Equipped	True	
2 Speed Fan Mechanical Relay System Equipped	False	
6.4 Liter V8 Engine	False	
6.1 Liter V8 Engine	False	
2.4 Liter W14 engine	False	
Trans Reverse Lockout Equipped	False	
CUSW (11-Bit) Equipped	False	
Auxiliary Coolant Pump Heater Equipped	Undefined	
Electric Water Pump Equipped	False	
3.5 Liter V6 Engine	False	
Hybrid Electric Vehicle Equipped	True	
2 Speed Fan PWM Relay System Equipped	False	

Wastegate H-Bridge Equipped	Undefined	
1.8 Liter W14 engine	False	
Operator Idle Speed Request Equipped	False	
Cylinder Pressure Sensor Equipped	False	
Throttle Inlet Temp Sensor Equipped	False	
Mass Airflow System Equipped	False	
Clutch Sensor Equipped	False	
Dual Fuel Pressure Sensor Equipped	False	
Make Up Air Sensor Equipped	False	
Bi-Directional Crank Sensor Equipped	True	
CUSW 4-Button Cruise Equipped	False	
SWAP HARDWIRED BRAKE SWITCH INPUTS	False	
5 Button Cruise (LIN) Equipped	True	
Power Steering Angle Sensor Mandatory	False	
LIN Humidity, Temp, and Pressure Sensor Equipped	False	
INTAKE O2 SENSOR EQUIPPED	False	
Brake Pedal Sensor Equipped	False	
Engine Oil Pressure Sensor Type	255	None
Remote Start Present	Present	
Coolant On-Off Pump Equipped	Not Equipped	
Primary Lin Alternator Equipped	Not Equipped	
Variable Valve Lift Equipped	Not Equipped	
2.0 Liter I4 Direct Injection Engine	False	
1.0 Liter I3 Engine	False	
Low Temp Radiator Coolant Pump Equipped	False	
Engine Idle Shutoff Equipped	False	
ZF 9-Speed Trans Equipped	False	
A/C Relay Powered from Engine Switched Battery	False	
PTO System Equipped	False	
HPT 6-Speed Trans Equipped	False	
Hybrid MEC Shifter Equipped	False	
CNG Large Gas Tank Equipped	False	
Dual Alternator Gen1 Capable	False	
Dual Fuel Tank Equipped	False	
Cooled EGR Equipped	False	
Auxillary Coolant Pump Equipped	False	
Supercharger Equipped	False	

ICS CONFIGURATION

NAME	VALUE	UNITS
Display Type (Mid)	False	
Display Type (High)	False	
Display Type (Base)	True	

RFH CONFIGURATION

NAME	VALUE	UNITS
Hardware Configuration: Trunk Door Handle H/W	Simple Switch AP	
Hardware Configuration: Remote Start Antenna	Present	
Hardware Configuration: Front Right Door Handle H/W	Serial AP	
Hardware Configuration: Front Left Door Handle H/W	Serial AP	
Hardware Configuration: Rear Right Door Handle H/W	No AP	
Hardware Configuration: Rear Left Door Handle H/W	No AP	
Valid Key In Ignition	Yes	
Fob Location #3 Successfully Programmed	Yes	
Fob Location #5 Key sense status	Fob is NOT Key Sense	
Secret Key Sent to Body Controller - Original attempt	Yes	
Fob Location #7 Key sense status	Fob is NOT Key Sense	
Fob Location #3 Key sense status	Fob is Key Sense	
Fob Location #7 Successfully Programmed	No	
Fob Location #6 Successfully Programmed	No	
Fob Location #5 Successfully Programmed	No	
Fob Location #8 Key sense status	Fob is NOT Key Sense	
PIN Successfully Programmed	Yes	
RFHub Locked	RFHUB Locked after IAC write	
Fob Location #1 Key sense status	Fob is NOT Key Sense	
Fob Location #4 Key sense status	Fob is NOT Key Sense	
Fob Location #6 Key sense status	Fob is NOT Key Sense	
Fob Location #1 Successfully Programmed	Yes	
Secret Key Sent to Body Controller - Most recent attempt	Yes	
Fob Location #2 Successfully Programmed	Yes	
Fob Location #4 Successfully Programmed	No	
Fob Location #2 Key sense status	Fob is NOT Key Sense	
VIN Successfully Programmed	Yes	
Fob Location #8 Successfully Programmed	No	
Base TPM	False	
Auto Park Present	True	
e-shifter present	True	
Secret Codes Programmed	True	
KeySense Configuration	True	
Ignition system type connected	KIN system	
RKE	True	
Remote Start Present	True	
\$0214 Programmed by	Programmed by Supplier EOL	
TPM Auto-Locate Enabled	True	
Keyless Go	True	
Passive Entry	True	
Hybrid Type	PHEV	
Module Configuration Status	True	

Premium TPM	True	
Back Up ECU Configuration 16	True	
Back Up ECU Configuration 14	True	
Back Up ECU Configuration 7	True	
Back Up Vehicle Config 1	True	
Back Up ECU Configuration 10	True	
Back Up ECU Configuration 11	True	
Back Up Vehicle Config 4	True	
Back Up Vehicle Config 3	True	
Back Up Customer Settings Menu 1 (CSM1)	True	
Back Up ECU Configuration 2	True	
Back Up ECU Configuration 1	True	
Back Up ECU Configuration 9	True	
Back Up Programmed ECUs: Cabin Network	True	
Back Up Vehicle Config 5	True	
Back Up ECU Configuration 3	True	
Back Up Customer Settings Menu 2 (CSM2)	True	
Back Up Vehicle Config 6	True	
Back Up ECU Configuration 12	True	
Back Up Programmed ECUs: P/T Chassis Network	True	
Back Up ECU Configuration 4	True	
Back Up ECU Configuration 17	True	
Back Up ECU Configuration 8	True	
Back Up ECU Configuration 13	True	
Back Up Vehicle Config 7	True	
Back Up ECU Configuration 5	True	
Back Up Vehicle Config 2	True	
Back Up ECU Configuration 15	True	
Back Up ECU Configuration 6	True	

ORC CONFIGURATION

NAME	VALUE	UNITS
First Row Driver Seatbelt Buckle Switch	Configured	
Driver Seat Track Position Sensor	Configured	
Second Row Left Seat Side Airbag	Not Configured	
Rollover Sensing	Configured	
Passenger Seatbelt Retractor Pretensioner	Configured	
Passenger Seatbelt Anchor Pretensioner	Configured	
Driver Seatbelt Anchor Pretensioner	Configured	
Left Side Seat Squib 1	Configured	
Driver Frontal Squib 3	Configured	
Passenger Seatbelt Load Limiter	Configured	
Passenger Occupant Detection Sensor	Not Configured	
Passenger Seatbelt Buckle Pretensioner	Not Configured	

Second Row Left seat belt Switch	Not Configured	
Left B-Pillar Impact Acceleration Sensor	Configured	
Right Up-Front Acceleration Sensor	Configured	
Configuration Column Identifier	A3	
Passenger Airbag Disable Indicator	Not Configured	
Passenger Frontal Squib 1	Configured	
Driver Frontal Squib 1	Configured	
Passenger Frontal Squib 3	Configured	
Right Side Seat Squib 1	Configured	
Second Row Right seat belt Switch	Not Configured	
Left Up-Front Acceleration Sensor	Configured	
Right Curtain Squib 1	Configured	
Left C-Pillar Impact Acceleration Sensor	Configured	
Passenger Seat Track Position Sensor	Configured	
Driver Knee Bolster Squib	Configured	
Occupant Classification (OCM)	Configured	
Passenger Frontal Squib 2	Configured	
Driver Frontal Squib 4	Not Configured	
Second Row Center seat belt Switch	Not Configured	
Left Curtain Squib 1	Configured	
Right Side Door Pressure Sensor	Configured	
First Row Passenger Seatbelt Buckle Switch	Configured	
Right B-Pillar Impact Acceleration Sensor	Configured	
Left D-Pillar Impact Acceleration Sensor	Configured	
Right D-Pillar Impact Acceleration Sensor	Configured	
Right C-Pillar Impact Acceleration Sensor	Configured	
Driver Seatbelt Load Limiter	Configured	
Driver Seatbelt Retractor Pretensioner	Configured	
Second Row Right Seat Side Airbag	Not Configured	
Passenger Frontal Squib 4	Not Configured	
Passenger Airbag Disable Switch	Not Configured	
Passenger Knee Bolster Squib	Configured	
Driver Frontal Squib 2	Configured	
Left Side Door Pressure Sensor	Configured	
EPPM	Not Configured	
Driver Seatbelt Buckle Pretensioner	Not Configured	

EPS CONFIGURATION

NAME	VALUE	UNITS
Stop/Start Feature Active	False	
Parallel Park Assist Feature Active	True	
Dynamic Steering Torque Feature Active	True	
Lane Feedback Feature Active	True	

HVAC CONFIGURATION

NAME	VALUE	UNITS
HVAC Configuration	Dual Zone ATC + Rear	
Single Zone MTC Control (BB)	False	
DualZone ATC Control (BB)	True	
Dual Zone MTC Control (BB)	False	
MTC Without EBL (3Knob)	False	
MTC With EBL (3Knob)	False	
DualZone ATC Control (Factory) (BB)	True	
MTC heater only (3Knob)	False	

PDM CONFIGURATION

NAME	VALUE	UNITS
Frameless Window	False	

PSDML CONFIGURATION

NAME	VALUE	UNITS
VSIM Status	False	

PSDMR CONFIGURATION

NAME	VALUE	UNITS
UPFM Status (Present = True, Absent = False)	False	

MSM CONFIGURATION

NAME	VALUE	UNITS
Adjustable Pedals	False	
Telescope/Tilt	False	

CSWM CONFIGURATION

NAME	VALUE	UNITS
EC - Seat A	Programmed	
EC - Seat B	Programmed	
Vehicle Line W-Series	False	
Vehicle Line P-Series	False	
Vehicle Line L-Series	False	
Vehicle Line R-Series	True	
Heated Steering Wheel	True	
Vehicle Line M-Series	False	
Vehicle Line D-Series	False	
Vehicle Line U-Series	False	
Vehicle Line J-Series	False	

AMP CONFIGURATION

--

NAME	VALUE	UNITS
Premuim - 2	False	
Premuim - 3	True	
No HALF Chimes	False	
No Rear Doors	False	
Premuim - 1	False	
Non -ANC	False	
ANC Status	Off - Window Mute	
ANC Calibration Date - Year	18	
ANC Calibration Date - Week	45	
ANC Calibration Date - Patch Level	2	
Surround Sound Activated	Not Set	
Door Module - Left Front	Present	
Door Module - Right Rear	Present	
Door Module - Left Rear	Present	
Door Module - Right Front	Present	
Current ANC Calibration ID - Service	RU PHEV 3.6L: Sunroof & Harman AMP	

IPC CONFIGURATION

NAME	VALUE	UNITS
PHEV	True	
Rear Fog Lamp	False	

PTS CONFIGURATION

NAME	VALUE	UNITS
Front License Plate Configuration	Front Plate Config - USA	
Front System with 6 Rear Sensors	True	
Rear System with 6 Front Sensors	True	

SCCM CONFIGURATION

NAME	VALUE	UNITS
Rear Wiper	True	
Paddle Shifter	False	
Cruise Control / ACC	True	
Tilt Telescope	False	

BCM CONFIGURATION

NAME	VALUE	UNITS
Number of Reprogramming Attempts - Counter #0	0	
Vehicle Configuration Programmed Status	True	
Last Programmed Status	Manufacturing	
ECU Configuration 9 (ITM)	3	
ECU Configuration 2 (CBC Features)	3	

Vehicle Config CSM2	3	
ECU Configuration 8 (LIN and Miscellaneous)	3	
Vehicle Configuration 7 - Write Counter	3	
ECU Configuration 6 (Safety)	3	
ECU Configuration 6 (Powertrain)	3	
Vehicle Configuration 5 - Write Counter	3	
ECU Configuration 5 (Memory)	3	
Programmed Network Configuration - Audio / Telematics Network	0	
ECU Configuration 5 (Wireless)	3	
Vehicle Configuration 2 - Write Counter	3	
ECU Configuration 4	3	
ECU Configuration 7 (CBC Exterior Lighting Calibrations)	3	
ECU Configuration 12	3	
Vehicle Configuration 4 - Write Counter	3	
ECU Configuration 5 (Doors)	3	
ECU Configuration 15 (CBC Features)	3	
ECU Configuration 6 (Suspension)	3	
ECU Configuration 6 (Brake)	3	
ECU Configuration 1 (CBC Configurable Inputs and Outputs)	3	
Vehicle Config CSM1	3	
Vehicle Configuration 3 - Write Counter	3	
ECU Configuration 3	3	
ECU Configuration 14	3	
Vehicle Configuration 1 - Write Counter	3	
ECU Configuration 10	3	
ECU Configuration 11	3	
Vehicle Configuration 6 - Write Counter	3	
Programmed ECUs: Cabin Network	3	
Programmed ECUs: Hybrid LAN Network	0	
Programmed ECUs: P/T Chassis Network	3	
Last Configuration Odometer	0	miles
ECU Configuration 15 (Suspension)	3	
ECU Configuration 9A	3	
ECU Configuration 13	3	
Vehicle Configuration Auto Write Counter	1	
Emode Present	Not Set	
Remote Start Present	Set	
Select Speed Control Feature Present	Not Set	
Performance Pages Present	Not Present	
Model Year	2021	
PTS Configuration	Semi Automatic / Semi Automatic	
Special Packages	74	
Auto Highbeam	Set	
Hill Descent Feature Present	Not Set	

Drive Configuration	2WD Front	
Maximum Vehicle Speed	0	MPH
Vehicle Line	RU	
Body Style	Station Wagon	
Country Code	USA	
Left/Right Hand Drive	Left Hand Drive	
Shifter Type	5 Position Rotary Eshifter PRNDL / Type RS5L	
Power Inverter Type	No Power Inverter	
Max Load Inflation Pressure Front Tire	36.0	PSI
Rain Sensor Present	Set	
Off Road Capable	Not Set	
SKIM System Present	Not Set	
Air Conditioning Present	Not Set	
Thatcham Present	Not Set	
Cruise Feature is Present	Not Set	
Full Size Spare	Not Set	
Flipper Glass Present	Not Set	
Special Packages IC	Pacifica	
Max Load Inflation Pressure Rear Tire	36.0	PSI
Keyless Go Present	Set	
Power Left Sliding Door Present	Set	
Two Fuel Sending Units Present	Not Set	
ESCL system present	Not Set	
Vehicle Brand	Chrysler	
Disable Display of Radio Clock	Not Set	
HVAC Configuration	Dual Zone ATC + Rear	
Display Outside Temperature Present	Set	
Door Alert Feature Present	Not Set	
FOBIK Safe Enable	Set	
Power Right Sliding Door Present	Set	
Fuel Capacity	17	gallons
T-Case Type	Not Present / Not Present	
Vehicle is an SRT	Not Set	
Police Lighting Feature	Not Set	
Paddle Shift Feature Present	Not Set	
Liftgate/Trunk Type	Power Liftgate	
Forward Collision Warning present	Set	
Auto Park Present	Set	
RKE System Present	Set	
Secondary Lock Present	Not Set	
Passive Entry Present	Set	
ELV Present	Not Set	
Collision Mitigation System present	Set	
Chassis Type	Type 8	

Window Express Feature Configuration	All windows express feature	
Wheel Base	Wheel base not programmed / WB_NP	
Display Compass Heading Present	Set	
Sport Mode Present	Not Set	
Adjustable Pedal Feature Present (non-Memory)	Not Set	
Base TPM system present	Not Set	
High Intensity Discharge Head Lamps	Set	
Premium TPM system present	Set	
Auto Headlamp Feature Present	Set	
Transfer Case High Ratio	1.000	No Unit
Axle Ratio	3.251	
Dynamic Tire Circumference (All or Rear)	89	inch
Transfer Case Low Range Reduction Ratio	0.000	
Air Quality System Present	Not Set	
Analog Door Sensor Configuration	Driver Door Only Analog Sensor	
Steering Ratio at Negative Angle 1	0.0	No Unit
Connector A Pin 3/Connector D Pin 2: Low Beam Output Present	Set	
Connector G Pin 24 (Internally tied to Connector F Pin 7): Ambient Lighting Output	Set	
Connector D Pin 10: Trailer Tow Tail Lamp Output Present	Not Set	
Connector D Pin 9: Trailer Tow Backup Output Present	Not Set	
Connector D Pin 11: Stop/Turn Trailer Tow Left Output Present	Not Set	
Connector F Pin 4: Liftgate Release Present	Not Set	
Connector A Pin 10/Connector D Pin 5: Side Markers Output Present	Set	
Connector G Pin 22: VTA Warning LED Output Present	Set	
Connector D Pin 7: Stop/Turn Trailer Tow Right Output Present	Not Set	
Connector F Pin 8 : Liftgate Release Outside Handle Switch Present	Not Set	
Connector E Pin 48 (Tied internally to Connector A Pin16): Rear Wiper Motor Control Output Present	Set	
Connector F Pin 35: Inverter Enable Relay Output Present	Set	
Connector E Pin 3/Connector F Pin 42: Rear Turn Lamps Output Present	Not Set	
Connector D Pin 22/ Connector D Pin 23: Ambient Temperature Signal/Return Present	Set	
Connector E Pin 39/Connector F Pin 5: Rear Fog Lamps Output Present	Not Set	
Connector F Pin 29: Horn Switch Present	Set	
Connector E Pin 4/Connector F Pin 32: Rear Park Lamps Output Present	Set	
Connector F Pin 23: Door Lock Switch Signal Front Passenger Present	Set	
Connector G Pin 15: UGDO Feed Output Present	Set	
Connector E Pin 7: Left HID Relay Control Output Present	Not Set	
Connector D Pin 12: PHEV ECM Hardwire Wake Up Output Present	Set	
Connector E Pin 11: Vacuum Switch Input	Not Set	
Connector E Pin 34: Vacuum Cleaner Relay Output Present	Not Set	
Connector E Pin 42: Charge Port Lock Output Present	Set	

Connector A Pin 11: Hood Ajar Switch Input Present	Set	
Connector E Pin 29: Rear Wiper Motor Park Signal Present	Set	
Connector F Pin 6: Fuel Door Motor Output Signal Present	Set	
Connector F Pin 9: Analog Door Ajar Signal Front Driver Present	Set	
Connector E Pin 5: PHEV Fuel Door Switch Input	Set	
Connector E Pin 9: Run-ACC Y Relay #2 Output Present	Set	
Connector E Pin 8: PHEV HCP Hardwire Wakeup	Set	
Connector E Pin 41: Charge Port Unlock Output Present	Set	
Connector G Pin 9: Ambient Light Dimmer Wheel Input Present	Set	
Connectro E Pin 37: Right HID Control Output Present	Not Set	
LED Rear Fog Lamps Present	Not Set	
Tip Start Enabled	Set	
Fuel Door Present	Not Set	
Trailer Tow Present	Not Set	
LED Low Beam Lamps Present	Set	
Side Repeaters Enable	Not Set	
LED CHMSL Lamp Present	Set	
LED Front Park/Marker Lamps Present	Set	
Illuminated approach Enabled	Not Set	
DRL Configuration	No DRL	
Park Lamp Loadshed Enable	Set	
Front Wiper Park Enable	Set	
Front Fog Lamp Dropout Enable	Set	
One Touch Lane Change	Set	
LED Front Turn Lamps Present	Not Set	
Combined Rear Lighting Enable	Set	
Reversible Washer Pump Enable	Set	
LED Rear Turn Lamps Present	Not Set	
Exterior Light Loadshed Enable	Set	
LED Dedicated DRL Present	Not Set	
LED Stop Lamps Present	Not Set	
Headlamp Washer Low Fluid Shut-Off Enable	Set	
Tunnel Detection	Not Set	
Dual Start Relay System Present	Not Set	
DRL Dropout Enable	Not Set	
Quad Headlamps Enable	Set	
Front Wiper Wipes After Wash	2 Wipes	
Intermittent Wiper States	4 Intermittent Wiper position Switch	
Rear Wiper Park Enable	Set	
Hazard Lamp Configuration	Latching Switch	
LED Reverse Lamps Present	Not Set	
Headlamp Wash Shot	double	
LED High Beam Lamps Present	Set	
Bi Xenon Headlamps Enable	Not Set	

Headlamp Wash Interval	wash cycle#11	
LED Front Fog Lamps Present	Set	
Headlamp Wash Spray Duration (at 100 ms intervals)	1100ms	
Horn Chirp Allowed	Set	
Combined Front Park/Turn Feature Enable	Not Set	
Wiper Service Position Enabled	Not Set	
LED Tail Lamps Present	Set	
DRL Lamp Location	Low Beam DRL	
Fuel Door Release Enabled	Not Present	
LED License Lamps Present	Set	
Microphone Tuning Parameter	Absent [Not Used]	
Front Park Assist Present	Set	
Microphone Configuration	2 Microphones	
Surround Sound Feature Present	Set	
Disable CD Eject	Not Set	
Rear Camera Present	Not Set	
Heated Steering Wheel Present	Set	
Antenna Type	Active Primary and no secondary antenna	
External Port Type	AUX + USB + extra USB	
Destination	United States of America	
Power Inverter Present	Not Set	
Front Heated Seats Present	Set	
Cabin Equilization Curve Number	RU Premium System - Harman 12ch	
Power Door Locks Present	Set	
Microphone Type	Peiker 300 mv	
Splashscreen Type	Vehicle Brand	
Fleet Vehicle Content	Not Set	
AP1 Left Front	Smart Switch	
AP3 Left Rear	CAN	
Airport Scenario Trunk	Not Set	
AP5 Trunk Lock	Simple Switch	
Vehicle Variant	Undefined	
Tip Start Present	Set	
AP2 Right Front	Smart Switch	
AP4 Right Rear	CAN	
AP5 Trunk Unlock	CAN	
Driver Memory Mirrors Present	Set	
Global Down	Not Set	
Rear Door Pre Short Drop	Not Set	
Electro-chromatic passenger mirror present	Not Set	
Window Hall Sensors Present	Not Set	
Electro-chromatic driver mirror present	Set	
Tow Mirror Present	Not Set	
Frameless Window Present	Not Set	

Passenger Window Lockout	Not Set	
Blindspot Mirror Present	Set	
Passenger Memory Mirror Present	Set	
Puddle Lamp Present	Not Set	
Folding mirrors present	Not Set	
Window Motor Type	Not Set	
Mirror turn signals present	Set	
Global Up	Not Set	
Heated Mirrors Present	Set	
Sun Shade	Not Set	
Tilt/Telescope Steering Present	Not Set	
Memory Adjustable Pedals Present	Not Set	
Stow 'n Assist Present - Passenger	Set	
Heated Steering Wheel Present	Present	
Heated Seat Material Type	Default	
Heated Wheel Material Type	Full Leather	
Stow 'n Assist Present - Driver	Set	
Front Vented Seats Present	Present	
Driver Memory Seat Present	Set	
Rear Heated Seats Present	Not Present	
Brake System ECU Configuration A	value 0	
Dual Alternator Present	Not Set	
ECO Mode Configuration	Remember Previous State with Ignition Key Cycle	
Connector F Pin 14: Right Sliding Door Switch Input (B-Pillar)	Right B-Pillar Sliding Door Switch	
Manual Door Locks Present	Not Set	
Connector E Pin 28: Secondary Door Ajar Switch Present - PIN E-28	Set	
Connector E Pin 48 (Tied internally to Connector A Pin16): Rear Wiper Motor Control Output Present	Rear Wiper (0)	
Connector F Pin 15: Driver Door Lock Switch Input	Not Present	
Connector F Pin 30: Fuel Door Lock (BUX)	Not Present	
Heatsoak Flush Time	105	Time
Humidy Sensor Long Present	Set	
Auto High Beam Module Location	HaLF	
Connector G Pin11/Connector G Pin 12: Not Used	ERS	
Connecetor F Pin 33: Fuel Door Unlock (BUX)	Not Present	
Connector E Pin 39: Right Rear Turn Signal	Right Rear Turn Signal	
CHMSL Lamp Output Disable	Not Set	
Rain Sensor Module #2 Present	Set	
Ambient Stable Counter Limit	40	Counter
License Plate Lamp Disable	Not Set	
Connector F Pin 29: Horn Switch Present	Horn Switch Input	
Engine Off Clear Time	180	Time
Heatsoak Set Time	15	Time
Max Engine Off Time	220	Time

Connector E Pin 3: Left Rear Turn Signal	Left Rear Turn Signal	
Heatsoak Speed	15	Counter
Connector F Pin 13: Left Sliding Door Switch Input (B-Pillar)	Left B-Pillar sliding Door Switch	
Connector F Pin 34: Spare HSD	Not Present	
Connector F Pin 37: Vacuum Cleaner Power Saver Indicator	Not Present	
Acceleration Factor	Filter Off	
Excess Lateral Acceleration Factor	Filter Off	
Excess Longitudinal Acceleration Factor	Filter Off	
Nose Dive Threshold	Filter Off	
Steering Smoothing Factor	Filter Off	
Average Last Lateral Acceleration Values	No Averaging	
Average Last Longitudinal Acceleration Values	No Averaging	
Acceleration Threshold	Filter Off	
Nose Dive Factor	Filter Off	
Maximum Longitudinal Change	Filter Off	
Brake Smoothing Duration	Filter Off	
Maximum Lateral Change	Filter Off	
Steering Smoothing Threshold	Filter Off	
Brake Smoothing Threshold	Filter Off	
Brake Smoothing Factor	Filter Off	
Steering Smoothing Duration	Filter Off	
VTA Hood Ajar Monitoring	Not Set	
Headlamp Soak Delay	1.0 sec	
Horn Chirp Duration	Short	
Auto High Beam OFF Threshold	20 km/hr	
Interior Lighting Day Threshold	4.27498	Volt
Parking Light Enable	Not Set	
RKE Auto-Relock Feature Enable	Not Set	
Interior Lighting Night Threshold	4.45147	Volt
Auto High Beam ON Threshold	25 km/hr	
PE Auto-Relock Feature Enable	Set	
Sunroof Present	Set	
TPMS Configuration	Logic 1 NHTSA Enable Warning	
Smart Alternator Present	Not Set	
Temperature Display Resolution	HaLF	
ANC Calibration Parameter Data Set	RU_PHEV_3.6L_tripane_SunRoof_Harman_AMP	
Drive Mode Version	Version 1	
Auto Dimming Mirror Hard Button Present	Set	
Surround View Camera On/Off Softkey Present	Set	
Radio Speaker Open Circuit Disable (RF)	Not Set	
Radio Speaker Open Circuit Disable (RR)	Not Set	
Automatic Crash Notification Feature Present	Undefined	
Radio Speaker Open Circuit Disable (LR)	Not Set	
Radio Speaker Open Circuit Disable (LF)	Not Set	

Show Phone Information in Cluster	01	
Park Assist Tuning Set	BUX Front and Rear Only	
EAC	Set	
ECM	Set	
ESM	Set	
ORC	Set	
AHCP	Set	
ESC	Set	
HCP	Set	
APM	Set	
OBCM	Set	
BPCM	Set	
EBCM	Set	
Flash Lamps on Lock	Set	
Sound Horn On Lock Status	Chirp on 1st press/FIRST	
Sound Horn on Remote Start	Set	
Unlock all doors on 1st press	Set	
Auto Highbeam	Set	
Illuminated Approach Time	30	seconds
Headlamp Delay Time	30	seconds
Daytime Running Lamps	Set	
Sliding Door Alert	Not Set	
Auto Unlock	Set	
Auto Wipers	Set	
Hands Free Sliding Door Enable	Set	
Headlamps on with Wipers	Set	
Accessory Delay Time	45	seconds
Sliding Door Chime Enable	Set	
Sound Horn on Lock	Set	
Auto Lock	Set	
Left Low Beam Voltage Regulation	13.6 Volts	
Left High Beam Voltage Regulation	13.6 Volts	
Front Park/Turn Voltage	Park to Turn ratio 55 Percent	
Left Front Corner Voltage	13.2 Volts	
Left Rear Corner Voltage	14 Volts	
Auto Headlamp On Threshold	3.31409	Volt
Right High Beam Voltage Regulation	13.8 Volts	
Auto Headlamp Off Threshold	2.54930	Volt
Right Low Beam Voltage Regulation	14 Volts	
Right Rear Corner Voltage	14 Volts	
Right Front Corner Voltage	13.4 Volts	
IBS Activate MWU	Not Set	
IBS Minimal Charge Limit	10	AmpHrs
IBS Minimum Voltage Limit	5.0	Volts

Battery Types	SNA	
Battery Type II	22	
IBS Minimum Charge Limit	600	mA
IBS Quiescence Current Limit	-250	mA
Alert On System Fault	Set	
EVIC SWS Module Present	Set	
Compass Mounting Orientation	Rightside up	
CRVMM Present	Set	
Compass Mounting Angle	0	Degree
Humidity Sensor Present	Set	
Washer Fluid Level Voltage Threshold	4.46 volts	
VTA System Present	VTA	
Illuminated Approach Headlamp Target Percentage	125 (62.5%)	
Alert no Reply	Set	
Illuminated Approach Taillamp Target Percentage	125 (62.5%)	
Illuminated Approach Interior Lighting Ramp Up Time	130(2600ms)	
Panic Enable	Set	
Alert On Search Timeout	Set	
HFRM Present	Set	
Auto Relock Time	60	seconds
OHC Module Present	Set	
IBS Present	Set	
Illuminated Approach Interior Lighting Target Percentage	100(50%)	
Fobik Safe Alerts Per Ignition Cycle	2	
ESL	Not Set	
AHLM	Not Set	
ACC	Set	
TCM	Not Set	
OCM	Set	
IPC	Set	
RFH	Set	
EPS	Set	
PCM	Set	
ABSO	Set	
ABS	Not Set	
ORC	Set	
PTS	Set	
ESM	Set	
SCCM	Set	
BCM (PT)	Set	
FFCM	Set	
HCP	Set	
DTV	Not Set	
DMRL	Set	

EOMR	Set	
EAM	Set	
PLGM	Set	
PDM	Set	
ANC	Not Set	
VRM	Set	
CVPM	Set	
HSM	Set	
PSDMR	Set	
BCM (Interior Bus)	Set	
ITM	Not Set	
FSM	Not Set	
MSMP	Set	
HVACR	Set	
DSM	Set	
DMRR	Set	
VTM	Not Set	
Radio	Set	
MSM	Set	
EDM	Set	
DDM	Set	
ICS	Set	
AMP	Set	
PSDML	Set	
HVAC	Set	
Connector A Pin 11: Hood Ajar Switch Signal	500 ohm series and 500 ohm parallel resistors	
Connector D Pin 1: Left High Beam Feed	AUX High Beam	
Connector E Pin 3: Left Rear Turn Signal	Left Rear Turn Signal	
Connector F Pin 29: Horn Switch Input	Horn Switch Input	
Connector E Pin 37: Right HID Relay Control	Right HID Lamp Relay	
Stop/Start Enable Switch Present	Not Set	
Connector F Pin 31: Right Sliding Door Ajar	Right Sliding Door Ajar	
Connector F Pin 42: Right Rear Turn Signal	Right Rear Turn Signal	
Connector D Pin 12: PHEV ECM Hardwire Wake Up	Engine Control Module Wake up (PHEV only)	
Connector D Pin 21: Brake Fluid Level Switch	no parallel resistor	
Connector E Pin 5: E-5 PHEV Fuel Door Switch Input	PHEV Fuel Door Switch	
Connector E Pin 29: Rear Wiper Motor Park Signal	Reserved	
Connector E Pin 39: Right Rear Fog Lamp	Output Disable	
Connector F Pin 27: Left Sliding Door Ajar	Left Sliding Door Ajar	
Connector F Pin 28: Right Rear Turn Lamp Fault Sense	Disable	
Connector A Pin 2: Right High Beam Feed	AUX High Beam	
Connector E Pin 1: Backup-Reverse lamp Right	Set	
Connector E Pin 7: Left HID Relay Control	Left HID Lamp Relay	
Connector F Pin 5: Left Rear Fog Lamp	Output Disable	

Connector F Pin 25: Left Rear Turn Lamp Fault Sense	Disable	
Connector F Pin 4: Liftgate Release	Trunk/Liftgate Release	
Connector F Pin 41: Backup-Reverse lamp Left	Not Set	
Ultrasonics	Not Set	
Siren	Not Set	
Tilt	Not Set	
ODS Present	False	
Passive Ped Pro Present	False	
Tow Hooks Present	False	
Curtain Airbags Present	True	
1st Row Seat Side Airbags Present	True	
Integrated EPP Present	False	
Passenger Kneebag Present	True	
Driver Kneebag Present	True	
BUX Market	False	
Rear View Camera Dynamic Grid Lines Enabled	Not Set	
Rear View Camera Static Grid Lines Enabled	Not Set	

RADIO CONFIGURATION

NAME	VALUE	UNITS
Suspend Month	44	
Suspend Year	57	
Suspend Day	58	
Satellite Subscription Status	59	
Reason Code	56	
Aux Jack	Not Inserted	
SD Card Readers Detected	0	No Unit
Enumerated USB Devices	0	No Unit
USB Hubs Detected	3	No Unit
Stereo Blend	Off	
Automated Loudness	Off	
Front Seat Video Playback	Disabled	
Cabin EQ Curve Number Currently Used by Radio	223	events
Distortion Limiting	Off	
Anti-Theft Enable Status	On	
High Cut	Off	
Clock Defeat	On	
12/24 Time Selection	12 Hour Time	
Splash Screen	Automatic	

HVACR CONFIGURATION

NAME	VALUE	UNITS
MTC wo EBL (3Knob)	False	
Single Zone MTC Control (BB)	False	

MTC w EBL (3Knob)	False	
Dual Zone MTC Control (BB)	False	
DualZone ATC Control (Factory) (BB)	False	
DualZone ATC Control (BB)	False	
MTC heater only (3Knob)	False	

LBSS CONFIGURATION

NAME	VALUE	UNITS
Steering (LHD/RHD)	Left Hand Drive/ LHD	
CFG FEATURE	CFG_NONE	
Teen Key (RU variant only)	Yes	

RBSS CONFIGURATION

NAME	VALUE	UNITS
Teen Key (RU variant only)	Yes	
Steering Variant (LHD/RHD)	Left Hand Drive/ LHD	

FFCM CONFIGURATION

NAME	VALUE	UNITS
XCP Enabled	False	
Traceability info	22212930010803	
Traceability info	02212912875813	
HIL mode Enabled	False	

EDM CONFIGURATION

NAME	VALUE	UNITS
Video Ent. System Screen 2 Module	Not Present	
Video Ent. System Screen 1 Module	Not Present	
Radio	Present	
CAN I in-dash disc player module	Present	
Intrusion module	Not Present	
Vehicle System Interface Module	Not Present	
Body Style	Station Wagon	
Vehicle Line	RU	
Vehicle Brand Type	Chrysler	
VES	False	


RCCC CONFIGURATION

NAME	VALUE	UNITS
MTC with EBL	False	
DualZone ATC Control	True	
MTC Heater Only	False	
Single Zone MTC Control	False	

Dual Zone MTC Control	False	
DualZone ATC Control	False	
MTC without EBL	False	

ABSO CONFIGURATION

NAME	VALUE	UNITS
Engine Displacement	3.6	No Unit
ESC BLA Enabled	False	
PN ESC Byte2	0	
PN ESC Byte1	0	
Drive Configuration	2WD Front	
Dynamic Tire Circumference	89	inch
VC Chassis Type	Type 8	
Axle Ratio	3.251	No Unit
Hardwired VSO	True	
ACC	True	
Multiple Pressure Sensors	True	
Rear Directional Sensors	True	
Feature PIN	False	
Front Directional Sensors	False	
EPB	True	



VEHICLE SCAN REPORT

Vehicle 2021 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN [REDACTED]

Odometer 97.9 miles
Publication Date Apr 5, 2022, 11:33:04 AM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
PCM	Powertrain Control Module	CAN-C	68499122AF	[REDACTED]	[REDACTED]	68499122AF
PLGM	Power Liftgate	CAN-I	68466171AI	[REDACTED]	—	68466171AI
ICS	Integrated Center Stack	CAN-I	7AS341X8AA	[REDACTED]	[REDACTED]	7AS341X8AA
RFH	Radio Frequency Hub	CAN-C	68500152AA	[REDACTED]	[REDACTED]	68500152AA
ESM	Electronic Shifter	CAN-C	68240089AN	[REDACTED]	[REDACTED]	68240089AN
ORC	Occupant Restraint	CAN-C	68526665AB	[REDACTED]	[REDACTED]	68526665AB
EPS	Electric Power Steering	CAN-C	68460392AA	[REDACTED]	[REDACTED]	68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68493454AE	[REDACTED]	[REDACTED]	68493454AE
DDM	Driver Door Module	CAN-I	68496463AB	[REDACTED]	[REDACTED]	68496463AB
PDM	Passenger Door Module	CAN-I	68496462AB	[REDACTED]	[REDACTED]	68496462AB
DMRL	Door Module Rear Left	CAN-I	68508894AB	[REDACTED]	[REDACTED]	68508894AB
DMRR	Door Module Rear Right	CAN-I	68508894AB	[REDACTED]	[REDACTED]	68508894AB
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD	[REDACTED]	[REDACTED]	68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD	[REDACTED]	[REDACTED]	68369596AD
MSM	Memory Seat Module	CAN-I	68321862AC	[REDACTED]	[REDACTED]	68321862AC
CSWM	Comfort Seat Wheel Module	CAN-I	68517013AB	[REDACTED]	[REDACTED]	68517013AB
AMP	Amplifier	CAN-I	68547722AB	[REDACTED]	[REDACTED]	68547722AB
IPC	Instrument Panel Cluster	CAN-C	68434960AF	[REDACTED]	[REDACTED]	68434960AF
PTS	Parktronics	CAN-C	68485862AB	[REDACTED]	[REDACTED]	68485862AB

SCCM	Steering Column Control Module	CAN-C	68531525AA			68531525AA
BCM	Body Controller	CAN-C	68491085AG			68491085AG
ACC	Adaptive Cruise Control	CAN-C	68540436AC			68540436AC
RADIO	Radio	CAN-I	68465292AE			68465292AE
OCM	Occupant Classification	CAN-C	68403127AA			68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB			68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AC			04672786AC
RBSS	Right Blind Spot Sensor	CAN-I	04672786AC			04672786AC
FFCM	Forward Facing Camera Module	CAN-C	68551091AA			68551091AA
EDM	External Disc Module	CAN-I	68499745AA			68499745AA
APM	Accessory Power Module	CAN-C	05185046AB			05185046AB
BPCM	Battery Pack Control Module	CAN-C	68487194AA			68487194AA
HCP	Hybrid Control Processor	CAN-C	05185116AJ			05185116AJ
OBCM	On Board Charging Module	CAN-C	05185047AE			05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC			68321862AC
DSM	Display Screen Module	CAN-I	68437339AF			68437339AF
VRM	Video Routing Module	CAN-I	68493702AD			68493702AD
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA			6WL30DX9AA
CVPM	Central vision processing module	CAN-I	56029920AB			56029920AB
EAC	Electric A/C Compressor	CAN-C	68237995AG			68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05185117AJ			05185117AJ
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB			68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68471122AD			68471122AD
SGW	Security Gateway Module	CAN-C	68488429AB			68488429AB
TBM2	Telematic Box Module 2	CAN-C	68444865AH			68444865AH

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	CVNS
-----	--------------	------------------	------------------	-------	------

PCM	USA	1B 47	75 02 00	4422	7DC2E312
PLGM	USA	0	5084	000200000034	
ICS	USA	0F 0C 00	13 31 01	4700	
RFH	USA / USA	10 17 00	13 26 00	4A00	
ESM	USA / USA	13 02 00	14 23 FF	4402	
ORC	USA / USA	14 06 00	14 12 00	4301	
EPS	USA / USA	12 2A 00	12 1E 01	4502	
HVAC	USA	0E 09 00	14 2F 01	4401	
DDM	USA	11 07 00	14 07 00	4202	
PDM	USA	11 07 00	14 07 00	4202	
DMRL	USA / USA	10 0B 00	14 08 00	4201	
DMRR	USA / USA	10 0B 00	14 08 00	4201	
PSDML	USA / USA	10 17 00	14 10 12	4001	
PSDMR	USA / USA	10 17 00	14 10 12	4001	
MSM	USA	0F 2B 00	10 27 03	4101	
CSWM	USA	11 2A 00	14 25 00	4302	
AMP	USA	0F 06 01	15 0F 01	4021	
IPC	USA / USA	12 06 00	14 34 00	4705	
PTS	USA	0E 32 00	15 05 00	4311	
SCCM	USA	13 28 00	13 29 00	4301	
BCM	USA	0D 11 00	14 26 90	4420	
ACC	USA / USA	14 2A 01	15 23 02	4400	
RADIO		65	5671	000200000008	
OCM	USA / USA	11 1F 01	0E 2F 02	4030	
HVACR	USA	0E 09 00	10 03 02	4301	
LBSS	USA / USA	11 30 02	15 08 00	4202	
RBSS	USA / USA	11 30 02	15 08 00	4202	
FFCM	USA / USA	11 06 00	15 0C 00	4102	
EDM	USA	12 0A 00	11 08 00	4000	
APM	USA / USA	11 32 00	11 32 00	4001	
BPCM		0E 03 00	13 12 00	4005	D3037C3A
HCP	USA	11 1F 04	0F 2D 00	4006	5D31A9B9 16AACD23 050DC953
OBCM	USA	0F 0D 00	12 02 00	4002	
MSMP	USA	0F 2B 00	10 27 03	4001	
DSM	USA / USA	14 0C 00	15 06 00	4300	
VRM	USA / USA	0F 1C 00	15 0E 12	4001	
RCCC	USA	0F 1D 00	13 04 00	4000	
CVPM	USA / USA	11 27 01	14 0C 01	4004	
EAC	USA	0E 34 00	12 0F 00	4102	
AHCP	USA	11 1F 04	0F 2D 00	4000	
EBBM	USA	0E 19 02	14 0D 18	4000	E5898FA5
ABSO	USA	0E 15 02	14 1B 26	4201	4F158D1B
SGW		5	969	4103	

TBM2	USA	13 0E 02	14 2A 5F	4104	
------	-----	----------	----------	------	--

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
ACC	C2225-00	PCM Disabled ECU-	Active
BPCM	P0C78-00	Hybrid/EV Battery System Precharge "A" Time Too Long-	Active
HCP	U0412-00	Invalid Data Received From Battery Energy Control Module "A"-	Active
HCP	U209E-00		Active
OBCM	U209E-00	OBCM Received Implausible Data from BPCM-	Active

ENVIRONMENTAL DATA SUMMARY

ACC | C2225-00 | Active | PCM Disabled ECU-

NAME	VALUE	UNITS
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	False	
Confirmed DTC	False	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag		
Original Odometer Value		miles
Most Recent Odometer Value		miles
Frequency Counter		
Operation Cycle Counter		
Vehicle Speed		MPH
Engine RPM		rpm
ACC Set Speed		MPH
Object of Interest Distance		FEET
Engine Torque Request		Ft-Lbs
PRNDL Status		
Ignition Voltage		
System Voltage		Volts

BPCM | P0C78-00 | Active | Hybrid/EV Battery System Precharge "A" Time Too Long-

NAME	VALUE	UNITS
DTC	0C 78 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	

Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	ERROR	
Original Odometer Value	89	miles
Most Recent Odometer Value	89	miles
Frequency Counter	1	
Ignition Cycle Counter	0	
FoM - for this DTC (lifetime fails)	3	events
FoM - for this DTC (lifetime fails counts on pass)	0.0000	seconds
FoM - for this DTC (lifetime longest fail on pass)	0.000	seconds
Battery Total Time Awake	3820	seconds
Key in Ignition	Key_Def	
Key Position	Ign_Lock	
EPT -WakeUp	Sourced	
HCP Contactor Command	Impact Open	
Qualified Contactor Command - QCC	Open	
Verified Contactor Command - VCC	Invalid	
Contactor Status	PreCharging Inhibited	
Plug in Status	Not plugged in	
ChargingLevel	Plug in, but no charge	
Balance Mode	False	
Battery in Periodic wake up (Just battery) at time of Fault	False	
Battery in Periodic wake up (Wake up vehicle) at time of Fault	False	
Vehicle mileage at time of fault (ODO signal in \$3D2)	97.87	miles
Battery Lifetime Miles	333352	miles
Vehicle Speed	0.0	MPH
System (12) Volts at time of fault	13.316	Volts
Battery Lifetime AmpHrs of Charge	0.0	AHr
Battery Lifetime AmpHrs of DisCharge	3.9	AHr
SOC at time of Fault	28.2	%
Power Up SOC at time of Fault	28.2	%
HVIL Status -Vehicle	PASS	
HVIL Status - Battery pack	PASS	
HVIL PWM Duty Cycle - Vehicle	50.2	%
HVIL PWM Frequency - Vehicle	87.9	Hz
HVIL PWM peak voltage Sourced - Vehicle	12.591	Volts
HVIL PWM peak voltage Sensed - Vehicle	12.532	Volts
HVIL Source Voltage- Battery	1.385	Volts
HVIL Returned current - Battery	30.70	mA
HV Battery Current Sensor 1 Hall High	-0.60	Amps
HV Battery Current Sensor 2 Hall Low	0.00	Amps
HV Battery Current HVBatCrnt	0.00	Amps
HV Cooling Speed Pump 1 Target	0	rpm

HV Cooling Speed pump 1 Speed	0	rpm
Charge indicator Temp	63	°F
BPCM temperature max	68	°F
BPCM temperature min	66	°F
Pump - Wire Open\Short to Gnd	PASS	
Pump - Dry Run Detection	PASS	
Pump - Overcurrent	PASS	
Pump - Overtemperature	PASS	
Pump - Switch Power Shorted	PASS	
Isolation Circuitry Va	2.500	Volts
Isolation Circuitry Vb	2.501	Volts
Isolation Circuitry Vd	0.000	Volts
WC and Circuitry 2.5V Reference Voltage	2.501	Volts
WC and Circuitry Vcc Voltage	4.987	Volts
WC and CircuitryISO 8V Reference Voltage	7.966	Volts
WC and Circuitry Weld Contactor Sensor G (Pack Negative) Voltage	0.0	Volts
CVTN COMP ERR H	Normal	
CVTN COMP ERR L	Normal	
CVTN COMP FLT H	Normal	
CVTN COMP FLT L	Normal	
CVTN EDGE ERR H	Normal	
CVTN EDGE ERR L	Normal	
CVTN ABORT H	Normal	
CVTN ABORT L	Normal	
CVTN CRC FAULT H	Normal	
CVTN CRC FAULT L	Normal	
CVTN FRAM ERR	Normal	
CVTN STOP ERR	Normal	
CVTN STK FAULT ERR	Latched	
CVTN SYS RESET	Normal	
CVTN COMM TIMEOUT	Active	
CVTN VDIG WAKE FAULT	Normal	
CVTN INT TEMP FAULT	Normal	
CVTN VDIG FAULT	Normal	
CVTN VM FAULT	Normal	
CVTN VP FAULT	Normal	
CVTN VP CLAMP	Normal	
CVTN FACT CKSUM ERR	Normal	
CVTN ANALOG FAULT ERR	Normal	
CVTN HREF FAULT	Normal	
CVTN HREF GND FAULT	Normal	
CVTN ADC CAL ERR	Normal	
CVTN CUST ECC COR	Normal	
CVTN CUST ECC ERR	Latched	

CVTN FACT ECC COR	Normal	
CVTN ACT ECC ERR	Normal	
Cycles left to self heal	40	No Unit
Fault trigger level 1	False	
Fault trigger level 2	False	
Fault trigger level 3	False	
Fault Path	01	
HV Battery Charge Power 2sec	92073	watts
HV Battery Charge Power 10sec	90504	watts
HV Battery Discharge Power 2sec	91341	watts
HV Battery Discharge Power 10sec	88329	watts
HV Battery Power	007530	watts
Key - DriveRdy (CAN)	True	
Battery Lifetime Number Of Closes	3	
Battery Full AmpHr Capacity	52	AmpHrs
Cell Impedance Max Discharge	0	mOhms
Cell Impedance Mim Discharge	0	mOhms
Battery Cell Voltage Maximum	3581	mV
Battery Cell Voltage Minimum	3577	mV
Battery Cell Voltage Average	3579	mV
Battery Cell Highest Cell number	42	
Battery Cell Lowest Cell number	30	
HV Battery Voltage (cell sum)	343.60	Volts
HV Battery Voltage (Module Sum)	343.30	Volts
HV Sensor A Pack Voltage	343.70	Volts
HV Sensor B Bus\Link (Pre-Fuse) Voltage	1.20	Volts
HV Sensor C OBCM (HVOBC Fuse) Voltage	0.60	Volts
HV Sensor D Heater (HVHTR Fuse) Voltage	0.60	Volts
HV Sensor G Weld Contactor(Pack Negative) Voltage	0.0	Volts
Battery Temperature Maximum Module	68	°F
Battery Temperature Minimum Module	66	°F
Battery Temperature Average Module	68	°F
Battery Temperature Highest Sensor number	04	
Battery Temperature Lowest Sensor number	01	
Battery Temperature Number of Failing Sensors	00	
HV Cooling Pump Relay Drive	Not Sourced	
HV Cooling Battery coolant inlet temp	64	°F
HV Cooling Battery coolant outlet temp	64	°F
HV Cooling OBCM temp inlet Temp	63	°F
Pump - Battery Coolant Level Low	False	
Isolation Vehicle Diagnostic Status	Run and Passed	
Isolation Vehicle Impedance	0.6390	Mega Ohms
Isolation Battery Diagnostic Status	Not Run	
Isolation Battery Impedance	9.8780	Mega Ohms

HCP | U0412-00 | Active | Invalid Data Received From Battery Energy Control Module "A"-

NAME	VALUE	UNITS
DTC	C4 12 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	False	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag		
Original Odometer Value		miles
Most Recent Odometer Value		miles
Frequency Counter		
Ignition Cycle Counter		
Real time clock		sec
RAM stamps keyOn		sec
RAM Stamps		Min
Accelerator Pedal Position		%
Brake Switch Status		
Engine Speed		rpm
HV Battery SOC		%
Ignition State		
PRND Position Display		
Propulsion System Active		
Vehicle Speed		MPH
Motor A Temp Sensor		°F
Motor B Temp Sensor		°F
Barometric Pressure		PSI
Engine Coolant Temperature		°F
Internal EPS Voltage Sense A		Volts
Internal EPS Voltage Sense B		Volts
Motor A Torque		Ft-Lbs
Motor B Torque		Ft-Lbs
Actual Torque - Motor A		Ft-Lbs
Actual Torque - Motor B		Ft-Lbs
Available Motor Torque - Motor A		Ft-Lbs
Available Motor Torque - Motor B		Ft-Lbs
Available Regen Torque - Motor A		Ft-Lbs
Available Regen Torque - Motor B		Ft-Lbs
Commanded Torque - Motor A		Ft-Lbs

Commanded Torque - Motor B		Ft-Lbs
Motor A - Inverter Current - phase A		AMP
Motor A - Inverter Current - phase B		AMP
Motor A - Inverter Current - phase C		AMP
Motor B - Inverter Current - phase A		AMP
Motor B - Inverter Current - phase B		AMP
Motor B - Inverter Current - phase C		AMP
Motor B Resolver Angle		Degree
Motor A Resolver Angle		Degree
Electric Motor A Speed		rpm
Electric Motor B Speed		rpm
PIM DC Link Voltage - A		Volts
PIM DC Link Voltage - B		Volts
HCP ePT Wake-Up Output		
CBC Wake-Up Input		
HCP System Shutdown Command		
HV Battery Voltage from BPCM		Volts
SW Build Release Version		
HCP SW Version		
EPT LOC Diag Enable		
HV Contactor Status		
APM Status		
Impact Event		
Outside Air Temperature		°F
OBCM Operating Mode		
J1772 Prox Detected State		
HV Battery Sleep Time		Days
Battery Feed Voltage 1 Sense		Volts
Battery Feed Voltage 2 Sense		Volts
Battery Feed Voltage 3 Sense		Volts
Hybrid System State		
Inverter A IGBT Temperature for phase A		°F
Inverter A IGBT Temperature for phase B		°F
Inverter A IGBT Temperature for phase C		°F
Inverter B IGBT Temperature for phase A		°F
Inverter B IGBT Temperature for phase B		°F
Inverter B IGBT Temperature for phase C		°F
PHEV Charging Status		
Distance Travelled with Light ON		miles
GPS Date - Year		Year
GPS Date - Month		
GPS Date - Day		Days
UTC Time - Hours		Hours
UTC Time - Minutes		

UTC Time - Seconds		seconds
ECU Time - Milliseconds		ms

HCP | U209E-00 | Active |

NAME	VALUE	UNITS
------	-------	-------

OBCM | U209E-00 | Active | OBCM Received Implausible Data from BPCM-

NAME	VALUE	UNITS
DTC	E0 9E 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	ERROR	
Original Odometer Value	89	miles
Most Recent Odometer Value	89	miles
Frequency Counter	1	
Ignition Cycle Counter	0	
DTC Extended Data Record Number - Record #2	30	
OBCM Status AC Present	AC Not OK	
AC Line Low	Valid	
AC Line High	Not Valid	
AC Side Current	0.50	Amps
AC Side Volt	1.9	Volts
HCP (EVCU) AC Current Max Cal	-0.50	Amps
HCP (EVCU) Voltage Request	0	Volts
HCP (EVCU) Current Request	0.00	AMP
Battery Not Detected	False	
Battery Voltage Under Min	Not Valid	
Battery Voltage Over Max	Not Valid	
Battery Side Current	0.20	Amps
Battery Side Voltage	0.0	Volts
HV OC	False	
HV OV	False	
HCP (EVCU) HV Current Max Cal	-12.00	Amps
HCP (EVCU) HV Volt Max Cal	152	Volt
HCP (EVCU) HV Volt Min Cal	244	Volt
OBCM Temperature 1	73	°F
OBCM Temperature 2	72	°F

OBCM Temperature 3	63	°F
OBCM Temperature 4	59	°F
NTC1 OT	False	
NTC2 OT	False	
NTC3 OT	False	
NTC4 OT	False	
External OBCM Inlet Temperature (CAN)	-40	°F
J1772 ICA	0	AMP
J1772 S2 Close	Open	
J1772 Stat	Veh Not Connected	
J1772 S2 Status	Open	
Control Pilot Amplitude	7.517	Volts
Control Pilot Duty Cycle	0.00	%
Control Pilot Frequency	1024	Hz
EVSE Pilot Stat	NO EVSE	
Prox Stat	Prox Out	
Prox Voltage	4.431	Volt
OBC Idle Tml	1	hrs
Watt-Hours of AC Power	0	W-Hrs
Watt Hours of Charge the HV Bus	0	W-Hrs
OBCM Mode	UTC	
OBCM Charger Ready	Off	
OBCM WU Status	Off	
Charge Enable Status	Chrg Disable	
HCP (EVCU) Shutdown Command	EVCU Operational	
HCP (EVCU) Enable Charge Command	Charge disable	
HCP (EVCU) OBC Mode Request	Idle	
Generic Fail Sts	At Least One DTC set on Sys Mem	
Chrg Fail Sts	No Faults detected	
OBCM Wake Up Reason	Master Wake Up	
OBC Control Mth	Current	
OBCM Deraing Reason	AC Voltage Limit Derating	
Close Chrg Cntctr	Open	
Chrg Cntctr Stat	Precharge Inhibited	
Chrg Mode	Charge Mode	
OBCM Fault Reason	No Faults detected	
Module A Primary - PFC Temperature	61	°F
Module A Primary - LLC Temperature	61	°F
Module A Secondary - Buck Temperature	59	°F
Module A Secondary - Ambient Temperature	72	°F
Module A Primary - AC Side Volt	2.6	Volts
Module A Primary - AC Side Current	-24.60	Amps
Module A Secondary - Battery Side Voltage	0.0	Volts
Module A Secondary - Battery Side Current	-24.90	Amps

Module A Secondary - Buck Output Voltage	0.1	Volts
Module B Primary - PFC Temperature	63	°F
Module B Primary - LLC Temperature	63	°F
Module B Secondary - Buck Temperature	63	°F
Module B Secondary - Ambient Temperature	73	°F
Module B Primary - AC Side Volt	1.3	Volts
Module B Primary - AC Side Current	-24.90	Amps
Module B Secondary - Battery Side Voltage	0.0	Volts
Module B Secondary - Battery Side Current	-24.90	Amps
Module B Secondary - Buck Output Voltage	0.1	Volts
OBCM - HV Over Voltage Protect	False	
OBCM - LV Aux Over Voltage Protect	False	
OBCM - LV Aux Under Voltage Protect	False	
OBCM - LLC Over Voltage Protect	False	
OBCM - LLC Under Voltage Protect	False	
OBCM - PFC Over Voltage Protect	False	
OBCM - PFC Under Voltage Protect	False	
OBCM - Battery 12V Under Voltage Protect	False	
OBCM - Battery 12V Over Voltage Protect	False	
OBCM - AC Under Voltage Protect	False	
OBCM - AC Over Voltage Protect	False	
OBCM - AC Over Current Protect	False	
OBCM - HV Voltage Over MaxCal Protect	False	
OBCM - HV Over Current Protect	False	
OBCM - Power Stage Over Voltage Protect	False	
OBCM - Internal Memory Fault	False	
OBCM - Over Temperature Protect	False	
OBCM - HCP Loss of Communication Protect	False	
OBCM - Loss BPCM Communication Protect	False	
OBCM - CAN Bus Off	False	
OBCM - Pilot Duty Fault	False	
OBCM - Prox Range To Low	False	
OBCM - Prox Range To High	False	
OBCM - HV Voltage Under MinCal Protect	False	
OBCM - SPI Communication Fault	False	
OBCM - Pilot Short To Battery	False	
OBCM - WakeUp Output Stuck Low	False	
OBCM - WakeUp Output Stuck High	False	
OBCM - ORC Loss of Communication	False	
OBCM - HV Battery Not Contact	False	
OBCM - Loss Communication Protect	False	
OBCM - Receive HV Battery Contact Open From BPCM	False	
OBCM - Secondary Aux Over Voltage Protect	False	
OBCM - Secondary Aux Under Voltage Protect	False	

OBCM - Primary Aux Over Voltage Protect	False	
OBCM - Primary Aux Under Voltage Protect	False	
OBCM - Stuck Shutdown	False	
OBCM - Cycle Shutdown	False	
OBCM - HV Under Voltage Protect	False	
OBCM - Vehicle Impact	False	
OBCM - ARC/CRC Fault	False	
OBCM - AC Contact Welded Fault	False	
Control Pilot Open fault	False	
Prox open fault	False	
OBCM - Internal S2 Switch Low Fault	False	
OBCM - Internal S2 Switch High Fault	False	
OBCM - Pilot Range Fault	False	
OBCM - Prox Range Fault	False	
force shutdown fault	False	
pilot signal wake up issue because of EVSE	False	
HCP stuck low fault	False	
HCP stuck High fault	False	
Plant mode flag	True	
Retry fault flag	False	
Loss SBC communcation (SPI)	False	
pilot input short to ground fault	False	
pilto input short to battery fault in Driver mode detecting	False	
pilot short to ground fault in driver mode detecting	False	
Charging ready line open fault	False	
Pilot frequency range fault	False	
OBCM - Internal S2 Switch High Fault in Driver mode detecting	False	
Module A Primary - AC Under Voltage Protect	False	
Module A Primary - PFC Power Limit	True	
Module A Primary - PFC Enable States	False	
Module A Primary - LLC Enable States	False	
Module A Primary - PFC Under Voltage Protect	False	
Module A Primary - PFC Over Voltage Protect	False	
Module A Primary - Over Temperature Protect	False	
Module A Primary - Hot Warning	False	
Module A Primary - AC Present	False	
Module A Primary - PFC Over Temperature Protect	False	
Module A Primary - LLC Over Temperature Protect	False	
Module A Primary - PFC Hot Warning	False	
Module A Primary - LLC Hot Warning	False	
Module A Primary - AC Over Voltage Protect	True	
Module A Primary - Relay Enable States	False	
Module A Primary - Aux Over Voltage Protect	False	
Module A Primary - Aux Under Voltage Protect	False	

Module A Primary - Secondary Micro Enable Command	False	
Module A Primary - AC Vin Lost	True	
Module A Primary - Loss Communication Protect	False	
Module A Primary - Standby Mode	True	
Module A Primary - Operate Mode	False	
Module A Primary - Shutdown Mode	False	
Module A Secondary - Aux Enable States	True	
Module A Secondary - HV Enable States	False	
Module A Secondary - LLC Under Voltage Protect	False	
Module A Secondary - LLC Over Voltage Protect	False	
Module A Secondary - HV Over Voltage Protect	False	
Module A Secondary - HV Over Current Protect	False	
Module A Secondary - Over Temperature Protect	False	
Module A Secondary - Hot Warning	False	
Module A Secondary - HV Over Temperature Protect	False	
Module A Secondary - Ambient Over Temperature Protect	False	
Module A Secondary - HV Hot Warning	False	
Module A Secondary - Ambient Hot Warning	False	
Module A Secondary - Aux Over Voltage Protect	False	
Module A Secondary - Aux Under Voltage Protect	False	
Module A Secondary - Loss Primary Communication Protect	False	
Module A Secondary - LV Micro Enable Command	False	
Module A Secondary - Loss LV Communication Protect	False	
Module A Secondary - Primary Turn On States	False	
Module A Secondary - Primary Shutdown States	False	
Module A Secondary - HV Under Voltage Protect	False	
Module A Secondary - Standby Mode	True	
Module A Secondary - Operate Mode	False	
Module A Secondary - Shutdown Mode	False	
Module A Secondary - LV Micro Disable Command	True	
Module A Secondary - PFC High Temperature Derating	False	
Module A Secondary - PFC Low Temperature Derating	False	
Module A Secondary - LLC High Temperature Derating	False	
Module A Secondary - LLC Low Temperature Derating	False	
Module A Secondary - HV High Temperature Derating	False	
Module A Secondary - HV Low Temperature Derating	False	
Module A Secondary - Ambient High Temperature Derating	False	
Module A Secondary - Ambient Low Temperature Derating	False	
Module A Secondary - AC Input Voltage Derating	True	
Module A Secondary - HV Output Voltage Derating	False	
Module B Primary - AC Under Voltage Protect	False	
Module B Primary - PFC Power Limit	True	
Module B Primary - PFC Enable States	False	
Module B Primary - LLC Enable States	False	

Module B Primary - PFC Under Voltage Protect	False	
Module B Primary - PFC Over Voltage Protect	False	
Module B Primary - Over Temperature Protect	False	
Module B Primary - Hot Warning	False	
Module B Primary - AC Present	False	
Module B Primary - PFC Over Temperature Protect	False	
Module B Primary - LLC Over Temperature Protect	False	
Module B Primary - PFC Hot Warning	False	
Module B Primary - LLC Hot Warning	False	
Module B Primary - AC Over Voltage Protect	True	
Module B Primary - Relay Enable States	False	
Module B Primary - Aux Over Voltage Protect	False	
Module B Primary - Aux Under Voltage Protect	False	
Module B Primary - Secondary Micro Enable Command	False	
Module B Primary - AC Vin Lost	True	
Module B Primary - Loss Communication Protect	False	
Module B Primary - Standby Mode	True	
Module B Primary - Operate Mode	False	
Module B Primary - Shutdown Mode	False	
Module B Secondary - Aux Enable States	True	
Module B Secondary - HV Enable States	False	
Module B Secondary - LLC Under Voltage Protect	False	
Module B Secondary - LLC Over Voltage Protect	False	
Module B Secondary - HV Over Voltage Protect	False	
Module B Secondary - HV Over Current Protect	False	
Module B Secondary - Over Temperature Protect	False	
Module B Secondary - Hot Warning	False	
Module B Secondary - HV Over Temperature Protect	False	
Module B Secondary - Ambient Over Temperature Protect	False	
Module B Secondary - HV Hot Warning	False	
Module B Secondary - Ambient Hot Warning	False	
Module B Secondary - Aux Over Voltage Protect	False	
Module B Secondary - Aux Under Voltage Protect	False	
Module B Secondary - Loss Primary Communication Protect	False	
Module B Secondary - LV Micro Enable Command	False	
Module B Secondary - Loss LV Communication Protect	False	
Module B Secondary - Primary Turn On States	False	
Module B Secondary - Primary Shutdown States	False	
Module B Secondary - HV Under Voltage Protect	False	
Module B Secondary - Standby Mode	True	
Module B Secondary - Operate Mode	False	
Module B Secondary - Shutdown Mode	False	
Module B Secondary - LV Micro Disable Command	True	
Module B Secondary - PFC High Temperature Derating	False	

Module B Secondary - PFC Low Temperature Derating	False	
Module B Secondary - LLC High Temperature Derating	False	
Module B Secondary - LLC Low Temperature Derating	False	
Module B Secondary - HV High Temperature Derating	False	
Module B Secondary - HV Low Temperature Derating	False	
Module B Secondary - Ambient High Temperature Derating	False	
Module B Secondary - Ambient Low Temperature Derating	False	
Module B Secondary - AC Input Voltage Derating	True	
Module B Secondary - HV Output Voltage Derating	False	
SBC State_DF00	00	
SBC State_DF80	00	
SBC State_E100	00	
SBC State_E180	00	
SBC State_E300	00	
SBC State_E500	00	
SBC State_E580	00	
OBCM Charge Current Available	0.00	AMP
BPCM HV Battery Contactor Open	False	
SBC Bus Off	False	
CANSIP Bus Off	False	
OBC Charge Time	0	sec
OBC Charge Tml	1	hrs
OBC Idle Time	0	sec
EPT LOC Diag Enable	Enable LOC Diagnostic	
HCP Shutdown Command	No Shutdown	
HV Battey Contactor Open	False	
BPCM Request for HV Contactor	False	
HV Contactor Status	Closed	
Ignition on Time for DTC	0	sec

SNAPSHOT DATA SUMMARY


No Snapshot Data available for C2225-00

No Snapshot Data available for P0C78-00

No Snapshot Data available for U0412-00

No Snapshot Data available for U209E-00

No Snapshot Data available for U209E-00



VEHICLE SCAN REPORT

Vehicle 2021 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN [REDACTED]

Odometer 97.9 miles
Publication Date 4/8/2022, 2:31:19 PM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
PCM	Powertrain Control Module	CAN-C	68499122AF	[REDACTED]	[REDACTED]	68499122AF
PLGM	Power Liftgate	CAN-I	68466171AI	[REDACTED]	—	68466171AI
ICS	Integrated Center Stack	CAN-I	7AS341X8AA	[REDACTED]	[REDACTED]	7AS341X8AA
RFH	Radio Frequency Hub	CAN-C	68500152AA	[REDACTED]	[REDACTED]	68500152AA
ESM	Electronic Shifter	CAN-C	68240089AN	[REDACTED]	[REDACTED]	68240089AN
ORC	Occupant Restraint	CAN-C	68526665AB	[REDACTED]	[REDACTED]	68526665AB
EPS	Electric Power Steering	CAN-C	68460392AA	[REDACTED]	[REDACTED]	68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68493454AE	[REDACTED]	[REDACTED]	68493454AE
DDM	Driver Door Module	CAN-I	68496463AB	[REDACTED]	[REDACTED]	68496463AB
PDM	Passenger Door Module	CAN-I	68496462AB	[REDACTED]	[REDACTED]	68496462AB
DMRL	Door Module Rear Left	CAN-I	68508894AB	[REDACTED]	[REDACTED]	68508894AB
DMRR	Door Module Rear Right	CAN-I	68508894AB	[REDACTED]	[REDACTED]	68508894AB
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD	[REDACTED]	[REDACTED]	68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD	[REDACTED]	[REDACTED]	68369596AD
MSM	Memory Seat Module	CAN-I	68321862AC	[REDACTED]	[REDACTED]	68321862AC
CSWM	Comfort Seat Wheel Module	CAN-I	68517013AB	[REDACTED]	[REDACTED]	68517013AB
AMP	Amplifier	CAN-I	68547722AB	[REDACTED]	[REDACTED]	68547722AB
IPC	Instrument Panel Cluster	CAN-C	68434960AF	[REDACTED]	[REDACTED]	68434960AF
PTS	Parktronics	CAN-C	68485862AB	[REDACTED]	[REDACTED]	68485862AB

SCCM	Steering Column Control Module	CAN-C	68531525AA			68531525AA
BCM	Body Controller	CAN-C	68491085AG			68491085AG
ACC	Adaptive Cruise Control	CAN-C	68540436AC			68540436AC
RADIO	Radio	CAN-I	68465292AE			68465292AE
OCM	Occupant Classification	CAN-C	68403127AA			68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB			68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AC			04672786AC
RBSS	Right Blind Spot Sensor	CAN-I	04672786AC			04672786AC
FFCM	Forward Facing Camera Module	CAN-C	68551091AA			68551091AA
EDM	External Disc Module	CAN-I	68499745AA			68499745AA
APM	Accessory Power Module	CAN-C	05185046AB			05185046AB
BPCM	Battery Pack Control Module	CAN-C	68487194AA			68487194AA
HCP	Hybrid Control Processor	CAN-C	05185116AJ			05185116AJ
OBCM	On Board Charging Module	CAN-C	05185047AE			05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC			68321862AC
DSM	Display Screen Module	CAN-I	68437339AF			68437339AF
VRM	Video Routing Module	CAN-I	68493702AD			68493702AD
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA			6WL30DX9AA
CVPM	Central vision processing module	CAN-I	56029920AB			56029920AB
EAC	Electric A/C Compressor	CAN-C	68237995AG			68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05185117AJ			05185117AJ
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB			68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68471122AD			68471122AD
SGW	Security Gateway Module	CAN-C	68488429AB			68488429AB
TBM2	Telematic Box Module 2	CAN-C	68444865AH			68444865AH

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	CVNS
-----	--------------	------------------	------------------	-------	------

PCM	USA	1B 47	75 02 00	4422	7DC2E312
PLGM	USA	0	5084	000200000034	
ICS	USA	0F 0C 00	13 31 01	4700	
RFH	USA / USA	10 17 00	13 26 00	4A00	
ESM	USA / USA	13 02 00	14 23 FF	4402	
ORC	USA / USA	14 06 00	14 12 00	4301	
EPS	USA / USA	12 2A 00	12 1E 01	4502	
HVAC	USA	0E 09 00	14 2F 01	4401	
DDM	USA	11 07 00	14 07 00	4202	
PDM	USA	11 07 00	14 07 00	4202	
DMRL	USA / USA	10 0B 00	14 08 00	4201	
DMRR	USA / USA	10 0B 00	14 08 00	4201	
PSDML	USA / USA	10 17 00	14 10 12	4001	
PSDMR	USA / USA	10 17 00	14 10 12	4001	
MSM	USA	0F 2B 00	10 27 03	4101	
CSWM	USA	11 2A 00	14 25 00	4302	
AMP	USA	0F 06 01	15 0F 01	4021	
IPC	USA / USA	12 06 00	14 34 00	4705	
PTS	USA	0E 32 00	15 05 00	4311	
SCCM	USA	13 28 00	13 29 00	4301	
BCM	USA	0D 11 00	14 26 90	4420	
ACC	USA / USA	14 2A 01	15 23 02	4400	
RADIO		65	5671	000200000008	
OCM	USA / USA	11 1F 01	0E 2F 02	4030	
HVACR	USA	0E 09 00	10 03 02	4301	
LBSS	USA / USA	11 30 02	15 08 00	4202	
RBSS	USA / USA	11 30 02	15 08 00	4202	
FFCM	USA / USA	11 06 00	15 0C 00	4102	
EDM	USA	12 0A 00	11 08 00	4000	
APM	USA / USA	11 32 00	11 32 00	4001	
BPCM		0E 03 00	13 12 00	4005	D3037C3A
HCP	USA	11 1F 04	0F 2D 00	4006	5D31A9B9 16AACD23 050DC953
OBCM	USA	0F 0D 00	12 02 00	4002	
MSMP	USA	0F 2B 00	10 27 03	4001	
DSM	USA / USA	14 0C 00	15 06 00	4300	
VRM	USA / USA	0F 1C 00	15 0E 12	4001	
RCCC	USA	0F 1D 00	13 04 00	4000	
CVPM	USA / USA	11 27 01	14 0C 01	4004	
EAC	USA	0E 34 00	12 0F 00	4102	
AHCP	USA	11 1F 04	0F 2D 00	4000	
EBBM	USA	0E 19 02	14 0D 18	4000	E5898FA5
ABSO	USA	0E 15 02	14 1B 26	4201	4F158D1B
SGW		5	969	4103	

TBM2	USA	13 0E 02	14 2A 5F	4104	
------	-----	----------	----------	------	--

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
MSM	B222D-00	ECU Unable To Configure/Configuration Not Learned-	Stored
ACC	C2225-00	PCM Disabled ECU-	Active
ACC	C2227-00	ABS Disabled ECU-	Stored
BPCM	P0AA4-00	Hybrid/EV Battery Negative Contactor "A" Stuck Closed-	Active
BPCM	P0C78-00	Hybrid/EV Battery System Precharge "A" Time Too Long-	Stored
HCP	P084F-00	Park/Neutral Switch Output-	Stored
HCP	P0A0A-00	High Voltage System Interlock Circuit "A"-	Active
HCP	U0412-00	Invalid Data Received From Battery Energy Control Module "A"-	Active
HCP	U209E-00		Active
OBCM	U209E-00	OBCM Received Implausible Data from BPCM-	Active
MSMP	B222D-00	ECU Unable To Configure/Configuration Not Learned-	Stored
TBM2	B210D-16	Battery Voltage Low-Circuit Voltage Below Threshold	Stored
TBM2	U0184-00	Lost Communication With Radio-	Stored

ENVIRONMENTAL DATA SUMMARY

MSM | B222D-00 | Stored | ECU Unable To Configure/Configuration Not Learned-

NAME	VALUE	UNITS
DTC	A2 2D 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	Occurrence	
Original Odometer Value	99	miles
Most Recent Odometer Value	99	miles
Frequency Counter	1	
Ignition Cycle Counter	3	
DTC Extended Data Record Number	14	
Calibration Version	03 09 00 01	
Front Hard Stop - Current	32986	Counts
Rear Hard Stop - Current	32204	Counts
Learned Seat Travel - Current	782	Counts
Default Seat travel length	780	Counts
Destandardization Reason	Diagnostics	

Front Hard Stop - Pre-destandardization	Not Learned	Counts
Rear Hard Stop - Pre-destandardization	Not Learned	Counts
Learned Seat Travel - Pre-destandardization	Not Learned	Counts
Front Hard Stop - Post-destandardization	32986	Counts
Rear Hard Stop - Post-destandardization	32204	Counts
Learned Seat Travel - Post-destandardization	782	Counts
ECU Voltage	2.186	Volts
Number of ECU hard resets since latest calibration	136	Counts
Vertical Front motor sensor - Short to ground	False	
Vertical Rear motor sensor - Short to ground	False	
Vertical Front motor sensor - Short to battery or open	False	
Vertical Rear motor sensor - Short to battery or open	False	
Horizontal motor sensor - Short to ground	False	
Horizontal motor sensor - Short to battery or open	False	
Recliner motor sensor - Short to ground	False	
Recliner motor sensor - Short to battery or open	False	
Position Horizontal Adjustment	32327	Counts
Position Vertical Rear	33054	Counts
Position Recliner	31928	Counts
Position Vertical Front	32793	Counts
Movement Direction - Horizontal Motor	Motor not moving	
Movement Direction - Recliner Motor	Motor not moving	
Movement Direction - Vertical Front Motor	Motor not moving	
Movement Direction - Vertical Rear Motor	Motor not moving	
ECU configuration - Vehicle Line	RU	
ECU configuration - Adjustable Pedals	False	
ECU configuration - Telescope/Tilt	False	
ECU configuration - Memory Seat	True	
ECU configuration - Stow n Assist	True	

ACC | C2225-00 | Active | PCM Disabled ECU-

NAME	VALUE	UNITS
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	False	
Confirmed DTC	False	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag		
Original Odometer Value		miles
Most Recent Odometer Value		miles
Frequency Counter		

Operation Cycle Counter		
Vehicle Speed		MPH
Engine RPM		rpm
ACC Set Speed		MPH
Object of Interest Distance		FEET
Engine Torque Request		Ft-Lbs
PRNDL Status		
Ignition Voltage		
System Voltage		Volts

ACC | C2227-00 | Stored | ABS Disabled ECU-

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	
Original Odometer Value	89	miles
Most Recent Odometer Value	89	miles
Frequency Counter	1	
Operation Cycle Counter	1	
Vehicle Speed	0	MPH
Engine RPM	0	rpm
ACC Set Speed	0	MPH
Object of Interest Distance	830	FEET
Engine Torque Request	SNA	Ft-Lbs
PRNDL Status	P range	
Ignition Voltage	11.9	
System Voltage	12.1	Volts

BPCM | P0AA4-00 | Active | Hybrid/EV Battery Negative Contactor "A" Stuck Closed-

NAME	VALUE	UNITS
DTC	0A A4 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	

Warning Indicator Requested	False	
Occurrence flag	Error	
Original Odometer Value	89	miles
Most Recent Odometer Value	89	miles
Frequency Counter	1	
Ignition Cycle Counter	0	
FoM - for this DTC (lifetime fails)	18	events
FoM - for this DTC (lifetime fails counts on pass)	0.0000	seconds
FoM - for this DTC (lifetime longest fail on pass)	0.000	seconds
Battery Total Time Awake	168578	seconds
Key in Ignition	Key_Def	
Key Position	Ign_Lock	
EPT -WakeUp	Sourced	
HCP Contactor Command	Open	
Qualified Contactor Command - QCC	Open	
Verified Contactor Command - VCC	Open	
Contactor Status	PreCharging Inhibited	
Plug in Status	Not plugged in	
ChargingLevel	Plug in, but no charge	
Balance Mode	False	
Battery in Periodic wake up (Just battery) at time of Fault	False	
Battery in Periodic wake up (Wake up vehicle) at time of Fault	False	
Vehicle mileage at time of fault (ODO signal in \$3D2)	97.87	miles
Battery Lifetime Miles	333352	miles
Vehicle Speed	0.0	MPH
System (12) Volts at time of fault	12.355	Volts
Battery Lifetime AmpHrs of Charge	0.0	AHr
Battery Lifetime AmpHrs of DisCharge	4.0	AHr
SOC at time of Fault	28.2	%
Power Up SOC at time of Fault	28.2	%
HVIL Status -Vehicle	PASS	
HVIL Status - Battery pack	PASS	
HVIL PWM Duty Cycle - Vehicle	50.2	%
HVIL PWM Frequency - Vehicle	87.9	Hz
HVIL PWM peak voltage Sourced - Vehicle	11.135	Volts
HVIL PWM peak voltage Sensed - Vehicle	11.067	Volts
HVIL Source Voltage- Battery	1.377	Volts
HVIL Returned current - Battery	30.70	mA
HV Battery Current Sensor 1 Hall High	-0.40	Amps
HV Battery Current Sensor 2 Hall Low	0.00	Amps
HV Battery Current HVBatCrnt	0.00	Amps
HV Cooling Speed Pump 1 Target	0	rpm
HV Cooling Speed pump 1 Speed	0	rpm
Charge indicator Temp	73	°F

BPCM temperature max	66	°F
BPCM temperature min	66	°F
Pump - Wire Open\Short to Gnd	PASS	
Pump - Dry Run Detection	PASS	
Pump - Overcurrent	PASS	
Pump - Overtemperature	PASS	
Pump - Switch Power Shorted	PASS	
Isolation Circuitry Va	2.498	Volts
Isolation Circuitry Vb	2.501	Volts
Isolation Circuitry Vd	0.000	Volts
WC and Circuitry 2.5V Reference Voltage	2.501	Volts
WC and Circuitry Vcc Voltage	4.982	Volts
WC and CircuitryISO 8V Reference Voltage	7.966	Volts
WC and Circuitry Weld Contactor Sensor G (Pack Negative) Voltage	0.0	Volts
CVTN COMP ERR H	Latched	
CVTN COMP ERR L	Normal	
CVTN COMP FLT H	Normal	
CVTN COMP FLT L	Normal	
CVTN EDGE ERR H	Normal	
CVTN EDGE ERR L	Normal	
CVTN ABORT H	Normal	
CVTN ABORT L	Normal	
CVTN CRC FAULT H	Normal	
CVTN CRC FAULT L	Normal	
CVTN FRAM ERR	Normal	
CVTN STOP ERR	Normal	
CVTN STK FAULT ERR	Latched	
CVTN SYS RESET	Normal	
CVTN COMM TIMEOUT	Normal	
CVTN VDIG WAKE FAULT	Normal	
CVTN INT TEMP FAULT	Normal	
CVTN VDIG FAULT	Normal	
CVTN VM FAULT	Normal	
CVTN VP FAULT	Normal	
CVTN VP CLAMP	Normal	
CVTN FACT CKSUM ERR	Normal	
CVTN ANALOG FAULT ERR	Normal	
CVTN HREF FAULT	Normal	
CVTN HREF GND FAULT	Normal	
CVTN ADC CAL ERR	Normal	
CVTN CUST ECC COR	Normal	
CVTN CUST ECC ERR	Normal	
CVTN FACT ECC COR	Active	
CVTN ACT ECC ERR	Latched	

Cycles left to self heal	40	No Unit
Fault trigger level 1	False	
Fault trigger level 2	False	
Fault trigger level 3	False	
Fault Path	01	
HV Battery Charge Power 2sec	92052	watts
HV Battery Charge Power 10sec	90486	watts
HV Battery Discharge Power 2sec	91323	watts
HV Battery Discharge Power 10sec	88308	watts
HV Battery Power	007530	watts
Key - DriveRdy (CAN)	True	
Battery Lifetime Number Of Closes	3	
Battery Full AmpHr Capacity	52	AmpHrs
Cell Impedance Max Discharge	0	mOhms
Cell Impedance Mim Discharge	0	mOhms
Battery Cell Voltage Maximum	3581	mV
Battery Cell Voltage Minimum	3576	mV
Battery Cell Voltage Average	3578	mV
Battery Cell Highest Cell number	42	
Battery Cell Lowest Cell number	73	
HV Battery Voltage (cell sum)	343.50	Volts
HV Battery Voltage (Module Sum)	343.20	Volts
HV Sensor A Pack Voltage	343.60	Volts
HV Sensor B Bus\Link (Pre-Fuse) Voltage	1.20	Volts
HV Sensor C OBCM (HVOBC Fuse) Voltage	0.60	Volts
HV Sensor D Heater (HVHTR Fuse) Voltage	0.60	Volts
HV Sensor G Weld Contactor(Pack Negative) Voltage	0.0	Volts
Battery Temperature Maximum Module	66	°F
Battery Temperature Minimum Module	66	°F
Battery Temperature Average Module	66	°F
Battery Temperature Highest Sensor number	04	
Battery Temperature Lowest Sensor number	03	
Battery Temperature Number of Failing Sensors	00	
HV Cooling Pump Relay Drive	Not Sourced	
HV Cooling Battery coolant inlet temp	66	°F
HV Cooling Battery coolant outlet temp	66	°F
HV Cooling OBCM temp inlet Temp	68	°F
Pump - Battery Coolant Level Low	False	
Isolation Vehicle Diagnostic Status	Run and Passed	
Isolation Vehicle Impedance	0.6390	Mega Ohms
Isolation Battery Diagnostic Status	Run and Passed	
Isolation Battery Impedance	0.8480	Mega Ohms
CVTN CUST CKSUM ERR	Normal	

BPCM | POC78-00 | Stored | Hybrid/EV Battery System Precharge "A" Time Too Long-

NAME	VALUE	UNITS
DTC	0C 78 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	
Original Odometer Value	89	miles
Most Recent Odometer Value	89	miles
Frequency Counter	2	
Ignition Cycle Counter	1	
FoM - for this DTC (lifetime fails)	10	events
FoM - for this DTC (lifetime fails counts on pass)	0.0000	seconds
FoM - for this DTC (lifetime longest fail on pass)	0.000	seconds
Battery Total Time Awake	167717	seconds
Key in Ignition	Key_Def	
Key Position	Ign_Run	
EPT -WakeUp	Sourced	
HCP Contactor Command	Open	
Qualified Contactor Command - QCC	Open	
Verified Contactor Command - VCC	Open	
Contactor Status	PreCharging Inhibited	
Plug in Status	Not plugged in	
ChargingLevel	Plug in, but no charge	
Balance Mode	False	
Battery in Periodic wake up (Just battery) at time of Fault	False	
Battery in Periodic wake up (Wake up vehicle) at time of Fault	False	
Vehicle mileage at time of fault (ODO signal in \$3D2)	97.87	miles
Battery Lifetime Miles	333352	miles
Vehicle Speed	0.0	MPH
System (12) Volts at time of fault	12.377	Volts
Battery Lifetime AmpHrs of Charge	0.0	AHr
Battery Lifetime AmpHrs of DisCharge	4.0	AHr
SOC at time of Fault	28.2	%
Power Up SOC at time of Fault	28.2	%
HVIL Status -Vehicle	PASS	
HVIL Status - Battery pack	PASS	
HVIL PWM Duty Cycle - Vehicle	50.2	%
HVIL PWM Frequency - Vehicle	87.9	Hz

HVIL PWM peak voltage Sourced - Vehicle	11.001	Volts
HVIL PWM peak voltage Sensed - Vehicle	10.957	Volts
HVIL Source Voltage- Battery	1.377	Volts
HVIL Returned current - Battery	30.70	mA
HV Battery Current Sensor 1 Hall High	0.00	Amps
HV Battery Current Sensor 2 Hall Low	0.00	Amps
HV Battery Current HVBatCmt	0.00	Amps
HV Cooling Speed Pump 1 Target	0	rpm
HV Cooling Speed pump 1 Speed	0	rpm
Charge indicator Temp	73	°F
BPCM temperature max	66	°F
BPCM temperature min	66	°F
Pump - Wire Open\Short to Gnd	PASS	
Pump - Dry Run Detection	PASS	
Pump - Overcurrent	PASS	
Pump - Overtemperature	PASS	
Pump - Switch Power Shorted	PASS	
Isolation Circuitry Va	2.500	Volts
Isolation Circuitry Vb	2.501	Volts
Isolation Circuitry Vd	0.000	Volts
WC and Circuitry 2.5V Reference Voltage	2.501	Volts
WC and Circuitry Vcc Voltage	4.982	Volts
WC and CircuitryISO 8V Reference Voltage	7.966	Volts
WC and Circuitry Weld Contactor Sensor G (Pack Negative) Voltage	0.0	Volts
CVTN COMP ERR H	Normal	
CVTN COMP ERR L	Normal	
CVTN COMP FLT H	Normal	
CVTN COMP FLT L	Normal	
CVTN EDGE ERR H	Normal	
CVTN EDGE ERR L	Normal	
CVTN ABORT H	Normal	
CVTN ABORT L	Normal	
CVTN CRC FAULT H	Normal	
CVTN CRC FAULT L	Normal	
CVTN FRAM ERR	Normal	
CVTN STOP ERR	Normal	
CVTN STK FAULT ERR	Latched	
CVTN SYS RESET	Normal	
CVTN COMM TIMEOUT	Active	
CVTN VDIG WAKE FAULT	Normal	
CVTN INT TEMP FAULT	Normal	
CVTN VDIG FAULT	Normal	
CVTN VM FAULT	Normal	
CVTN VP FAULT	Normal	

CVTN VP CLAMP	Normal	
CVTN FACT CKSUM ERR	Normal	
CVTN ANALOG FAULT ERR	Normal	
CVTN HREF FAULT	SNA	
CVTN HREF GND FAULT	Normal	
CVTN ADC CAL ERR	Active	
CVTN CUST ECC COR	Normal	
CVTN CUST ECC ERR	SNA	
CVTN FACT ECC COR	Normal	
CVTN ACT ECC ERR	Latched	
Cycles left to self heal	40	No Unit
Fault trigger level 1	False	
Fault trigger level 2	False	
Fault trigger level 3	False	
Fault Path	01	
HV Battery Charge Power 2sec	92052	watts
HV Battery Charge Power 10sec	90486	watts
HV Battery Discharge Power 2sec	91323	watts
HV Battery Discharge Power 10sec	88311	watts
HV Battery Power	007530	watts
Key - DriveRdy (CAN)	True	
Battery Lifetime Number Of Closes	3	
Battery Full AmpHr Capacity	52	AmpHrs
Cell Impedance Max Discharge	0	mOhms
Cell Impedance Mim Discharge	0	mOhms
Battery Cell Voltage Maximum	3581	mV
Battery Cell Voltage Minimum	3577	mV
Battery Cell Voltage Average	3579	mV
Battery Cell Highest Cell number	42	
Battery Cell Lowest Cell number	17	
HV Battery Voltage (cell sum)	343.60	Volts
HV Battery Voltage (Module Sum)	343.20	Volts
HV Sensor A Pack Voltage	343.60	Volts
HV Sensor B Bus\Link (Pre-Fuse) Voltage	1.20	Volts
HV Sensor C OBCM (HVOBC Fuse) Voltage	0.60	Volts
HV Sensor D Heater (HVHTR Fuse) Voltage	0.60	Volts
HV Sensor G Weld Contactor(Pack Negative) Voltage	0.0	Volts
Battery Temperature Maximum Module	66	°F
Battery Temperature Minimum Module	66	°F
Battery Temperature Average Module	66	°F
Battery Temperature Highest Sensor number	04	
Battery Temperature Lowest Sensor number	03	
Battery Temperature Number of Failing Sensors	00	
HV Cooling Pump Relay Drive	Not Sourced	

HV Cooling Battery coolant inlet temp	66	°F
HV Cooling Battery coolant outlet temp	66	°F
HV Cooling OBCM temp inlet Temp	68	°F
Pump - Battery Coolant Level Low	False	
Isolation Vehicle Diagnostic Status	Run and Passed	
Isolation Vehicle Impedance	0.6390	Mega Ohms
Isolation Battery Diagnostic Status	Run and Passed	
Isolation Battery Impedance	0.8480	Mega Ohms
CVTN CUST CKSUM ERR	Normal	

HCP | P084F-00 | Stored | Park/Neutral Switch Output-

NAME	VALUE	UNITS
DTC	08 4F 00	
Test Failed	False	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Occurrence	
Original Odometer Value	97.9	miles
Most Recent Odometer Value	97.9	miles
Frequency Counter	2	
Ignition Cycle Counter	0	
Real time clock	168596	sec
RAM stamps keyOn	0	sec
RAM Stamps	304	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
PHEV Charging Status	No Charging	
Engine Speed	0	rpm
HV Battery SOC	28	%
Ignition State	Ignition Lock	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Barometric Pressure	15	PSI
Engine Coolant Temperature	176	°F
PP Actuator Position Sensor Voltage	4.08	Volts
Shift Lock Status	Locked	
Reverse Shift Lock Status	Unlocked	
PRND Blink	Initialization	

Auto Correction Request	APCM Off	
Park Pawl Motor PWM1	0	%
Park Pawl Motor Direction	Out of Park/Move Towards Disengage	
Park Pawl Motor Enable Feedback	Disabled	
Park Pawl Motor Current	0.1	AMP
Park Pawl Motor Counts	408	Counts
Park Pawl Status Feedback	Segment Two Complete	
Park Gated Switch	In Park	
Failure Reasons for Level 2 eShift	Reserved	
Battery Feed Voltage 2 Sense	12.240	Volts
Battery Feed Voltage 3 Sense	12.240	Volts
Internal EPS Voltage Sense A	0.000	Volts
Internal EPS Voltage Sense B	0.000	Volts
Battery Feed Voltage 1 Sense	12.240	Volts
Hybrid System State	Evaluate High Voltage Enable	
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.000	Ft-Lbs
Available Motor Torque - Motor A	43.603	Ft-Lbs
Available Motor Torque - Motor B	116.150	Ft-Lbs
Available Regen Torque - Motor A	-43.603	Ft-Lbs
Available Regen Torque - Motor B	-116.150	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor A - Inverter Current - phase A	-4	AMP
Motor A - Inverter Current - phase B	-4	AMP
Motor A - Inverter Current - phase C	-4	AMP
Motor B - Inverter Current - phase A	0	AMP
Motor B - Inverter Current - phase B	-4	AMP
Motor B - Inverter Current - phase C	0	AMP
Motor A Resolver Angle	224	Degree
Motor B Resolver Angle	276	Degree
Motor A Temp Sensor	72	°F
Motor B Temp Sensor	72	°F
Outside Air Temperature	68.0	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
EPT LOC Diag Enable	Disable LOC Daignostic	
HV Contactor Status	Precharge_Inhibited	
HV Battery Voltage from BPCM	180.00	Volts
Electric Motor A Speed	0.0	rpm
Electric Motor B Speed	0.0	rpm
PIM DC Link Voltage - A	3	Volts
PIM DC Link Voltage - B	2	Volts
Inverter A IGBT Temperature for phase A	68	°F

Inverter A IGBT Temperature for phase B	68	°F
Inverter A IGBT Temperature for phase C	68	°F
Inverter B IGBT Temperature for phase A	68	°F
Inverter B IGBT Temperature for phase B	68	°F
Inverter B IGBT Temperature for phase C	68	°F
APM Status	Idle	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	0	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.000	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
GPS Date - Year	0	Year
GPS Date - Month	1	
GPS Date - Day	1	Days
UTC Time - Hours	0	Hours
UTC Time - Minutes	0	
UTC Time - Seconds	2	seconds
ECU Time - Milliseconds	624	ms

HCP | P0A0A-00 | Active | High Voltage System Interlock Circuit "A"-

NAME	VALUE	UNITS
DTC	0A 0A 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	Occurrence	
Original Odometer Value	97.9	miles
Most Recent Odometer Value	97.9	miles
Frequency Counter	2	
Ignition Cycle Counter	0	
Real time clock	168743	sec
RAM stamps keyOn	0	sec
RAM Stamps	304	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
Engine Speed	0	rpm

HV Battery SOC	28	%
Ignition State	Reserved	
PRND Position Display	N	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Motor A Temp Sensor	72	°F
Motor B Temp Sensor	72	°F
Barometric Pressure	14	PSI
Engine Coolant Temperature	68	°F
Internal EPS Voltage Sense A	0.000	Volts
Internal EPS Voltage Sense B	0.000	Volts
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.000	Ft-Lbs
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.000	Ft-Lbs
Available Motor Torque - Motor A	43.603	Ft-Lbs
Available Motor Torque - Motor B	232.301	Ft-Lbs
Available Regen Torque - Motor A	-43.603	Ft-Lbs
Available Regen Torque - Motor B	-232.301	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor A - Inverter Current - phase A	-4	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	0	AMP
Motor B - Inverter Current - phase A	0	AMP
Motor B - Inverter Current - phase B	-4	AMP
Motor B - Inverter Current - phase C	0	AMP
Motor B Resolver Angle	142	Degree
Motor A Resolver Angle	16	Degree
Electric Motor A Speed	17.0	rpm
Electric Motor B Speed	-5.0	rpm
PIM DC Link Voltage - A	3	Volts
PIM DC Link Voltage - B	2	Volts
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
HCP System Shutdown Command	Default	
HV Battery Voltage from BPCM	180.00	Volts
SW Build Release Version	PIM_21B_2109A0_RU_HCP_	
HCP SW Version	21B	
EPT LOC Diag Enable	Enable Limited LOC Diagnostic	
HV Contactor Status	Precharge_Inhibited	
APM Status	Idle	
Impact Event	False	
Outside Air Temperature	68.0	°F

OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Battery Feed Voltage 1 Sense	12.024	Volts
Battery Feed Voltage 2 Sense	12.024	Volts
Battery Feed Voltage 3 Sense	11.880	Volts
Hybrid System State	SNA	
Inverter A IGBT Temperature for phase A	68	°F
Inverter A IGBT Temperature for phase B	68	°F
Inverter A IGBT Temperature for phase C	68	°F
Inverter B IGBT Temperature for phase A	68	°F
Inverter B IGBT Temperature for phase B	68	°F
Inverter B IGBT Temperature for phase C	68	°F
PHEV Charging Status	No Charging	
Distance Travelled with Light ON	0	miles
GPS Date - Year	0	Year
GPS Date - Month	1	
GPS Date - Day	1	Days
UTC Time - Hours	0	Hours
UTC Time - Minutes	0	
UTC Time - Seconds	14	seconds
ECU Time - Milliseconds	416	ms

HCP | U0412-00 | Active | Invalid Data Received From Battery Energy Control Module "A"-

NAME	VALUE	UNITS
DTC	C4 12 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	False	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag		
Original Odometer Value		miles
Most Recent Odometer Value		miles
Frequency Counter		
Ignition Cycle Counter		
Real time clock		sec
RAM stamps keyOn		sec
RAM Stamps		Min
Accelerator Pedal Position		%
Brake Switch Status		

Engine Speed		rpm
HV Battery SOC		%
Ignition State		
PRND Position Display		
Propulsion System Active		
Vehicle Speed		MPH
Motor A Temp Sensor		°F
Motor B Temp Sensor		°F
Barometric Pressure		PSI
Engine Coolant Temperature		°F
Internal EPS Voltage Sense A		Volts
Internal EPS Voltage Sense B		Volts
Motor A Torque		Ft-Lbs
Motor B Torque		Ft-Lbs
Actual Torque - Motor A		Ft-Lbs
Actual Torque - Motor B		Ft-Lbs
Available Motor Torque - Motor A		Ft-Lbs
Available Motor Torque - Motor B		Ft-Lbs
Available Regen Torque - Motor A		Ft-Lbs
Available Regen Torque - Motor B		Ft-Lbs
Commanded Torque - Motor A		Ft-Lbs
Commanded Torque - Motor B		Ft-Lbs
Motor A - Inverter Current - phase A		AMP
Motor A - Inverter Current - phase B		AMP
Motor A - Inverter Current - phase C		AMP
Motor B - Inverter Current - phase A		AMP
Motor B - Inverter Current - phase B		AMP
Motor B - Inverter Current - phase C		AMP
Motor B Resolver Angle		Degree
Motor A Resolver Angle		Degree
Electric Motor A Speed		rpm
Electric Motor B Speed		rpm
PIM DC Link Voltage - A		Volts
PIM DC Link Voltage - B		Volts
HCP ePT Wake-Up Output		
CBC Wake-Up Input		
HCP System Shutdown Command		
HV Battery Voltage from BPCM		Volts
SW Build Release Version		
HCP SW Version		
EPT LOC Diag Enable		
HV Contactor Status		
APM Status		
Impact Event		

Outside Air Temperature		°F
OBCM Operating Mode		
J1772 Prox Detected State		
HV Battery Sleep Time		Days
Battery Feed Voltage 1 Sense		Volts
Battery Feed Voltage 2 Sense		Volts
Battery Feed Voltage 3 Sense		Volts
Hybrid System State		
Inverter A IGBT Temperature for phase A		°F
Inverter A IGBT Temperature for phase B		°F
Inverter A IGBT Temperature for phase C		°F
Inverter B IGBT Temperature for phase A		°F
Inverter B IGBT Temperature for phase B		°F
Inverter B IGBT Temperature for phase C		°F
PHEV Charging Status		
Distance Travelled with Light ON		miles
GPS Date - Year		Year
GPS Date - Month		
GPS Date - Day		Days
UTC Time - Hours		Hours
UTC Time - Minutes		
UTC Time - Seconds		seconds
ECU Time - Milliseconds		ms

HCP | U209E-00 | Active |

NAME	VALUE	UNITS
------	-------	-------

OBCM | U209E-00 | Active | OBCM Received Implausible Data from BPCM-

NAME	VALUE	UNITS
DTC	E0 9E 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	Error	
Original Odometer Value	89	miles
Most Recent Odometer Value	89	miles
Frequency Counter	3	
Ignition Cycle Counter	0	

DTC Extended Data Record Number - Record #2	30	
OBCM Status AC Present	AC Not OK	
AC Line Low	Valid	
AC Line High	Not Valid	
AC Side Current	0.50	Amps
AC Side Volt	1.9	Volts
HCP (EVCU) AC Current Max Cal	-0.50	Amps
HCP (EVCU) Voltage Request	0	Volts
HCP (EVCU) Current Request	0.00	AMP
Battery Not Detected	False	
Battery Voltage Under Min	Not Valid	
Battery Voltage Over Max	Not Valid	
Battery Side Current	0.20	Amps
Battery Side Voltage	0.0	Volts
HV OC	False	
HV OV	False	
HCP (EVCU) HV Current Max Cal	-12.00	Amps
HCP (EVCU) HV Volt Max Cal	152	Volt
HCP (EVCU) HV Volt Min Cal	244	Volt
OBCM Temperature 1	84	°F
OBCM Temperature 2	84	°F
OBCM Temperature 3	72	°F
OBCM Temperature 4	68	°F
NTC1 OT	False	
NTC2 OT	False	
NTC3 OT	False	
NTC4 OT	False	
External OBCM Inlet Temperature (CAN)	-40	°F
J1772 ICA	0	AMP
J1772 S2 Close	Open	
J1772 Stat	Veh Not Connected	
J1772 S2 Status	Open	
Control Pilot Amplitude	7.529	Volts
Control Pilot Duty Cycle	0.00	%
Control Pilot Frequency	1024	Hz
EVSE Pilot Stat	NO EVSE	
Prox Stat	Prox Out	
Prox Voltage	4.431	Volt
OBC Idle Tml	1	hrs
Watt-Hours of AC Power	0	W-Hrs
Watt Hours of Charge the HV Bus	0	W-Hrs
OBCM Mode	UTC	
OBCM Charger Ready	On	
OBCM WU Status	On	

Charge Enable Status	Chrg Disable	
HCP (EVCU) Shutdown Command	EVCU Operational	
HCP (EVCU) Enable Charge Command	Charge disable	
HCP (EVCU) OBC Mode Request	Idle	
Generic Fail Sts	At Least One DTC set on Sys Mem	
Chrg Fail Sts	No Faults detected	
OBCM Wake Up Reason	Pilot PWM	
OBC Control Mth	Current	
OBCM Deraing Reason	AC Voltage Limit Derating	
Close Chrgr Cntctr	Open	
Chrgr Cntctr Stat	Precharge Inhibited	
Chrg Mode	Charge Mode	
OBCM Fault Reason	No Faults detected	
Module A Primary - PFC Temperature	70	°F
Module A Primary - LLC Temperature	70	°F
Module A Secondary - Buck Temperature	68	°F
Module A Secondary - Ambient Temperature	84	°F
Module A Primary - AC Side Volt	2.6	Volts
Module A Primary - AC Side Current	-24.60	Amps
Module A Secondary - Battery Side Voltage	0.0	Volts
Module A Secondary - Battery Side Current	-24.90	Amps
Module A Secondary - Buck Output Voltage	0.1	Volts
Module B Primary - PFC Temperature	73	°F
Module B Primary - LLC Temperature	72	°F
Module B Secondary - Buck Temperature	72	°F
Module B Secondary - Ambient Temperature	84	°F
Module B Primary - AC Side Volt	1.3	Volts
Module B Primary - AC Side Current	-24.90	Amps
Module B Secondary - Battery Side Voltage	0.0	Volts
Module B Secondary - Battery Side Current	-24.90	Amps
Module B Secondary - Buck Output Voltage	0.1	Volts
OBCM - HV Over Voltage Protect	False	
OBCM - LV Aux Over Voltage Protect	False	
OBCM - LV Aux Under Voltage Protect	False	
OBCM - LLC Over Voltage Protect	False	
OBCM - LLC Under Voltage Protect	False	
OBCM - PFC Over Voltage Protect	False	
OBCM - PFC Under Voltage Protect	False	
OBCM - Battery 12V Under Voltage Protect	False	
OBCM - Battery 12V Over Voltage Protect	False	
OBCM - AC Under Voltage Protect	False	
OBCM - AC Over Voltage Protect	False	
OBCM - AC Over Current Protect	False	
OBCM - HV Voltage Over MaxCal Protect	False	

OBCM - HV Over Current Protect	False	
OBCM - Power Stage Over Voltage Protect	False	
OBCM - Internal Memory Fault	False	
OBCM - Over Temperature Protect	False	
OBCM - HCP Loss of Communication Protect	False	
OBCM - Loss BPCM Communication Protect	False	
OBCM - CAN Bus Off	False	
OBCM - Pilot Duty Fault	False	
OBCM - Prox Range To Low	False	
OBCM - Prox Range To High	False	
OBCM - HV Voltage Under MinCal Protect	False	
OBCM - SPI Communication Fault	False	
OBCM - Pilot Short To Battery	False	
OBCM - WakeUp Output Stuck Low	False	
OBCM - WakeUp Output Stuck High	False	
OBCM - ORC Loss of Communication	False	
OBCM - HV Battery Not Contact	False	
OBCM - Loss Communication Protect	False	
OBCM - Receive HV Battery Contact Open From BPCM	False	
OBCM - Secondary Aux Over Voltage Protect	False	
OBCM - Secondary Aux Under Voltage Protect	False	
OBCM - Primary Aux Over Voltage Protect	False	
OBCM - Primary Aux Under Voltage Protect	False	
OBCM - Stuck Shutdown	False	
OBCM - Cycle Shutdown	False	
OBCM - HV Under Voltage Protect	False	
OBCM - Vehicle Impact	False	
OBCM - ARC/CRC Fault	False	
OBCM - AC Contact Welded Fault	False	
Control Pilot Open fault	False	
Prox open fault	False	
OBCM - Internal S2 Switch Low Fault	False	
OBCM - Internal S2 Switch High Fault	False	
OBCM - Pilot Range Fault	False	
OBCM - Prox Range Fault	False	
force shutdown fault	False	
pilot signal wake up issue because of EVSE	False	
HCP stuck low fault	False	
HCP stuck High fault	False	
Plant mode flag	True	
Retry fault flag	False	
Loss SBC communcation (SPI)	False	
pilot input short to ground fault	False	
pilto input short to battery fault in Driver mode detecting	False	

pilot short to ground fault in driver mode detecting	False	
Charging ready line open fault	False	
Pilot frequency range fault	False	
OBCM - Internal S2 Switch High Fault in Driver mode detecting	False	
Module A Primary - AC Under Voltage Protect	False	
Module A Primary - PFC Power Limit	True	
Module A Primary - PFC Enable States	False	
Module A Primary - LLC Enable States	False	
Module A Primary - PFC Under Voltage Protect	False	
Module A Primary - PFC Over Voltage Protect	False	
Module A Primary - Over Temperature Protect	False	
Module A Primary - Hot Warning	False	
Module A Primary - AC Present	False	
Module A Primary - PFC Over Temperature Protect	False	
Module A Primary - LLC Over Temperature Protect	False	
Module A Primary - PFC Hot Warning	False	
Module A Primary - LLC Hot Warning	False	
Module A Primary - AC Over Voltage Protect	True	
Module A Primary - Relay Enable States	False	
Module A Primary - Aux Over Voltage Protect	False	
Module A Primary - Aux Under Voltage Protect	False	
Module A Primary - Secondary Micro Enable Command	False	
Module A Primary - AC Vin Lost	True	
Module A Primary - Loss Communication Protect	False	
Module A Primary - Standby Mode	True	
Module A Primary - Operate Mode	False	
Module A Primary - Shutdown Mode	False	
Module A Secondary - Aux Enable States	True	
Module A Secondary - HV Enable States	False	
Module A Secondary - LLC Under Voltage Protect	False	
Module A Secondary - LLC Over Voltage Protect	False	
Module A Secondary - HV Over Voltage Protect	False	
Module A Secondary - HV Over Current Protect	False	
Module A Secondary - Over Temperature Protect	False	
Module A Secondary - Hot Warning	False	
Module A Secondary - HV Over Temperature Protect	False	
Module A Secondary - Ambient Over Temperature Protect	False	
Module A Secondary - HV Hot Warning	False	
Module A Secondary - Ambient Hot Warning	False	
Module A Secondary - Aux Over Voltage Protect	False	
Module A Secondary - Aux Under Voltage Protect	False	
Module A Secondary - Loss Primary Communication Protect	False	
Module A Secondary - LV Micro Enable Command	False	
Module A Secondary - Loss LV Communication Protect	False	

Module A Secondary - Primary Turn On States	False	
Module A Secondary - Primary Shutdown States	False	
Module A Secondary - HV Under Voltage Protect	False	
Module A Secondary - Standby Mode	True	
Module A Secondary - Operate Mode	False	
Module A Secondary - Shutdown Mode	False	
Module A Secondary - LV Micro Disable Command	True	
Module A Secondary - PFC High Temperature Derating	False	
Module A Secondary - PFC Low Temperature Derating	False	
Module A Secondary - LLC High Temperature Derating	False	
Module A Secondary - LLC Low Temperature Derating	False	
Module A Secondary - HV High Temperature Derating	False	
Module A Secondary - HV Low Temperature Derating	False	
Module A Secondary - Ambient High Temperature Derating	False	
Module A Secondary - Ambient Low Temperature Derating	False	
Module A Secondary - AC Input Voltage Derating	True	
Module A Secondary - HV Output Voltage Derating	False	
Module B Primary - AC Under Voltage Protect	False	
Module B Primary - PFC Power Limit	True	
Module B Primary - PFC Enable States	False	
Module B Primary - LLC Enable States	False	
Module B Primary - PFC Under Voltage Protect	False	
Module B Primary - PFC Over Voltage Protect	False	
Module B Primary - Over Temperature Protect	False	
Module B Primary - Hot Warning	False	
Module B Primary - AC Present	False	
Module B Primary - PFC Over Temperature Protect	False	
Module B Primary - LLC Over Temperature Protect	False	
Module B Primary - PFC Hot Warning	False	
Module B Primary - LLC Hot Warning	False	
Module B Primary - AC Over Voltage Protect	True	
Module B Primary - Relay Enable States	False	
Module B Primary - Aux Over Voltage Protect	False	
Module B Primary - Aux Under Voltage Protect	False	
Module B Primary - Secondary Micro Enable Command	False	
Module B Primary - AC Vin Lost	True	
Module B Primary - Loss Communication Protect	False	
Module B Primary - Standby Mode	True	
Module B Primary - Operate Mode	False	
Module B Primary - Shutdown Mode	False	
Module B Secondary - Aux Enable States	True	
Module B Secondary - HV Enable States	False	
Module B Secondary - LLC Under Voltage Protect	False	
Module B Secondary - LLC Over Voltage Protect	False	

Module B Secondary - HV Over Voltage Protect	False	
Module B Secondary - HV Over Current Protect	False	
Module B Secondary - Over Temperature Protect	False	
Module B Secondary - Hot Warning	False	
Module B Secondary - HV Over Temperature Protect	False	
Module B Secondary - Ambient Over Temperature Protect	False	
Module B Secondary - HV Hot Warning	False	
Module B Secondary - Ambient Hot Warning	False	
Module B Secondary - Aux Over Voltage Protect	False	
Module B Secondary - Aux Under Voltage Protect	False	
Module B Secondary - Loss Primary Communication Protect	False	
Module B Secondary - LV Micro Enable Command	False	
Module B Secondary - Loss LV Communication Protect	False	
Module B Secondary - Primary Turn On States	False	
Module B Secondary - Primary Shutdown States	False	
Module B Secondary - HV Under Voltage Protect	False	
Module B Secondary - Standby Mode	True	
Module B Secondary - Operate Mode	False	
Module B Secondary - Shutdown Mode	False	
Module B Secondary - LV Micro Disable Command	True	
Module B Secondary - PFC High Temperature Derating	False	
Module B Secondary - PFC Low Temperature Derating	False	
Module B Secondary - LLC High Temperature Derating	False	
Module B Secondary - LLC Low Temperature Derating	False	
Module B Secondary - HV High Temperature Derating	False	
Module B Secondary - HV Low Temperature Derating	False	
Module B Secondary - Ambient High Temperature Derating	False	
Module B Secondary - Ambient Low Temperature Derating	False	
Module B Secondary - AC Input Voltage Derating	True	
Module B Secondary - HV Output Voltage Derating	False	
SBC State_DF00	00	
SBC State_DF80	00	
SBC State_E100	00	
SBC State_E180	00	
SBC State_E300	00	
SBC State_E500	00	
SBC State_E580	00	
OBCM Charge Current Available	0.00	AMP
BPCM HV Battery Contactor Open	False	
SBC Bus Off	False	
CANSIP Bus Off	False	
OBC Charge Time	0	sec
OBC Charge Tml	1	hrs
OBC Idle Time	0	sec

EPT LOC Diag Enable	Enable LOC Diagnostic	
HCP Shutdown Command	No Shutdown	
HV Battey Contactor Open	False	
BPCM Request for HV Contactor	False	
HV Contactor Status	Closed	
Ignition on Time for DTC	0	sec

MSMP | B222D-00 | Stored | ECU Unable To Configure/Configuration Not Learned-

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	Occurrence	
Original Odometer Value	99	miles
Most Recent Odometer Value	99	miles
Frequency Counter	1	
Ignition Cycle Counter	3	

TBM2 | B210D-16 | Stored | Battery Voltage Low-Circuit Voltage Below Threshold

NAME	VALUE	UNITS
DTC	A1 0D 16	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Frequency Counter	4	

TBM2 | U0184-00 | Stored | Lost Communication With Radio-

NAME	VALUE	UNITS
DTC	C1 84 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	

Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Frequency Counter	1	

SNAPSHOT DATA SUMMARY

- No Snapshot Data available for B222D-00
- No Snapshot Data available for C2225-00
- No Snapshot Data available for C2227-00
- No Snapshot Data available for P0AA4-00
- No Snapshot Data available for P0C78-00
- No Snapshot Data available for P084F-00
- No Snapshot Data available for P0A0A-00
- No Snapshot Data available for U0412-00
- No Snapshot Data available for U209E-00
- No Snapshot Data available for U209E-00
- No Snapshot Data available for B222D-00
- No Snapshot Data available for B210D-16
- No Snapshot Data available for U0184-00

Snapshot from the dealer's scan

EPT -WakeUp	Sourced	
HCP Contactor Command	<u>Impact Open</u>	
Qualified Contactor Command - QCC	Open	
Verified Contactor Command - VCC	Invalid	
Contactor Status	<u>PreCharging Inhibited</u>	
Plug in Status	Not plugged in	
ChargingLevel	Plug in, but no charge	