

This file represents a consolidation of multiple files sent by the manufacturer. Please use the bookmarks to navigate to each file. (Each bookmark label is the name of the original file.)



VEHICLE SCAN REPORT

Vehicle 2021 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN [REDACTED]

Odometer 15647.9 miles
Publication Date Jun 10, 2022, 8:22:08 AM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
PCM	Powertrain Control Module	CAN-C	68499122AE	[REDACTED]	[REDACTED]	68499122AE
PLGM	Power Liftgate	CAN-I	68466171AI			68466171AI
ICS	Integrated Center Stack	CAN-I	7AS341X8AA			7AS341X8AA
RFH	Radio Frequency Hub	CAN-C	68500152AA			68500152AA
ESM	Electronic Shifter	CAN-C	68240089AN			68240089AN
ORC	Occupant Restraint	CAN-C	68526665AB			68526665AB
EPS	Electric Power Steering	CAN-C	68460392AA			68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68493454AE			68493454AE
DDM	Driver Door Module	CAN-I	68496463AB			68496463AB
PDM	Passenger Door Module	CAN-I	68496462AB			68496462AB
DMRL	Door Module Rear Left	CAN-I	68508894AB			68508894AB
DMRR	Door Module Rear Right	CAN-I	68508894AB			68508894AB
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD			68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD			68369596AD
MSM	Memory Seat Module	CAN-I	68321862AC			68321862AC
CSWM	Comfort Seat Wheel Module	CAN-I	68517011AB			68517011AB
AMP	Amplifier	CAN-I	68476878AA			68476878AA
IPC	Instrument Panel Cluster	CAN-C	68434960AF			68434960AF
PTS	Parktronics	CAN-C	68485862AB			68485862AB
SCCM	Steering Column Control Module	CAN-C	68531525AA			68531525AA
BCM	Body Controller	CAN-C	68491085AG			68491085AG

ACC	Adaptive Cruise Control	CAN-C	68540436AC		68540436AC
RADIO	Radio	CAN-I	68465292AE		68465292AE
OCM	Occupant Classification	CAN-C	68403127AA		68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB		68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AC		04672786AC
RBSS	Right Blind Spot Sensor	CAN-I	04672786AC		04672786AC
FFCM	Forward Facing Camera Module	CAN-C	68551091AA		68551091AA
APM	Accessory Power Module	CAN-C	05185046AB		05185046AB
BPCM	Battery Pack Control Module	CAN-C	05193183AF		05193183AF
HCP	Hybrid Control Processor	CAN-C	68573672AA		68573672AA
OBCM	On Board Charging Module	CAN-C	05185047AE		05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC		68321862AC
DSM	Display Screen Module	CAN-I	68438382AF		68438382AF
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30PD2AA		6WL30PD2AA
CVPM	Central vision processing module	CAN-I	56029920AB		56029920AB
EAC	Electric A/C Compressor	CAN-C	68237995AG		68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	68573673AA		68573673AA
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB		68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68471122AD		68471122AD
SGW	Security Gateway Module	CAN-C	68488429AB		68488429AB
TBM2	Telematic Box Module 2	CAN-C	68444865AH		68444865AH

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	CVNS
PCM	USA	1B 47	75 01 01	4422	
PLGM	USA	0	5084	000200000031	
ICS	USA	0F 0C 00	13 31 01	4700	
RFH	USA / USA	10 17 00	13 26 00	4A00	
ESM	USA / USA	13 02 00	14 23 FF	4402	
ORC	USA / USA	14 06 00	14 12 00	4301	
EPS	USA / USA	12 2A 00	12 1E 01	4502	

HVAC	USA	0E 09 00	14 2F 01	4401	
DDM	USA	11 07 00	14 07 00	4202	
PDM	USA	11 07 00	14 07 00	4202	
DMRL	USA / USA	10 0B 00	14 08 00	4201	
DMRR	USA / USA	10 0B 00	14 08 00	4201	
PSDML	USA / USA	10 17 00	14 10 12	4001	
PSDMR	USA / USA	10 17 00	14 10 12	4001	
MSM	USA	0F 2B 00	10 27 03	4101	
CSWM	USA	11 2A 00	14 25 00	4302	
AMP	USA	18 2E 01	13 15 00	4030	
IPC	USA / USA	12 06 00	14 34 00	4705	
PTS	USA	0E 32 00	15 05 00	4311	
SCCM	USA	13 28 00	13 29 00	4301	
BCM	USA	0D 11 00	14 26 90	4420	
ACC	USA / USA	14 2A 01	15 23 02	4400	
RADIO		65	5671	000200000008	
OCM	USA / USA	11 1F 01	0E 2F 02	4030	
HVACR	USA	0E 09 00	10 03 02	4301	
LBSS	USA / USA	11 30 02	15 08 00	4202	
RBSS	USA / USA	11 30 02	15 08 00	4202	
FFCM	USA / USA	11 06 00	15 0C 00	4102	
APM	USA / USA	11 32 00	11 32 00	4001	
BPCM		0E 03 00	15 07 00	4005	
HCP	USA	11 1F 04	0F 2D 00	4006	
OBCM	USA	0F 0D 00	12 02 00	4002	
MSMP	USA	0F 2B 00	10 27 03	4001	
DSM	USA / USA	14 0C 00	15 06 00	4300	
RCCC	USA	0F 1D 00	13 04 00	4000	
CVPM	USA / USA	11 27 01	14 0C 01	4004	
EAC	USA	0E 34 00	12 0F 00	4102	
AHCP	USA	11 1F 04	0F 2D 00	4000	
EBBM	USA	0E 19 02	14 0D 18	4000	
ABSO	USA	0E 15 02	14 1B 26	4201	
SGW		5	969	4103	
TBM2	USA	13 0E 02	14 2A 5F	4104	

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
RFH	C0077-00	Low Tire Pressure-	Stored
HVAC	B10EB-00	Blower Power Module-	Stored
MSM	B233C-00	Commanded Position Not Reachable-	Stored
RADIO	B15A1-00	Media Port 1 Connection-	Stored
HCP	P06B1-00	Sensor Power Supply 1 Circuit Low-	Stored

HCP	P0A3F-00	Drive Motor A Position Sensor 1 Circuit-	Stored
-----	----------	--	--------

ENVIRONMENTAL DATA SUMMARY

RFH | C0077-00 | Stored | Low Tire Pressure-

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	False	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	ERROR	
Original Odometer Value	15231	miles
Most Recent Odometer Value	15231	miles
Frequency Counter	1	
Ignition Cycle Counter	65	

HVAC | B10EB-00 | Stored | Blower Power Module-

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	ERROR	
Original Odometer Value	15639	miles
Most Recent Odometer Value	15639	miles
Frequency Counter	9	
Ignition Cycle Counter	13	

MSM | B233C-00 | Stored | Commanded Position Not Reachable-

NAME	VALUE	UNITS
Failed Movement Information - Horizontal Motor	Movement aborted by operator	
Failed Movement Information - Recliner Motor	No Failed Movement	
Failed Movement Information - Vertical Front Motor	No Failed Movement	
Failed Movement Information - Vertical Rear Motor	No Failed Movement	
Obstacle Detection Location - Horizontal Motor	No Obstacle Detected	Counts

Horizontal Motor Position - end of movement	32517	Counts
Recliner Motor Position - end of movement	32021	Counts
Vertical Front Motor Position - end of movement	32958	Counts
Vertical Rear Motor Position - end of movement	32355	Counts
Horizontal Motor Position - start of movement	32454	Counts
Recliner Motor Position - start of movement	32021	Counts
Vertical Front Motor Position - start of movement	32958	Counts
Vertical Rear Motor Position - start of movement	32355	Counts
ECU Voltage - at start of movement	382E	Volts
ECU Voltage - minimum voltage during movement	36C2	Volts
Movement Direction - Recliner Motor	Motor not moving	
Movement Direction - Horizontal Motor	Forward / Up	
Movement Direction - Vertical Front Motor	Motor not moving	
Movement Direction - Vertical Rear Motor	Motor not moving	

RADIO | B15A1-00 | Stored | Media Port 1 Connection-

NAME	VALUE	UNITS
DTC	95 A1 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

HCP | P06B1-00 | Stored | Sensor Power Supply 1 Circuit Low-

NAME	VALUE	UNITS
DTC	06 B1 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Occurrence	
Original Odometer Value	15621.4	miles
Most Recent Odometer Value	15641.1	miles
Frequency Counter	2	
Ignition Cycle Counter	0	
Real time clock	19674014	sec
RAM stamps keyOn	315	sec
RAM Stamps	29038	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Applied	

PHEV Charging Status	No Charging	
Engine Speed	0	rpm
HV Battery SOC	24	%
Ignition State	Reserved	
PRND Position Display	N	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Motor A Temp Sensor	158	°F
Motor B Temp Sensor	178	°F
Barometric Pressure	14	PSI
Engine Coolant Temperature	196	°F
Motor A Resolver Offset Learn Erase	not requested	
Motor A Resolver Offset Learning Status Flag	Applied	
Motor B Resolver Offset Learning Status Flag	Applied	
Motor A Resolver Angle Offset	2.00	Degree
Motor B Resolver Angle Offset	3.20	Degree
Motor A Resolver Supply Voltage Value	03FD	Volts
Motor B Resolver Supply Voltage Value	15.75	Volts
Motor A Resolver to Digital Low Level Driver Faults	Resolver Loss of Signal	
Motor B Resolver to Digital Low Level Driver Faults	No fault	
Battery Feed Voltage 2 Sense	12.600	Volts
Internal EPS Voltage Sense A	4.248	Volts
Internal EPS Voltage Sense B	2.304	Volts
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.092	Ft-Lbs
Available Motor Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor B	233.499	Ft-Lbs
Available Regen Torque - Motor A	0.000	Ft-Lbs
Available Regen Torque - Motor B	-233.499	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Electric Motor A Speed	0.0	rpm
Electric Motor B Speed	-13.5	rpm
Battery Feed Voltage 1 Sense	12.600	Volts
Battery Feed Voltage 3 Sense	12.600	Volts
Hybrid System State	SNA	
Motor A - Inverter Current - phase A	-4	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	0	AMP
Motor B - Inverter Current - phase A	0	AMP
Motor B - Inverter Current - phase B	0	AMP
Motor B - Inverter Current - phase C	0	AMP
Outside Air Temperature	89.6	°F
HCP ePT Wake-Up Output	On	

CBC Wake-Up Input	Off	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Open	
HV Battery Voltage from BPCM	180.00	Volts
PIM DC Link Voltage - A	7	Volts
PIM DC Link Voltage - B	6	Volts
Inverter A IGBT Temperature for phase A	124	°F
Inverter A IGBT Temperature for phase B	124	°F
Inverter A IGBT Temperature for phase C	124	°F
Inverter B IGBT Temperature for phase A	124	°F
Inverter B IGBT Temperature for phase B	124	°F
Inverter B IGBT Temperature for phase C	126	°F
APM Status	Idle	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	25	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.092	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Motor B Resolver Offset Learn Erase	not requested	
GPS Date - Year	2022	Year
GPS Date - Month	6	
GPS Date - Day	7	Days
UTC Time - Hours	17	Hours
UTC Time - Minutes	17	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	219	ms

HCP | P0A3F-00 | Stored | Drive Motor A Position Sensor 1 Circuit-

NAME	VALUE	UNITS
DTC	0A 3F 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Occurrence	
Original Odometer Value	15618.8	miles
Most Recent Odometer Value	15641.1	miles

Frequency Counter	5	
Ignition Cycle Counter	0	
Real time clock	19674008	sec
RAM stamps keyOn	315	sec
RAM Stamps	29038	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Applied	
PHEV Charging Status	No Charging	
Engine Speed	29	rpm
HV Battery SOC	24	%
Ignition State	Reserved	
PRND Position Display	N	
Propulsion System Active	False	
Vehicle Speed	16.5926	MPH
Motor A Temp Sensor	160	°F
Motor B Temp Sensor	176	°F
Barometric Pressure	14	PSI
Engine Coolant Temperature	194	°F
Motor A Resolver Offset Learn Erase	not requested	
Motor A Resolver Offset Learning Status Flag	Applied	
Motor B Resolver Offset Learning Status Flag	Applied	
Motor A Resolver Angle Offset	2.00	Degree
Motor B Resolver Angle Offset	3.20	Degree
Motor A Resolver Supply Voltage Value	15.75	Volts
Motor B Resolver Supply Voltage Value	15.75	Volts
Motor A Resolver to Digital Low Level Driver Faults	Resolver Loss of Signal	
Motor B Resolver to Digital Low Level Driver Faults	No fault	
Battery Feed Voltage 2 Sense	14.184	Volts
Internal EPS Voltage Sense A	8.064	Volts
Internal EPS Voltage Sense B	8.064	Volts
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	-0.461	Ft-Lbs
Available Motor Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor B	235.988	Ft-Lbs
Available Regen Torque - Motor A	0.000	Ft-Lbs
Available Regen Torque - Motor B	-235.988	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Electric Motor A Speed	0.0	rpm
Electric Motor B Speed	1757.0	rpm
Battery Feed Voltage 1 Sense	14.184	Volts
Battery Feed Voltage 3 Sense	14.184	Volts
Hybrid System State	Determine Hybrid System State	
Motor A - Inverter Current - phase A	0	AMP

Motor A - Inverter Current - phase B	-4	AMP
Motor A - Inverter Current - phase C	-4	AMP
Motor B - Inverter Current - phase A	0	AMP
Motor B - Inverter Current - phase B	0	AMP
Motor B - Inverter Current - phase C	-4	AMP
Outside Air Temperature	89.6	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	Off	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Closed	
HV Battery Voltage from BPCM	343.10	Volts
PIM DC Link Voltage - A	344	Volts
PIM DC Link Voltage - B	343	Volts
Inverter A IGBT Temperature for phase A	127	°F
Inverter A IGBT Temperature for phase B	126	°F
Inverter A IGBT Temperature for phase C	126	°F
Inverter B IGBT Temperature for phase A	135	°F
Inverter B IGBT Temperature for phase B	135	°F
Inverter B IGBT Temperature for phase C	138	°F
APM Status	Buck CV	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	25	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	-0.461	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Motor B Resolver Offset Learn Erase	not requested	
GPS Date - Year	2022	Year
GPS Date - Month	6	
GPS Date - Day	7	Days
UTC Time - Hours	17	Hours
UTC Time - Minutes	17	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	356	ms

SNAPSHOT DATA SUMMARY

No Snapshot Data available for C0077-00

No Snapshot Data available for B10EB-00

No Snapshot Data available for B233C-00

RADIO | B15A1-00 | Stored | Media Port 1 Connection-Record 0

NAME	VALUE	UNITS
DTC	95 A1 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

Record 1

NAME	VALUE	UNITS
DTC	95 A1 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

Record 2

NAME	VALUE	UNITS
DTC	95 A1 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

Record 3

NAME	VALUE	UNITS
DTC	95 A1 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

No Snapshot Data available for P06B1-00

No Snapshot Data available for P0A3F-00



