

This file represents a consolidation of multiple files sent by the manufacturer. Please use the bookmarks to navigate to each file. (Each bookmark label is the name of the original file.)



CONFIGURATION REPORT

Vehicle 2020 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN 2C4RC1N74LR [REDACTED]

Odometer 56862.7 miles
Publication Date Aug 29, 2022, 2:59:12 PM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT V	ORIGINAL VIN	PART #
PCM	Powertrain Control Module	CAN-C	68444228AE	2C4RC1N7	2C4RC1N74LR	68444228AE
ICS	Integrated Center Stack	CAN-I	6UX621X8AA	2C4RC1N7	2C4RC1N74LR	6UX621X8AA
RFH	Radio Frequency Hub	CAN-C	68453559AB	2C4RC1N7	2C4RC1N74LR	68453559AB
ESM	Electronic Shifter	CAN-C	68240089AM	2C4RC1N7	2C4RC1N74LR	68240089AM
ORC	Occupant Restraint	CAN-C	68405567AC	2C4RC1N7	2C4RC1N74LR	68405567AC
EPS	Electric Power Steering	CAN-C	68460392AA	2C4RC1N7	2C4RC1N74LR	68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68447893AC	2C4RC1N7	2C4RC1N74LR	68447893AC
DDM	Driver Door Module	CAN-I	68424449AC	2C4RC1N7	2C4RC1N74LR	68424449AC
PDM	Passenger Door Module	CAN-I	68424448AC	2C4RC1N7	2C4RC1N74LR	68424448AC
DMRL	Door Module Rear Left	CAN-I	68225096AG	2C4RC1N7	2C4RC1N74LR	68225096AG
DMRR	Door Module Rear Right	CAN-I	68225096AG	2C4RC1N7	2C4RC1N74LR	68225096AG
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AC	2C4RC1N7	2C4RC1N74LR	68369596AC
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AC	2C4RC1N7	2C4RC1N74LR	68369596AC
MSM	Memory Seat Module	CAN-I	68321862AC	2C4RC1N7	2C4RC1N74LR	68321862AC
PLGM	Power Liftgate	CAN-I	68316094AF	2C4RC1N7	2C4RC1N74LR	68316094AF
CSWM	Comfort Seat Wheel Module	CAN-I	68434912AC	2C4RC1N7	2C4RC1N74LR	68434912AC
AMP	Amplifier	CAN-I	68448067AA	2C4RC1N7	2C4RC1N74LR	68448067AA
IPC	Instrument Panel Cluster	CAN-C	68434956AC	2C4RC1N7	2C4RC1N74LR	68434956AC
PTS	Parktronics	CAN-C	68193775AJ	2C4RC1N7	2C4RC1N74LR	68193775AJ
SCCM	Steering Column Control Module	CAN-C	68360889AC	2C4RC1N7	2C4RC1N74LR	68360889AC
BCM	Body Controller	CAN-C	68424601AD	2C4RC1N7	2C4RC1N74LR	68424601AD

ACC	Adaptive Cruise Control	CAN-C	04672758AB	2C4RC1N74L	2C4RC1N74LR	04672758AB
RADIO	Radio	CAN-I	68461768AD	2C4RC1	2C4RC1N74LR	68461768AD
OCM	Occupant Classification	CAN-C	68403127AA	2C4RC1N74L	2C4RC1N74LR	68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB	2C4RC1N74L	2C4RC1N74LR	68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AB	2C4RC1N74L	2C4RC1N74LR	04672786AB
RBSS	Right Blind Spot Sensor	CAN-I	04672786AB	2C4RC1N74L	2C4RC1N74LR	04672786AB
FFCM	Forward Facing Camera Module	CAN-C	04672776AA	2C4RC1N74L	2C4RC1N74LR	04672776AA
EDM	External Disc Module	CAN-I	68378304AA	2C4RC1N74L	2C4RC1N74LR	68378304AA
APM	Accessory Power Module	CAN-C	05185046AB	2C4RC1N74L	2C4RC1N74LR	05185046AB
BPCM	Battery Pack Control Module	CAN-C	05193166AF	2C4RC1N74L	2C4RC1N74LR	05193166AF
HCP	Hybrid Control Processor	CAN-C	05190265AG	2C4RC1N74L	2C4RC1N74LR	05190265AG
OBCM	On Board Charging Module	CAN-C	05185047AE	2C4RC1N74L	2C4RC1N74LR	05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC	2C4RC1N74L	2C4RC1N74LR	68321862AC
DSM	Display Screen Module	CAN-I	68316174AC	2C4RC1N74L	2C4RC1N74LR	68316174AC
VRM	Video Routing Module	CAN-I	68376134AF	2C4RC1N74L	2C4RC1N74LR	68376134AF
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA	2C4RC1N74L	2C4RC1N74LR	6WL30DX9AA
CVPM	Central vision processing module	CAN-I	68375113AB	2C4RC1N74L	2C4RC1N74LR	68375113AB
EAC	Electric A/C Compressor	CAN-C	68237995AG	2C4RC1N74L	2C4RC1N74LR	68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05190266AG	2C4RC1N74L	2C4RC1N74LR	05190266AG
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB	2C4RC1N74L	2C4RC1N74LR	68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68461812AA	2C4RC1N74L	2C4RC1N74LR	68461812AA
SGW	Security Gateway Module	CAN-C	68447193AB		2C4RC1N74LR	68447193AB

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	SERIAL NUMBER	CVNS
PCM	USA	1B 47	46 03 01	4419		
ICS	USA	0F 0C 00	12 25 00	4700		
RFH	USA / USA	10 17 00	13 09 00	4A00		
ESM	USA / USA	0F 24 00	12 28 FF	4402		
ORC	USA / USA	11 1F 00	12 2B 00	4301		
EPS	USA / USA	12 2A 00	12 1E 01	4502		

HVAC	USA	0E 09 00	13 05 01	4401
DDM	USA	11 07 00	13 0B 00	4202
PDM	USA	11 07 00	13 0B 00	4202
DMRL	USA / USA	10 0B 00	12 0C 00	4201
DMRR	USA / USA	10 0B 00	12 0C 00	4201
PSDML	USA / USA	10 17 00	13 1E 11	4001
PSDMR	USA / USA	10 17 00	13 1E 11	4001
MSM	USA	0F 2B 00	10 27 03	4101
PLGM	USA	17 19 00	18 22 00	4202
CSWM	USA	11 2A 00	13 2C 00	4302
AMP	USA	0F 06 01	12 2E 01	4021
IPC	USA / USA	12 06 00	13 27 00	4704
PTS	USA	0E 32 00	12 1F 00	4311
SCCM	USA	0E 30 00	10 2B 00	4301
BCM	USA	0D 11 00	13 0C 90	4415
ACC	USA / USA	13 33 00	11 0D 00	4201
RADIO	USA	13 31 14	13 31 14	8205
OCM	USA / USA	11 1F 01	0E 2F 02	4030
HVACR	USA	0E 09 00	10 03 02	4301
LBSS	USA / USA	11 30 02	12 0D 00	4202
RBSS	USA / USA	11 30 02	12 0D 00	4202
FFCM	USA / USA	11 06 00	11 2B 00	4102
EDM	USA	12 0A 00	11 08 00	4000
APM	USA / USA	11 32 00	11 32 00	4001
BPCM		0E 03 00	14 17 00	4005
HCP	USA	11 1F 04	19 48 01	4005
OBCM	USA	0F 0D 00	12 02 00	4002
MSMP	USA	0F 2B 00	10 27 03	4001
DSM	USA / USA	13 29 00	12 23 00	4000
VRM	USA / USA	0F 1C 00	13 0C 10	4001
RCCC	USA	0F 1D 00	13 04 00	4000
CVPM	USA / USA	11 32 01	12 33 00	4003
EAC	USA	0E 34 00	12 0F 00	4102
AHCP	USA	11 1F 04	19 48 01	4000
EBBM	USA	0E 19 02	14 0D 18	4000
ABSO	USA	0E 15 02	12 2E 1E	4201
SGW		5	779	4103

CONFIGURATION

PCM CONFIGURATION

NAME	VALUE	UNITS
AC Equipped	False	
AC Equipped Over Bus	False	

Power Steering Switch Equipped	False	
4 Button Integrated Cruise Control	False	
EMAT (Getrag DCT transmission) Equipped	False	
Vehicle Speed Sensor #1 Calculated from CAN	False	
Police Package Equipped	False	
Unleaded Gasoline Fuel	True	
Unleaded diesel fuel	False	
6.4 Liter V8 Engine	False	
4 Speed Automatic Transmission Equipped	False	
Electronic Automatic Transmission (EATX) Equipped	False	
Vehicle Speed Sensor #1 Calculated by ECU	False	
4.7 Liter V8 Engine	False	
5.7 Liter V8 Engine	False	
6.1 Liter V8 Engine	False	
Sensorless FFV Enabled	False	
Electronic Throttle Control Equipped	True	
3.6 Liter V6 Engine	True	
4.0 Liter I6 Engine	False	
3.8 Liter V6 Engine	False	
3.7 Liter V6 Engine	False	
3.5 Liter V6 Engine	False	
3.3 Liter V6 Engine	False	
3.2 Liter V6 Engine	False	
2.7 Liter V6 Engine	False	
MTV Solenoid Equipped	False	
MDS Equipped	False	
Turbocharger Equipped	False	
SRV Equipped	False	
Secondary Air Equipped	False	
Shift Indicator Lamp Equipped	False	
Barometric Sensor Equipped	False	
TIP Equipped	False	
Battery Temp Sensor Equipped	False	
Knock Sensor 1 Equipped	True	
Knock Sensor 2 Equipped	True	
WI4 Variable Valve Timing Equipped	True	
Clutch Interlock Switch Equipped	False	
ESIM Equipped	False	
Linear Purge Equipped	False	
Linear EGR Equipped	False	
Continuous Variable Transmission Equipped	False	
Direct Injection Equipped	False	
Secondary Fuel Pump Equipped	False	
Electronic Coolant Pump Equipped	False	

O2 Sensor Bank 1 Sensor 1 Equipped	True	
O2 Sensor Bank 1 Sensor 2 Equipped	True	
O2 Sensor Bank 1 Sensor 3 Equipped	False	
O2 Sensor Bank 2 Sensor 1 Equipped	True	
O2 Sensor Bank 2 Sensor 2 Equipped	True	
Variable Displacement AC Equipped	False	
Fixed displacement AC Equipped	True	
WI4 Intake Flow Control Valve Equipped	False	
Electric Coolant Valve Equipped	False	
Engine Oil Heater Cooler Equipped	True	
Transmission Oil Heater Equipped	False	
Electric Water Pump Equipped	False	
Rear Heater Equipped	False	
Starter Relay 2 Equipped	False	
Inrush Current Reduction Relay Equipped	False	
Active Grille Shutter Equipped	False	
Electronic Vacuum Pump Equipped	False	
Wide Range O2 Sensor 1/1 Equipped	False	
Wide Range O2 Sensor 2/1 Equipped	False	
MultiAir Equipped	False	
Engine Stop Start Equipped	False	
Viscosity Sensor Equipped	False	
Duty Cycle Purge Valve Equipped	True	
Electric Thermostat Heater Equipped	False	
Exhaust Cam 1 Equipped	True	
Intake Cam 1 Equipped	True	
1.8 Liter WI4 engine	False	
2.0 Liter WI4 engine	False	
2.4 Liter WI4 engine	False	
3.0 Liter V6 Engine	False	
Tumble Generator Valve Equipped	False	
Hybrid Electric Vehicle Equipped	True	
Auxiliary Heater Electric Water Pump Equipped	False	
Dual Speed Fuel Pump Equipped	False	
Exhaust Cam 2 Equipped	True	
Intake Cam 2 Equipped	True	
1 Speed Fan Mechanical Relay System Equipped	False	
2 Speed Fan Mechanical Relay System Equipped	False	
2 Speed Fan PWM Relay System Equipped	False	
Linear PWM Fan Relay System Equipped	False	
PWM Fan Motor System Equipped	True	
3 Speed Fan Mechanical Relay System Equipped	False	
Fan Wake Up Relay System Equipped	False	
2 Speed Fan 3 Driver 3 Relay System Equipped	False	

40TE / 41TE / 41TEA	False	
42RLE	False	
45RFE / 545RFE / 65RFE	False	
62TE	False	
66RFE / 68RFE	False	
VLP Is Learnable Indicator	False	
VLP Equipped Indicator	False	
VFS Actuators Available Indicator	False	
ERS Equipped Indicator	False	
Engine Software In Package	True	
Transmission Software Included	False	
ICC Cruise Equipped	False	
ETC Cruise equipped	False	
Adaptive Cruise Control Equipped	True	
A/C Equipped	True	
Adaptive Cruise Control Hardware Equipped	False	
DUAL_ALTERNATOR_GEN1_LEARNEDCOPY	False	
TOOLCONFIG_OIL_PRESS_ABS_EQUIPPED	True	
GPEC2 Equipped	False	
GPEC2A Equipped	True	
GPEC3 Equipped	False	
Cummins Equipped	False	
GPEC4 Equipped	False	
VMM Equipped	False	
Powernet Equipped	True	
CUSW (29-Bit) Equipped	False	
CUSW (11-Bit) Equipped	False	
Fiat 940 Compact Equipped	False	
Next Gen Bus Equipped	False	
Constant Heater Temperature Control Valve Equipped	False	
High Side Port Tumble Valve Equipped	Undefined	
CMCV H-Bridge Equipped	Undefined	
Turbine Volute Valve Actuator Equipped	Undefined	
Wastegate H-Bridge Equipped	Undefined	
Active Exhaust Valve Equipped	False	
Active Exhaust Pressure Sensor Equipped	False	
Engine Idle Shutoff Equipped	False	
Aisin 6-Speed RWD Transmission Equipped	False	
Cooled EGR Equipped	False	
Supercharger Equipped	False	
Low Temperature Radiator Coolant Pump Equipped	False	
Mechanical Coolant Pump Heater Equipped	False	
Auxiliary Coolant Pump Heater Equipped	Undefined	
Compressed Natural Gas Equipped	False	

CUSW PROXI Write Programming Support Enabled	False	
Active Engine Mount Equipped	False	
ZF 9-Speed Transmission Equipped	False	
HPT 6-Speed Transmission Equipped	False	
Variable Speed Fuel Pump Equipped	True	
Operator Idle Speed Request Equipped	False	
PTO System Equipped	False	
Air Shutoff Valve Bank 1 Control Solenoid 1 Equipped	False	
Air Shutoff Valve Bank 1 Control Solenoid 2 Equipped	False	
Air Shutoff Valve Bank 2 Control Solenoid 2 Equipped	False	
Dual Stage Oil Pump Equipped	True	
Auxiliary Coolant Pump Equipped	False	
Trans Skip Shift Equipped	False	
Trans Reverse Lockout Equipped	False	
Port Flap Valve Equipped	False	
Brushless PWM Fan Equipped	NOT_FAN_PWM_BOSCH_BRUSHLESS_CNFG	
6.2 Liter V8 Engine	False	
Primary Lin Alternator Equipped	False	
Coolant On-Off Pump Equipped	False	
Oil Pressure Sensor Enabled	True	
Fiat VIN Learning Strategy Equipped	False	
Dual Fuel Tank Equipped	False	
Yaw Rate Sensor ESC Equipped	False	
1.0 Liter I3 Engine	False	
Coolant On-Off Valve Equipped	False	
Buffered Crank Output for ANC (Active Noise Cancellation) Equipped	True	
Buffered Crank Output for PHEV Engine Pulse Calculation Equipped	True	
Throttle Inlet Temp Sensor Equipped	False	
Humidity, Temperature and Pressure Sensor (LIN) Equipped	False	
Dual Fuel Pressure Sensor Equipped	False	
Brake Pedal Sensor Equipped	False	
Dual Fuel Tank Equipped	False	
PTO System Equipped	False	
Low Temp Radiator Coolant Pump Equipped	False	
Engine Idle Shutoff Equipped	False	
A/C Relay Powered from Engine Switched Battery	False	
CNG Large Gas Tank Equipped	False	
Cooled EGR Equipped	False	
Supercharger Equipped	False	
Hybrid MEC Shifter Equipped	False	
Dual Alternator Gen1 Capable	False	
Auxillary Coolant Pump Equipped	False	
ZF 9-Speed Trans Equipped	False	
HPT 6-Speed Trans Equipped	False	

CUSW 4-Button Cruise Equipped	False	
Power Steering Angle Sensor Mandatory	False	
Throttle Inlet Temp Sensor Equipped	False	
LIN Humidity, Temp, and Pressure Sensor Equipped	False	
Dual Fuel Pressure Sensor Equipped	False	
Brake Pedal Sensor Equipped	False	
Clutch Sensor Equipped	False	
SWAP HARDWIRED BRAKE SWITCH INPUTS	False	
Mass Airflow System Equipped	False	
Bi-Directional Crank Sensor Equipped	True	
5 Button Cruise (LIN) Equipped	True	
Operator Idle Speed Request Equipped	False	
INTAKE O2 SENSOR EQUIPPED	False	
Cylinder Pressure Sensor Equipped	False	
Make Up Air Sensor Equipped	False	
Active Exhaust Pressure Sensor Equipped	False	
Secondary Mass Airflow Sensor Equipped	False	
1.0 Liter I3 Engine	False	
2.0 Liter I4 Direct Injection Engine	False	
Variable Valve Lift Equipped	Not Equipped	
Coolant On-Off Pump Equipped	Not Equipped	
Primary Lin Alternator Equipped	Not Equipped	
Electronic Parking Brake Equipped	True	
Active Exhaust Valve(s) Equipped	False	
Mechanical Coolant Pump Equipped	False	
Aux Coolant Pump Heater Equipped	False	
Heater Temp Control Valve Equipped	False	
High Side Port Tumble Valve Equipped	False	
Wastegate HBridge Equipped	False	
Remote Start Present	Present	
Engine Oil Pressure Sensor Type	255	None

ICS CONFIGURATION

NAME	VALUE	UNITS
Display Type (Base)	True	
Display Type (Mid)	False	
Display Type (High)	False	

RFH CONFIGURATION

NAME	VALUE	UNITS
PIN Successfully Programmed	Yes	
VIN Successfully Programmed	Yes	
Valid Key In Ignition	Yes	
KeySense Configuration	True	

Keyless Go	True	
Ignition system type connected	KIN system	
TPM Auto-Locate Enabled	True	
e-shifter present	True	
Auto Park Present	True	
Secret Codes Programmed	True	
Passive Entry	True	
Premium TPM	True	
Base TPM	False	
RKE	True	
Module Configuration Status	True	
Remote Start Present	True	
Hybrid Type	PHEV	
\$0214 Programmed by	Programmed by Supplier EOL	
Hardware Configuration: Remote Start Antenna	Present	
Hardware Configuration: Front Left Door Handle H/W	Serial AP	
Hardware Configuration: Front Right Door Handle H/W	Serial AP	
Hardware Configuration: Rear Left Door Handle H/W	No AP	
Hardware Configuration: Rear Right Door Handle H/W	No AP	
Hardware Configuration: Trunk Door Handle H/W	Simple Switch AP	
RFHub Locked	RFHUB Locked after IAC write	
Fob Location #1 Successfully Programmed	Yes	
Fob Location #2 Successfully Programmed	Yes	
Fob Location #3 Successfully Programmed	Yes	
Fob Location #4 Successfully Programmed	No	
Fob Location #5 Successfully Programmed	No	
Fob Location #6 Successfully Programmed	No	
Fob Location #7 Successfully Programmed	No	
Fob Location #8 Successfully Programmed	No	
Fob Location #1 Key sense status	Fob is NOT Key Sense	
Fob Location #2 Key sense status	Fob is NOT Key Sense	
Fob Location #3 Key sense status	Fob is Key Sense	
Fob Location #4 Key sense status	Fob is NOT Key Sense	
Fob Location #5 Key sense status	Fob is NOT Key Sense	
Fob Location #6 Key sense status	Fob is NOT Key Sense	
Fob Location #7 Key sense status	Fob is NOT Key Sense	
Fob Location #8 Key sense status	Fob is NOT Key Sense	
Back Up Vehicle Config 1	True	
Back Up Vehicle Config 2	True	
Back Up Vehicle Config 3	True	
Back Up Vehicle Config 4	True	
Back Up Vehicle Config 5	True	
Back Up Vehicle Config 6	True	
Back Up Vehicle Config 7	True	

Back Up ECU Configuration 1	True	
Back Up ECU Configuration 2	True	
Back Up ECU Configuration 3	True	
Back Up ECU Configuration 4	True	
Back Up ECU Configuration 5	True	
Back Up ECU Configuration 6	True	
Back Up ECU Configuration 7	True	
Back Up ECU Configuration 8	True	
Back Up ECU Configuration 9	True	
Back Up ECU Configuration 10	True	
Back Up ECU Configuration 11	True	
Back Up ECU Configuration 12	True	
Back Up ECU Configuration 13	True	
Back Up ECU Configuration 14	True	
Back Up ECU Configuration 15	True	
Back Up ECU Configuration 16	True	
Back Up ECU Configuration 17	True	
Back Up Customer Settings Menu 1 (CSM1)	True	
Back Up Customer Settings Menu 2 (CSM2)	True	
Back Up Programmed ECUs: Cabin Network	True	
Back Up Programmed ECUs: P/T Chassis Network	True	
Secret Key Sent to Body Controller - Most recent attempt	Yes	
Secret Key Sent to Body Controller - Original attempt	Yes	

ORC CONFIGURATION

NAME	VALUE	UNITS
Rollover Sensing	Configured	
EPPM	Not Configured	
Occupant Classification (OCM)	Configured	
First Row Driver Seatbelt Buckle Switch	Configured	
First Row Passenger Seatbelt Buckle Switch	Configured	
Second Row Left seat belt Switch	Not Configured	
Second Row Center seat belt Switch	Not Configured	
Second Row Right seat belt Switch	Not Configured	
Driver Seat Track Position Sensor	Configured	
Passenger Seat Track Position Sensor	Configured	
Passenger Occupant Detection Sensor	Not Configured	
Passenger Airbag Disable Switch	Not Configured	
Passenger Airbag Disable Indicator	Not Configured	
Driver Frontal Squib 1	Configured	
Driver Frontal Squib 2	Configured	
Driver Frontal Squib 3	Configured	
Passenger Frontal Squib 1	Configured	
Passenger Frontal Squib 2	Configured	

Passenger Frontal Squib 3	Configured	
Driver Knee Bolster Squib	Configured	
Passenger Knee Bolster Squib	Configured	
Driver Seatbelt Retractor Pretensioner	Configured	
Passenger Seatbelt Retractor Pretensioner	Configured	
Driver Seatbelt Load Limiter	Configured	
Passenger Seatbelt Load Limiter	Configured	
Driver Seatbelt Anchor Pretensioner	Configured	
Passenger Seatbelt Anchor Pretensioner	Configured	
Driver Seatbelt Buckle Pretensioner	Not Configured	
Passenger Seatbelt Buckle Pretensioner	Not Configured	
Left Curtain Squib 1	Configured	
Right Curtain Squib 1	Configured	
Left Side Seat Squib 1	Configured	
Right Side Seat Squib 1	Configured	
Second Row Left Seat Side Airbag	Not Configured	
Second Row Right Seat Side Airbag	Not Configured	
Driver Frontal Squib 4	Not Configured	
Passenger Frontal Squib 4	Not Configured	
Left Up-Front Acceleration Sensor	Configured	
Right Up-Front Acceleration Sensor	Configured	
Right B-Pillar Impact Acceleration Sensor	Configured	
Left B-Pillar Impact Acceleration Sensor	Configured	
Left C-Pillar Impact Acceleration Sensor	Configured	
Right C-Pillar Impact Acceleration Sensor	Configured	
Right D-Pillar Impact Acceleration Sensor	Configured	
Left D-Pillar Impact Acceleration Sensor	Configured	
Left Side Door Pressure Sensor	Configured	
Right Side Door Pressure Sensor	Configured	
Configuration Column Identifier	A3	

EPS CONFIGURATION

NAME	VALUE	UNITS
Stop/Start Feature Active	False	
Lane Feedback Feature Active	True	
Parallel Park Assist Feature Active	True	
Dynamic Steering Torque Feature Active	True	

HVAC CONFIGURATION

NAME	VALUE	UNITS
DualZone ATC Control (Factory) (BB)	False	
DualZone ATC Control (BB)	False	
Dual Zone MTC Control (BB)	False	
Single Zone MTC Control (BB)	False	

MTC With EBL (3Knob)	False	
MTC Without EBL (3Knob)	False	
MTC heater only (3Knob)	False	
HVAC Configuration	Dual Zone ATC + Rear	

PDM CONFIGURATION

NAME	VALUE	UNITS
Frameless Window	False	

PSDML CONFIGURATION

NAME	VALUE	UNITS
VSIM Status	False	

PSDMR CONFIGURATION

NAME	VALUE	UNITS
UPFM Status (Present = True, Absent = False)	False	

MSM CONFIGURATION

NAME	VALUE	UNITS
Adjustable Pedals	False	
Telescope/Tilt	False	

CSWM CONFIGURATION

NAME	VALUE	UNITS
Heated Steering Wheel	True	
Vehicle Line D-Series	False	
Vehicle Line R-Series	True	
Vehicle Line W-Series	False	
Vehicle Line J-Series	False	
Vehicle Line L-Series	False	
Vehicle Line M-Series	False	
Vehicle Line P-Series	False	
Vehicle Line U-Series	False	
EC - Seat A	Programmed	
EC - Seat B	Programmed	

AMP CONFIGURATION

NAME	VALUE	UNITS
Premuim - 1 (8 channel)	False	
Premuim - 2 (12 Channel)	False	
Premium - 3	True	
Non -ANC	False	
Current ANC Calibration ID - Service	RU PHEV 3.6L: Steel Roof & Harman AMP	

ANC Status	Off - Window Mute	
ANC Calibration Date - Year	18	
ANC Calibration Date - Week	45	
ANC Calibration Date - Patch Level	2	
Teen Key Present	False	
Left/Right Hand Drive	Left Hand Drive	
Door Module - Left Front	Present	
Door Module - Left Rear	Present	
Door Module - Right Front	Present	
Door Module - Right Rear	Present	
Cabin Equalization Curve Number	53	
Sub-EQ Set Selected	Sub-EQ#6 Selected	
Current EQ Checksum	6F F1 A3 D1	
Surround Sound Activated	Set	

IPC CONFIGURATION

NAME	VALUE	UNITS
PHEV	True	
Rear Fog Lamp	False	

PTS CONFIGURATION

NAME	VALUE	UNITS
Front License Plate Configuration	Front Plate Config - USA	
Rear System with 6 Front Sensors	True	
Front System with 6 Rear Sensors	True	

SCCM CONFIGURATION

NAME	VALUE	UNITS
Rear Wiper	True	
Tilt Telescope	False	
Paddle Shifter	False	
Cruise Control / ACC	True	

BCM CONFIGURATION

NAME	VALUE	UNITS
BCM (Interior Bus)	Set	
HSM	Set	
DDM	Set	
PDM	Set	
DMRL	Set	
DMRR	Set	
HVAC	Set	
MSM	Set	
PLGM	Set	

VTM	Not Set	
PSDML	Set	
PSDMR	Set	
FSM	Not Set	
Radio	Set	
DTV	Not Set	
ITM	Not Set	
AMP	Set	
EDM	Set	
ICS	Set	
HVACR	Set	
CVPM	Set	
EOMR	Set	
MSMP	Set	
VRM	Set	
DSM	Set	
EAM	Not Set	
ANC	Not Set	
AHLM	Not Set	
BCM (PT)	Set	
PCM	Set	
EPS	Set	
ESM	Set	
ABS	Not Set	
RFH	Set	
IPC	Set	
ACC	Set	
ORC	Set	
PTS	Set	
SCCM	Set	
TCM	Not Set	
OCM	Set	
FFCM	Set	
ABSO	Set	
ESL	Not Set	
HCP	Set	
EBCM	Set	
ORC	Set	
ESM	Set	
ESC	Set	
ECM	Set	
HCP	Set	
OBCM	Set	
AHCP	Set	

EAC	Set	
BPCM	Set	
APM	Set	
Number of Reprogramming Attempts - Counter #0	0	
Vehicle Configuration Programmed Status	True	
Last Programmed Status	Service	
Last Configuration Odometer	52981	miles
Vehicle Configuration Auto Write Counter	1	
Vehicle Configuration 1 - Write Counter	2	
Vehicle Configuration 2 - Write Counter	2	
Vehicle Configuration 3 - Write Counter	2	
Vehicle Configuration 4 - Write Counter	2	
Vehicle Configuration 5 - Write Counter	2	
Vehicle Configuration 6 - Write Counter	2	
Programmed ECUs: Cabin Network	2	
Programmed ECUs: P/T Chassis Network	2	
Programmed Network Configuration - Audio / Telematics Network	0	
Programmed ECUs: Hybrid LAN Network	0	
ECU Configuration 1 (CBC Configurable Inputs and Outputs)	2	
ECU Configuration 2 (CBC Features)	2	
ECU Configuration 3	2	
ECU Configuration 4	2	
ECU Configuration 5 (Wireless)	2	
ECU Configuration 5 (Doors)	2	
ECU Configuration 5 (Memory)	2	
ECU Configuration 6 (Brake)	2	
ECU Configuration 6 (Suspension)	2	
ECU Configuration 6 (Powertrain)	2	
ECU Configuration 6 (Safety)	2	
ECU Configuration 7 (CBC Exterior Lighting Calibrations)	2	
ECU Configuration 8 (LIN and Miscellaneous)	2	
ECU Configuration 9A	2	
ECU Configuration 9 (ITM)	2	
ECU Configuration 10	2	
ECU Configuration 11	2	
ECU Configuration 12	2	
ECU Configuration 13	2	
ECU Configuration 14	2	
ECU Configuration 15 (CBC Features)	2	
ECU Configuration 15 (Suspension)	2	
Vehicle Configuration 7 - Write Counter	2	
Vehicle Config CSM1	2	
Vehicle Config CSM2	2	
Model Year	2020	

Vehicle Line	RU	
Country Code	USA	
Left/Right Hand Drive	Left Hand Drive	
Remote Start Present	Set	
Drive Configuration	2WD Front	
Emode Present	Not Set	
Auto Highbeam	Set	
Body Style	Station Wagon	
Maximum Vehicle Speed	0	MPH
Shifter Type	5 Position Rotary Eshifter PRNDL / Type RS5L	
Performance Pages Present	Not Present	
Special Packages	74	
PTS Configuration	Semi Automatic / Semi Automatic	
Hill Descent Feature Present	Not Set	
Select Speed Control Feature Present	Not Set	
Power Inverter Type	No Power Inverter	
Thatcham Present	Not Set	
Rain Sensor Present	Set	
SKIM System Present	Not Set	
Air Conditioning Present	Not Set	
Cruise Feature is Present	Not Set	
Flipper Glass Present	Not Set	
Full Size Spare	Not Set	
Off Road Capable	Not Set	
Special Packages IC	Pacifica	
Max Load Inflation Pressure Rear Tire	36.0	PSI
Max Load Inflation Pressure Front Tire	36.0	PSI
Police Lighting Feature	Not Set	
Power Right Sliding Door Present	Set	
Power Left Sliding Door Present	Set	
RKE System Present	Set	
T-Case Type	Not Present / Not Present	
Wheel Base	Wheel base not programmed / WB_NP	
FOBIK Safe Enable	Set	
ELV Present	Not Set	
Fuel Capacity	17	gallons
Window Express Feature Configuration	All windows express feature	
Adjustable Pedal Feature Present (non-Memory)	Not Set	
Auto Headlamp Feature Present	Set	
Door Alert Feature Present	Not Set	
Two Fuel Sending Units Present	Not Set	
Vehicle is an SRT	Not Set	
Disable Display of Radio Clock	Not Set	

Chassis Type	Type 9	
Display Outside Temperature Present	Set	
HVAC Configuration	Dual Zone ATC + Rear	
Vehicle Brand	Chrysler	
Display Compass Heading Present	Set	
ESCL system present	Not Set	
High Intensity Discharge Head Lamps	Not Set	
Secondary Lock Present	Not Set	
Liftgate/Trunk Type	Power Liftgate	
Collision Mitigation System present	Set	
Forward Collision Warning present	Set	
Base TPM system present	Not Set	
Premium TPM system present	Set	
Paddle Shift Feature Present	Not Set	
Sport Mode Present	Not Set	
Auto Park Present	Set	
Passive Entry Present	Set	
Keyless Go Present	Set	
Transfer Case High Ratio	1.000	No Unit
Axle Ratio	3.251	
Transfer Case Low Range Reduction Ratio	0.000	
Dynamic Tire Circumference (All or Rear)	89	inch
Analog Door Sensor Configuration	Driver Door Only Analog Sensor	
Air Quality System Present	Not Set	
Steering Ratio at Negative Angle 1	0.0	No Unit
Connector G Pin 9: Ambient Light Dimmer Wheel Input Present	Set	
Connector A Pin 3/Connector D Pin 2: Low Beam Output Present	Set	
Connector E Pin 29: Rear Wiper Motor Park Signal Present	Set	
Connector F Pin 9: Analog Door Ajar Signal Front Driver Present	Set	
Connector F Pin 23: Door Lock Switch Signal Front Passenger Present	Set	
Connector F Pin 29: Horn Switch Present	Set	
Connector A Pin 11: Hood Ajar Switch Input Present	Set	
Connector F Pin 8 : Liftgate Release Outside Handle Switch Present	Not Set	
Connector E Pin 5: PHEV Fuel Door Switch Input	Set	
Connector F Pin 6: Fuel Door Motor Output Signal Present	Set	
Connector D Pin 7: Stop/Turn Trailer Tow Right Output Present	Not Set	
Connector D Pin 9: Trailer Tow Backup Output Present	Not Set	
Connector D Pin 10: Trailer Tow Tail Lamp Output Present	Not Set	
Connector D Pin 11: Stop/Turn Trailer Tow Left Output Present	Not Set	
Connector D Pin 12: PHEV ECM Hardwire Wake Up Output Present	Set	
Connector A Pin 22: Right Dedicated DRL Lamp Output Present	Set	
Connector D Pin 15: Left Dedicated DRL Lamps Output Present	Set	
Connector E Pin 34: Vacuum Cleaner Relay Output Present	Not Set	
Connector G Pin 24 (Internally tied to Connector F Pin 7): Ambient Lighting Output	Not Set	

Connector A Pin 1 and Connector D Pin 13: Front Fog Lamps Output Present	Set	
Connector F Pin 35: Inverter Enable Relay Output Present	Set	
Connector E Pin 39/Connector F Pin 5: Rear Fog Lamps Output Present	Not Set	
Connector E Pin 4/Connector F Pin 32: Rear Park Lamps Output Present	Set	
Connector E Pin 3/Connector F Pin 42: Rear Turn Lamps Output Present	Not Set	
Connector E Pin 48 (Tied internally to Connector A Pin16): Rear Wiper Motor Control Output Present	Set	
Connector E Pin 9: Run-ACC Y Relay #2 Output Present	Set	
Connector A Pin 10/Connector D Pin 5: Side Markers Output Present	Set	
Connector E Pin 8: PHEV HCP Hardwire Wakeup	Set	
Connector E Pin 42: Charge Port Lock Output Present	Set	
Connector E Pin 41: Charge Port Unlock Output Present	Set	
Connector F Pin 4: Liftgate Release Present	Not Set	
Connector G Pin 15: UGDO Feed Output Present	Set	
Connector G Pin 22: VTA Warning LED Output Present	Set	
Connector E Pin 11: Vacuum Switch Input	Not Set	
Connector E Pin 37: Right HID Control Output Present	Not Set	
Connector E Pin 7: Left HID Relay Control Output Present	Not Set	
Connector D Pin 22/ Connector D Pin 23: Ambient Temperature Signal/Return Present	Set	
Tip Start Enabled	Set	
Dual Start Relay System Present	Not Set	
Wiper Service Position Enabled	Not Set	
Fuel Door Release Enabled	Not Present	
Trailer Tow Present	Not Set	
Quad Headlamps Enable	Set	
Horn Chirp Allowed	Set	
Bi Xenon Headlamps Enable	Not Set	
Hazard Lamp Configuration	Latching Switch	
Park Lamp Loadshed Enable	Set	
Front Fog Lamp Dropout Enable	Set	
Combined Rear Lighting Enable	Set	
Side Repeaters Enable	Not Set	
One Touch Lane Change	Set	
Exterior Light Loadshed Enable	Set	
Front Wiper Park Enable	Set	
Rear Wiper Park Enable	Set	
Reversible Washer Pump Enable	Set	
Combined Front Park/Turn Feature Enable	Not Set	
DRL Configuration	No DRL	
DRL Lamp Location	Dedicated	
DRL Dropout Enable	Set	
Tunnel Detection	Not Set	
Fuel Door Present	Not Set	
LED Reverse Lamps Present	Not Set	

LED Stop Lamps Present	Not Set	
LED Rear Turn Lamps Present	Not Set	
LED Tail Lamps Present	Set	
LED Rear Fog Lamps Present	Not Set	
LED License Lamps Present	Set	
LED Front Turn Lamps Present	Not Set	
LED Front Fog Lamps Present	Not Set	
LED Dedicated DRL Present	Set	
LED Low Beam Lamps Present	Not Set	
LED High Beam Lamps Present	Not Set	
LED Front Park/Marker Lamps Present	Set	
Illuminated approach Enabled	Not Set	
Headlamp Wash Spray Duration (at 100 ms intervals)	1100ms	
Headlamp Wash Interval	wash cycle#11	
Headlamp Wash Shot	double	
Front Wiper Wipes After Wash	2 Wipes	
Headlamp Washer Low Fluid Shut-Off Enable	Set	
Intermittent Wiper States	4 Intermittent Wiper position Switch	
LED CHMSL Lamp Present	Set	
Rear Camera Present	Not Set	
Power Inverter Present	Not Set	
Front Park Assist Present	Set	
Front Heated Seats Present	Set	
Destination	United States of America	
Cabin Equilization Curve Number	RU Premium System - Harman 12ch	
Heated Steering Wheel Present	Set	
Surround Sound Feature Present	Set	
Power Door Locks Present	Set	
Antenna Type	Active Primary and no secondary antenna	
Disable CD Eject	Not Set	
Microphone Tuning Parameter	Absent [Not Used]	
Microphone Configuration	2 Microphones	
Microphone Type	Peiker 300 mv	
External Port Type	AUX + USB	
Splashscreen Type	Vehicle Brand	
Fleet Vehicle Content	Not Set	
Vehicle Variant	Undefined	
Tip Start Present	Set	
AP5 Trunk Unlock	CAN	
Airport Scenario Trunk	Not Set	
AP5 Trunk Lock	Simple Switch	
AP1 Left Front	Smart Switch	
AP2 Right Front	Smart Switch	
AP3 Left Rear	CAN	

AP4 Right Rear	CAN	
Global Up	Not Set	
Global Down	Not Set	
Sun Shade	Not Set	
Puddle Lamp Present	Not Set	
Rear Door Pre Short Drop	Not Set	
Passenger Window Lockout	Not Set	
Folding mirrors present	Set	
Heated Mirrors Present	Set	
Mirror turn signals present	Set	
Driver Memory Mirrors Present	Set	
Passenger Memory Mirror Present	Set	
Electro-chromatic driver mirror present	Set	
Electro-chromatic passenger mirror present	Not Set	
Tow Mirror Present	Not Set	
Blindspot Mirror Present	Set	
Window Motor Type	Not Set	
Window Hall Sensors Present	Not Set	
Frameless Window Present	Not Set	
Memory Adjustable Pedals Present	Not Set	
Tilt/Telescope Steering Present	Not Set	
Driver Memory Seat Present	Set	
Stow 'n Assist Present - Driver	Set	
Stow 'n Assist Present - Passenger	Set	
Rear Heated Seats Present	Not Present	
Front Vented Seats Present	Present	
Heated Steering Wheel Present	Present	
Heated Seat Material Type	Base Leather	
Heated Wheel Material Type	Full Leather	
Brake System ECU Configuration A	value 0	
ECO Mode Configuration	Remember Previous State with Ignition Key Cycle	
Dual Alternator Present	Not Set	
ODS Present	False	
Driver Kneebag Present	True	
Passenger Kneebag Present	True	
Curtain Airbags Present	True	
Tow Hooks Present	False	
Passive Ped Pro Present	False	
1st Row Seat Side Airbags Present	True	
Integrated EPP Present	False	
BUX Market	False	
Front Park/Turn Voltage	Park to Turn ratio 55 Percent	
Auto Headlamp On Threshold	3.31409	Volt

Auto Headlamp Off Threshold	2.54930	Volt
Left Low Beam Voltage Regulation	13.6 Volts	
Left High Beam Voltage Regulation	13.6 Volts	
Right Low Beam Voltage Regulation	14 Volts	
Right High Beam Voltage Regulation	13.8 Volts	
Left Front Corner Voltage	13.2 Volts	
Right Front Corner Voltage	13.4 Volts	
Left Rear Corner Voltage	14 Volts	
Right Rear Corner Voltage	14 Volts	
Alert no Reply	Set	
Alert On System Fault	Set	
Alert On Search Timeout	Set	
Panic Enable	Set	
Compass Mounting Orientation	Rightside up	
Washer Fluid Level Voltage Threshold	4.46 volts	
Fobik Safe Alerts Per Ignition Cycle	2	
IBS Present	Set	
OHC Module Present	Set	
Humidity Sensor Present	Set	
HFRM Present	Set	
Auto Relock Time	60	seconds
VTA System Present	VTA	
Illuminated Approach Interior Lighting Target Percentage	100(50%)	
Illuminated Approach Headlamp Target Percentage	125 (62.5%)	
Illuminated Approach Taillamp Target Percentage	125 (62.5%)	
Illuminated Approach Interior Lighting Ramp Up Time	130(2600ms)	
CRVMM Present	Set	
EVIC SWS Module Present	Set	
Compass Mounting Angle	0	Degree
IBS Activate MWU	Not Set	
Battery Types	SNA	
IBS Quiescence Current Limit	-250	mA
IBS Minimum Voltage Limit	5.0	Volts
IBS Minimal Charge Limit	10	AmpHrs
Battery Type II	255	
IBS Minimum Charge Limit	600	mA
Connector D Pin 11: Stop/Turn Trailer Tow Left Output Present	Reserved	
Connector F Pin 41: Backup-Reverse lamp Left	Set	
Connector E Pin 1: Backup-Reverse lamp Right	Set	
Connector F Pin 5: Left Rear Fog Lamp	Output Disable	
Connector E Pin 39: Right Rear Fog Lamp	Output Disable	
Connector F Pin 42: Right Rear Turn Signal	Right Rear Turn Signal	
Connector E Pin 3: Left Rear Turn Signal	Left Rear Turn Signal	
Connector D Pin 1: Left High Beam Feed	Left High Beam (0)	

Connector A Pin 2: Right High Beam Feed	Right High Beam (0)	
Connector F Pin 25: Left Rear Turn Lamp Fault Sense	Disable	
Connector F Pin 28: Right Rear Turn Lamp Fault Sense	Disable	
Connector F Pin 27: Left Sliding Door Ajar	Left Sliding Door Ajar	
Connector F Pin 4: Liftgate Release	Trunk/Liftgate Release	
Connector F Pin 31: Right Sliding Door Ajar	Right Sliding Door Ajar	
Connector D Pin 21: Brake Fluid Level Switch	no parallel resistor	
Connector D Pin 12: PHEV ECM Hardwire Wake Up	Engine Control Module Wake up (PHEV only)	
Connector F Pin 29: Horn Switch Input	Horn Switch Input	
Connector A Pin 11: Hood Ajar Switch Signal	500 ohm series and 500 ohm parallel resistors	
Connector E Pin 7: Left HID Relay Control	Left HID Lamp Relay	
Connector E Pin 37: Right HID Relay Control	Right HID Lamp Relay	
Connector E Pin 29: Rear Wiper Motor Park Signal	Reserved	
Connector E Pin 5: E-5 PHEV Fuel Door Switch Input	PHEV Fuel Door Switch	
Stop/Start Enable Switch Present	Not Set	
Siren	Not Set	
Ultrasonics	Not Set	
Tilt	Not Set	
Connector F Pin 13: Left Sliding Door Switch Input (B-Pillar)	Left B-Pillar sliding Door Switch	
Connector F Pin 14: Right Sliding Door Switch Input (B-Pillar)	Right B-Pillar Sliding Door Switch	
Connector F Pin 15: Driver Door Lock Switch Input	Not Present	
Connector F Pin 16: Passenger Door Lock Switch Input	Not Present	
Connector G Pin 2: Fog Lamp Switch Input	Fog Lamp Switch	
Connector D Pin 4: Digital Spare Input #1	Not Present	
Connector D Pin 8: Digital Spare Input #2	Not Present	
Heatsoak Flush Time	105	Time
Engine Off Clear Time	180	Time
Connector F Pin 30: Fuel Door Lock (BUX)	Not Present	
Connector F Pin 33: Fuel Door Unlock (BUX)	Not Present	
Connector F Pin 34: Spare HSD	Not Present	
Connector F Pin 37: Vacuum Cleaner Power Saver Indicator	Not Present	
Ambient Stable Counter Limit	40	Counter
Heatsoak Speed	15	Counter
Heatsoak Set Time	15	Time
Max Engine Off Time	220	Time
CHMSL Lamp Output Disable	Not Set	
Connector E Pin 28: Secondary Door Ajar Switch Present - PIN E-28	Set	
Manual Door Locks Present	Not Set	
Connector E Pin 48 (Tied internally to Connector A Pin16): Rear Wiper Motor Control Output Present	Rear Wiper (0)	
Connector G Pin11/Connector G Pin 12: Not Used	ERS	
Rain Sensor Module #2 Present	Set	
Humidy Sensor Long Present	Set	

Auto High Beam Module Location	HaLF	
License Plate Lamp Disable	Not Set	
Connector F Pin 29: Horn Switch Present	Horn Switch Input	
Connector E Pin 39: Right Rear Turn Signal	Right Rear Turn Signal	
Connector E Pin 3: Left Rear Turn Signal	Left Rear Turn Signal	
Excess Lateral Acceleration Factor	Filter Off	
Average Last Lateral Acceleration Values	No Averaging	
Excess Longitudinal Acceleration Factor	Filter Off	
Average Last Longitudinal Acceleration Values	No Averaging	
Brake Smoothing Duration	Filter Off	
Brake Smoothing Factor	Filter Off	
Steering Smoothing Duration	Filter Off	
Steering Smoothing Factor	Filter Off	
Steering Smoothing Threshold	Filter Off	
Brake Smoothing Threshold	Filter Off	
Maximum Longitudinal Change	Filter Off	
Maximum Lateral Change	Filter Off	
Acceleration Threshold	Filter Off	
Acceleration Factor	Filter Off	
Nose Dive Threshold	Filter Off	
Nose Dive Factor	Filter Off	
Horn Chirp Duration	Short	
VTA Hood Ajar Monitoring	Not Set	
Headlamp Soak Delay	1.0 sec	
Auto High Beam ON Threshold	25 km/hr	
Auto High Beam OFF Threshold	20 km/hr	
RKE Auto-Relock Feature Enable	Not Set	
PE Auto-Relock Feature Enable	Set	
Parking Light Enable	Not Set	
Interior Lighting Night Threshold	4.45147	Volt
Interior Lighting Day Threshold	4.27498	Volt
TPMS Configuration	Logic 1 NHTSA Enable Warning	
Smart Alternator Present	Not Set	
Temperature Display Resolution	HaLF	
Sunroof Present	Not Set	
Radio Speaker Open Circuit Disable (LF)	Not Set	
Radio Speaker Open Circuit Disable (RF)	Not Set	
Radio Speaker Open Circuit Disable (LR)	Not Set	
Radio Speaker Open Circuit Disable (RR)	Not Set	
ANC Calibration Parameter Data Set	Harman Amplified 3.6L PHEV	
Surround View Camera On/Off Softkey Present	Set	
Drive Mode Version	Version 1	
Show Phone Information in Cluster	01	
Auto Dimming Mirror Hard Button Present	Set	

Automatic Crash Notification Feature Present	Undefined	
Park Assist Tuning Set	BUX Front and Rear Only	
Unlock all doors on 1st press	Set	
Sound Horn on Lock	Set	
Flash Lamps on Lock	Set	
Headlamps on with Wipers	Set	
Auto Lock	Set	
Auto Unlock	Set	
Sliding Door Alert	Not Set	
Auto Wipers	Set	
Illuminated Approach Time	30	seconds
Headlamp Delay Time	30	seconds
Accessory Delay Time	45	seconds
Daytime Running Lamps	Set	
Hands Free Sliding Door Enable	Set	
Sliding Door Chime Enable	Set	
Auto Highbeam	Set	
Sound Horn on Remote Start	Set	
Sound Horn On Lock Status	Chirp on 1st press/FIRST	
Rear View Camera Static Grid Lines Enabled	Not Set	
Rear View Camera Dynamic Grid Lines Enabled	Not Set	
3rd Row Lock CSO	Not Set	

RADIO CONFIGURATION

NAME	VALUE	UNITS
Satellite Subscription ID	759N9DCE	
Satellite Subscription Status	Subscribed	
Satellite Subscription Reason Code	00	
Satellite Subscription Suspend Day	01	
Satellite Subscription Suspend Month	01	
Satellite Subscription Suspend Year	46	
911 Button	On	
SDARS	True	
Navigation Active	True	
Cellular	True	
Internal CD Player	False	
Wi-Fi	True	
Bluetooth	True	
Application Framework	True	
FM Diversity	False	
Clock Defeat	Off	
Automated Loudness	On	
Anti-Theft Enable Status	On	
12/24 Time Selection	12 Hour Time	

Front Seat Video Playback	Enabled	
Cabin EQ Curve Number Currently Used by Radio	35	
Splash Screen	Chrysler	
Compass on the bus messaging Authorization	Allowed	
GPS on the Bus messaging Authorization	Allowed	
USB Hubs Detected	1	No Unit
SD Card Readers Detected	0	No Unit
Enumerated USB Devices	0	No Unit
Aux Jack	Not Inserted	
DTV Short Term Configuration	—	

HVACR CONFIGURATION

NAME	VALUE	UNITS
DualZone ATC Control (Factory) (BB)	False	
DualZone ATC Control (BB)	False	
Dual Zone MTC Control (BB)	False	
Single Zone MTC Control (BB)	False	
MTC w EBL (3Knob)	False	
MTC wo EBL (3Knob)	False	
MTC heater only (3Knob)	False	

FFCM CONFIGURATION

NAME	VALUE	UNITS
HIL mode Enabled	False	
Traceability info	02193501109309	
Traceability info	11193575729201	
XCP Enabled	False	

EDM CONFIGURATION

NAME	VALUE	UNITS
VES	False	
VRM	False	
Vehicle Line	RU	
Body Style	Station Wagon	
Vehicle Brand Type	Chrysler	
Blind-Spot Module	Not Present	
Common Body Controller Int Bus	Not Present	
Comfot Seats and Wheel Module	Not Present	
Driver Door Control Module	Not Present	
Passenger Door Control Module	Not Present	
Left Rear Door Control Module	Not Present	
Right Rear Door Control Module	Not Present	
Heating Ventilation Air Conditioning	Not Present	
Memory Seat Module	Not Present	

Power Liftgate Module	Not Present	
Left Power Sliding Door Module	Not Present	
Right Power Sliding Door Module	Not Present	
Folding Seat Module	Not Present	
Power Top Control Module	Not Present	
Rear Body Controller Module	Not Present	
Radio	Present	
Vehicle System Interface Module	Not Present	
Intrusion module	Not Present	
Amplifier Module	Not Present	
CAN I in-dash disc player module	Present	
Convergence Telematics Module	Not Present	
Integrated Center Stack Module	Not Present	
Video Ent. System Screen 2 Module	Not Present	
Video Ent. System Screen 1 Module	Not Present	
Left/Right Hand Drive	Not Programmed	
Remote Start Present	False	
E-Mode Feature Present	False	

RCCC CONFIGURATION

NAME	VALUE	UNITS
DualZone ATC Control	False	
DualZone ATC Control	True	
Dual Zone MTC Control	False	
Single Zone MTC Control	False	
MTC with EBL	False	
MTC without EBL	False	
MTC Heater Only	False	

ABSO CONFIGURATION

NAME	VALUE	UNITS
Multiple Pressure Sensors	True	
Front Directional Sensors	False	
Rear Directional Sensors	True	
Feature PIN	False	
EPB	True	
ACC	True	
Hardwired VSO	True	
Drive Configuration	2WD Front	
VC Chassis Type	Type 9	
ESC BLA Enabled	False	
Dynamic Tire Circumference	89	inch
Axle Ratio	3.251	No Unit
Engine Displacement	3.6	No Unit

PN ESC Byte1	0	
PN ESC Byte2	0	



VEHICLE SCAN REPORT

Vehicle 2020 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN 2C4RC1N74L [REDACTED]

Odometer 56862.7 miles
Publication Date Aug 29, 2022, 2:59:31 PM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
PCM	Powertrain Control Module	CAN-C	68444228AE	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68444228AE
ICS	Integrated Center Stack	CAN-I	6UX621X8AA	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	6UX621X8AA
RFH	Radio Frequency Hub	CAN-C	68453559AB	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68453559AB
ESM	Electronic Shifter	CAN-C	68240089AM	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68240089AM
ORC	Occupant Restraint	CAN-C	68405567AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68405567AC
EPS	Electric Power Steering	CAN-C	68460392AA	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68447893AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68447893AC
DDM	Driver Door Module	CAN-I	68424449AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68424449AC
PDM	Passenger Door Module	CAN-I	68424448AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68424448AC
DMRL	Door Module Rear Left	CAN-I	68225096AG	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68225096AG
DMRR	Door Module Rear Right	CAN-I	68225096AG	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68225096AG
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68369596AC
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68369596AC
MSM	Memory Seat Module	CAN-I	68321862AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68321862AC
PLGM	Power Liftgate	CAN-I	68316094AF	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68316094AF
CSWM	Comfort Seat Wheel Module	CAN-I	68434912AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68434912AC
AMP	Amplifier	CAN-I	68448067AA	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68448067AA
IPC	Instrument Panel Cluster	CAN-C	68434956AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68434956AC
PTS	Parktronics	CAN-C	68193775AJ	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68193775AJ
SCCM	Steering Column Control Module	CAN-C	68360889AC	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68360889AC
BCM	Body Controller	CAN-C	68424601AD	2C4RC1N74L [REDACTED]	2C4RC1N74LR [REDACTED]	68424601AD

ACC	Adaptive Cruise Control	CAN-C	04672758AB	2C4RC1N74LR	2C4RC1N74LR	04672758AB
RADIO	Radio	CAN-I	68461768AD	2C4RC1	2C4RC1N74LR	68461768AD
OCM	Occupant Classification	CAN-C	68403127AA	2C4RC1N74LR	2C4RC1N74LR	68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB	2C4RC1N74LR	2C4RC1N74LR	68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AB	2C4RC1N74LR	2C4RC1N74LR	04672786AB
RBSS	Right Blind Spot Sensor	CAN-I	04672786AB	2C4RC1N74LR	2C4RC1N74LR	04672786AB
FFCM	Forward Facing Camera Module	CAN-C	04672776AA	2C4RC1N74LR	2C4RC1N74LR	04672776AA
EDM	External Disc Module	CAN-I	68378304AA	2C4RC1N74LR	2C4RC1N74LR	68378304AA
APM	Accessory Power Module	CAN-C	05185046AB	2C4RC1N74LR	2C4RC1N74LR	05185046AB
BPCM	Battery Pack Control Module	CAN-C	05193166AF	2C4RC1N74LR	2C4RC1N74LR	05193166AF
HCP	Hybrid Control Processor	CAN-C	05190265AG	2C4RC1N74LR	2C4RC1N74LR	05190265AG
OBCM	On Board Charging Module	CAN-C	05185047AE	2C4RC1N74LR	2C4RC1N74LR	05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC	2C4RC1N74LR	2C4RC1N74LR	68321862AC
DSM	Display Screen Module	CAN-I	68316174AC	2C4RC1N74LR	2C4RC1N74LR	68316174AC
VRM	Video Routing Module	CAN-I	68376134AF	2C4RC1N74LR	2C4RC1N74LR	68376134AF
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA	2C4RC1N74LR	2C4RC1N74LR	6WL30DX9AA
CVPM	Central vision processing module	CAN-I	68375113AB	2C4RC1N74LR	2C4RC1N74LR	68375113AB
EAC	Electric A/C Compressor	CAN-C	68237995AG	2C4RC1N74LR	2C4RC1N74LR	68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05190266AG	2C4RC1N74LR	2C4RC1N74LR	05190266AG
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB	2C4RC1N74LR	2C4RC1N74LR	68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68461812AA	2C4RC1N74LR	2C4RC1N74LR	68461812AA
SGW	Security Gateway Module	CAN-C	68447193AB		2C4RC1N74LR	68447193AB

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	SERIAL NUMBER	CVNS
PCM	USA	1B 47	46 03 01	4419		
ICS	USA	0F 0C 00	12 25 00	4700		
RFH	USA / USA	10 17 00	13 09 00	4A00		
ESM	USA / USA	0F 24 00	12 28 FF	4402		
ORC	USA / USA	11 1F 00	12 2B 00	4301		
EPS	USA / USA	12 2A 00	12 1E 01	4502		

Page 3 of 27

HVAC	USA	0E 09 00	13 05 01	4401	
DDM	USA	11 07 00	13 0B 00	4202	
PDM	USA	11 07 00	13 0B 00	4202	
DMRL	USA / USA	10 0B 00	12 0C 00	4201	
DMRR	USA / USA	10 0B 00	12 0C 00	4201	
PSDML	USA / USA	10 17 00	13 1E 11	4001	
PSDMR	USA / USA	10 17 00	13 1E 11	4001	
MSM	USA	0F 2B 00	10 27 03	4101	
PLGM	USA	17 19 00	18 22 00	4202	
CSWM	USA	11 2A 00	13 2C 00	4302	
AMP	USA	0F 06 01	12 2E 01	4021	
IPC	USA / USA	12 06 00	13 27 00	4704	
PTS	USA	0E 32 00	12 1F 00	4311	
SCCM	USA	0E 30 00	10 2B 00	4301	
BCM	USA	0D 11 00	13 0C 90	4415	
ACC	USA / USA	13 33 00	11 0D 00	4201	
RADIO	USA	13 31 14	13 31 14	8205	
OCM	USA / USA	11 1F 01	0E 2F 02	4030	
HVACR	USA	0E 09 00	10 03 02	4301	
LBSS	USA / USA	11 30 02	12 0D 00	4202	
RBSS	USA / USA	11 30 02	12 0D 00	4202	
FFCM	USA / USA	11 06 00	11 2B 00	4102	
EDM	USA	12 0A 00	11 08 00	4000	
APM	USA / USA	11 32 00	11 32 00	4001	
BPCM		0E 03 00	14 17 00	4005	
HCP	USA	11 1F 04	19 48 01	4005	
OBCM	USA	0F 0D 00	12 02 00	4002	
MSMP	USA	0F 2B 00	10 27 03	4001	
DSM	USA / USA	13 29 00	12 23 00	4000	
VRM	USA / USA	0F 1C 00	13 0C 10	4001	
RCCC	USA	0F 1D 00	13 04 00	4000	
CVPM	USA / USA	11 32 01	12 33 00	4003	
EAC	USA	0E 34 00	12 0F 00	4102	
AHCP	USA	11 1F 04	19 48 01	4000	
EBBM	USA	0E 19 02	14 0D 18	4000	
ABSO	USA	0E 15 02	12 2E 1E	4201	
SGW		5	779	4103	

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
HVAC	B10EB-00	Blower Power Module-	Stored
BPCM	P0A95-00	High Voltage Fuse "A"-	Active
HCP	P0A78-00	Drive Motor A Inverter Performance-	Active

HCP	P0C0B-00	Drive Motor A Inverter Power Supply Circuit/Open-	Active
HCP	P16F9-00	HCP Internal - Shutdown Performance-	Stored
HCP	P1AEC-00	MCPA HV Battery Voltage Sensor Circuit Performance-	Pending
HCP	P1AED-00	MCPB High Voltage Battery Voltage Sensor Circuit Performance-	Pending

ENVIRONMENTAL DATA SUMMARY

HVAC | B10EB-00 | Stored | Blower Power Module-

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	True	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	
Original Odometer Value	56858	miles
Most Recent Odometer Value	56858	miles
Frequency Counter	1	
Ignition Cycle Counter	2	

BPCM | P0A95-00 | Active | High Voltage Fuse "A"-

NAME	VALUE	UNITS
DTC	0A 95 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	
Original Odometer Value	16136	miles
Most Recent Odometer Value	16136	miles
Frequency Counter	1	
Ignition Cycle Counter	0	
FoM - for this DTC (lifetime fails)	18	events
FoM - for this DTC (lifetime fails counts on pass)	3.8400	seconds
FoM - for this DTC (lifetime longest fail on pass)	3.840	seconds
Battery Total Time Awake	77966776	seconds
Key in Ignition	Key_Def	

Key Position	Ign_Run	
EPT -WakeUp	Sourced	
HCP Contactor Command	Open	
Qualified Contactor Command - QCC	Open	
Verified Contactor Command - VCC	Open	
Contactor Status	Open	
Plug in Status	Not plugged in	
ChargingLevel	Plug in, but no charge	
Balance Mode	False	
Battery in Periodic wake up (Just battery) at time of Fault	False	
Battery in Periodic wake up (Wake up vehicle) at time of Fault	False	
Vehicle mileage at time of fault (ODO signal in \$3D2)	56862.66	miles
Battery Lifetime Miles	0.00	miles
Vehicle Speed	0.0	MPH
System (12) Volts at time of fault	12.132	Volts
Battery Lifetime AmpHrs of Charge	28926.7	AHr
Battery Lifetime AmpHrs of DisCharge	28877.5	AHr
SOC at time of Fault	59.6	%
Power Up SOC at time of Fault	59.2	%
HVIL Status -Vehicle	PASS	
HVIL Status - Battery pack	PASS	
HVIL PWM Duty Cycle - Vehicle	50.2	%
HVIL PWM Frequency - Vehicle	88.0	Hz
HVIL PWM peak voltage Sourced - Vehicle	10.864	Volts
HVIL PWM peak voltage Sensed - Vehicle	10.817	Volts
HVIL Source Voltage- Battery	1.377	Volts
HVIL Returned current - Battery	30.60	mA
HV Battery Current Sensor 1 Hall High	-0.85	Amps
HV Battery Current Sensor 2 Hall Low	0.05	Amps
HV Battery Current HVBatCrnt	0.00	Amps
HV Cooling Speed Pump 1 Target	0	rpm
HV Cooling Speed pump 1 Speed	0	rpm
Charge indicator Temp	142	°F
BPCM temperature max	73	°F
BPCM temperature min	73	°F
Pump - Wire Open\Short to Gnd	PASS	
Pump - Dry Run Detection	PASS	
Pump - Overcurrent	PASS	
Pump - Overtemperature	PASS	
Pump - Switch Power Shorted	PASS	
Isolation Circuitry Va	2.500	Volts
Isolation Circuitry Vb	2.501	Volts
Isolation Circuitry Vd	0.000	Volts
WC and Circuitry 2.5V Reference Voltage	2.500	Volts

WC and Circuitry Vcc Voltage	5.017	Volts
WC and CircuitryISO 8V Reference Voltage	7.990	Volts
WC and Circuitry Weld Contactor Sensor G (Pack Negative) Voltage	0.0	Volts
CVTN COMP ERR H	Normal	
CVTN COMP ERR L	Normal	
CVTN COMP FLT H	Normal	
CVTN COMP FLT L	Normal	
CVTN EDGE ERR H	Normal	
CVTN EDGE ERR L	Normal	
CVTN ABORT H	Normal	
CVTN ABORT L	Normal	
CVTN CRC FAULT H	Normal	
CVTN CRC FAULT L	Normal	
CVTN FRAM ERR	Normal	
CVTN STOP ERR	Normal	
CVTN STK FAULT ERR	Latched	
CVTN SYS RESET	Normal	
CVTN COMM TIMEOUT	Active	
CVTN VDIG WAKE FAULT	Normal	
CVTN INT TEMP FAULT	Normal	
CVTN VDIG FAULT	Normal	
CVTN VM FAULT	Normal	
CVTN VP FAULT	Normal	
CVTN VP CLAMP	Normal	
CVTN FACT CKSUM ERR	Normal	
CVTN ANALOG FAULT ERR	Normal	
CVTN HREF FAULT	Normal	
CVTN HREF GND FAULT	Active	
CVTN ADC CAL ERR	Active	
CVTN CUST ECC COR	Normal	
CVTN CUST ECC ERR	SNA	
CVTN FACT ECC COR	SNA	
CVTN ACT ECC ERR	SNA	
Cycles left to self heal	40	No Unit
Fault trigger level 1	False	
Fault trigger level 2	False	
Fault trigger level 3	False	
Fault Path	01	
HV Battery Charge Power 2sec	97503	watts
HV Battery Charge Power 10sec	95784	watts
HV Battery Discharge Power 2sec	97563	watts
HV Battery Discharge Power 10sec	95478	watts
HV Battery Power	007530	watts
Key - DriveRdy (CAN)	True	

Battery Lifetime Number Of Closes	6690	
Battery Full AmpHr Capacity	43	AmpHrs
Cell Impedance Max Discharge	0	mOhms
Cell Impedance Mim Discharge	0	mOhms
Battery Cell Voltage Maximum	3762	mV
Battery Cell Voltage Minimum	3746	mV
Battery Cell Voltage Average	3756	mV
Battery Cell Highest Cell number	88	
Battery Cell Lowest Cell number	34	
HV Battery Voltage (cell sum)	360.60	Volts
HV Battery Voltage (Module Sum)	359.90	Volts
HV Sensor A Pack Voltage	1.40	Volts
HV Sensor B Bus\Link (Pre-Fuse) Voltage	0.70	Volts
HV Sensor C OBCM (HVOBC Fuse) Voltage	0.70	Volts
HV Sensor D Heater (HVHTR Fuse) Voltage	0.70	Volts
HV Sensor G Weld Contactor(Pack Negative) Voltage	0.0	Volts
Battery Temperature Maximum Module	73	°F
Battery Temperature Minimum Module	73	°F
Battery Temperature Average Module	73	°F
Battery Temperature Highest Sensor number	12	
Battery Temperature Lowest Sensor number	03	
Battery Temperature Number of Failing Sensors	00	
HV Cooling Pump Relay Drive	Not Sourced	
HV Cooling Battery coolant inlet temp	79	°F
HV Cooling Battery coolant outlet temp	79	°F
HV Cooling OBCM temp inlet Temp	81	°F
Pump - Battery Coolant Level Low	False	
Isolation Vehicle Diagnostic Status	Run and Passed	
Isolation Vehicle Impedance	7.3125	Mega Ohms
Isolation Battery Diagnostic Status	Run and Passed	
Isolation Battery Impedance	0.8480	Mega Ohms
CVTN CUST CKSUM ERR	Normal	

HCP | POA78-00 | Active | Drive Motor A Inverter Performance-

NAME	VALUE	UNITS
DTC	0A 78 00	
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	

Occurrence flag	Occurrence	
Original Odometer Value	56862.7	miles
Most Recent Odometer Value	56862.7	miles
Frequency Counter	1	
Ignition Cycle Counter	0	
Real time clock	77966768	sec
RAM stamps keyOn	90	sec
RAM Stamps	3847	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
PHEV Charging Status	No Charging	
Engine Speed	0	rpm
HV Battery SOC	60	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Barometric Pressure	13	PSI
Engine Coolant Temperature	79	°F
Actual Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor A	0.000	Ft-Lbs
Inverter A Input DC Current	0.0	AMP
Electric Motor A Speed	0.0	rpm
Motor A - Inverter Current - phase A	-4	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	0	AMP
Motor A Phase U Short Fault - High-Side	False	
Motor A Phase U Cross Conduction Fault - High-Side	False	
Motor A Phase U Over Current Fault - High-Side	False	
Motor A Phase U Thermal Warning Fault - High-Side	False	
Motor A Phase U Thermal Shutdown Fault - High-Side	False	
Motor A Phase U Comm Error High Voltage Regulator Fault - High-Side	True	
Motor A Phase U Comm Error Low Voltage Regulator Fault - High-Side	True	
Motor A Phase U SPI Error Fault - High-Side	False	
Motor A Phase U Hardware Error Fault - High-Side	True	
Motor A Phase U Short Fault - Low-Side	False	
Motor A Phase U Cross Conduction Fault - Low-Side	False	
Motor A Phase U Over Current Fault - Low-Side	False	
Motor A Phase U Thermal Warning Fault - Low-Side	False	
Motor A Phase U Thermal Shutdown Fault - Low-Side	False	
Motor A Phase U SPI Error Fault - Low-Side	False	
Motor A Phase U Hardware Error Fault - Low-Side	True	
Motor A Phase V Short Fault - High-Side	False	
Motor A Phase V Cross Conduction Fault - High-Side	False	

Motor A Phase V Over Current Fault - High-Side	False	
Motor A Phase V Thermal Warning Fault - High-Side	False	
Motor A Phase V Thermal Shutdown Fault - High-Side	False	
Motor A Phase V Comm Error High Voltage Regulator Fault - High-Side	True	
Motor A Phase V Comm Error Low Voltage Regulator Fault - High-Side	True	
Motor A Phase V SPI Error Fault - High-Side	False	
Motor A Phase V Hardware Error Fault - High-Side	True	
Motor A Phase V Short Fault - Low-Side	False	
Motor A Phase V Cross Conduction Fault - Low-Side	False	
Motor A Phase V Over Current Fault - Low-Side	False	
Motor A Phase V Thermal Warning Fault - Low-Side	False	
Motor A Phase V Thermal Shutdown Fault - Low-Side	False	
Motor A Phase V SPI Error Fault - Low-Side	False	
Motor A Phase V Hardware Error Fault - Low-Side	True	
Motor A Phase W Short Fault - High-Side	False	
Motor A Phase W Over Current Fault - High-Side	False	
Motor A Phase W Thermal Warning Fault - High-Side	False	
Motor A Phase W Thermal Shutdown Fault - High-Side	False	
Motor A Phase W Comm Error Low Voltage Regulator Fault - High-Side	True	
Motor A Phase W SPI Error Fault - High-Side	False	
Motor A Phase W Hardware Error Fault - High-Side	True	
Motor A Phase W Short Fault - Low-Side	False	
Motor A Phase W Cross Conduction Fault - Low-Side	False	
Motor A Phase W Over Current Fault - Low-Side	False	
Motor A Phase W Thermal Warning Fault - Low-Side	False	
Motor A Phase W Thermal Shutdown Fault - Low-Side	False	
Motor A Phase W Comm Error Low Voltage Regulator Fault - Low-Side	True	
Motor A Phase W SPI Error Fault - Low-Side	False	
Motor A Phase W Hardware Error Fault - Low-Side	True	
Motor A Resolver Supply Voltage Value	15.75	Volts
Battery Feed Voltage 2 Sense	11.880	Volts
Battery Feed Voltage 3 Sense	11.736	Volts
Internal EPS Voltage Sense A	0.000	Volts
Internal EPS Voltage Sense B	0.000	Volts
Hybrid System State	SNA	
PIM DC Link Voltage - A	2	Volts
PIM DC Link Voltage - B	4	Volts
Passive Pump Coolant Temp In Sensor	82	°F
Low Temp Active Pump Speed	0	rpm
High Temp Aux Pump - Actual Speed	0	rpm
Outside Air Temperature	89.6	°F
HV Contactor Status	Open	
Inverter B Status Feedback	Normal OFF	
Battery Feed Voltage 1 Sense	11.808	Volts

Actual Torque - Motor B	0.184	Ft-Lbs
Available Motor Torque - Motor B	232.301	Ft-Lbs
Available Regen Torque - Motor A	0.000	Ft-Lbs
Available Regen Torque - Motor B	-232.301	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor B - Inverter Current - phase A	-4	AMP
Motor B - Inverter Current - phase B	-4	AMP
Motor B - Inverter Current - phase C	-4	AMP
Motor B Resolver Angle	180	Degree
Motor B Temp Sensor	81	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	Off	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Battery Voltage from BPCM	180.00	Volts
Electric Motor B Speed	0.0	rpm
Inverter A IGBT Temperature for phase A	82	°F
Inverter A IGBT Temperature for phase B	82	°F
Inverter A IGBT Temperature for phase C	82	°F
Inverter B IGBT Temperature for phase A	82	°F
Inverter B IGBT Temperature for phase B	82	°F
Inverter B IGBT Temperature for phase C	82	°F
APM Status	Idle	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	0	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.184	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Commanded Inverter A State	Inverter Disabled	
Inverter Status Feedback	Inverter Faulted	
Motor A Phase U Over Voltage Fault VH - High-Side	False	
Motor A Phase U Under Voltage Fault VH - High-Side	True	
Motor A Phase U Over Voltage Fault VL - High-Side	False	
Motor A Phase U Under Voltage Fault VL - High-Side	False	
Motor A Phase U Over Voltage Fault VDD - High-Side	False	
Motor A Phase U Under Voltage Fault VDD - High-Side	False	
Motor A Phase U Over Voltage Fault VH - Low-Side	False	
Motor A Phase U Under Voltage Fault VH - Low-Side	True	
Motor A Phase U Over Voltage Fault VL - Low-Side	False	
Motor A Phase U Under Voltage Fault VL - Low-Side	False	
Motor A Phase U Over Voltage Fault VDD - Low-Side	False	

Motor A Phase U Under Voltage Fault VDD - Low-Side	False	
Motor A Phase U Comm Error High Voltage Regulator Fault - Low-Side	True	
Motor A Phase U Comm Error Low Voltage Regulator Fault - Low-Side	True	
Motor A Phase V Over Voltage Fault VH - High-Side	False	
Motor A Phase V Under Voltage Fault VH - High-Side	True	
Motor A Phase V Over Voltage Fault VL - High-Side	False	
Motor A Phase V Under Voltage Fault VL - High-Side	False	
Motor A Phase V Over Voltage Fault VDD - High-SideSide	False	
Motor A Phase V Under Voltage Fault VDD - High-Side	False	
Motor A Phase V Over Voltage Fault VH - Low-Side	False	
Motor A Phase V Under Voltage Fault VH - Low-Side	True	
Motor A Phase V Over Voltage Fault VL - Low-Side	False	
Motor A Phase V Under Voltage Fault VL - Low-Side	False	
Motor A Phase V Over Voltage Fault VDD - Low-Side	False	
Motor A Phase V Under Voltage Fault VDD - Low-Side	False	
Motor A Phase V Comm Error High Voltage Regulator Fault - Low-Side	True	
Motor A Phase V Comm Error Low Voltage Regulator Fault - Low-Side	True	
Motor A Phase W Cross Conduction Fault - High-Side	False	
Motor A Phase W Over Voltage Fault VH - High-Side	False	
Motor A Phase W Under Voltage Fault VH - High-Side	True	
Motor A Phase W Over Voltage Fault VL - High-Side	False	
Motor A Phase W Under Voltage Fault VL - High-Side	False	
Motor A Phase W Over Voltage Fault VDD - High-Side	False	
Motor A Phase W Under Voltage Fault VDD - High-Side	False	
Motor A Phase W Comm Error High Voltage Regulator Fault - High-Side	True	
Motor A Phase W Over Voltage Fault VH - Low-Side	False	
Motor A Phase W Under Voltage Fault VH - Low-Side	True	
Motor A Phase W Over Voltage Fault VL - Low-Side	False	
Motor A Phase W Under Voltage Fault VL - Low-Side	False	
Motor A Phase W Over Voltage Fault VDD - Low-Side	False	
Motor A Phase W Under Voltage Fault VDD - Low-Side	False	
Motor A Phase W Comm Error High Voltage Regulator Fault - Low-Side	True	
Inverter A Status Feedback	Inverter Faulted	
GPS Date - Year	0	Year
GPS Date - Month	1	
GPS Date - Day	1	Days
UTC Time - Hours	0	Hours
UTC Time - Minutes	0	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	0	ms

HCP | POC0B-00 | Active | Drive Motor A Inverter Power Supply Circuit/Open-

NAME	VALUE	UNITS
DTC	0C 0B 00	

Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	Occurrence	
Original Odometer Value	56862.7	miles
Most Recent Odometer Value	56862.7	miles
Frequency Counter	1	
Ignition Cycle Counter	0	
Real time clock	77966768	sec
RAM stamps keyOn	90	sec
RAM Stamps	3847	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
PHEV Charging Status	No Charging	
Engine Speed	0	rpm
HV Battery SOC	60	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Barometric Pressure	13	PSI
Engine Coolant Temperature	79	°F
Actual Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor A	5.254	Ft-Lbs
Inverter A Input DC Current	0.0	AMP
Electric Motor A Speed	0.0	rpm
Motor A - Inverter Current - phase A	-4	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	0	AMP
Motor A Phase U Short Fault - High-Side	False	
Motor A Phase U Cross Conduction Fault - High-Side	False	
Motor A Phase U Over Current Fault - High-Side	False	
Motor A Phase U Thermal Warning Fault - High-Side	False	
Motor A Phase U Thermal Shutdown Fault - High-Side	False	
Motor A Phase U Comm Error High Voltage Regulator Fault - High-Side	True	
Motor A Phase U Comm Error Low Voltage Regulator Fault - High-Side	True	
Motor A Phase U SPI Error Fault - High-Side	False	
Motor A Phase U Hardware Error Fault - High-Side	True	
Motor A Phase U Short Fault - Low-Side	False	

Motor A Phase U Cross Conduction Fault - Low-Side	False	
Motor A Phase U Over Current Fault - Low-Side	False	
Motor A Phase U Thermal Warning Fault - Low-Side	False	
Motor A Phase U Thermal Shutdown Fault - Low-Side	False	
Motor A Phase U SPI Error Fault - Low-Side	False	
Motor A Phase U Hardware Error Fault - Low-Side	True	
Motor A Phase V Short Fault - High-Side	False	
Motor A Phase V Cross Conduction Fault - High-Side	False	
Motor A Phase V Over Current Fault - High-Side	False	
Motor A Phase V Thermal Warning Fault - High-Side	False	
Motor A Phase V Thermal Shutdown Fault - High-Side	False	
Motor A Phase V Comm Error High Voltage Regulator Fault - High-Side	True	
Motor A Phase V Comm Error Low Voltage Regulator Fault - High-Side	True	
Motor A Phase V SPI Error Fault - High-Side	False	
Motor A Phase V Hardware Error Fault - High-Side	True	
Motor A Phase V Short Fault - Low-Side	False	
Motor A Phase V Cross Conduction Fault - Low-Side	False	
Motor A Phase V Over Current Fault - Low-Side	False	
Motor A Phase V Thermal Warning Fault - Low-Side	False	
Motor A Phase V Thermal Shutdown Fault - Low-Side	False	
Motor A Phase V SPI Error Fault - Low-Side	False	
Motor A Phase V Hardware Error Fault - Low-Side	True	
Motor A Phase W Short Fault - High-Side	False	
Motor A Phase W Over Current Fault - High-Side	False	
Motor A Phase W Thermal Warning Fault - High-Side	False	
Motor A Phase W Thermal Shutdown Fault - High-Side	False	
Motor A Phase W Comm Error Low Voltage Regulator Fault - High-Side	True	
Motor A Phase W SPI Error Fault - High-Side	False	
Motor A Phase W Hardware Error Fault - High-Side	True	
Motor A Phase W Short Fault - Low-Side	False	
Motor A Phase W Cross Conduction Fault - Low-Side	False	
Motor A Phase W Over Current Fault - Low-Side	False	
Motor A Phase W Thermal Warning Fault - Low-Side	False	
Motor A Phase W Thermal Shutdown Fault - Low-Side	False	
Motor A Phase W Comm Error Low Voltage Regulator Fault - Low-Side	True	
Motor A Phase W SPI Error Fault - Low-Side	False	
Motor A Phase W Hardware Error Fault - Low-Side	True	
Motor A Resolver Supply Voltage Value	15.75	Volts
Battery Feed Voltage 2 Sense	11.880	Volts
Battery Feed Voltage 3 Sense	11.736	Volts
Internal EPS Voltage Sense A	0.072	Volts
Internal EPS Voltage Sense B	0.000	Volts
Hybrid System State	SNA	
PIM DC Link Voltage - A	2	Volts

PIM DC Link Voltage - B	4	Volts
Passive Pump Coolant Temp In Sensor	82	°F
Low Temp Active Pump Speed	0	rpm
High Temp Aux Pump - Actual Speed	0	rpm
Outside Air Temperature	89.6	°F
HV Contactor Status	Open	
Inverter B Status Feedback	Normal OFF	
Battery Feed Voltage 1 Sense	11.808	Volts
Actual Torque - Motor B	0.184	Ft-Lbs
Available Motor Torque - Motor B	232.301	Ft-Lbs
Available Regen Torque - Motor A	-5.254	Ft-Lbs
Available Regen Torque - Motor B	-232.301	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor B - Inverter Current - phase A	-4	AMP
Motor B - Inverter Current - phase B	0	AMP
Motor B - Inverter Current - phase C	-4	AMP
Motor B Resolver Angle	180	Degree
Motor B Temp Sensor	81	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	Off	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Battery Voltage from BPCM	180.00	Volts
Electric Motor B Speed	0.0	rpm
Inverter A IGBT Temperature for phase A	82	°F
Inverter A IGBT Temperature for phase B	82	°F
Inverter A IGBT Temperature for phase C	82	°F
Inverter B IGBT Temperature for phase A	82	°F
Inverter B IGBT Temperature for phase B	82	°F
Inverter B IGBT Temperature for phase C	82	°F
APM Status	Idle	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	0	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.184	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Commanded Inverter A State	Inverter Disabled	
Inverter Status Feedback	Inverter Faulted	
Motor A Phase U Over Voltage Fault VH - High-Side	False	
Motor A Phase U Under Voltage Fault VH - High-Side	True	
Motor A Phase U Over Voltage Fault VL - High-Side	False	

Motor A Phase U Under Voltage Fault VL - High-Side	False	
Motor A Phase U Over Voltage Fault VDD - High-Side	False	
Motor A Phase U Under Voltage Fault VDD - High-Side	False	
Motor A Phase U Over Voltage Fault VH - Low-Side	False	
Motor A Phase U Under Voltage Fault VH - Low-Side	True	
Motor A Phase U Over Voltage Fault VL - Low-Side	False	
Motor A Phase U Under Voltage Fault VL - Low-Side	False	
Motor A Phase U Over Voltage Fault VDD - Low-Side	False	
Motor A Phase U Under Voltage Fault VDD - Low-Side	False	
Motor A Phase U Comm Error High Voltage Regulator Fault - Low-Side	True	
Motor A Phase U Comm Error Low Voltage Regulator Fault - Low-Side	True	
Motor A Phase V Over Voltage Fault VH - High-Side	False	
Motor A Phase V Under Voltage Fault VH - High-Side	True	
Motor A Phase V Over Voltage Fault VL - High-Side	False	
Motor A Phase V Under Voltage Fault VL - High-Side	False	
Motor A Phase V Over Voltage Fault VDD - High-SideSide	False	
Motor A Phase V Under Voltage Fault VDD - High-Side	False	
Motor A Phase V Over Voltage Fault VH - Low-Side	False	
Motor A Phase V Under Voltage Fault VH - Low-Side	True	
Motor A Phase V Over Voltage Fault VL - Low-Side	False	
Motor A Phase V Under Voltage Fault VL - Low-Side	False	
Motor A Phase V Over Voltage Fault VDD - Low-Side	False	
Motor A Phase V Under Voltage Fault VDD - Low-Side	False	
Motor A Phase V Comm Error High Voltage Regulator Fault - Low-Side	True	
Motor A Phase V Comm Error Low Voltage Regulator Fault - Low-Side	True	
Motor A Phase W Cross Conduction Fault - High-Side	False	
Motor A Phase W Over Voltage Fault VH - High-Side	False	
Motor A Phase W Under Voltage Fault VH - High-Side	True	
Motor A Phase W Over Voltage Fault VL - High-Side	False	
Motor A Phase W Under Voltage Fault VL - High-Side	False	
Motor A Phase W Over Voltage Fault VDD - High-Side	False	
Motor A Phase W Under Voltage Fault VDD - High-Side	False	
Motor A Phase W Comm Error High Voltage Regulator Fault - High-Side	True	
Motor A Phase W Over Voltage Fault VH - Low-Side	False	
Motor A Phase W Under Voltage Fault VH - Low-Side	True	
Motor A Phase W Over Voltage Fault VL - Low-Side	False	
Motor A Phase W Under Voltage Fault VL - Low-Side	False	
Motor A Phase W Over Voltage Fault VDD - Low-Side	False	
Motor A Phase W Under Voltage Fault VDD - Low-Side	False	
Motor A Phase W Comm Error High Voltage Regulator Fault - Low-Side	True	
Inverter A Status Feedback	Inverter Faulted	
GPS Date - Year	0	Year
GPS Date - Month	1	
GPS Date - Day	1	Days

UTC Time - Hours	0	Hours
UTC Time - Minutes	0	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	0	ms

HCP | P16F9-00 | Stored | HCP Internal - Shutdown Performance-

NAME	VALUE	UNITS
DTC	16 F9 00	
Test Failed	False	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
DTC Extended Data Record Number	05	
Occurrence flag	Occurrence	
Original Odometer Value	56862.7	miles
Most Recent Odometer Value	56862.7	miles
Frequency Counter	1	
Ignition Cycle Counter	0	
Real time clock	77966768	sec
RAM stamps keyOn	90	sec
RAM Stamps	3847	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
PHEV Charging Status	No Charging	
Engine Speed	0	rpm
HV Battery SOC	60	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Barometric Pressure	13	PSI
Engine Coolant Temperature	79	°F
Main Processor Reset Source - Core 0	Power Up	
Main Processor Reset Source - Core 1	Power Up	
Static NVM CRC Status	Passed	
Cumulative NVM CRC Status	Passed	
Adaptable NVM CRC Status	Passed	
Preserved NVM CRC Status	Passed	
Expendable NVM CRC Status	Passed	
MCPUninit EEPROM CRC Status	Passed	

MCPInit EEPROM CRC Status	Passed	
Non Volatile RAM CRC Status	Passed	
BSW EEPROM CRC Status	Passed	
HCP - MCPA SPI CRC Error Count	00	
HCP - MCPA SPI ARC Error Count	00	
MCPB - MCPA SPI CRC Error Count	00	
MCPB - MCPA SPI ARC Error Count	00	
MemShare CRC Error Count- Core 0	88	
MemShare ARC Error Count- Core 0	00	
MemShare CRC Error Count- Core 1	FF	
MemShare ARC Error Count- Core 1	04	
Main Stack Fault	False	
Main Analog-to-Digital Converter Fault	False	
External Watchdog Fault	False	
MainTPU_Flt	False	
Main Clock Fault	False	
MAIN ALU Fault	False	
MAIN Detected SPI Fault	False	
Main Detected Seed Received In Wrong Order	False	
Battery Feed Voltage 2 Sense	11.880	Volts
Internal EPS Voltage Sense A	0.072	Volts
Internal EPS Voltage Sense B	0.000	Volts
Battery Feed Voltage 1 Sense	11.808	Volts
Battery Feed Voltage 3 Sense	11.736	Volts
Hybrid System State	SNA	
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.092	Ft-Lbs
Available Motor Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor B	232.301	Ft-Lbs
Available Regen Torque - Motor A	0.000	Ft-Lbs
Available Regen Torque - Motor B	-232.301	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor A - Inverter Current - phase A	0	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	0	AMP
Motor B - Inverter Current - phase A	-4	AMP
Motor B - Inverter Current - phase B	-4	AMP
Motor B - Inverter Current - phase C	0	AMP
Motor A Resolver Angle	196	Degree
Motor B Resolver Angle	180	Degree
Motor A Temp Sensor	81	°F
Motor B Temp Sensor	81	°F
Outside Air Temperature	89.6	°F

HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	Off	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Open	
HV Battery Voltage from BPCM	180.00	Volts
Electric Motor A Speed	0.0	rpm
Electric Motor B Speed	0.5	rpm
PIM DC Link Voltage - A	2	Volts
PIM DC Link Voltage - B	4	Volts
Inverter A IGBT Temperature for phase A	32	°F
Inverter A IGBT Temperature for phase B	32	°F
Inverter A IGBT Temperature for phase C	32	°F
Inverter B IGBT Temperature for phase A	32	°F
Inverter B IGBT Temperature for phase B	32	°F
Inverter B IGBT Temperature for phase C	32	°F
APM Status	Idle	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	0	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.092	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
GPS Date - Year	0	Year
GPS Date - Month	1	
GPS Date - Day	1	Days
UTC Time - Hours	0	Hours
UTC Time - Minutes	0	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	0	ms

HCP | P1AEC-00 | Pending | MCPA HV Battery Voltage Sensor Circuit Performance-

NAME	VALUE	UNITS
DTC	1A EC 00	
Test Failed	False	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	False	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag		

Original Odometer Value		miles
Most Recent Odometer Value		miles
Frequency Counter		
Ignition Cycle Counter		
Real time clock		sec
RAM stamps keyOn		sec
RAM Stamps		Min
Accelerator Pedal Position		%
Brake Switch Status		
PHEV Charging Status		
Engine Speed		rpm
HV Battery SOC		%
Ignition State		
PRND Position Display		
Propulsion System Active		
Vehicle Speed		MPH
Barometric Pressure		PSI
Engine Coolant Temperature		°F
Actual Torque - Motor A		Ft-Lbs
Available Motor Torque - Motor A		Ft-Lbs
Inverter A Input DC Current		AMP
Electric Motor A Speed		rpm
Motor A - Inverter Current - phase A		AMP
Motor A - Inverter Current - phase B		AMP
Motor A - Inverter Current - phase C		AMP
Motor A Phase U Short Fault - High-Side		
Motor A Phase U Cross Conduction Fault - High-Side		
Motor A Phase U Over Current Fault - High-Side		
Motor A Phase U Thermal Warning Fault - High-Side		
Motor A Phase U Thermal Shutdown Fault - High-Side		
Motor A Phase U Comm Error High Voltage Regulator Fault - High-Side		
Motor A Phase U Comm Error Low Voltage Regulator Fault - High-Side		
Motor A Phase U SPI Error Fault - High-Side		
Motor A Phase U Hardware Error Fault - High-Side		
Motor A Phase U Short Fault - Low-Side		
Motor A Phase U Cross Conduction Fault - Low-Side		
Motor A Phase U Over Current Fault - Low-Side		
Motor A Phase U Thermal Warning Fault - Low-Side		
Motor A Phase U Thermal Shutdown Fault - Low-Side		
Motor A Phase U SPI Error Fault - Low-Side		
Motor A Phase U Hardware Error Fault - Low-Side		
Motor A Phase V Short Fault - High-Side		
Motor A Phase V Cross Conduction Fault - High-Side		
Motor A Phase V Over Current Fault - High-Side		

Motor A Phase V Thermal Warning Fault - High-Side		
Motor A Phase V Thermal Shutdown Fault - High-Side		
Motor A Phase V Comm Error High Voltage Regulator Fault - High-Side		
Motor A Phase V Comm Error Low Voltage Regulator Fault - High-Side		
Motor A Phase V SPI Error Fault - High-Side		
Motor A Phase V Hardware Error Fault - High-Side		
Motor A Phase V Short Fault - Low-Side		
Motor A Phase V Cross Conduction Fault - Low-Side		
Motor A Phase V Over Current Fault - Low-Side		
Motor A Phase V Thermal Warning Fault - Low-Side		
Motor A Phase V Thermal Shutdown Fault - Low-Side		
Motor A Phase V SPI Error Fault - Low-Side		
Motor A Phase V Hardware Error Fault - Low-Side		
Motor A Phase W Short Fault - High-Side		
Motor A Phase W Over Current Fault - High-Side		
Motor A Phase W Thermal Warning Fault - High-Side		
Motor A Phase W Thermal Shutdown Fault - High-Side		
Motor A Phase W Comm Error Low Voltage Regulator Fault - High-Side		
Motor A Phase W SPI Error Fault - High-Side		
Motor A Phase W Hardware Error Fault - High-Side		
Motor A Phase W Short Fault - Low-Side		
Motor A Phase W Cross Conduction Fault - Low-Side		
Motor A Phase W Over Current Fault - Low-Side		
Motor A Phase W Thermal Warning Fault - Low-Side		
Motor A Phase W Thermal Shutdown Fault - Low-Side		
Motor A Phase W Comm Error Low Voltage Regulator Fault - Low-Side		
Motor A Phase W SPI Error Fault - Low-Side		
Motor A Phase W Hardware Error Fault - Low-Side		
Motor A Resolver Supply Voltage Value		Volts
Battery Feed Voltage 2 Sense		Volts
Battery Feed Voltage 3 Sense		Volts
Internal EPS Voltage Sense A		Volts
Internal EPS Voltage Sense B		Volts
Hybrid System State		
PIM DC Link Voltage - A		Volts
PIM DC Link Voltage - B		Volts
Passive Pump Coolant Temp In Sensor		°F
Low Temp Active Pump Speed		rpm
High Temp Aux Pump - Actual Speed		rpm
Outside Air Temperature		°F
HV Contactor Status		
Inverter B Status Feedback		
Battery Feed Voltage 1 Sense		Volts
Actual Torque - Motor B		Ft-Lbs

Available Motor Torque - Motor B		Ft-Lbs
Available Regen Torque - Motor A		Ft-Lbs
Available Regen Torque - Motor B		Ft-Lbs
Commanded Torque - Motor A		Ft-Lbs
Commanded Torque - Motor B		Ft-Lbs
Motor B - Inverter Current - phase A		AMP
Motor B - Inverter Current - phase B		AMP
Motor B - Inverter Current - phase C		AMP
Motor B Resolver Angle		Degree
Motor B Temp Sensor		°F
HCP ePT Wake-Up Output		
CBC Wake-Up Input		
EPT LOC Diag Enable		
HV Battery Voltage from BPCM		Volts
Electric Motor B Speed		rpm
Inverter A IGBT Temperature for phase A		°F
Inverter A IGBT Temperature for phase B		°F
Inverter A IGBT Temperature for phase C		°F
Inverter B IGBT Temperature for phase A		°F
Inverter B IGBT Temperature for phase B		°F
Inverter B IGBT Temperature for phase C		°F
APM Status		
Impact Event		
HCP System Shutdown Command		
Distance Travelled with Light ON		miles
Motor A Torque		Ft-Lbs
Motor B Torque		Ft-Lbs
OBCM Operating Mode		
J1772 Prox Detected State		
HV Battery Sleep Time		Days
Commanded Inverter A State		
Inverter Status Feedback		
Motor A Phase U Over Voltage Fault VH - High-Side		
Motor A Phase U Under Voltage Fault VH - High-Side		
Motor A Phase U Over Voltage Fault VL - High-Side		
Motor A Phase U Under Voltage Fault VL - High-Side		
Motor A Phase U Over Voltage Fault VDD - High-Side		
Motor A Phase U Under Voltage Fault VDD - High-Side		
Motor A Phase U Over Voltage Fault VH - Low-Side		
Motor A Phase U Under Voltage Fault VH - Low-Side		
Motor A Phase U Over Voltage Fault VL - Low-Side		
Motor A Phase U Under Voltage Fault VL - Low-Side		
Motor A Phase U Over Voltage Fault VDD - Low-Side		
Motor A Phase U Under Voltage Fault VDD - Low-Side		

Motor A Phase U Comm Error High Voltage Regulator Fault - Low-Side		
Motor A Phase U Comm Error Low Voltage Regulator Fault - Low-Side		
Motor A Phase V Over Voltage Fault VH - High-Side		
Motor A Phase V Under Voltage Fault VH - High-Side		
Motor A Phase V Over Voltage Fault VL - High-Side		
Motor A Phase V Under Voltage Fault VL - High-Side		
Motor A Phase V Over Voltage Fault VDD - High-SideSide		
Motor A Phase V Under Voltage Fault VDD - High-Side		
Motor A Phase V Over Voltage Fault VH - Low-Side		
Motor A Phase V Under Voltage Fault VH - Low-Side		
Motor A Phase V Over Voltage Fault VL - Low-Side		
Motor A Phase V Under Voltage Fault VL - Low-Side		
Motor A Phase V Over Voltage Fault VDD - Low-Side		
Motor A Phase V Under Voltage Fault VDD - Low-Side		
Motor A Phase V Comm Error High Voltage Regulator Fault - Low-Side		
Motor A Phase V Comm Error Low Voltage Regulator Fault - Low-Side		
Motor A Phase W Cross Conduction Fault - High-Side		
Motor A Phase W Over Voltage Fault VH - High-Side		
Motor A Phase W Under Voltage Fault VH - High-Side		
Motor A Phase W Over Voltage Fault VL - High-Side		
Motor A Phase W Under Voltage Fault VL - High-Side		
Motor A Phase W Over Voltage Fault VDD - High-Side		
Motor A Phase W Under Voltage Fault VDD - High-Side		
Motor A Phase W Comm Error High Voltage Regulator Fault - High-Side		
Motor A Phase W Over Voltage Fault VH - Low-Side		
Motor A Phase W Under Voltage Fault VH - Low-Side		
Motor A Phase W Over Voltage Fault VL - Low-Side		
Motor A Phase W Under Voltage Fault VL - Low-Side		
Motor A Phase W Over Voltage Fault VDD - Low-Side		
Motor A Phase W Under Voltage Fault VDD - Low-Side		
Motor A Phase W Comm Error High Voltage Regulator Fault - Low-Side		
Inverter A Status Feedback		
GPS Date - Year		Year
GPS Date - Month		
GPS Date - Day		Days
UTC Time - Hours		Hours
UTC Time - Minutes		
UTC Time - Seconds		seconds
ECU Time - Milliseconds		ms

HCP | P1AED-00 | Pending | MCPB High Voltage Battery Voltage Sensor Circuit Performance-

NAME	VALUE	UNITS
DTC	1A ED 00	
Test Failed	False	

Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	False	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag		
Original Odometer Value		miles
Most Recent Odometer Value		miles
Frequency Counter		
Ignition Cycle Counter		
Real time clock		sec
RAM stamps keyOn		sec
RAM Stamps		Min
Accelerator Pedal Position		%
Brake Switch Status		
PHEV Charging Status		
Engine Speed		rpm
HV Battery SOC		%
Ignition State		
PRND Position Display		
Propulsion System Active		
Vehicle Speed		MPH
Barometric Pressure		PSI
Engine Coolant Temperature		°F
Actual Torque - Motor B		Ft-Lbs
Available Motor Torque - Motor B		Ft-Lbs
Inverter B Input DC Current		AMP
Electric Motor B Speed		rpm
Commanded Inverter B State		
Motor B - Inverter Current - phase A		AMP
Motor B - Inverter Current - phase B		AMP
Motor B - Inverter Current - phase C		AMP
Inverter B Status Feedback		
Motor B Phase U Short Fault - High-Side		
Motor B Phase U Cross Conduction Fault - High-Side		
Motor B Phase U Thermal Warning Fault - High-Side		
Motor B Phase U Thermal Shutdown Fault - High-Side		
Motor B Phase U Comm Error High Voltage Regulator Fault - High-Side		
Motor B Phase U SPI Error Fault - High-Side		
Motor B Phase U Hardware Error Fault - High-Side		
Motor B Phase U Short Fault - Low-Side		
Motor B Phase U Cross Conduction Fault - Low-Side		

Motor B Phase U Over Current Fault - Low-Side		
Motor B Phase U Thermal Warning Fault - Low-Side		
Motor B Phase U Thermal Shutdown Fault - Low-Side		
Motor B Phase U Comm Error High Voltage Regulator Fault - Low-Side		
Motor B Phase U Comm Error Low Voltage Regulator Fault - Low-Side		
Motor B Phase U SPI Error Fault - Low-Side		
Motor B Phase U Hardware Error Fault - Low-Side		
Motor B Phase V Short Fault - High-Side		
Motor B Phase V Cross Conduction Fault - High-Side		
Motor B Phase V Over Current Fault - High-Side		
Motor B Phase V Thermal Warning Fault - High-Side		
Motor B Phase V Thermal Shutdown Fault - High-Side		
Motor B Phase V Comm Error High Voltage Regulator Fault - High-Side		
Motor B Phase V Comm Error Low Voltage Regulator Fault - High-Side		
Motor B Phase V SPI Error Fault - High-Side		
Motor B Phase V Hardware Error Fault - High-Side		
Motor B Phase V Short Fault - Low-Side		
Motor B Phase V Cross Conduction Fault - Low-Side		
Motor B Phase V Over Current Fault - Low-Side		
Motor B Phase V Thermal Warning Fault - Low-Side		
Motor B Phase V Thermal Shutdown Fault - Low-Side		
Motor B Phase V Comm Error High Voltage Regulator Fault - Low-Side		
Motor B Phase V Comm Error Low Voltage Regulator Fault - Low-Side		
Motor B Phase V SPI Error Fault - Low-Side		
Motor B Phase V Hardware Error Fault - Low-Side		
Motor B Phase W Short Fault - High-Side		
Motor B Phase W Cross Conduction Fault - High-Side		
Motor B Phase W Over Current Fault - High-Side		
Motor B Phase W Thermal Warning Fault - High-Side		
Motor B Phase W Comm Error High Voltage Regulator Fault - High-Side		
Motor B Phase W Comm Error Low Voltage Regulator Fault - High-Side		
Motor B Phase W SPI Error Fault - High-Side		
Motor B Phase W Hardware Error Fault - High-Side		
Motor B Phase W Short Fault - Low-Side		
Motor B Phase W Cross Conduction Fault - Low-Side		
Motor B Phase W Over Current Fault - Low-Side		
Motor B Phase W Thermal Warning Fault - Low-Side		
Motor B Phase W Thermal Shutdown Fault - Low-Side		
Motor B Phase W Comm Error High Voltage Regulator Fault - Low-Side		
Motor B Phase W Comm Error Low Voltage Regulator Fault - Low-Side		
Motor B Phase W SPI Error Fault - Low-Side		
Motor B Phase W Hardware Error Fault - Low-Side		
Motor B Resolver Supply Voltage Value		Volts
Battery Feed Voltage 2 Sense		Volts

Internal EPS Voltage Sense A		Volts
Internal EPS Voltage Sense B		Volts
Battery Feed Voltage 1 Sense		Volts
Battery Feed Voltage 3 Sense		Volts
Hybrid System State		
Actual Torque - Motor A		Ft-Lbs
Available Motor Torque - Motor A		Ft-Lbs
Available Regen Torque - Motor A		Ft-Lbs
Available Regen Torque - Motor B		Ft-Lbs
Commanded Torque - Motor A		Ft-Lbs
Commanded Torque - Motor B		Ft-Lbs
Motor A - Inverter Current - phase A		AMP
Motor A - Inverter Current - phase B		AMP
Motor A - Inverter Current - phase C		AMP
Motor A Resolver Angle		Degree
Motor A Temp Sensor		°F
Outside Air Temperature		°F
HCP ePT Wake-Up Output		
CBC Wake-Up Input		
EPT LOC Diag Enable		
HV Contactor Status		
HV Battery Voltage from BPCM		Volts
Electric Motor A Speed		rpm
PIM DC Link Voltage - A		Volts
PIM DC Link Voltage - B		Volts
Inverter A IGBT Temperature for phase A		°F
Inverter A IGBT Temperature for phase B		°F
Inverter A IGBT Temperature for phase C		°F
Inverter B IGBT Temperature for phase A		°F
Inverter B IGBT Temperature for phase B		°F
Inverter B IGBT Temperature for phase C		°F
APM Status		
Impact Event		
HCP System Shutdown Command		
Distance Travelled with Light ON		miles
Motor A Torque		Ft-Lbs
Motor B Torque		Ft-Lbs
OBCM Operating Mode		
J1772 Prox Detected State		
HV Battery Sleep Time		Days
Motor B Phase U Over Current Fault - High-Side		
Motor B Phase U Over Voltage Fault VH - High-Side		
Motor B Phase U Under Voltage Fault VH - High-Side		
Motor B Phase U Over Voltage Fault VL - High-Side		

Motor B Phase U Under Voltage Fault VL - High-Side		
Motor B Phase U Over Voltage Fault VDD - High-Side		
Motor B Phase U Under Voltage Fault VDD - High-Side		
Motor B Phase U Comm Error Low Voltage Regulator Fault - High-Side		
Motor B Phase U Over Voltage Fault VH - Low-Side		
Motor B Phase U Under Voltage Fault VH - Low-Side		
Motor B Phase U Over Voltage Fault VL - Low-Side		
Motor B Phase U Under Voltage Fault VL - Low-Side		
Motor B Phase U Over Voltage Fault VDD - Low-Side		
Motor B Phase U Under Voltage Fault VDD - Low-Side		
Motor B Phase V Over Voltage Fault VH - High-Side		
Motor B Phase V Under Voltage Fault VH - High-Side		
Motor B Phase V Over Voltage Fault VL - High-Side		
Motor B Phase V Under Voltage Fault VL - High-Side		
Motor B Phase V Over Voltage Fault VDD - High-Side		
Motor B Phase V Under Voltage Fault VDD - High-Side		
Motor B Phase V Over Voltage Fault VH - Low-Side		
Motor B Phase V Under Voltage Fault VH - Low-Side		
Motor B Phase V Over Voltage Fault VL - Low-Side		
Motor B Phase V Under Voltage Fault VL - Low-Side		
Motor B Phase V Over Voltage Fault VDD - Low-Side		
Motor B Phase V Under Voltage Fault VDD - Low-Side		
Motor B Phase W Over Voltage Fault VH - High-Side		
Motor B Phase W Under Voltage Fault VH - High-Side		
Motor B Phase W Over Voltage Fault VL - High-Side		
Motor B Phase W Under Voltage Fault VL - High-Side		
Motor B Phase W Over Voltage Fault VDD - High-Side		
Motor B Phase W Under Voltage Fault VDD - High-Side		
Motor B Phase W Thermal Shutdown Fault - High-Side		
Motor B Phase W Over Voltage Fault VH - Low-Side		
Motor B Phase W Under Voltage Fault VH - Low-Side		
Motor B Phase W Over Voltage Fault VL - Low-Side		
Motor B Phase W Under Voltage Fault VL - Low-Side		
Motor B Phase W Over Voltage Fault VDD - Low-Side		
Motor B Phase W Under Voltage Fault VDD - Low-Side		
GPS Date - Year		Year
GPS Date - Month		
GPS Date - Day		Days
UTC Time - Hours		Hours
UTC Time - Minutes		
UTC Time - Seconds		seconds
ECU Time - Milliseconds		ms

SNAPSHOT DATA SUMMARY

No Snapshot Data available for B10EB-00

No Snapshot Data available for P0A95-00

No Snapshot Data available for P0A78-00

No Snapshot Data available for P0C0B-00

No Snapshot Data available for P16F9-00

No Snapshot Data available for P1AEC-00

No Snapshot Data available for P1AED-00