


This file represents a consolidation of multiple files sent by the manufacturer. Please use the bookmarks to navigate to each file. (Each bookmark label is the name of the original file.)



CONFIGURATION REPORT

Vehicle 2021 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN 2C4RC1S72MR [REDACTED]

Odometer 36896.1 miles
Publication Date Aug 30, 2022, 8:24:07 AM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
PCM	Powertrain Control Module	CAN-C	68499122AE	2C4RC1S72M	2C4RC1S72MR	68499122AE
PLGM	Power Liftgate	CAN-I	68466171AI	2C4RC1S72M	—	68466171AI
ICS	Integrated Center Stack	CAN-I	7AS341X8AA	2C4RC1S72M	2C4RC1S72MR	7AS341X8AA
RFH	Radio Frequency Hub	CAN-C	68500152AA	2C4RC1S72M	2C4RC1S72MR	68500152AA
ESM	Electronic Shifter	CAN-C	68240089AM	2C4RC1S72M	2C4RC1S72MR	68240089AM
ORC	Occupant Restraint	CAN-C	68480710AC	2C4RC1S72M	2C4RC1S72MR	68480710AC
EPS	Electric Power Steering	CAN-C	68460392AA	2C4RC1S72M	2C4RC1S72MR	68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68493454AE	2C4RC1S72M	2C4RC1S72MR	68493454AE
DDM	Driver Door Module	CAN-I	68496461AB	2C4RC1S72M	2C4RC1S72MR	68496461AB
PDM	Passenger Door Module	CAN-I	68496460AB	2C4RC1S72M	2C4RC1S72MR	68496460AB
DMRL	Door Module Rear Left	CAN-I	68508894AB	2C4RC1S72M	2C4RC1S72MR	68508894AB
DMRR	Door Module Rear Right	CAN-I	68508894AB	2C4RC1S72M	2C4RC1S72MR	68508894AB
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD	2C4RC1S72M	2C4RC1S72MR	68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD	2C4RC1S72M	2C4RC1S72MR	68369596AD
MSM	Memory Seat Module	CAN-I	68321862AC	2C4RC1S72M	2C4RC1S72MR	68321862AC
CSWM	Comfort Seat Wheel Module	CAN-I	68517013AB	2C4RC1S72M	2C4RC1S72MR	68517013AB
AMP	Amplifier	CAN-I	68448067AA	2C4RC1S72M	2C4RC1S72MR	68448067AA
IPC	Instrument Panel Cluster	CAN-C	68434960AE	2C4RC1S72M	2C4RC1S72MR	68434960AE
PTS	Parktronics	CAN-C	68485862AA	2C4RC1S72M	2C4RC1S72MR	68485862AA
SCCM	Steering Column Control Module	CAN-C	68360889AD	2C4RC1S72M	2C4RC1S72MR	68360889AD
BCM	Body Controller	CAN-C	68491085AG	2C4RC1S72M	2C4RC1S72MR	68491085AG

ACC	Adaptive Cruise Control	CAN-C	68540436AA	2C4RC1S72MR522610		68540436AA
RADIO	Radio	CAN-I	68465292AC	2C4RC1S72M		68465292AC
OCM	Occupant Classification	CAN-C	68403127AA	2C4RC1S72M		68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB	2C4RC1S72M		68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AB	2C4RC1S72M		04672786AB
RBSS	Right Blind Spot Sensor	CAN-I	04672786AB	2C4RC1S72M		04672786AB
FFCM	Forward Facing Camera Module	CAN-C	68493395AA	2C4RC1S72M		68493395AA
EDM	External Disc Module	CAN-I	68499745AA	2C4RC1S72M		68499745AA
APM	Accessory Power Module	CAN-C	05185046AB	2C4RC1S72M		05185046AB
BPCM	Battery Pack Control Module	CAN-C	05193183AE	2C4RC1S72M		05193183AE
HCP	Hybrid Control Processor	CAN-C	05185116AH	2C4RC1S72M		05185116AH
OBCM	On Board Charging Module	CAN-C	05185047AE	2C4RC1S72M		05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC	2C4RC1S72M		68321862AC
DSM	Display Screen Module	CAN-I	68437339AD	2C4RC1S72M		68437339AD
VRM	Video Routing Module	CAN-I	68493702AA	2C4RC1S72M		68493702AA
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA	2C4RC1S72M		6WL30DX9AA
CVPM	Central vision processing module	CAN-I	56029920AB	2C4RC1S72M		56029920AB
EAC	Electric A/C Compressor	CAN-C	68237995AG	2C4RC1S72M		68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05185117AH	2C4RC1S72M		05185117AH
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB	2C4RC1S72M		68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68471122AD	2C4RC1S72M		68471122AD
SGW	Security Gateway Module	CAN-C	68488429AB		2C4RC1S72M	68488429AB
TBM2	Telematic Box Module 2	CAN-C	68546266AB	2C4RC1S72M		68546266AB

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	SERIAL NUMBER	CVNS
PCM	USA	1B 47	75 01 01	4422		
PLGM	USA	0	5084	000200000031		
ICS	USA	0F 0C 00	13 31 01	4700		

RFH	USA / USA	10 17 00	13 26 00	4A00
ESM	USA / USA	0F 24 00	12 28 FF	4402
ORC	USA / USA	12 1A 00	13 2E 00	4301
EPS	USA / USA	12 2A 00	12 1E 01	4502
HVAC	USA	0E 09 00	14 2F 01	4401
DDM	USA	11 07 00	14 07 00	4202
PDM	USA	11 07 00	14 07 00	4202
DMRL	USA / USA	10 0B 00	14 08 00	4201
DMRR	USA / USA	10 0B 00	14 08 00	4201
PSDML	USA / USA	10 17 00	14 10 12	4001
PSDMR	USA / USA	10 17 00	14 10 12	4001
MSM	USA	0F 2B 00	10 27 03	4101
CSWM	USA	11 2A 00	14 25 00	4302
AMP	USA	0F 06 01	12 2E 01	4021
IPC	USA / USA	12 06 00	14 2B 00	4705
PTS	USA	0E 32 00	14 07 00	4311
SCCM	USA	13 28 00	13 29 00	4301
BCM	USA	0D 11 00	14 26 90	4420
ACC	USA / USA	14 12 01	14 26 01	4400
RADIO		65	5175	000200000008
OCM	USA / USA	11 1F 01	0E 2F 02	4030
HVACR	USA	0E 09 00	10 03 02	4301
LBSS	USA / USA	11 30 02	12 0D 00	4202
RBSS	USA / USA	11 30 02	12 0D 00	4202
FFCM	USA / USA	11 06 00	13 1E 00	4102
EDM	USA	12 0A 00	11 08 00	4000
APM	USA / USA	11 32 00	11 32 00	4001
BPCM		0E 03 00	14 2C 00	4005
HCP	USA	11 1F 04	0F 2D 00	4006
OBCM	USA	0F 0D 00	12 02 00	4002
MSMP	USA	0F 2B 00	10 27 03	4001
DSM	USA / USA	14 0C 00	14 28 00	4300
VRM	USA / USA	0F 1C 00	14 1E 14	4001
RCCC	USA	0F 1D 00	13 04 00	4000
CVPM	USA / USA	11 27 01	14 0C 01	4004
EAC	USA	0E 34 00	12 0F 00	4102
AHCP	USA	11 1F 04	0F 2D 00	4000
EBBM	USA	0E 19 02	14 0D 18	4000
ABSO	USA	0E 15 02	14 1B 26	4201
SGW		5	969	4103
TBM2	USA	13 0E 02	14 2A 5C	4104

CONFIGURATION

PCM CONFIGURATION

NAME	VALUE	UNITS
AC Equipped	False	
AC Equipped Over Bus	False	
Power Steering Switch Equipped	False	
4 Button Integrated Cruise Control	False	
EMAT (Getrag DCT transmission) Equipped	False	
Vehicle Speed Sensor #1 Calculated from CAN	False	
Police Package Equipped	False	
Unleaded Gasoline Fuel	True	
Unleaded diesel fuel	False	
6.4 Liter V8 Engine	False	
4 Speed Automatic Transmission Equipped	False	
Electronic Automatic Transmission (EATX) Equipped	False	
Vehicle Speed Sensor #1 Calculated by ECU	False	
4.7 Liter V8 Engine	False	
5.7 Liter V8 Engine	False	
6.1 Liter V8 Engine	False	
Sensorless FFV Enabled	False	
Electronic Throttle Control Equipped	True	
3.6 Liter V6 Engine	True	
4.0 Liter I6 Engine	False	
3.8 Liter V6 Engine	False	
3.7 Liter V6 Engine	False	
3.5 Liter V6 Engine	False	
3.3 Liter V6 Engine	False	
3.2 Liter V6 Engine	False	
2.7 Liter V6 Engine	False	
MTV Solenoid Equipped	False	
MDS Equipped	False	
Turbocharger Equipped	False	
SRV Equipped	False	
Secondary Air Equipped	False	
Shift Indicator Lamp Equipped	False	
Barometric Sensor Equipped	False	
TIP Equipped	False	
Battery Temp Sensor Equipped	False	
Knock Sensor 1 Equipped	True	
Knock Sensor 2 Equipped	True	
WI4 Variable Valve Timing Equipped	True	
Clutch Interlock Switch Equipped	False	
ESIM Equipped	False	
Linear Purge Equipped	False	
Linear EGR Equipped	False	

Continuous Variable Transmission Equipped	False	
Direct Injection Equipped	False	
Secondary Fuel Pump Equipped	False	
Electronic Coolant Pump Equipped	False	
O2 Sensor Bank 1 Sensor 1 Equipped	True	
O2 Sensor Bank 1 Sensor 2 Equipped	True	
O2 Sensor Bank 1 Sensor 3 Equipped	False	
O2 Sensor Bank 2 Sensor 1 Equipped	True	
O2 Sensor Bank 2 Sensor 2 Equipped	True	
Variable Displacement AC Equipped	False	
Fixed displacement AC Equipped	True	
WI4 Intake Flow Control Valve Equipped	False	
Electric Coolant Valve Equipped	False	
Engine Oil Heater Cooler Equipped	True	
Transmission Oil Heater Equipped	False	
Electric Water Pump Equipped	False	
Rear Heater Equipped	False	
Starter Relay 2 Equipped	False	
Inrush Current Reduction Relay Equipped	False	
Active Grille Shutter Equipped	True	
Electronic Vacuum Pump Equipped	False	
Wide Range O2 Sensor 1/1 Equipped	False	
Wide Range O2 Sensor 2/1 Equipped	False	
MultiAir Equipped	False	
Engine Stop Start Equipped	False	
Viscosity Sensor Equipped	False	
Duty Cycle Purge Valve Equipped	True	
Electric Thermostat Heater Equipped	False	
Exhaust Cam 1 Equipped	True	
Intake Cam 1 Equipped	True	
1.8 Liter WI4 engine	False	
2.0 Liter WI4 engine	False	
2.4 Liter WI4 engine	False	
3.0 Liter V6 Engine	False	
Tumble Generator Valve Equipped	False	
Hybrid Electric Vehicle Equipped	True	
Auxiliary Heater Electric Water Pump Equipped	False	
Dual Speed Fuel Pump Equipped	False	
Exhaust Cam 2 Equipped	True	
Intake Cam 2 Equipped	True	
1 Speed Fan Mechanical Relay System Equipped	False	
2 Speed Fan Mechanical Relay System Equipped	False	
2 Speed Fan PWM Relay System Equipped	False	
Linear PWM Fan Relay System Equipped	False	

PWM Fan Motor System Equipped	True	
3 Speed Fan Mechanical Relay System Equipped	False	
Fan Wake Up Relay System Equipped	False	
2 Speed Fan 3 Driver 3 Relay System Equipped	False	
40TE / 41TE / 41TEA	False	
42RLE	False	
45RFE / 545RFE / 65RFE	False	
62TE	False	
66RFE / 68RFE	False	
VLP Is Learnable Indicator	False	
VLP Equipped Indicator	False	
VFS Actuators Available Indicator	False	
ERS Equipped Indicator	False	
Engine Software In Package	True	
Transmission Software Included	False	
ICC Cruise Equipped	False	
ETC Cruise equipped	False	
Adaptive Cruise Control Equipped	True	
A/C Equipped	True	
Adaptive Cruise Control Hardware Equipped	False	
DUAL_ALTERNATOR_GEN1_LEARNEDCOPY	False	
TOOLCONFIG_OIL_PRESS_ABS_EQUIPPED	True	
GPEC2 Equipped	False	
GPEC2A Equipped	True	
GPEC3 Equipped	False	
Cummins Equipped	False	
GPEC4 Equipped	False	
VMM Equipped	False	
Powernet Equipped	True	
CUSW (11-Bit) Equipped	False	
Fiat 940 Compact Equipped	False	
Next Gen Bus Equipped	False	
Constant Heater Temperature Control Valve Equipped	False	
High Side Port Tumble Valve Equipped	Undefined	
CMCV H-Bridge Equipped	Undefined	
Turbine Volute Valve Actuator Equipped	Undefined	
Wastegate H-Bridge Equipped	Undefined	
Active Exhaust Valve Equipped	False	
Active Exhaust Pressure Sensor Equipped	False	
Engine Idle Shutoff Equipped	False	
Aisin 6-Speed RWD Transmission Equipped	False	
Cooled EGR Equipped	False	
Supercharger Equipped	False	
Low Temperature Radiator Coolant Pump Equipped	False	

Mechanical Coolant Pump Heater Equipped	False	
Auxiliary Coolant Pump Heater Equipped	Undefined	
Compressed Natural Gas Equipped	False	
CUSW PROXI Write Programming Support Enabled	False	
Active Engine Mount Equipped	False	
ZF 9-Speed Transmission Equipped	False	
HPT 6-Speed Transmission Equipped	False	
Variable Speed Fuel Pump Equipped	True	
Operator Idle Speed Request Equipped	False	
PTO System Equipped	False	
Air Shutoff Valve Bank 1 Control Solenoid 1 Equipped	False	
Air Shutoff Valve Bank 1 Control Solenoid 2 Equipped	False	
Air Shutoff Valve Bank 2 Control Solenoid 2 Equipped	False	
Dual Stage Oil Pump Equipped	True	
Auxiliary Coolant Pump Equipped	False	
Trans Skip Shift Equipped	False	
Trans Reverse Lockout Equipped	False	
Port Flap Valve Equipped	False	
Brushless PWM Fan Equipped	NOT_FAN_PWM_BOSCH_BRUSHLESS_CNFG	
6.2 Liter V8 Engine	False	
Primary Lin Alternator Equipped	False	
Coolant On-Off Pump Equipped	False	
Oil Pressure Sensor Enabled	True	
Fiat VIN Learning Strategy Equipped	False	
Dual Fuel Tank Equipped	False	
Yaw Rate Sensor ESC Equipped	False	
1.0 Liter I3 Engine	False	
Coolant On-Off Valve Equipped	False	
Buffered Crank Output for ANC (Active Noise Cancellation) Equipped	True	
Buffered Crank Output for PHEV Engine Pulse Calculation Equipped	True	
Throttle Inlet Temp Sensor Equipped	False	
Humidity, Temperature and Pressure Sensor (LIN) Equipped	False	
Dual Fuel Pressure Sensor Equipped	False	
Brake Pedal Sensor Equipped	False	
Dual Fuel Tank Equipped	False	
PTO System Equipped	False	
Low Temp Radiator Coolant Pump Equipped	False	
Engine Idle Shutoff Equipped	False	
A/C Relay Powered from Engine Switched Battery	False	
CNG Large Gas Tank Equipped	False	
Cooled EGR Equipped	False	
Supercharger Equipped	False	
Hybrid MEC Shifter Equipped	False	
Dual Alternator Gen1 Capable	False	

Auxillary Coolant Pump Equipped	False	
ZF 9-Speed Trans Equipped	False	
HPT 6-Speed Trans Equipped	False	
CUSW 4-Button Cruise Equipped	False	
Power Steering Angle Sensor Mandatory	False	
Throttle Inlet Temp Sensor Equipped	False	
LIN Humidity, Temp, and Pressure Sensor Equipped	False	
Dual Fuel Pressure Sensor Equipped	False	
Brake Pedal Sensor Equipped	False	
Clutch Sensor Equipped	False	
SWAP HARDWIRED BRAKE SWITCH INPUTS	False	
Mass Airflow System Equipped	False	
Bi-Directional Crank Sensor Equipped	True	
5 Button Cruise (LIN) Equipped	True	
Operator Idle Speed Request Equipped	False	
INTAKE O2 SENSOR EQUIPPED	False	
Cylinder Pressure Sensor Equipped	False	
Make Up Air Sensor Equipped	False	
Active Exhaust Pressure Sensor Equipped	False	
Secondary Mass Airflow Sensor Equipped	False	
1.0 Liter I3 Engine	False	
2.0 Liter I4 Direct Injection Engine	False	
Variable Valve Lift Equipped	Not Equipped	
Coolant On-Off Pump Equipped	Not Equipped	
Primary Lin Alternator Equipped	Not Equipped	
Electronic Parking Brake Equipped	True	
Active Exhaust Valve(s) Equipped	False	
Mechanical Coolant Pump Equipped	False	
Aux Coolant Pump Heater Equipped	False	
Heater Temp Control Valve Equipped	False	
High Side Port Tumble Valve Equipped	False	
Wastegate HBridge Equipped	False	
Remote Start Present	Present	
Engine Oil Pressure Sensor Type	255	None

ICS CONFIGURATION

NAME	VALUE	UNITS
Display Type (Base)	True	
Display Type (Mid)	False	
Display Type (High)	False	

RFH CONFIGURATION

NAME	VALUE	UNITS
PIN Successfully Programmed	Yes	

VIN Successfully Programmed	Yes	
Valid Key In Ignition	Yes	
KeySense Configuration	True	
Keyless Go	True	
Ignition system type connected	KIN system	
TPM Auto-Locate Enabled	True	
e-shifter present	True	
Auto Park Present	True	
Secret Codes Programmed	True	
Passive Entry	True	
Premium TPM	True	
Base TPM	False	
RKE	True	
Module Configuration Status	True	
Remote Start Present	True	
Hybrid Type	PHEV	
\$0214 Programmed by	Programmed by Supplier EOL	
Hardware Configuration: Remote Start Antenna	Present	
Hardware Configuration: Front Left Door Handle H/W	Serial AP	
Hardware Configuration: Front Right Door Handle H/W	Serial AP	
Hardware Configuration: Rear Left Door Handle H/W	No AP	
Hardware Configuration: Rear Right Door Handle H/W	No AP	
Hardware Configuration: Trunk Door Handle H/W	Simple Switch AP	
RFHub Locked	RFHUB Locked after IAC write	
Fob Location #1 Successfully Programmed	Yes	
Fob Location #2 Successfully Programmed	Yes	
Fob Location #3 Successfully Programmed	Yes	
Fob Location #4 Successfully Programmed	No	
Fob Location #5 Successfully Programmed	No	
Fob Location #6 Successfully Programmed	No	
Fob Location #7 Successfully Programmed	No	
Fob Location #8 Successfully Programmed	No	
Fob Location #1 Key sense status	Fob is NOT Key Sense	
Fob Location #2 Key sense status	Fob is NOT Key Sense	
Fob Location #3 Key sense status	Fob is Key Sense	
Fob Location #4 Key sense status	Fob is NOT Key Sense	
Fob Location #5 Key sense status	Fob is NOT Key Sense	
Fob Location #6 Key sense status	Fob is NOT Key Sense	
Fob Location #7 Key sense status	Fob is NOT Key Sense	
Fob Location #8 Key sense status	Fob is NOT Key Sense	
Back Up Vehicle Config 1	True	
Back Up Vehicle Config 2	True	
Back Up Vehicle Config 3	True	
Back Up Vehicle Config 4	True	

Back Up Vehicle Config 5	True	
Back Up Vehicle Config 6	True	
Back Up Vehicle Config 7	True	
Back Up ECU Configuration 1	True	
Back Up ECU Configuration 2	True	
Back Up ECU Configuration 3	True	
Back Up ECU Configuration 4	True	
Back Up ECU Configuration 5	True	
Back Up ECU Configuration 6	True	
Back Up ECU Configuration 7	True	
Back Up ECU Configuration 8	True	
Back Up ECU Configuration 9	True	
Back Up ECU Configuration 10	True	
Back Up ECU Configuration 11	True	
Back Up ECU Configuration 12	True	
Back Up ECU Configuration 13	True	
Back Up ECU Configuration 14	True	
Back Up ECU Configuration 15	True	
Back Up ECU Configuration 16	True	
Back Up ECU Configuration 17	True	
Back Up Customer Settings Menu 1 (CSM1)	True	
Back Up Customer Settings Menu 2 (CSM2)	True	
Back Up Programmed ECUs: Cabin Network	True	
Back Up Programmed ECUs: P/T Chassis Network	True	
Secret Key Sent to Body Controller - Most recent attempt	Yes	
Secret Key Sent to Body Controller - Original attempt	Yes	

ORC CONFIGURATION

NAME	VALUE	UNITS
Rollover Sensing	Configured	
EPPM	Not Configured	
Occupant Classification (OCM)	Configured	
First Row Driver Seatbelt Buckle Switch	Configured	
First Row Passenger Seatbelt Buckle Switch	Configured	
Second Row Left seat belt Switch	Not Configured	
Second Row Center seat belt Switch	Not Configured	
Second Row Right seat belt Switch	Not Configured	
Driver Seat Track Position Sensor	Configured	
Passenger Seat Track Position Sensor	Configured	
Passenger Occupant Detection Sensor	Not Configured	
Passenger Airbag Disable Switch	Not Configured	
Passenger Airbag Disable Indicator	Not Configured	
Driver Frontal Squib 1	Configured	
Driver Frontal Squib 2	Configured	

Driver Frontal Squib 3	Configured	
Passenger Frontal Squib 1	Configured	
Passenger Frontal Squib 2	Configured	
Passenger Frontal Squib 3	Configured	
Driver Knee Bolster Squib	Configured	
Passenger Knee Bolster Squib	Configured	
Driver Seatbelt Retractor Pretensioner	Configured	
Passenger Seatbelt Retractor Pretensioner	Configured	
Driver Seatbelt Load Limiter	Configured	
Passenger Seatbelt Load Limiter	Configured	
Driver Seatbelt Anchor Pretensioner	Configured	
Passenger Seatbelt Anchor Pretensioner	Configured	
Driver Seatbelt Buckle Pretensioner	Not Configured	
Passenger Seatbelt Buckle Pretensioner	Not Configured	
Left Curtain Squib 1	Configured	
Right Curtain Squib 1	Configured	
Left Side Seat Squib 1	Configured	
Right Side Seat Squib 1	Configured	
Second Row Left Seat Side Airbag	Not Configured	
Second Row Right Seat Side Airbag	Not Configured	
Driver Frontal Squib 4	Not Configured	
Passenger Frontal Squib 4	Not Configured	
Left Up-Front Acceleration Sensor	Configured	
Right Up-Front Acceleration Sensor	Configured	
Right B-Pillar Impact Acceleration Sensor	Configured	
Left B-Pillar Impact Acceleration Sensor	Configured	
Left C-Pillar Impact Acceleration Sensor	Configured	
Right C-Pillar Impact Acceleration Sensor	Configured	
Right D-Pillar Impact Acceleration Sensor	Configured	
Left D-Pillar Impact Acceleration Sensor	Configured	
Left Side Door Pressure Sensor	Configured	
Right Side Door Pressure Sensor	Configured	
Configuration Column Identifier	A3	

EPS CONFIGURATION

NAME	VALUE	UNITS
Stop/Start Feature Active	False	
Lane Feedback Feature Active	True	
Parallel Park Assist Feature Active	True	
Dynamic Steering Torque Feature Active	True	

HVAC CONFIGURATION

NAME	VALUE	UNITS
DualZone ATC Control (Factory) (BB)	True	

DualZone ATC Control (BB)	True	
Dual Zone MTC Control (BB)	False	
Single Zone MTC Control (BB)	False	
MTC With EBL (3Knob)	False	
MTC Without EBL (3Knob)	False	
MTC heater only (3Knob)	False	
HVAC Configuration	Dual Zone ATC + Rear	

PDM CONFIGURATION

NAME	VALUE	UNITS
Frameless Window	False	

PSDML CONFIGURATION

NAME	VALUE	UNITS
VSIM Status	False	

PSDMR CONFIGURATION

NAME	VALUE	UNITS
UPFM Status (Present = True, Absent = False)	False	

MSM CONFIGURATION

NAME	VALUE	UNITS
Adjustable Pedals	False	
Telescope/Tilt	False	

CSWM CONFIGURATION

NAME	VALUE	UNITS
Heated Steering Wheel	True	
Vehicle Line D-Series	False	
Vehicle Line R-Series	True	
Vehicle Line W-Series	False	
Vehicle Line J-Series	False	
Vehicle Line L-Series	False	
Vehicle Line M-Series	False	
Vehicle Line P-Series	False	
Vehicle Line U-Series	False	
EC - Seat A	Programmed	
EC - Seat B	Programmed	

AMP CONFIGURATION

NAME	VALUE	UNITS
ANC Calibration Date - Year	18	
ANC Calibration Date - Week	45	

ANC Calibration Date - Patch Level	2	
Current ANC Calibration ID - Service	RU PHEV 3.6L: Sunroof & Harman AMP	
ANC Status	Off - Window Mute	
Surround Sound Activated	Set	
Door Module - Left Front	Present	
Door Module - Left Rear	Present	
Door Module - Right Front	Present	
Door Module - Right Rear	Present	
Premuim - 1	False	
Premuim - 2	False	
Premuim - 3	True	
Non -ANC	False	
No Rear Doors	False	
No HALF Chimes	False	

IPC CONFIGURATION

NAME	VALUE	UNITS
PHEV	True	
Rear Fog Lamp	False	

PTS CONFIGURATION

NAME	VALUE	UNITS
Front License Plate Configuration	Front Plate Config - USA	
Rear System with 6 Front Sensors	True	
Front System with 6 Rear Sensors	True	

SCCM CONFIGURATION

NAME	VALUE	UNITS
Rear Wiper	True	
Tilt Telescope	False	
Paddle Shifter	False	
Cruise Control / ACC	True	

BCM CONFIGURATION

NAME	VALUE	UNITS
BCM (Interior Bus)	Set	
HSM	Set	
DDM	Set	
PDM	Set	
DMRL	Set	
DMRR	Set	
HVAC	Set	
MSM	Set	
PLGM	Set	

VTM	Not Set	
PSDML	Set	
PSDMR	Set	
FSM	Not Set	
Radio	Set	
DTV	Not Set	
ITM	Not Set	
AMP	Set	
EDM	Set	
ICS	Set	
HVACR	Set	
CVPM	Set	
EOMR	Set	
MSMP	Set	
VRM	Set	
DSM	Set	
EAM	Set	
ANC	Not Set	
AHLM	Not Set	
BCM (PT)	Set	
PCM	Set	
EPS	Set	
ESM	Set	
ABS	Not Set	
RFH	Set	
IPC	Set	
ACC	Set	
ORC	Set	
PTS	Set	
SCCM	Set	
TCM	Not Set	
OCM	Set	
FFCM	Set	
ABSO	Set	
ESL	Not Set	
HCP	Set	
EBCM	Set	
ORC	Set	
ESM	Set	
ESC	Set	
ECM	Set	
HCP	Set	
OBCM	Set	
AHCP	Set	

EAC	Set	
BPCM	Set	
APM	Set	
Number of Reprogramming Attempts - Counter #0	1	
Vehicle Configuration Programmed Status	True	
Last Programmed Status	Manufacturing	
Last Configuration Odometer	0	miles
Vehicle Configuration Auto Write Counter	1	
Vehicle Configuration 1 - Write Counter	5	
Vehicle Configuration 2 - Write Counter	5	
Vehicle Configuration 3 - Write Counter	5	
Vehicle Configuration 4 - Write Counter	5	
Vehicle Configuration 5 - Write Counter	5	
Vehicle Configuration 6 - Write Counter	5	
Programmed ECUs: Cabin Network	5	
Programmed ECUs: P/T Chassis Network	5	
Programmed Network Configuration - Audio / Telematics Network	0	
Programmed ECUs: Hybrid LAN Network	0	
ECU Configuration 1 (CBC Configurable Inputs and Outputs)	5	
ECU Configuration 2 (CBC Features)	5	
ECU Configuration 3	5	
ECU Configuration 4	5	
ECU Configuration 5 (Wireless)	5	
ECU Configuration 5 (Doors)	5	
ECU Configuration 5 (Memory)	5	
ECU Configuration 6 (Brake)	5	
ECU Configuration 6 (Suspension)	5	
ECU Configuration 6 (Powertrain)	5	
ECU Configuration 6 (Safety)	5	
ECU Configuration 7 (CBC Exterior Lighting Calibrations)	5	
ECU Configuration 8 (LIN and Miscellaneous)	5	
ECU Configuration 9A	5	
ECU Configuration 9 (ITM)	5	
ECU Configuration 10	5	
ECU Configuration 11	5	
ECU Configuration 12	5	
ECU Configuration 13	5	
ECU Configuration 14	5	
ECU Configuration 15 (CBC Features)	5	
ECU Configuration 15 (Suspension)	5	
Vehicle Configuration 7 - Write Counter	5	
Vehicle Config CSM1	5	
Vehicle Config CSM2	5	
Model Year	2021	

Vehicle Line	RU	
Country Code	USA	
Left/Right Hand Drive	Left Hand Drive	
Remote Start Present	Set	
Drive Configuration	2WD Front	
Emode Present	Not Set	
Auto Highbeam	Set	
Body Style	Station Wagon	
Maximum Vehicle Speed	0	MPH
Shifter Type	5 Position Rotary Eshifter PRNDL / Type RS5L	
Performance Pages Present	Not Present	
Special Packages	74	
PTS Configuration	Semi Automatic / Semi Automatic	
Hill Descent Feature Present	Not Set	
Select Speed Control Feature Present	Not Set	
Power Inverter Type	No Power Inverter	
Thatcham Present	Not Set	
Rain Sensor Present	Set	
SKIM System Present	Not Set	
Air Conditioning Present	Not Set	
Cruise Feature is Present	Not Set	
Flipper Glass Present	Not Set	
Full Size Spare	Not Set	
Off Road Capable	Not Set	
Special Packages IC	Pacifica	
Max Load Inflation Pressure Rear Tire	36.0	PSI
Max Load Inflation Pressure Front Tire	36.0	PSI
Police Lighting Feature	Not Set	
Power Right Sliding Door Present	Set	
Power Left Sliding Door Present	Set	
RKE System Present	Set	
T-Case Type	Not Present / Not Present	
Wheel Base	Wheel base not programmed / WB_NP	
FOBIK Safe Enable	Set	
ELV Present	Not Set	
Fuel Capacity	17	gallons
Window Express Feature Configuration	All windows express feature	
Adjustable Pedal Feature Present (non-Memory)	Not Set	
Auto Headlamp Feature Present	Set	
Door Alert Feature Present	Not Set	
Two Fuel Sending Units Present	Not Set	
Vehicle is an SRT	Not Set	
Disable Display of Radio Clock	Not Set	
Chassis Type	Type 8	

Display Outside Temperature Present	Set	
HVAC Configuration	Dual Zone ATC + Rear	
Vehicle Brand	Chrysler	
Display Compass Heading Present	Set	
ESCL system present	Not Set	
High Intensity Discharge Head Lamps	Set	
Secondary Lock Present	Not Set	
Liftgate/Trunk Type	Power Liftgate	
Collision Mitigation System present	Set	
Forward Collision Warning present	Set	
Base TPM system present	Not Set	
Premium TPM system present	Set	
Paddle Shift Feature Present	Not Set	
Sport Mode Present	Not Set	
Auto Park Present	Set	
Passive Entry Present	Set	
Keyless Go Present	Set	
Transfer Case High Ratio	1.000	No Unit
Axle Ratio	3.251	
Transfer Case Low Range Reduction Ratio	0.000	
Dynamic Tire Circumference (All or Rear)	89	inch
Analog Door Sensor Configuration	Driver Door Only Analog Sensor	
Air Quality System Present	Not Set	
Steering Ratio at Negative Angle 1	0.0	No Unit
Connector G Pin 9: Ambient Light Dimmer Wheel Input Present	Set	
Connector A Pin 3/Connector D Pin 2: Low Beam Output Present	Set	
Connector E Pin 29: Rear Wiper Motor Park Signal Present	Set	
Connector F Pin 9: Analog Door Ajar Signal Front Driver Present	Set	
Connector F Pin 23: Door Lock Switch Signal Front Passenger Present	Set	
Connector F Pin 29: Horn Switch Present	Set	
Connector A Pin 11: Hood Ajar Switch Input Present	Set	
Connector F Pin 8 : Liftgate Release Outside Handle Switch Present	Not Set	
Connector E Pin 5: PHEV Fuel Door Switch Input	Set	
Connector F Pin 6: Fuel Door Motor Output Signal Present	Set	
Connector D Pin 7: Stop/Turn Trailer Tow Right Output Present	Not Set	
Connector D Pin 9: Trailer Tow Backup Output Present	Not Set	
Connector D Pin 10: Trailer Tow Tail Lamp Output Present	Not Set	
Connector D Pin 11: Stop/Turn Trailer Tow Left Output Present	Not Set	
Connector D Pin 12: PHEV ECM Hardwire Wake Up Output Present	Set	
Connector E Pin 34: Vacuum Cleaner Relay Output Present	Not Set	
Connector G Pin 24 (Internally tied to Connector F Pin 7): Ambient Lighting Output	Set	
Connector F Pin 35: Inverter Enable Relay Output Present	Set	

Connector E Pin 39/Connector F Pin 5: Rear Fog Lamps Output Present	Not Set	
Connector E Pin 4/Connector F Pin 32: Rear Park Lamps Output Present	Set	
Connector E Pin 3/Connector F Pin 42: Rear Turn Lamps Output Present	Not Set	
Connector E Pin 48 (Tied internally to Connector A Pin16): Rear Wiper Motor Control Output Present	Set	
Connector E Pin 9: Run-ACC Y Relay #2 Output Present	Set	
Connector A Pin 10/Connector D Pin 5: Side Markers Output Present	Set	
Connector E Pin 8: PHEV HCP Hardwire Wakeup	Set	
Connector E Pin 42: Charge Port Lock Output Present	Set	
Connector E Pin 41: Charge Port Unlock Output Present	Set	
Connector F Pin 4: Liftgate Release Present	Not Set	
Connector G Pin 15: UGDO Feed Output Present	Set	
Connector G Pin 22: VTA Warning LED Output Present	Set	
Connector E Pin 11: Vacuum Switch Input	Not Set	
Connectro E Pin 37: Right HID Control Output Present	Not Set	
Connector E Pin 7: Left HID Relay Control Output Present	Not Set	
Connector D Pin 22/ Connector D Pin 23: Ambient Temperature Signal/Return Present	Set	
Tip Start Enabled	Set	
Dual Start Relay System Present	Not Set	
Wiper Service Position Enabled	Not Set	
Fuel Door Release Enabled	Not Present	
Trailer Tow Present	Not Set	
Quad Headlamps Enable	Set	
Horn Chirp Allowed	Set	
Bi Xenon Headlamps Enable	Not Set	
Hazard Lamp Configuration	Latching Switch	
Park Lamp Loadshed Enable	Set	
Front Fog Lamp Dropout Enable	Set	
Combined Rear Lighting Enable	Set	
Side Repeaters Enable	Not Set	
One Touch Lane Change	Set	
Exterior Light Loadshed Enable	Set	
Front Wiper Park Enable	Set	
Rear Wiper Park Enable	Set	
Reversible Washer Pump Enable	Set	
Combined Front Park/Turn Feature Enable	Not Set	
DRL Configuration	No DRL	
DRL Lamp Location	Low Beam DRL	
DRL Dropout Enable	Not Set	
Tunnel Detection	Not Set	
Fuel Door Present	Not Set	
LED Reverse Lamps Present	Not Set	

LED Stop Lamps Present	Not Set	
LED Rear Turn Lamps Present	Not Set	
LED Tail Lamps Present	Set	
LED Rear Fog Lamps Present	Not Set	
LED License Lamps Present	Set	
LED Front Turn Lamps Present	Not Set	
LED Front Fog Lamps Present	Set	
LED Dedicated DRL Present	Not Set	
LED Low Beam Lamps Present	Set	
LED High Beam Lamps Present	Set	
LED Front Park/Marker Lamps Present	Set	
Illuminated approach Enabled	Not Set	
Headlamp Wash Spray Duration (at 100 ms intervals)	1100ms	
Headlamp Wash Interval	wash cycle#11	
Headlamp Wash Shot	double	
Front Wiper Wipes After Wash	2 Wipes	
Headlamp Washer Low Fluid Shut-Off Enable	Set	
Intermittent Wiper States	4 Intermittent Wiper position Switch	
LED CHMSL Lamp Present	Set	
Rear Camera Present	Not Set	
Power Inverter Present	Not Set	
Front Park Assist Present	Set	
Front Heated Seats Present	Set	
Destination	United States of America	
Cabin Equilization Curve Number	RU Premium System - Harman 12ch	
Heated Steering Wheel Present	Set	
Surround Sound Feature Present	Set	
Power Door Locks Present	Set	
Antenna Type	Active Primary and no secondary antenna	
Disable CD Eject	Not Set	
Microphone Tuning Parameter	Absent [Not Used]	
Microphone Configuration	2 Microphones	
Microphone Type	Peiker 300 mv	
External Port Type	AUX + USB + extra USB	
Splashscreen Type	Vehicle Brand	
Fleet Vehicle Content	Not Set	
Vehicle Variant	Undefined	
Tip Start Present	Set	
AP5 Trunk Unlock	CAN	
Airport Scenario Trunk	Not Set	
AP5 Trunk Lock	Simple Switch	
AP1 Left Front	Smart Switch	
AP2 Right Front	Smart Switch	
AP3 Left Rear	CAN	

AP4 Right Rear	CAN	
Global Up	Not Set	
Global Down	Not Set	
Sun Shade	Not Set	
Puddle Lamp Present	Not Set	
Rear Door Pre Short Drop	Not Set	
Passenger Window Lockout	Not Set	
Folding mirrors present	Set	
Heated Mirrors Present	Set	
Mirror turn signals present	Set	
Driver Memory Mirrors Present	Set	
Passenger Memory Mirror Present	Set	
Electro-chromatic driver mirror present	Set	
Electro-chromatic passenger mirror present	Not Set	
Tow Mirror Present	Not Set	
Blindspot Mirror Present	Set	
Window Motor Type	Not Set	
Window Hall Sensors Present	Not Set	
Frameless Window Present	Not Set	
Memory Adjustable Pedals Present	Not Set	
Tilt/Telescope Steering Present	Not Set	
Driver Memory Seat Present	Set	
Stow 'n Assist Present - Driver	Set	
Stow 'n Assist Present - Passenger	Set	
Rear Heated Seats Present	Not Present	
Front Vented Seats Present	Present	
Heated Steering Wheel Present	Present	
Heated Seat Material Type	Base Leather	
Heated Wheel Material Type	Full Leather	
Brake System ECU Configuration A	value 0	
ECO Mode Configuration	Remember Previous State with Ignition Key Cycle	
Dual Alternator Present	Not Set	
ODS Present	False	
Driver Kneebag Present	True	
Passenger Kneebag Present	True	
Curtain Airbags Present	True	
Tow Hooks Present	False	
Passive Ped Pro Present	False	
1st Row Seat Side Airbags Present	True	
Integrated EPP Present	False	
BUX Market	False	
Front Park/Turn Voltage	Park to Turn ratio 55 Percent	
Auto Headlamp On Threshold	3.31409	Volt
Auto Headlamp Off Threshold	2.54930	Volt

Left Low Beam Voltage Regulation	13.6 Volts	
Left High Beam Voltage Regulation	13.6 Volts	
Right Low Beam Voltage Regulation	14 Volts	
Right High Beam Voltage Regulation	13.8 Volts	
Left Front Corner Voltage	13.2 Volts	
Right Front Corner Voltage	13.4 Volts	
Left Rear Corner Voltage	14 Volts	
Right Rear Corner Voltage	14 Volts	
Alert no Reply	Set	
Alert On System Fault	Set	
Alert On Search Timeout	Set	
Panic Enable	Set	
Compass Mounting Orientation	Rightside up	
Washer Fluid Level Voltage Threshold	4.46 volts	
Fobik Safe Alerts Per Ignition Cycle	2	
IBS Present	Set	
OHC Module Present	Set	
Humidity Sensor Present	Set	
HFRM Present	Set	
Auto Relock Time	60	seconds
VTA System Present	VTA	
Illuminated Approach Interior Lighting Target Percentage	100(50%)	
Illuminated Approach Headlamp Target Percentage	125 (62.5%)	
Illuminated Approach Taillamp Target Percentage	125 (62.5%)	
Illuminated Approach Interior Lighting Ramp Up Time	130(2600ms)	
CRVMM Present	Set	
EVIC SWS Module Present	Set	
Compass Mounting Angle	0	Degree
IBS Activate MWU	Not Set	
Battery Types	SNA	
IBS Quiescence Current Limit	-250	mA
IBS Minimum Voltage Limit	5.0	Volts
IBS Minimal Charge Limit	10	AmpHrs
Battery Type II	22	
IBS Minimum Charge Limit	600	mA
Connector F Pin 41: Backup-Reverse lamp Left	Not Set	
Connector E Pin 1: Backup-Reverse lamp Right	Set	
Connector F Pin 5: Left Rear Fog Lamp	Output Disable	
Connector E Pin 39: Right Rear Fog Lamp	Output Disable	
Connector F Pin 42: Right Rear Turn Signal	Right Rear Turn Signal	
Connector E Pin 3: Left Rear Turn Signal	Left Rear Turn Signal	
Connector D Pin 1: Left High Beam Feed	AUX High Beam	
Connector A Pin 2: Right High Beam Feed	AUX High Beam	
Connector F Pin 25: Left Rear Turn Lamp Fault Sense	Disable	

Connector F Pin 28: Right Rear Turn Lamp Fault Sense	Disable	
Connector F Pin 27: Left Sliding Door Ajar	Left Sliding Door Ajar	
Connector F Pin 4: Liftgate Release	Trunk/Liftgate Release	
Connector F Pin 31: Right Sliding Door Ajar	Right Sliding Door Ajar	
Connector D Pin 21: Brake Fluid Level Switch	no parallel resistor	
Connector D Pin 12: PHEV ECM Hardwire Wake Up	Engine Control Module Wake up (PHEV only)	
Connector F Pin 29: Horn Switch Input	Horn Switch Input	
Connector A Pin 11: Hood Ajar Switch Signal	500 ohm series and 500 ohm parallel resistors	
Connector E Pin 7: Left HID Relay Control	Left HID Lamp Relay	
Connector E Pin 37: Right HID Relay Control	Right HID Lamp Relay	
Connector E Pin 29: Rear Wiper Motor Park Signal	Reserved	
Connector E Pin 5: E-5 PHEV Fuel Door Switch Input	PHEV Fuel Door Switch	
Stop/Start Enable Switch Present	Not Set	
Siren	Not Set	
Ultrasonics	Not Set	
Tilt	Not Set	
Connector F Pin 13: Left Sliding Door Switch Input (B-Pillar)	Left B-Pillar sliding Door Switch	
Connector F Pin 14: Right Sliding Door Switch Input (B-Pillar)	Right B-Pillar Sliding Door Switch	
Connector F Pin 15: Driver Door Lock Switch Input	Not Present	
Heatsoak Flush Time	105	Time
Engine Off Clear Time	180	Time
Connector F Pin 30: Fuel Door Lock (BUX)	Not Present	
Connector F Pin 33: Fuel Door Unlock (BUX)	Not Present	
Connector F Pin 34: Spare HSD	Not Present	
Connector F Pin 37: Vacuum Cleaner Power Saver Indicator	Not Present	
Ambient Stable Counter Limit	40	Counter
Heatsoak Speed	15	Counter
Heatsoak Set Time	15	Time
Max Engine Off Time	220	Time
CHMSL Lamp Output Disable	Not Set	
Connector E Pin 28: Secondary Door Ajar Switch Present - PIN E-28	Set	
Manual Door Locks Present	Not Set	
Connector E Pin 48 (Tied internally to Connector A Pin16): Rear Wiper Motor Control Output Present	Rear Wiper (0)	
Connector G Pin11/Connector G Pin 12: Not Used	ERS	
Rain Sensor Module #2 Present	Set	
Humidy Sensor Long Present	Set	
Auto High Beam Module Location	HaLF	
License Plate Lamp Disable	Not Set	
Connector F Pin 29: Horn Switch Present	Horn Switch Input	
Connector E Pin 39: Right Rear Turn Signal	Right Rear Turn Signal	
Connector E Pin 3: Left Rear Turn Signal	Left Rear Turn Signal	
Excess Lateral Acceleration Factor	Filter Off	
Average Last Lateral Acceleration Values	No Averaging	
Excess Longitudinal Acceleration Factor	Filter Off	

Average Last Longitudinal Acceleration Values	No Averaging	
Brake Smoothing Duration	Filter Off	
Brake Smoothing Factor	Filter Off	
Steering Smoothing Duration	Filter Off	
Steering Smoothing Factor	Filter Off	
Steering Smoothing Threshold	Filter Off	
Brake Smoothing Threshold	Filter Off	
Maximum Longitudinal Change	Filter Off	
Maximum Lateral Change	Filter Off	
Acceleration Threshold	Filter Off	
Acceleration Factor	Filter Off	
Nose Dive Threshold	Filter Off	
Nose Dive Factor	Filter Off	
Horn Chirp Duration	Short	
VTA Hood Ajar Monitoring	Not Set	
Headlamp Soak Delay	1.0 sec	
Auto High Beam ON Threshold	25 km/hr	
Auto High Beam OFF Threshold	20 km/hr	
RKE Auto-Relock Feature Enable	Not Set	
PE Auto-Relock Feature Enable	Set	
Parking Light Enable	Not Set	
Interior Lighting Night Threshold	4.45147	Volt
Interior Lighting Day Threshold	4.27498	Volt
TPMS Configuration	Logic 1 NHTSA Enable Warning	
Smart Alternator Present	Not Set	
Temperature Display Resolution	HaLF	
Sunroof Present	Set	
Radio Speaker Open Circuit Disable (LF)	Not Set	
Radio Speaker Open Circuit Disable (RF)	Not Set	
Radio Speaker Open Circuit Disable (LR)	Not Set	
Radio Speaker Open Circuit Disable (RR)	Not Set	
ANC Calibration Parameter Data Set	RU_PHEV_3.6L_tripane_SunRoof_Harman_AMP	
Surround View Camera On/Off Softkey Present	Set	
Drive Mode Version	Version 1	
Show Phone Information in Cluster	01	
Auto Dimming Mirror Hard Button Present	Set	
Automatic Crash Notification Feature Present	Undefined	
Park Assist Tuning Set	BUX Front and Rear Only	
Unlock all doors on 1st press	Set	
Sound Horn on Lock	Set	
Flash Lamps on Lock	Set	
Headlamps on with Wipers	Set	
Auto Lock	Set	
Auto Unlock	Set	

Sliding Door Alert	Set	
Auto Wipers	Set	
Illuminated Approach Time	30	seconds
Headlamp Delay Time	30	seconds
Accessory Delay Time	45	seconds
Daytime Running Lamps	Set	
Hands Free Sliding Door Enable	Set	
Sliding Door Chime Enable	Set	
Auto Highbeam	Set	
Sound Horn on Remote Start	Set	
Sound Horn On Lock Status	Chirp on 1st press/FIRST	
Rear View Camera Static Grid Lines Enabled	Not Set	
Rear View Camera Dynamic Grid Lines Enabled	Not Set	

RADIO CONFIGURATION

NAME	VALUE	UNITS
Satellite Subscription Status	Not Subscribed	
Reason Code	00	
Suspend Day	00	
Suspend Month	00	
Suspend Year	00	
Distortion Limiting	Off	
Clock Defeat	On	
Stereo Blend	Off	
High Cut	Off	
Automated Loudness	Off	
Anti-Theft Enable Status	On	
12/24 Time Selection	12 Hour Time	
Front Seat Video Playback	Disabled	
Cabin EQ Curve Number Currently Used by Radio	223	events
Splash Screen	Automatic	
USB Hubs Detected	3	No Unit
SD Card Readers Detected	0	No Unit
Enumerated USB Devices	0	No Unit
Aux Jack	Not Inserted	

HVACR CONFIGURATION

NAME	VALUE	UNITS
DualZone ATC Control (Factory) (BB)	False	
DualZone ATC Control (BB)	False	
Dual Zone MTC Control (BB)	False	
Single Zone MTC Control (BB)	False	
MTC w EBL (3Knob)	False	
MTC wo EBL (3Knob)	False	

MTC heater only (3Knob)

False

LBSS CONFIGURATION

NAME	VALUE	UNITS
Steering (LHD/RHD)	Left Hand Drive/ LHD	
Teen Key (RU variant only)	Yes	
CFG FEATURE	CFG_NONE	

RBSS CONFIGURATION

NAME	VALUE	UNITS
Steering Variant (LHD/RHD)	Left Hand Drive/ LHD	
Teen Key (RU variant only)	Yes	

FFCM CONFIGURATION

NAME	VALUE	UNITS
HIL mode Enabled	False	
Traceability info	02203374770409	
Traceability info	22203380021503	
XCP Enabled	False	

EDM CONFIGURATION


NAME	VALUE	UNITS
VES	False	
Vehicle Line	RU	
Body Style	Station Wagon	
Vehicle Brand Type	Chrysler	
Radio	Present	
Vehicle System Interface Module	Not Present	
Intrusion module	Not Present	
CAN I in-dash disc player module	Present	
Video Ent. System Screen 2 Module	Not Present	
Video Ent. System Screen 1 Module	Not Present	

RCCC CONFIGURATION

NAME	VALUE	UNITS
DualZone ATC Control	False	
DualZone ATC Control	True	
Dual Zone MTC Control	False	
Single Zone MTC Control	False	
MTC with EBL	False	
MTC without EBL	False	
MTC Heater Only	False	

ABSO CONFIGURATION

NAME	VALUE	UNITS
Multiple Pressure Sensors	True	
Front Directional Sensors	False	
Rear Directional Sensors	True	
Feature PIN	False	
EPB	True	
ACC	True	
Hardwired VSO	True	
Drive Configuration	2WD Front	
VC Chassis Type	Type 8	
ESC BLA Enabled	False	
Dynamic Tire Circumference	89	inch
Axle Ratio	3.251	No Unit
Engine Displacement	3.6	No Unit
PN ESC Byte1	0	
PN ESC Byte2	0	



VEHICLE HEALTH REPORT

Vehicle 2021 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN 2C4RC1S72M [REDACTED]

Odometer 36896.1 miles
Publication Date Aug 30, 2022, 8:25:04 AM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
PCM	Powertrain Control Module	CAN-C	68499122AE	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68499122AE
PLGM	Power Liftgate	CAN-I	68466171AI	2C4RC1S72M [REDACTED]	—	68466171AI
ICS	Integrated Center Stack	CAN-I	7AS341X8AA	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	7AS341X8AA
RFH	Radio Frequency Hub	CAN-C	68500152AA	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68500152AA
ESM	Electronic Shifter	CAN-C	68240089AM	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68240089AM
ORC	Occupant Restraint	CAN-C	68480710AC	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68480710AC
EPS	Electric Power Steering	CAN-C	68460392AA	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68493454AE	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68493454AE
DDM	Driver Door Module	CAN-I	68496461AB	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68496461AB
PDM	Passenger Door Module	CAN-I	68496460AB	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68496460AB
DMRL	Door Module Rear Left	CAN-I	68508894AB	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68508894AB
DMRR	Door Module Rear Right	CAN-I	68508894AB	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68508894AB
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68369596AD
MSM	Memory Seat Module	CAN-I	68321862AC	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68321862AC
CSWM	Comfort Seat Wheel Module	CAN-I	68517013AB	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68517013AB
AMP	Amplifier	CAN-I	68448067AA	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68448067AA
IPC	Instrument Panel Cluster	CAN-C	68434960AE	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68434960AE
PTS	Parktronics	CAN-C	68485862AA	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68485862AA
SCCM	Steering Column Control Module	CAN-C	68360889AD	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68360889AD
BCM	Body Controller	CAN-C	68491085AG	2C4RC1S72M [REDACTED]	2C4RC1S72MR [REDACTED]	68491085AG

ACC	Adaptive Cruise Control	CAN-C	68540436AA	2C4RC1S72M		68540436AA
RADIO	Radio	CAN-I	68465292AC	2C4RC1S72M	2C4RC1S72M	68465292AC
OCM	Occupant Classification	CAN-C	68403127AA	2C4RC1S72M	2C4RC1S72M	68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB	2C4RC1S72M	2C4RC1S72M	68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AB	2C4RC1S72M	2C4RC1S72M	04672786AB
RBSS	Right Blind Spot Sensor	CAN-I	04672786AB	2C4RC1S72M	2C4RC1S72M	04672786AB
FFCM	Forward Facing Camera Module	CAN-C	68493395AA	2C4RC1S72M	2C4RC1S72M	68493395AA
EDM	External Disc Module	CAN-I	68499745AA	2C4RC1S72M	2C4RC1S72M	68499745AA
APM	Accessory Power Module	CAN-C	05185046AB	2C4RC1S72M	2C4RC1S72M	05185046AB
BPCM	Battery Pack Control Module	CAN-C	05193183AE	2C4RC1S72M	2C4RC1S72M	05193183AE
HCP	Hybrid Control Processor	CAN-C	05185116AH	2C4RC1S72M	2C4RC1S72M	05185116AH
OBCM	On Board Charging Module	CAN-C	05185047AE	2C4RC1S72M	2C4RC1S72M	05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC	2C4RC1S72M	2C4RC1S72M	68321862AC
DSM	Display Screen Module	CAN-I	68437339AD	2C4RC1S72M	2C4RC1S72M	68437339AD
VRM	Video Routing Module	CAN-I	68493702AA	2C4RC1S72M	2C4RC1S72M	68493702AA
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA	2C4RC1S72M	2C4RC1S72M	6WL30DX9AA
CVPM	Central vision processing module	CAN-I	56029920AB	2C4RC1S72M	2C4RC1S72M	56029920AB
EAC	Electric A/C Compressor	CAN-C	68237995AG	2C4RC1S72M	2C4RC1S72M	68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05185117AH	2C4RC1S72M	2C4RC1S72M	05185117AH
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB	2C4RC1S72M	2C4RC1S72M	68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68471122AD	2C4RC1S72M	2C4RC1S72M	68471122AD
SGW	Security Gateway Module	CAN-C	68488429AB		2C4RC1S72M	68488429AB
TBM2	Telematic Box Module 2	CAN-C	68546266AB	2C4RC1S72M	2C4RC1S72M	68546266AB

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	SERIAL NUMBER	CVNS
PCM	USA	1B 47	75 01 01	4422		
PLGM	USA	0	5084	000200000031		
ICS	USA	0F 0C 00	13 31 01	4700		

RFH	USA / USA	10 17 00	13 26 00	4A00
ESM	USA / USA	0F 24 00	12 28 FF	4402
ORC	USA / USA	12 1A 00	13 2E 00	4301
EPS	USA / USA	12 2A 00	12 1E 01	4502
HVAC	USA	0E 09 00	14 2F 01	4401
DDM	USA	11 07 00	14 07 00	4202
PDM	USA	11 07 00	14 07 00	4202
DMRL	USA / USA	10 0B 00	14 08 00	4201
DMRR	USA / USA	10 0B 00	14 08 00	4201
PSDML	USA / USA	10 17 00	14 10 12	4001
PSDMR	USA / USA	10 17 00	14 10 12	4001
MSM	USA	0F 2B 00	10 27 03	4101
CSWM	USA	11 2A 00	14 25 00	4302
AMP	USA	0F 06 01	12 2E 01	4021
IPC	USA / USA	12 06 00	14 2B 00	4705
PTS	USA	0E 32 00	14 07 00	4311
SCCM	USA	13 28 00	13 29 00	4301
BCM	USA	0D 11 00	14 26 90	4420
ACC	USA / USA	14 12 01	14 26 01	4400
RADIO		65	5175	000200000008
OCM	USA / USA	11 1F 01	0E 2F 02	4030
HVACR	USA	0E 09 00	10 03 02	4301
LBSS	USA / USA	11 30 02	12 0D 00	4202
RBSS	USA / USA	11 30 02	12 0D 00	4202
FFCM	USA / USA	11 06 00	13 1E 00	4102
EDM	USA	12 0A 00	11 08 00	4000
APM	USA / USA	11 32 00	11 32 00	4001
BPCM		0E 03 00	14 2C 00	4005
HCP	USA	11 1F 04	0F 2D 00	4006
OBCM	USA	0F 0D 00	12 02 00	4002
MSMP	USA	0F 2B 00	10 27 03	4001
DSM	USA / USA	14 0C 00	14 28 00	4300
VRM	USA / USA	0F 1C 00	14 1E 14	4001
RCCC	USA	0F 1D 00	13 04 00	4000
CVPM	USA / USA	11 27 01	14 0C 01	4004
EAC	USA	0E 34 00	12 0F 00	4102
AHCP	USA	11 1F 04	0F 2D 00	4000
EBBM	USA	0E 19 02	14 0D 18	4000
ABSO	USA	0E 15 02	14 1B 26	4201
SGW		5	969	4103
TBM2	USA	13 0E 02	14 2A 5C	4104

FLASHES

PCM | 2021 RU 3.6L PCM PHEV NAFTA**Applicable Bulletins**

NUMBER	TYPE	RSU #	DESCRIPTION
18-050-22 REV. A	TSB	21-063	Flash: Powertrain Control Module (PCM) Updates

MSM | 2021 - 2022 RU MSM / MSMP NAFTA**Applicable Bulletins**

NUMBER	TYPE	RSU #	DESCRIPTION
08-047-22	TSB		Flash: Memory Seat Module (MSM) and Memory Seat Module Passenger (MSMP) Updates

ACC | 2020 - 2021 RU DASM / ACC**Applicable Bulletins**

NUMBER	TYPE	RSU #	DESCRIPTION
08-139-21	TSB		Flash: Adaptive Cruise Control (ACC) Module Enhancements

HCP | 2021 RU HCP PHEV .8MM NAFTA**Applicable Bulletins**

NUMBER	TYPE	RSU #	DESCRIPTION
08-052-22	TSB	21-062	Flash: Hybrid Control Processor (HCP) and Auxiliary Hybrid Control Processor (AHCP) Updates

MSMP | 2021 - 2022 RU MSM / MSMP NAFTA**Applicable Bulletins**

NUMBER	TYPE	RSU #	DESCRIPTION
08-047-22	TSB		Flash: Memory Seat Module (MSM) and Memory Seat Module Passenger (MSMP) Updates

DSM | 2021 RU DSM / DCSD 10.1 W/CHROME BEZEL NAFTA**Applicable Bulletins**

NUMBER	TYPE	RSU #	DESCRIPTION
08-104-21 REV. A	TSB		Flash: Display Screen Module (DSM) System Updates

AHCP | 2021 RU AHCP PHEV .8MM NAFTA**Applicable Bulletins**

NUMBER	TYPE	RSU #	DESCRIPTION
08-052-22	TSB	21-062	Flash: Hybrid Control Processor (HCP) and Auxiliary Hybrid Control Processor (AHCP) Updates

RSUS

RSU #	DESCRIPTION	STATUS
21-063	2021 RU PHEV PCM UPDATE	Complete
21-062	2021 RU PHEV HCP AND AHCP UPDATE	Complete

RECALLS

RECALL #	DESCRIPTION	STATUS
Y50	Customer Satisfaction Notification Y50 - Power Liftgate	Complete

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
PCM	U140C	Implausible Right Rear Wheel Speed Signal Received	Active
HVAC	U11BB-00	Lost Communication with Video Routing Module-	Stored
ACC	C2227-00	ABS Disabled ECU-	Active
RADIO	B1431-00	Bluetooth Antenna Internal Performance-	Stored
HCP	P0A43-00	Drive Motor "A" Position Sensor Circuit Intermittent-	Stored
HCP	U0415-00	Invalid Data Received from Anti-Lock Brake System (ABS) Control Module "A"-	Stored
HCP	U1852-00	Implausible Data Received from ABS on D-PT-	Stored
CVPM	B23C7-92	Right Camera-Performance or Incorrect Operation	Stored

ENVIRONMENTAL DATA SUMMARY**PCM | U140C | Active | Implausible Right Rear Wheel Speed Signal Received**

NAME	VALUE	UNITS
Number of DTC	1	
DTC	D4 0C	
DTC Readiness Flag	Not Complete	
DTC Storage State	Active	
Warning Indicator Request State	Off	
Odometer	36813.0	miles
Accumulation Timer	19	minutes
Ignition Key Cycles	0	
Starts Since Set Counter	0	
Key Cycles Since DTC Last Set Counter	0	
Warm Up Cycles	0	
Good Trip Counter	0	

HVAC | U11BB-00 | Stored | Lost Communication with Video Routing Module-

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	ERROR	
Original Odometer Value	36368	miles
Most Recent Odometer Value	36368	miles
Frequency Counter	1	
Ignition Cycle Counter	51	

ACC | C2227-00 | Active | ABS Disabled ECU-

NAME	VALUE	UNITS
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	ERROR	
Original Odometer Value	36895	miles
Most Recent Odometer Value	36895	miles
Frequency Counter	1	
Operation Cycle Counter	0	
Vehicle Speed	0	MPH
Engine RPM	0	rpm
ACC Set Speed	0	MPH
Object of Interest Distance	830	FEET
Engine Torque Request	SNA	Ft-Lbs
PRNDL Status	P range	
Ignition Voltage	14.4	
System Voltage	14.5	Volts

RADIO | B1431-00 | Stored | Bluetooth Antenna Internal Performance-

NAME	VALUE	UNITS
DTC	94 31 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

HCP | POA43-00 | Stored | Drive Motor "A" Position Sensor Circuit Intermittent-

NAME	VALUE	UNITS
DTC	0A 43 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Occurrence	
Original Odometer Value	36882.6	miles

Most Recent Odometer Value	36884.7	miles
Frequency Counter	2	
Ignition Cycle Counter	1	
Real time clock	53208384	sec
RAM stamps keyOn	150	sec
RAM Stamps	230588	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
PHEV Charging Status	No Charging	
Engine Speed	0	rpm
HV Battery SOC	41	%
Ignition State	Reserved	
PRND Position Display	D	
Propulsion System Active	False	
Vehicle Speed	75.6956	MPH
Motor A Temp Sensor	167	°F
Motor B Temp Sensor	171	°F
Barometric Pressure	12	PSI
Engine Coolant Temperature	169	°F
Motor A Resolver Offset Learn Erase	not requested	
Motor A Resolver Offset Learning Status Flag	Applied	
Motor B Resolver Offset Learning Status Flag	Applied	
Motor A Resolver Angle Offset	-0.40	Degree
Motor B Resolver Angle Offset	2.80	Degree
Motor A Resolver Supply Voltage Value	15.75	Volts
Motor B Resolver Supply Voltage Value	15.75	Volts
Motor A Resolver to Digital Low Level Driver Faults	No fault	
Motor B Resolver to Digital Low Level Driver Faults	No fault	
Battery Feed Voltage 2 Sense	14.544	Volts
Internal EPS Voltage Sense A	8.208	Volts
Internal EPS Voltage Sense B	8.208	Volts
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	27.655	Ft-Lbs
Available Motor Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor B	77.987	Ft-Lbs
Available Regen Torque - Motor A	0.000	Ft-Lbs
Available Regen Torque - Motor B	-77.987	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	31.803	Ft-Lbs
Electric Motor A Speed	-10333.5	rpm
Electric Motor B Speed	8391.0	rpm
Battery Feed Voltage 1 Sense	14.472	Volts
Battery Feed Voltage 3 Sense	14.472	Volts
Hybrid System State	Determine Hybrid System State	

Motor A - Inverter Current - phase A	0	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	-4	AMP
Motor B - Inverter Current - phase A	44	AMP
Motor B - Inverter Current - phase B	-36	AMP
Motor B - Inverter Current - phase C	-12	AMP
Outside Air Temperature	73.4	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	Off	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Closed	
HV Battery Voltage from BPCM	335.20	Volts
PIM DC Link Voltage - A	334	Volts
PIM DC Link Voltage - B	337	Volts
Inverter A IGBT Temperature for phase A	95	°F
Inverter A IGBT Temperature for phase B	93	°F
Inverter A IGBT Temperature for phase C	93	°F
Inverter B IGBT Temperature for phase A	91	°F
Inverter B IGBT Temperature for phase B	91	°F
Inverter B IGBT Temperature for phase C	91	°F
APM Status	Buck CV	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	3	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	27.655	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Motor B Resolver Offset Learn Erase	not requested	
GPS Date - Year	2022	Year
GPS Date - Month	8	
GPS Date - Day	22	Days
UTC Time - Hours	14	Hours
UTC Time - Minutes	41	
UTC Time - Seconds	1	seconds
ECU Time - Milliseconds	887	ms

HCP | U0415-00 | Stored | Invalid Data Received from Anti-Lock Brake System (ABS) Control Module "A"-

NAME	VALUE	UNITS
DTC	C4 15 00	
Test Failed	False	
Test Failed This Operation Cycle	True	
Pending DTC	True	

Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	Occurrence	
Original Odometer Value	36896.0	miles
Most Recent Odometer Value	36896.1	miles
Frequency Counter	3	
Ignition Cycle Counter	1	
Real time clock	53897568	sec
RAM stamps keyOn	75	sec
RAM Stamps	230809	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
Engine Speed	0	rpm
HV Battery SOC	32	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Motor A Temp Sensor	81	°F
Motor B Temp Sensor	84	°F
Barometric Pressure	12	PSI
Engine Coolant Temperature	79	°F
Internal EPS Voltage Sense A	8.208	Volts
Internal EPS Voltage Sense B	8.136	Volts
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.000	Ft-Lbs
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.000	Ft-Lbs
Available Motor Torque - Motor A	87.205	Ft-Lbs
Available Motor Torque - Motor B	232.393	Ft-Lbs
Available Regen Torque - Motor A	-87.205	Ft-Lbs
Available Regen Torque - Motor B	-232.393	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor A - Inverter Current - phase A	0	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	-4	AMP
Motor B - Inverter Current - phase A	0	AMP
Motor B - Inverter Current - phase B	-4	AMP
Motor B - Inverter Current - phase C	-4	AMP
Motor B Resolver Angle	188	Degree

Motor A Resolver Angle	222	Degree
Electric Motor A Speed	1.0	rpm
Electric Motor B Speed	1.5	rpm
PIM DC Link Voltage - A	348	Volts
PIM DC Link Voltage - B	350	Volts
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
HCP System Shutdown Command	Default	
HV Battery Voltage from BPCM	348.80	Volts
SW Build Release Version	PIM_21B_2011B0_RU_HCP___	
HCP SW Version	21B	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Closed	
APM Status	Buck CV	
Impact Event	False	
Outside Air Temperature	75.2	°F
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Battery Feed Voltage 1 Sense	14.544	Volts
Battery Feed Voltage 2 Sense	14.544	Volts
Battery Feed Voltage 3 Sense	14.400	Volts
Hybrid System State	Inverters Enabled	
Inverter A IGBT Temperature for phase A	81	°F
Inverter A IGBT Temperature for phase B	82	°F
Inverter A IGBT Temperature for phase C	81	°F
Inverter B IGBT Temperature for phase A	82	°F
Inverter B IGBT Temperature for phase B	82	°F
Inverter B IGBT Temperature for phase C	82	°F
PHEV Charging Status	No Charging	
Distance Travelled with Light ON	0	miles
GPS Date - Year	2022	Year
GPS Date - Month	8	
GPS Date - Day	30	Days
UTC Time - Hours	14	Hours
UTC Time - Minutes	8	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	813	ms

HCP | U1852-00 | Stored | Implausible Data Received from ABS on D-PT-

NAME	VALUE	UNITS
DTC	D8 52 00	
Test Failed	False	
Test Failed This Operation Cycle	True	


Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	Occurrence	
Original Odometer Value	36896.0	miles
Most Recent Odometer Value	36896.1	miles
Frequency Counter	3	
Ignition Cycle Counter	1	
Real time clock	53897568	sec
RAM stamps keyOn	75	sec
RAM Stamps	230809	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
Engine Speed	0	rpm
HV Battery SOC	32	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Motor A Temp Sensor	81	°F
Motor B Temp Sensor	84	°F
Barometric Pressure	12	PSI
Engine Coolant Temperature	79	°F
Internal EPS Voltage Sense A	8.208	Volts
Internal EPS Voltage Sense B	8.136	Volts
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.000	Ft-Lbs
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.000	Ft-Lbs
Available Motor Torque - Motor A	87.205	Ft-Lbs
Available Motor Torque - Motor B	232.393	Ft-Lbs
Available Regen Torque - Motor A	-87.205	Ft-Lbs
Available Regen Torque - Motor B	-232.393	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor A - Inverter Current - phase A	0	AMP
Motor A - Inverter Current - phase B	-4	AMP
Motor A - Inverter Current - phase C	0	AMP
Motor B - Inverter Current - phase A	0	AMP
Motor B - Inverter Current - phase B	-4	AMP
Motor B - Inverter Current - phase C	0	AMP

Motor B Resolver Angle	188	Degree
Motor A Resolver Angle	222	Degree
Electric Motor A Speed	1.0	rpm
Electric Motor B Speed	1.5	rpm
PIM DC Link Voltage - A	348	Volts
PIM DC Link Voltage - B	350	Volts
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
HCP System Shutdown Command	Default	
HV Battery Voltage from BPCM	348.80	Volts
SW Build Release Version	PIM_21B_2011B0_RU_HCP___	
HCP SW Version	21B	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Closed	
APM Status	Buck CV	
Impact Event	False	
Outside Air Temperature	75.2	°F
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Battery Feed Voltage 1 Sense	14.544	Volts
Battery Feed Voltage 2 Sense	14.544	Volts
Battery Feed Voltage 3 Sense	14.400	Volts
Hybrid System State	Inverters Enabled	
Inverter A IGBT Temperature for phase A	81	°F
Inverter A IGBT Temperature for phase B	82	°F
Inverter A IGBT Temperature for phase C	81	°F
Inverter B IGBT Temperature for phase A	82	°F
Inverter B IGBT Temperature for phase B	82	°F
Inverter B IGBT Temperature for phase C	82	°F
PHEV Charging Status	No Charging	
Distance Travelled with Light ON	0	miles
GPS Date - Year	2022	Year
GPS Date - Month	8	
GPS Date - Day	30	Days
UTC Time - Hours	14	Hours
UTC Time - Minutes	8	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	813	ms

CVPM | B23C7-92 | Stored | Right Camera-Performance or Incorrect Operation

NAME	VALUE	UNITS
DTC	A3 C7 92	
Test Failed	False	

Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	ERROR	
Original Odometer Value	33882	miles
Most Recent Odometer Value	36765	miles
Frequency Counter	13	
Ignition Cycle Counter	26	
DTC Extended Data Record Number 2	2	
ECU Failure – Internal Voltage	Off	
ECU Failure – ECU Memory	Off	
ECU Failure – Internal Communication Error	Off	
ECU Failure – Video Subsystem Error	Off	
ECU Failure – Watchdog Error	Off	
Calibration Failure - Calibration not Executed	Off	
Calibration Failure - Calibration Data Inconsistent	Off	
Battery Voltage	14.6	V
ECU Voltage	14.3	V
Vehicle Speed	9.505037	MPH
Ignition Status	Ignition Status: Running	
Steering Wheel Angle	122.5	Deg
Steering Wheel Angle Status	Steering Wheel Status: Okay	
Driver Door Ajar	Inactive	
Rear Left Door Ajar	Inactive	
Passenger Door Ajar	Inactive	
Rear Right Door Ajar	Inactive	
Reverse Gear	Inactive	
Liftgate Ajar	Inactive	
Touch Screen Status	Touch Screen Status: Not Pressed	
Touch Screen X Coordinate	0000	
Touch Screen Y Coordinate	0000	
Radio Display Status	Display Status: Off	



VEHICLE SCAN REPORT

Vehicle 2021 CHRYSLER PACIFICA (PHEV) 3.6L V6 HYBRID ENGINE
VIN 2C4RC1S72M [REDACTED]

Odometer 36896.1 miles
Publication Date Aug 30, 2022, 8:22:51 AM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
PCM	Powertrain Control Module	CAN-C	68499122AE	2C4RC1S72M	2C4RC1S72M	68499122AE
PLGM	Power Liftgate	CAN-I	68466171AI	2C4RC1S72M	—	68466171AI
ICS	Integrated Center Stack	CAN-I	7AS341X8AA	2C4RC1S72M	2C4RC1S72M	7AS341X8AA
RFH	Radio Frequency Hub	CAN-C	68500152AA	2C4RC1S72M	2C4RC1S72M	68500152AA
ESM	Electronic Shifter	CAN-C	68240089AM	2C4RC1S72M	2C4RC1S72M	68240089AM
ORC	Occupant Restraint	CAN-C	68480710AC	2C4RC1S72M	2C4RC1S72M	68480710AC
EPS	Electric Power Steering	CAN-C	68460392AA	2C4RC1S72M	2C4RC1S72M	68460392AA
HVAC	Heat, Ventilation and A/C	CAN-I	68493454AE	2C4RC1S72M	2C4RC1S72M	68493454AE
DDM	Driver Door Module	CAN-I	68496461AB	2C4RC1S72M	2C4RC1S72M	68496461AB
PDM	Passenger Door Module	CAN-I	68496460AB	2C4RC1S72M	2C4RC1S72M	68496460AB
DMRL	Door Module Rear Left	CAN-I	68508894AB	2C4RC1S72M	2C4RC1S72M	68508894AB
DMRR	Door Module Rear Right	CAN-I	68508894AB	2C4RC1S72M	2C4RC1S72M	68508894AB
PSDML	Power Sliding Doors (Left)	CAN-I	68369596AD	2C4RC1S72M	2C4RC1S72M	68369596AD
PSDMR	Power Sliding Doors (Right)	CAN-I	68369596AD	2C4RC1S72M	2C4RC1S72M	68369596AD
MSM	Memory Seat Module	CAN-I	68321862AC	2C4RC1S72M	2C4RC1S72M	68321862AC
CSWM	Comfort Seat Wheel Module	CAN-I	68517013AB	2C4RC1S72M	2C4RC1S72M	68517013AB
AMP	Amplifier	CAN-I	68448067AA	2C4RC1S72M	2C4RC1S72M	68448067AA
IPC	Instrument Panel Cluster	CAN-C	68434960AE	2C4RC1S72M	2C4RC1S72M	68434960AE
PTS	Parktronics	CAN-C	68485862AA	2C4RC1S72M	2C4RC1S72M	68485862AA
SCCM	Steering Column Control Module	CAN-C	68360889AD	2C4RC1S72M	2C4RC1S72M	68360889AD
BCM	Body Controller	CAN-C	68491085AG	2C4RC1S72M	2C4RC1S72M	68491085AG

ACC	Adaptive Cruise Control	CAN-C	68540436AA	2C4RC1S72			68540436AA
RADIO	Radio	CAN-I	68465292AC	2C4RC1S72		2C4RC1S72M	68465292AC
OCM	Occupant Classification	CAN-C	68403127AA	2C4RC1S72		2C4RC1S72M	68403127AA
HVACR	Heat, Ventilation and A/C Rear	CAN-I	68373079AB	2C4RC1S72		2C4RC1S72M	68373079AB
LBSS	Left Blind Spot Sensor	CAN-I	04672786AB	2C4RC1S72		2C4RC1S72M	04672786AB
RBSS	Right Blind Spot Sensor	CAN-I	04672786AB	2C4RC1S72		2C4RC1S72M	04672786AB
FFCM	Forward Facing Camera Module	CAN-C	68493395AA	2C4RC1S72		2C4RC1S72M	68493395AA
EDM	External Disc Module	CAN-I	68499745AA	2C4RC1S72		2C4RC1S72M	68499745AA
APM	Accessory Power Module	CAN-C	05185046AB	2C4RC1S72		2C4RC1S72M	05185046AB
BPCM	Battery Pack Control Module	CAN-C	05193183AE	2C4RC1S72		2C4RC1S72M	05193183AE
HCP	Hybrid Control Processor	CAN-C	05185116AH	2C4RC1S72		2C4RC1S72M	05185116AH
OBCM	On Board Charging Module	CAN-C	05185047AE	2C4RC1S72		2C4RC1S72M	05185047AE
MSMP	Memory Seat Module - Passenger	CAN-I	68321862AC	2C4RC1S72		2C4RC1S72M	68321862AC
DSM	Display Screen Module	CAN-I	68437339AD	2C4RC1S72		2C4RC1S72M	68437339AD
VRM	Video Routing Module	CAN-I	68493702AA	2C4RC1S72		2C4RC1S72M	68493702AA
RCCC	Rear Cabin Comfort Controls	CAN-I	6WL30DX9AA	2C4RC1S72		2C4RC1S72M	6WL30DX9AA
CVPM	Central vision processing module	CAN-I	56029920AB	2C4RC1S72		2C4RC1S72M	56029920AB
EAC	Electric A/C Compressor	CAN-C	68237995AG	2C4RC1S72		2C4RC1S72M	68237995AG
AHCP	Auxiliary Hybrid Control Processor	CAN-C	05185117AH	2C4RC1S72		2C4RC1S72M	05185117AH
EBBM	Electronic Brake Booster Module	CAN-C	68461813AB	2C4RC1S72		2C4RC1S72M	68461813AB
ABSO	Anti Lock Brakes OBD	CAN-C	68471122AD	2C4RC1S72		2C4RC1S72M	68471122AD
SGW	Security Gateway Module	CAN-C	68488429AB			2C4RC1S72M	68488429AB
TBM2	Telematic Box Module 2	CAN-C	68546266AB	2C4RC1S72		2C4RC1S72M	68546266AB

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	SERIAL NUMBER	CVNS
PCM	USA	1B 47	75 01 01	4422		
PLGM	USA	0	5084	000200000031		
ICS	USA	0F 0C 00	13 31 01	4700		

RFH	USA / USA	10 17 00	13 26 00	4A00	T04Z22980P1353	
ESM	USA / USA	0F 24 00	12 28 FF	4402	T3K2660D0089	
ORC	USA / USA	12 1A 00	13 2E 00	4301	T03JF3020G00FC	
EPS	USA / USA	12 2A 00	12 1E 01	4502	T5M342000418	
HVAC	USA	0E 09 00	14 2F 01	4401	???????????	
DDM	USA	11 07 00	14 07 00	4202	TRU1B30700001C	
PDM	USA	11 07 00	14 07 00	4202	TRU2B292000367	
DMRL	USA / USA	10 0B 00	14 08 00	4201	TRURB28500078A	
DMRR	USA / USA	10 0B 00	14 08 00	4201	TRURB28600199A	
PSDML	USA / USA	10 17 00	14 10 12	4001		
PSDMR	USA / USA	10 17 00	14 10 12	4001		
MSM	USA	0F 2B 00	10 27 03	4101	TLK312000189	
CSWM	USA	11 2A 00	14 25 00	4302	TRU3B319000710	
AMP	USA	0F 06 01	12 2E 01	4021	5022BB33600714	
IPC	USA / USA	12 06 00	14 2B 00	4705	TCL337000037	
PTS	USA	0E 32 00	14 07 00	4311	T00FF330000050	
SCCM	USA	13 28 00	13 29 00	4301	S32701814	
BCM	USA	0D 11 00	14 26 90	4420	TYH317010997	
ACC	USA / USA	14 12 01	14 26 01	4400	T07UE297000027	
RADIO		65	5175	000200000008	T00123260702970	
OCM	USA / USA	11 1F 01	0E 2F 02	4030	TRUJY32301425G	
HVACR	USA	0E 09 00	10 03 02	4301		
LBSS	USA / USA	11 30 02	12 0D 00	4202	T00 338080017	
RBSS	USA / USA	11 30 02	12 0D 00	4202	T00 338010023	
FFCM	USA / USA	11 06 00	13 1E 00	4102	T00IV3380217670	
EDM	USA	12 0A 00	11 08 00	4000	T00AM2490T0309	
APM	USA / USA	11 32 00	11 32 00	4001	TD6VA2270R0475	
BPCM		0E 03 00	14 2C 00	4005	TESIG307030051	79855957
HCP	USA	11 1F 04	0F 2D 00	4006	TMMVL0259C0002	879F1587 D754327D 050DC953
OBCM	USA	0F 0D 00	12 02 00	4002	TD63H2480R2899	
MSMP	USA	0F 2B 00	10 27 03	4001	TLK312000191	
DSM	USA / USA	14 0C 00	14 28 00	4300	000000034514	
VRM	USA / USA	0F 1C 00	14 1E 14	4001	T 323020283	
RCCC	USA	0F 1D 00	13 04 00	4000	T291010310	
CVPM	USA / USA	11 27 01	14 0C 01	4004	T00324041056	
EAC	USA	0E 34 00	12 0F 00	4102	200803200290	
AHCP	USA	11 1F 04	0F 2D 00	4000		
EBBM	USA	0E 19 02	14 0D 18	4000	T006M273060142	E5898FA5
ABSO	USA	0E 15 02	14 1B 26	4201	T004F217068439	4F158D1B
SGW		5	969	4103	TF1163430J14300	
TBM2	USA	13 0E 02	14 2A 5C	4104	TF0342980000150	

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
PCM	U140C	Implausible Right Rear Wheel Speed Signal Received	Active
HVAC	U11BB-00	Lost Communication with Video Routing Module-	Stored
ACC	C2227-00	ABS Disabled ECU-	Active
RADIO	B1431-00	Bluetooth Antenna Internal Performance-	Stored
HCP	P0A43-00	Drive Motor "A" Position Sensor Circuit Intermittent-	Stored
HCP	U0415-00	Invalid Data Received from Anti-Lock Brake System (ABS) Control Module "A"-	Stored
HCP	U1852-00	Implausible Data Received from ABS on D-PT-	Stored
CVPM	B23C7-92	Right Camera-Performance or Incorrect Operation	Stored

ENVIRONMENTAL DATA SUMMARY

PCM | U140C | Active | Implausible Right Rear Wheel Speed Signal Received

NAME	VALUE	UNITS
Number of DTC	1	
DTC	D4 0C	
DTC Readiness Flag	Not Complete	
DTC Storage State	Active	
Warning Indicator Request State	Off	
Odometer	36813.0	miles
Accumulation Timer	17	minutes
Ignition Key Cycles	0	
Starts Since Set Counter	0	
Key Cycles Since DTC Last Set Counter	0	
Warm Up Cycles	0	
Good Trip Counter	0	

HVAC | U11BB-00 | Stored | Lost Communication with Video Routing Module-

NAME	VALUE	UNITS
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	ERROR	
Original Odometer Value	36368	miles
Most Recent Odometer Value	36368	miles
Frequency Counter	1	
Ignition Cycle Counter	51	

ACC | C2227-00 | Active | ABS Disabled ECU-

NAME	VALUE	UNITS
Test Failed	True	
Test Failed This Operation Cycle	True	
Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	ERROR	
Original Odometer Value	36895	miles
Most Recent Odometer Value	36895	miles
Frequency Counter	1	
Operation Cycle Counter	0	
Vehicle Speed	0	MPH
Engine RPM	0	rpm
ACC Set Speed	0	MPH
Object of Interest Distance	830	FEET
Engine Torque Request	SNA	Ft-Lbs
PRNDL Status	P range	
Ignition Voltage	14.4	
System Voltage	14.5	Volts

RADIO | B1431-00 | Stored | Bluetooth Antenna Internal Performance-

NAME	VALUE	UNITS
DTC	94 31 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

HCP | P0A43-00 | Stored | Drive Motor "A" Position Sensor Circuit Intermittent-

NAME	VALUE	UNITS
DTC	0A 43 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Occurrence	
Original Odometer Value	36882.6	miles

Most Recent Odometer Value	36884.7	miles
Frequency Counter	2	
Ignition Cycle Counter	1	
Real time clock	53208384	sec
RAM stamps keyOn	150	sec
RAM Stamps	230588	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
PHEV Charging Status	No Charging	
Engine Speed	0	rpm
HV Battery SOC	41	%
Ignition State	Reserved	
PRND Position Display	D	
Propulsion System Active	False	
Vehicle Speed	75.6956	MPH
Motor A Temp Sensor	167	°F
Motor B Temp Sensor	171	°F
Barometric Pressure	12	PSI
Engine Coolant Temperature	169	°F
Motor A Resolver Offset Learn Erase	not requested	
Motor A Resolver Offset Learning Status Flag	Applied	
Motor B Resolver Offset Learning Status Flag	Applied	
Motor A Resolver Angle Offset	-0.40	Degree
Motor B Resolver Angle Offset	2.80	Degree
Motor A Resolver Supply Voltage Value	15.75	Volts
Motor B Resolver Supply Voltage Value	15.75	Volts
Motor A Resolver to Digital Low Level Driver Faults	No fault	
Motor B Resolver to Digital Low Level Driver Faults	No fault	
Battery Feed Voltage 2 Sense	14.544	Volts
Internal EPS Voltage Sense A	8.208	Volts
Internal EPS Voltage Sense B	8.208	Volts
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	27.655	Ft-Lbs
Available Motor Torque - Motor A	0.000	Ft-Lbs
Available Motor Torque - Motor B	77.987	Ft-Lbs
Available Regen Torque - Motor A	0.000	Ft-Lbs
Available Regen Torque - Motor B	-77.987	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	31.803	Ft-Lbs
Electric Motor A Speed	-10333.5	rpm
Electric Motor B Speed	8391.0	rpm
Battery Feed Voltage 1 Sense	14.472	Volts
Battery Feed Voltage 3 Sense	14.472	Volts
Hybrid System State	Determine Hybrid System State	

Motor A - Inverter Current - phase A	0	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	-4	AMP
Motor B - Inverter Current - phase A	44	AMP
Motor B - Inverter Current - phase B	-36	AMP
Motor B - Inverter Current - phase C	-12	AMP
Outside Air Temperature	73.4	°F
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	Off	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Closed	
HV Battery Voltage from BPCM	335.20	Volts
PIM DC Link Voltage - A	334	Volts
PIM DC Link Voltage - B	337	Volts
Inverter A IGBT Temperature for phase A	95	°F
Inverter A IGBT Temperature for phase B	93	°F
Inverter A IGBT Temperature for phase C	93	°F
Inverter B IGBT Temperature for phase A	91	°F
Inverter B IGBT Temperature for phase B	91	°F
Inverter B IGBT Temperature for phase C	91	°F
APM Status	Buck CV	
Impact Event	False	
HCP System Shutdown Command	Default	
Distance Travelled with Light ON	3	miles
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	27.655	Ft-Lbs
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Motor B Resolver Offset Learn Erase	not requested	
GPS Date - Year	2022	Year
GPS Date - Month	8	
GPS Date - Day	22	Days
UTC Time - Hours	14	Hours
UTC Time - Minutes	41	
UTC Time - Seconds	1	seconds
ECU Time - Milliseconds	887	ms

HCP | U0415-00 | Stored | Invalid Data Received from Anti-Lock Brake System (ABS) Control Module "A"-

NAME	VALUE	UNITS
DTC	C4 15 00	
Test Failed	False	
Test Failed This Operation Cycle	True	
Pending DTC	True	

Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	Occurrence	
Original Odometer Value	36896.0	miles
Most Recent Odometer Value	36896.1	miles
Frequency Counter	3	
Ignition Cycle Counter	1	
Real time clock	53897568	sec
RAM stamps keyOn	75	sec
RAM Stamps	230809	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
Engine Speed	0	rpm
HV Battery SOC	32	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Motor A Temp Sensor	81	°F
Motor B Temp Sensor	84	°F
Barometric Pressure	12	PSI
Engine Coolant Temperature	79	°F
Internal EPS Voltage Sense A	8.208	Volts
Internal EPS Voltage Sense B	8.136	Volts
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.000	Ft-Lbs
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.000	Ft-Lbs
Available Motor Torque - Motor A	87.205	Ft-Lbs
Available Motor Torque - Motor B	232.393	Ft-Lbs
Available Regen Torque - Motor A	-87.205	Ft-Lbs
Available Regen Torque - Motor B	-232.393	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor A - Inverter Current - phase A	0	AMP
Motor A - Inverter Current - phase B	0	AMP
Motor A - Inverter Current - phase C	-4	AMP
Motor B - Inverter Current - phase A	0	AMP
Motor B - Inverter Current - phase B	-4	AMP
Motor B - Inverter Current - phase C	-4	AMP
Motor B Resolver Angle	188	Degree

Motor A Resolver Angle	222	Degree
Electric Motor A Speed	1.0	rpm
Electric Motor B Speed	1.5	rpm
PIM DC Link Voltage - A	348	Volts
PIM DC Link Voltage - B	350	Volts
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
HCP System Shutdown Command	Default	
HV Battery Voltage from BPCM	348.80	Volts
SW Build Release Version	PIM_21B_2011B0_RU_HCP___	
HCP SW Version	21B	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Closed	
APM Status	Buck CV	
Impact Event	False	
Outside Air Temperature	75.2	°F
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Battery Feed Voltage 1 Sense	14.544	Volts
Battery Feed Voltage 2 Sense	14.544	Volts
Battery Feed Voltage 3 Sense	14.400	Volts
Hybrid System State	Inverters Enabled	
Inverter A IGBT Temperature for phase A	81	°F
Inverter A IGBT Temperature for phase B	82	°F
Inverter A IGBT Temperature for phase C	81	°F
Inverter B IGBT Temperature for phase A	82	°F
Inverter B IGBT Temperature for phase B	82	°F
Inverter B IGBT Temperature for phase C	82	°F
PHEV Charging Status	No Charging	
Distance Travelled with Light ON	0	miles
GPS Date - Year	2022	Year
GPS Date - Month	8	
GPS Date - Day	30	Days
UTC Time - Hours	14	Hours
UTC Time - Minutes	8	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	813	ms

HCP | U1852-00 | Stored | Implausible Data Received from ABS on D-PT-

NAME	VALUE	UNITS
DTC	D8 52 00	
Test Failed	False	
Test Failed This Operation Cycle	True	

Pending DTC	True	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	True	
Occurrence flag	Occurrence	
Original Odometer Value	36896.0	miles
Most Recent Odometer Value	36896.1	miles
Frequency Counter	3	
Ignition Cycle Counter	1	
Real time clock	53897568	sec
RAM stamps keyOn	75	sec
RAM Stamps	230809	Min
Accelerator Pedal Position	0	%
Brake Switch Status	Not Applied	
Engine Speed	0	rpm
HV Battery SOC	32	%
Ignition State	Reserved	
PRND Position Display	P	
Propulsion System Active	False	
Vehicle Speed	0.0000	MPH
Motor A Temp Sensor	81	°F
Motor B Temp Sensor	84	°F
Barometric Pressure	12	PSI
Engine Coolant Temperature	79	°F
Internal EPS Voltage Sense A	8.208	Volts
Internal EPS Voltage Sense B	8.136	Volts
Motor A Torque	0.000	Ft-Lbs
Motor B Torque	0.000	Ft-Lbs
Actual Torque - Motor A	0.000	Ft-Lbs
Actual Torque - Motor B	0.000	Ft-Lbs
Available Motor Torque - Motor A	87.205	Ft-Lbs
Available Motor Torque - Motor B	232.393	Ft-Lbs
Available Regen Torque - Motor A	-87.205	Ft-Lbs
Available Regen Torque - Motor B	-232.393	Ft-Lbs
Commanded Torque - Motor A	0.000	Ft-Lbs
Commanded Torque - Motor B	0.000	Ft-Lbs
Motor A - Inverter Current - phase A	0	AMP
Motor A - Inverter Current - phase B	-4	AMP
Motor A - Inverter Current - phase C	0	AMP
Motor B - Inverter Current - phase A	0	AMP
Motor B - Inverter Current - phase B	-4	AMP
Motor B - Inverter Current - phase C	0	AMP

Motor B Resolver Angle	188	Degree
Motor A Resolver Angle	222	Degree
Electric Motor A Speed	1.0	rpm
Electric Motor B Speed	1.5	rpm
PIM DC Link Voltage - A	348	Volts
PIM DC Link Voltage - B	350	Volts
HCP ePT Wake-Up Output	On	
CBC Wake-Up Input	On	
HCP System Shutdown Command	Default	
HV Battery Voltage from BPCM	348.80	Volts
SW Build Release Version	PIM_21B_2011B0_RU_HCP_	
HCP SW Version	21B	
EPT LOC Diag Enable	Enable LOC Diagnostic	
HV Contactor Status	Closed	
APM Status	Buck CV	
Impact Event	False	
Outside Air Temperature	75.2	°F
OBCM Operating Mode	UTC	
J1772 Prox Detected State	Prox Out	
HV Battery Sleep Time	0	Days
Battery Feed Voltage 1 Sense	14.544	Volts
Battery Feed Voltage 2 Sense	14.544	Volts
Battery Feed Voltage 3 Sense	14.400	Volts
Hybrid System State	Inverters Enabled	
Inverter A IGBT Temperature for phase A	81	°F
Inverter A IGBT Temperature for phase B	82	°F
Inverter A IGBT Temperature for phase C	81	°F
Inverter B IGBT Temperature for phase A	82	°F
Inverter B IGBT Temperature for phase B	82	°F
Inverter B IGBT Temperature for phase C	82	°F
PHEV Charging Status	No Charging	
Distance Travelled with Light ON	0	miles
GPS Date - Year	2022	Year
GPS Date - Month	8	
GPS Date - Day	30	Days
UTC Time - Hours	14	Hours
UTC Time - Minutes	8	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	813	ms

CVPM | B23C7-92 | Stored | Right Camera-Performance or Incorrect Operation

NAME	VALUE	UNITS
DTC	A3 C7 92	
Test Failed	False	

Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	ERROR	
Original Odometer Value	33882	miles
Most Recent Odometer Value	36765	miles
Frequency Counter	13	
Ignition Cycle Counter	26	
DTC Extended Data Record Number 2	2	
ECU Failure – Internal Voltage	Off	
ECU Failure – ECU Memory	Off	
ECU Failure – Internal Communication Error	Off	
ECU Failure – Video Subsystem Error	Off	
ECU Failure – Watchdog Error	Off	
Calibration Failure - Calibration not Executed	Off	
Calibration Failure - Calibration Data Inconsistent	Off	
Battery Voltage	14.6	V
ECU Voltage	14.3	V
Vehicle Speed	9.505037	MPH
Ignition Status	Ignition Status: Running	
Steering Wheel Angle	122.5	Deg
Steering Wheel Angle Status	Steering Wheel Status: Okay	
Driver Door Ajar	Inactive	
Rear Left Door Ajar	Inactive	
Passenger Door Ajar	Inactive	
Rear Right Door Ajar	Inactive	
Reverse Gear	Inactive	
Liftgate Ajar	Inactive	
Touch Screen Status	Touch Screen Status: Not Pressed	
Touch Screen X Coordinate	0000	
Touch Screen Y Coordinate	0000	
Radio Display Status	Display Status: Off	

SNAPSHOT DATA SUMMARY

No Snapshot Data available for U140C

No Snapshot Data available for U11BB-00

No Snapshot Data available for C2227-00

RADIO | B1431-00 | Stored | Bluetooth Antenna Internal Performance-

Record 0

NAME	VALUE	UNITS
DTC	94 31 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

Record 1

NAME	VALUE	UNITS
DTC	94 31 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

Record 2

NAME	VALUE	UNITS
DTC	94 31 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

Record 3

NAME	VALUE	UNITS
DTC	94 31 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	

No Snapshot Data available for P0A43-00

No Snapshot Data available for U0415-00

No Snapshot Data available for U1852-00

No Snapshot Data available for B23C7-92

[Clear Form](#)

AUTOMATIC TRANSMISSION DIAGNOSTIC WORKSHEET

[Save to PC](#)[Print](#)

This information will be used by FCA US. Powertrain Engineering during the assembly tear down review.

All Fields that are visible or become visible are required to be completed.

Dealer Code	:	27198	Dealer Name	:										
Contact Name	:				Phone Number	:								
VIN Last 8	:		Mileage	:	36895	Date	:	Aug 30, 2022	RO #	:	416093	Tech	:	

Verified Complaint : ☒ Yes ☐ No

Transmission Type : 948TE Engine Type : ☒ Gas ☐ Diesel

[Fluid Level Instructions Show/Hide](#)

Using the Scan tool and indicator special tool outlined under Standard Procedure - Fluid Level and Condition check add the transmission temperature and level below.

Fluid Temp F : 185 Fluid Level mm. : 25 **The Fluid Level is Within the specification of 22-29 mm.**

Fluid Condition : Burnt

Primary Concern : No Engagement Concern Area : Into Drive or Reverse

Concern Details : vehicle shut off. hybrid trans, has motor code p0a43-00, not in list below

DTC Set? : ☐ Yes ☒ No



TKT
CUB
01010
#

