


INFORMATION REDACTED PURSUANT TO THE FREEDOM OF INFORMATION ACT (FOIA), 5 U.S.C. 552(B)(6)


WI
TECH 2.0

CONFIGURATION REPORT

Vehicle 2022 JEEP WRANGLER 2.0L I4 DOHC DI TURBO PHEV ENGINE
VIN [REDACTED]

Odometer 1112.6 miles
Publication Date Apr 29, 2022, 11:34:27 AM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
TCM	Transmission Control Module	CAN-C	68563825AB	[REDACTED]	[REDACTED]	68563825AB
PCM	Powertrain Control Module	CAN-C	05188195AC			05188195AC
ASBS	Automatic Sway Bar System	CAN-C	68570943AA			68570943AA
ICS	Integrated Center Stack	CAN-I	6SX94DX9AE			6SX94DX9AE
RFH	Radio Frequency Hub	CAN-C	56029925AB			56029925AB
ESM	Electronic Shifter	CAN-C	04670716AD			04670716AD
DTCM	Drive Train Control Module	CAN-C	68547689AB			68547689AB
ORC	Occupant Restraint	CAN-C	68526670AB			68526670AB
EPS	Electric Power Steering	CAN-C	68529427AC			68529427AC
HVAC	Heat, Ventilation and A/C	CAN-I	52080486AB			52080486AB
CSWM	Comfort Seat Wheel Module	CAN-I	68530204AB			68530204AB
AMP	Amplifier	CAN-I	68549084AB			68549084AB
IPC	Instrument Panel Cluster	CAN-C	68525023AA			68525023AA
PTS	Parktronics	CAN-C	68441031AC			68441031AC
SCCM	Steering Column Control Module	CAN-C	68526258AA			68526258AA
BCM	Body Controller	CAN-C	68525356AC			68525355AC
RADIO	Radio	CAN-I	68472587AJ			68472587AJ
OCM	Occupant Classification	CAN-C	68403128AA			68403128AA
LBSS	Left Blind Spot Sensor	CAN-I	68454896AA			68454896AA
RBSS	Right Blind Spot Sensor	CAN-I	68454896AA			68454896AA

BPCM	Battery Pack Control Module	CAN-C	05193168AH		05193168AH
HCP	Hybrid Control Processor	CAN-C	68540073AB		68540073AB
AHCP	Auxiliary Hybrid Control Processor	CAN-C	68540084AB		68540084AB
ABSO	Anti Lock Brakes OBD	CAN-C	68532850AC		68532850AC
SGW	Security Gateway Module	CAN-C	68532299AB		68532299AB
DPDM	Driver Presence Detection Module	CAN-C	68403129AA		68403129AA
DASM	Driver Assistance System Module	CAN-C	04672888AC		04672888AC
IDCM	Integrated Dual Charge Module	CAN-C	05185035AQ		05185035AQ

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	CVNS
TCM	USA / USA	13 05 0E	15 2B 00	4700	5033262D
PCM	USA	1D 47	21 22 00	4928	A51CF452
ASBS	USA	10 01 00	15 0E 01	4500	
ICS	USA	10 1E 00	14 33 00	4802	
RFH	USA / USA	10 17 00	15 1D 00	4604	
ESM	USA	15 18 00	12 2A 00	4322	
DTCM	USA	11 22 00	15 0A 01	4501	
ORC	USA	14 0B 00	14 12 01	4501	
EPS	USA	10 13 00	14 31 DC	4005	
HVAC	USA	13 20 00	15 01 01	4420	
CSWM	USA	11 2A 00	15 06 00	4202	
AMP	USA	21 01 01	15 16 00	4034	
IPC	USA	17 17 01	15 0B 01	4805	
PTS	USA	10 32 01	13 24 03	4401	
SCCM	USA	13 28 00	13 29 00	4301	
BCM	USA	0D 11 00	15 21 50	4630	
RADIO	USA	15 20 14	15 20 14	8205	
OCM	USA	11 31 01	11 07 04	4060	
LBSS	USA	11 23 01	12 25 00	4204	
RBSS	USA	11 23 01	12 25 00	4204	
BPCM	Rest of world / ROW	13 0C 04	15 24 42	5701	49906456
HCP	USA	15 0C 04	15 29 01	5403	6F5143CE 20A924DE 4C99835C
AHCP	USA	15 0C 04	14 33 01	5600	
ABSO	USA	15 26 00	15 22 03	4300	D74722B2
SGW		5	1125	4103	
DPDM	USA	11 31 01	11 0F 04	4510	
DASM	USA	11 0E 00	15 26 01	401C	

IDCM	USA	15 0E 00	15 28 00	4000	
------	-----	----------	----------	------	--

CONFIGURATION

TCM CONFIGURATION

NAME	VALUE	UNITS
ERS/Autostick/Tip Non-paddle on Shifter in D position equipped	False	
4WD with switchable Lo Range equipped	False	
FWD Equipped	False	
Short Learn Enabled	False	
ERS/Autostick/Tip Non-paddle on Shifter in A or M position equipped	False	
ERS/Autostick/Tip Non-paddle on Steering Wheel equipped	True	
Shifter with Sport Mode Position Equipped	False	
Overdrive Off or Tow Haul Mode Switch or Virtual Switch (Non-Terrain) Equipped	False	
ECO/Optimizer Switch Equipped	False	
Engine Start/Stop equipped	False	
Sport Mode Switch or Virtual Switch (Non-Terrain) Equipped	False	
Shifter with Low Mode Position Equipped	False	
Autostick/ERS On/Off Switch Equipped	False	
Paddle-Shift Switches Equipped	False	
RWD Equipped	False	
Long Learn Enabled	False	
AWD Equipped	False	
Polystable E-shift (Cableless without return-to-center) equipped	False	

PCM CONFIGURATION

NAME	VALUE	UNITS
Active Exhaust Pressure Sensor Equipped	False	
Secondary Mass Airflow Sensor Equipped	False	
Active Exhaust Valve(s) Equipped	False	
Electronic Parking Brake Equipped	False	
Aux Coolant Pump Heater Equipped	False	
Heater Temp Control Valve Equipped	False	
Wastegate HBridge Equipped	True	
Mechanical Coolant Pump Equipped	False	
High Side Port Tumble Valve Equipped	False	
Cooled EGR Equipped	True	
Auxillary Coolant Pump Equipped	True	
Supercharger Equipped	False	
HPT 6-Speed Trans Equipped	False	
Hybrid MEC Shifter Equipped	False	
ZF 9-Speed Trans Equipped	False	
CNG Large Gas Tank Equipped	False	
PTO System Equipped	False	
Dual Alternator Gen1 Capable	False	

Engine Idle Shutoff Equipped	False	
Low Temp Radiator Coolant Pump Equipped	False	
Dual Fuel Tank Equipped	False	
A/C Relay Powered from Engine Switched Battery	False	
Engine Oil Pressure Sensor Type	255	None
2.0 Liter I4 Direct Injection Engine	True	
Coolant On-Off Pump Equipped	Equipped	
1.0 Liter I3 Engine	False	
Variable Valve Lift Equipped	Not Equipped	
Primary Lin Alternator Equipped	Not Equipped	
Active Exhaust Pressure Sensor Equipped	False	
Exhaust Cam 1 Equipped	True	
Active Exhaust Valve Equipped	False	
Linear PWM Fan Relay System Equipped	True	
Auxiliary Coolant Pump Equipped	True	
3.6 Liter V6 Engine	False	
EMAT (Getrag DCT transmission) Equipped	False	
Primary Lin Alternator Equipped	False	
Knock Sensor 1 Equipped	True	
4 Speed Automatic Transmission Equipped	False	
Electric Water Pump Equipped	False	
3.5 Liter V6 Engine	False	
Power Steering Switch Equipped	False	
Auxiliary Heater Electric Water Pump Equipped	False	
Fiat 940 Compact Equipped	False	
Adaptive Cruise Control Equipped	True	
Unleaded Gasoline Fuel	True	
Active Engine Mount Equipped	False	
4.7 Liter V8 Engine	False	
ICC Cruise Equipped	False	
6.4 Liter V8 Engine	False	
Transmission Software Included	False	
ETC Cruise equipped	False	
Rear Heater Equipped	False	
AC Equipped	False	
TIP Equipped	True	
Buffered Crank Output for ANC (Active Noise Cancellation) Equipped	True	
Buffered Crank Output for PHEV Engine Pulse Calculation Equipped	True	
Continuous Variable Transmission Equipped	False	
SRV Equipped	False	
Dual Speed Fuel Pump Equipped	False	
O2 Sensor Bank 1 Sensor 3 Equipped	False	
Air Shutoff Valve Bank 2 Control Solenoid 2 Equipped	False	
2 Speed Fan 3 Driver 3 Relay System Equipped	False	

Dual Fuel Tank Equipped	False	
PWM Fan Motor System Equipped	False	
Brake Pedal Sensor Equipped	True	
Constant Heater Temperature Control Valve Equipped	False	
GPEC3 Equipped	False	
VLP Is Learnable Indicator	False	
1 Speed Fan Mechanical Relay System Equipped	False	
Engine Oil Heater Cooler Equipped	True	
Fiat VIN Learning Strategy Equipped	False	
Mechanical Coolant Pump Heater Equipped	False	
2.0 Liter WI4 engine	False	
VFS Actuators Available Indicator	False	
O2 Sensor Bank 1 Sensor 1 Equipped	True	
Coolant On-Off Valve Equipped	False	
45RFE / 545RFE / 65RFE	False	
Vehicle Speed Sensor #1 Calculated by ECU	False	
Shift Indicator Lamp Equipped	False	
Wide Range O2 Sensor 1/1 Equipped	True	
GPEC2 Equipped	False	
Supercharger Equipped	False	
Variable Displacement AC Equipped	False	
1.0 Liter I3 Engine	False	
Electric Thermostat Heater Equipped	False	
2 Speed Fan PWM Relay System Equipped	False	
PTO System Equipped	False	
High Side Port Tumble Valve Equipped	Undefined	
Tumble Generator Valve Equipped	False	
3.8 Liter V6 Engine	False	
3.0 Liter V6 Engine	False	
Starter Relay 2 Equipped	False	
40TE / 41TE / 41TEA	False	
Wastegate H-Bridge Equipped	01	
Linear EGR Equipped	False	
ZF 9-Speed Transmission Equipped	False	
Direct Injection Equipped	True	
Cummins Equipped	False	
3.3 Liter V6 Engine	False	
ESIM Equipped	False	
Hybrid Electric Vehicle Equipped	True	
WI4 Variable Valve Timing Equipped	True	
Engine Idle Shutoff Equipped	False	
Intake Cam 1 Equipped	True	
O2 Sensor Bank 2 Sensor 1 Equipped	False	
3.2 Liter V6 Engine	False	

Cooled EGR Equipped	True	
Air Shutoff Valve Bank 1 Control Solenoid 2 Equipped	False	
VLP Equipped Indicator	False	
Low Temperature Radiator Coolant Pump Equipped	False	
Dual Stage Oil Pump Equipped	True	
CUSW PROXI Write Programming Support Enabled	True	
6.1 Liter V8 Engine	False	
42RLE	False	
Humidity, Temperature and Pressure Sensor (LIN) Equipped	False	
Compressed Natural Gas Equipped	False	
HPT 6-Speed Transmission Equipped	False	
Secondary Fuel Pump Equipped	False	
Adaptive Cruise Control Hardware Equipped	False	
2.7 Liter V6 Engine	False	
WI4 Intake Flow Control Valve Equipped	False	
Engine Stop Start Equipped	False	
Coolant On-Off Pump Equipped	True	
MDS Equipped	False	
DUAL_ALTERNATOR_GEN1_LEARNEDCOPY	False	
Next Gen Bus Equipped	False	
2.4 Liter WI4 engine	False	
Transmission Oil Heater Equipped	False	
Brushless PWM Fan Equipped	FAN_PWM_BOSCH_BRUSHLESS_CNFG	
Auxiliary Coolant Pump Heater Equipped	Undefined	
2 Speed Fan Mechanical Relay System Equipped	False	
Aisin 6-Speed RWD Transmission Equipped	False	
CMCV H-Bridge Equipped	Undefined	
Turbine Volute Valve Actuator Equipped	Undefined	
MultiAir Equipped	False	
Active Grille Shutter Equipped	False	
Intake Cam 2 Equipped	False	
Electronic Throttle Control Equipped	True	
O2 Sensor Bank 1 Sensor 2 Equipped	True	
Duty Cycle Purge Valve Equipped	True	
Throttle Inlet Temp Sensor Equipped	True	
Fixed displacement AC Equipped	False	
Yaw Rate Sensor ESC Equipped	True	
3 Speed Fan Mechanical Relay System Equipped	False	
Air Shutoff Valve Bank 1 Control Solenoid 1 Equipped	False	
Clutch Interlock Switch Equipped	False	
Powernet Equipped	False	
Electric Coolant Valve Equipped	False	
Electronic Automatic Transmission (EATX) Equipped	False	
4 Button Integrated Cruise Control	False	

Inrush Current Reduction Relay Equipped	False	
1.8 Liter W14 engine	False	
Trans Reverse Lockout Equipped	False	
CUSW (11-Bit) Equipped	False	
4.0 Liter I6 Engine	False	
Sensorless FFV Enabled	False	
3.7 Liter V6 Engine	False	
Knock Sensor 2 Equipped	True	
Battery Temp Sensor Equipped	False	
GPEC2A Equipped	False	
Barometric Sensor Equipped	True	
Exhaust Cam 2 Equipped	False	
AC Equipped Over Bus	False	
5.7 Liter V8 Engine	False	
Linear Purge Equipped	False	
Unleaded diesel fuel	False	
Electronic Vacuum Pump Equipped	False	
Dual Fuel Pressure Sensor Equipped	False	
Oil Pressure Sensor Enabled	True	
Fan Wake Up Relay System Equipped	False	
Turbocharger Equipped	True	
62TE	False	
Wide Range O2 Sensor 2/1 Equipped	False	
MTV Solenoid Equipped	False	
ERS Equipped Indicator	False	
O2 Sensor Bank 2 Sensor 2 Equipped	False	
Electronic Coolant Pump Equipped	False	
Variable Speed Fuel Pump Equipped	True	
Engine Software In Package	True	
Vehicle Speed Sensor #1 Calculated from CAN	False	
Viscosity Sensor Equipped	False	
VMM Equipped	False	
A/C Equipped	True	
6.2 Liter V8 Engine	False	
CUSW (29-Bit) Equipped	False	
GPEC4 Equipped	True	
Secondary Air Equipped	False	
Port Flap Valve Equipped	False	
66RFE / 68RFE	False	
TOOLCONFIG_OIL_PRESS_ABS_EQUIPPED	True	
Operator Idle Speed Request Equipped	False	
Police Package Equipped	False	
Trans Skip Shift Equipped	False	
Mass Airflow System Equipped	False	

Operator Idle Speed Request Equipped	False	
INTAKE O2 SENSOR EQUIPPED	False	
Clutch Sensor Equipped	False	
5 Button Cruise (LIN) Equipped	True	
LIN Humidity, Temp, and Pressure Sensor Equipped	False	
Make Up Air Sensor Equipped	True	
Brake Pedal Sensor Equipped	True	
Cylinder Pressure Sensor Equipped	False	
SWAP HARDWIRED BRAKE SWITCH INPUTS	True	
Power Steering Angle Sensor Mandatory	False	
Bi-Directional Crank Sensor Equipped	True	
Dual Fuel Pressure Sensor Equipped	False	
Throttle Inlet Temp Sensor Equipped	True	
CUSW 4-Button Cruise Equipped	False	
Remote Start Present	Present	

ICS CONFIGURATION

NAME	VALUE	UNITS
Display Type (Base)	True	
Display Type (High)	False	
Display Type (Mid)	False	

RFH CONFIGURATION

NAME	VALUE	UNITS
Base TPM Present	Not Set	
Full Size Matching Spare Tire Present	Set	
Fob Location #3 Successfully Programmed	No	
Valid Key In Ignition	Yes	
Fob Location #4 Successfully Programmed	No	
Secret Key Sent to Body Controller - Most recent attempt	Yes	
Fob Location #7 Successfully Programmed	No	
Fob Location #8 Successfully Programmed	No	
Secret Key Sent to Body Controller - Original attempt	Yes	
Fob Location #1 Successfully Programmed	Yes	
RFHub Locked	RFHUB Locked after IAC write	
PIN Successfully Programmed	Yes	
Fob Location #6 Successfully Programmed	No	
Fob Location #2 Successfully Programmed	Yes	
VIN Successfully Programmed	Yes	
Fob Location #5 Successfully Programmed	No	
Passive Entry	True	
TPMS Configuration	Logic 1 NHTSA Enable Warning	
Tire Pressure System	True	
Auto Park Present	True	

Module Configuration Status	True	
Secret Codes Programmed	True	
\$0214 Programmed by	Programmed by FCA manufacturing	
e-shifter present	True	
Selectable Tire Fill Alert	False	
TPM Auto-Locate Enabled	True	
RKE	True	
Ignition system type connected	KIN system	
Remote Start Present	True	
Keyless Go	True	
Back Up Customer Settings Menu 1 (CSM1)	True	
Back Up Customer Settings Menu 2 (CSM2)	True	
Back Up Vehicle Config 1	True	
Back Up ECU Configuration 13	True	
Back Up Vehicle Config 5	True	
Back Up ECU Configuration 2	True	
Back Up Vehicle Config 2	True	
Back Up ECU Configuration 10	True	
Back Up Vehicle Config 6	True	
Back Up Vehicle Config 7	True	
Back Up ECU Configuration 3	True	
Back Up ECU Configuration 4	True	
Back Up Vehicle Config 4	True	
Back Up ECU Configuration 14	True	
Back Up ECU Configuration 11	True	
Back Up ECU Configuration 6	True	
Back Up ECU Configuration 17	True	
Back Up Programmed ECUs: P/T Chassis Network	True	
Back Up ECU Configuration 1	True	
Back Up ECU Configuration 15	True	
Back Up ECU Configuration 8	True	
Back Up ECU Configuration 16	True	
Back Up ECU Configuration 12	True	
Back Up ECU Configuration 9	True	
Back Up Programmed ECUs: Cabin Network	True	
Back Up ECU Configuration 7	True	
Back Up Vehicle Config 3	True	
Back Up ECU Configuration 5	True	
Hardware Configuration: Remote Start Antenna	Present	
Hardware Configuration: Front Left Door Handle H/W	Serial AP	
Hardware Configuration: Trunk Door Handle H/W	Serial AP	
Hardware Configuration: Rear Right Door Handle H/W	No AP	
Hardware Configuration: Front Right Door Handle H/W	Serial AP	
Hardware Configuration: Rear Left Door Handle H/W	No AP	

ECU Ship Status

Normal Mode

DTCM CONFIGURATION

NAME	VALUE	UNITS
Rear Locker Present	True	
FAD Present	True	
Mode Switch Present	True	
Full-Time T-Case	True	
Front Locker Present	True	
SRT Present	—	
T-Case Type	MPT 3025C	
Left/Right Hand Drive	Left Hand Drive	
Axle Ratio	4.100	

ORC CONFIGURATION

NAME	VALUE	UNITS
Right Curtain Squib 1	Not Configured	
Driver Seatbelt Retractor Pretensioner	Configured	
Passenger Seatbelt Anchor Pretensioner	Configured	
Driver Frontal Squib 2	Configured	
Left B-Pillar Impact Acceleration Sensor	Configured	
Right Side Door Pressure Sensor	Not Configured	
First Row Driver Seatbelt Buckle Switch	Configured	
First Row Passenger Seatbelt Buckle Switch	Configured	
Right B-Pillar Impact Acceleration Sensor	Configured	
Passenger Seatbelt Load Limiter	Configured	
Driver Frontal Squib 1	Configured	
Configuration Column Identifier	A2	
Passenger Frontal Squib 3	Configured	
Second Row Left Seat Side Airbag	Not Configured	
Passenger Seat Track Position Sensor	Configured	
Right Up-Front Acceleration Sensor	Configured	
Second Row Center seat belt Switch	Not Configured	
Passenger Frontal Squib 2	Configured	
Passenger Frontal Squib 1	Configured	
EPPM	Not Configured	
Passenger Seatbelt Buckle Pretensioner	Not Configured	
Right Side Seat Squib 1	Configured	
Driver Seat Track Position Sensor	Configured	
Passenger Airbag Disable Indicator	Configured	
Driver Frontal Squib 4	Not Configured	
Left Curtain Squib 1	Not Configured	
Driver Seatbelt Anchor Pretensioner	Configured	
Passenger Seatbelt Retractor Pretensioner	Configured	

Second Row Right seat belt Switch	Not Configured	
Right C-Pillar Impact Acceleration Sensor	Not Configured	
Driver Frontal Squib 3	Configured	
Passenger Airbag Disable Switch	Not Configured	
Occupant Classification (OCM)	Configured	
Left Side Door Pressure Sensor	Not Configured	
Left D-Pillar Impact Acceleration Sensor	Not Configured	
Second Row Left seat belt Switch	Not Configured	
Driver Seatbelt Buckle Pretensioner	Not Configured	
Passenger Knee Bolster Squib	Not Configured	
Passenger Frontal Squib 4	Not Configured	
Right D-Pillar Impact Acceleration Sensor	Not Configured	
Left Up-Front Acceleration Sensor	Configured	
Driver Knee Bolster Squib	Not Configured	
Second Row Right Seat Side Airbag	Not Configured	
Rollover Sensing	Not Configured	
Passenger Occupant Detection Sensor	Not Configured	
Driver Seatbelt Load Limiter	Configured	
Left C-Pillar Impact Acceleration Sensor	Not Configured	
Left Side Seat Squib 1	Configured	

HVAC CONFIGURATION

NAME	VALUE	UNITS
DualZone ATC Control	True	
MTC Without EBL (3Knob)	False	
MTC heater only (3Knob)	False	
Single Zone MTC Control	False	
Dual Zone MTC Control	False	
DualZone ATC Control (Factory)	False	
MTC With EBL (3Knob)	False	

AMP CONFIGURATION

NAME	VALUE	UNITS
ANC Status	Off - RPM Out of Range	
ANC Calibration Date - Year	20	
ANC Calibration Date - Patch Level	0	
ANC Calibration Date - Week	6	
Surround Sound Activated	Not Set	
Current ANC Calibration ID - Service	B602	
Premuim - 3	False	
Premuim - 2	True	
No HALF Chimes	True	
Non -ANC	False	
No Rear Doors	True	

Premuim - 1	False	
Door Module - Right Front	Not Present	
Door Module - Left Front	Not Present	

IPC CONFIGURATION

NAME	VALUE	UNITS
Main Fuel Tank Gauge - Full Stop Calibration	0.000	Volts
Main Fuel Tank Gauge - 1/2 Datum Calibration	0.000	Volts
Main Fuel Tank Gauge - 3/4 Datum Calibration	0.000	Volts
Main Fuel Tank Gauge -1/4th Datum Calibration	0.000	Volts
Main Fuel Tank Gauge - Empty Stop Calibration	0.000	Volts
Sub Fuel Tank Gauge - Empty Stop Calibration	0.000	Volts
Sub Fuel Tank Gauge - 1/2 Datum Calibration	0.000	Volts
Sub Fuel Tank Gauge - 3/4 Datum Calibration	0.000	Volts
Sub Fuel Tank Gauge - Full Stop Calibration	0.000	Volts
Sub Fuel Tank Gauge - 1/4 Datum Calibration	0.000	Volts

PTS CONFIGURATION

NAME	VALUE	UNITS
Rear System with 6 Front Sensors	False	
Front System with 6 Rear Sensors	False	

SCCM CONFIGURATION

NAME	VALUE	UNITS
Rear Wiper	True	
Paddle Shifter	False	
Cruise Control / ACC	True	
Tilt Telescope	False	

BCM CONFIGURATION

NAME	VALUE	UNITS
Number of Reprogramming Attempts - Counter #0	0	
Vehicle Configuration Programmed Status	True	
Last Programmed Status	Manufacturing	
Programmed Network Configuration - Audio / Telematics Network	2	
ECU Configuration 3	2	
ECU Configuration 6 (Suspension)	2	
Programmed ECUs: Cabin Network	2	
ECU Configuration 15 (CBC Features)	2	
ECU Configuration 8 (LIN and Miscellaneous)	2	
Vehicle Configuration 7 - Write Counter	2	
ECU Configuration 12	2	
Vehicle Configuration Auto Write Counter	1	
ECU Configuration 4	2	

ECU Configuration 11	2	
ECU Configuration 6 (Brake)	2	
ECU Configuration 9 (ITM)	2	
ECU Configuration 5 (Wireless)	2	
Vehicle Configuration 6 - Write Counter	2	
ECU Configuration 5 (Memory)	2	
ECU Configuration 2 (CBC Features)	2	
ECU Configuration 5 (Doors)	2	
Vehicle Config CSM1	2	
ECU Configuration 10	2	
ECU Configuration 14	2	
Programmed ECUs: P/T Chassis Network	2	
Vehicle Configuration 1 - Write Counter	2	
Vehicle Configuration 5 - Write Counter	2	
Vehicle Config CSM2	2	
ECU Configuration 6 (Safety)	2	
Vehicle Configuration 4 - Write Counter	2	
ECU Configuration 1 (CBC Configurable Inputs and Outputs)	2	
Vehicle Configuration 2 - Write Counter	2	
ECU Configuration 7 (CBC Exterior Lighting Calibrations)	2	
Vehicle Configuration 3 - Write Counter	4	
ECU Configuration 9A	2	
ECU Configuration 13	2	
Programmed ECUs: Hybrid LAN Network	2	
ECU Configuration 15 (Suspension)	2	
ECU Configuration 6 (Powertrain)	2	
Last Configuration Odometer	0	miles
Remote Start Present	Set	
Left/Right Hand Drive	Left Hand Drive	
Special Packages	Default	
Shifter Type	5 Pos Polystable Eshifter / Type PS5	
Auto Highbeam	Set	
PTS Configuration	Rear / REAR	
Vehicle Line	JL	
Emode Present	Not Set	
Model Year	2022	
Maximum Vehicle Speed	94	MPH
Hill Descent Feature Present	Not Set	
Country Code	USA	
Select Speed Control Feature Present	Set	
Drive Configuration	Selectable 4wd	
Performance Pages Present	Not Present	
Body Style	4-Door Hatchback	
SKIM System Present	Not Set	

Power Inverter Type	No Power Inverter	
Rain Sensor Present	Not Set	
Off Road Capable	Not Set	
Air Conditioning Present	Set	
Max Load Inflation Pressure Front Tire	37.0	PSI
Full Size Spare	Set	
Max Load Inflation Pressure Rear Tire	37.0	PSI
Cruise Feature is Present	Not Set	
Thatcham Present	Not Set	
Special Packages	Wrangler Rubicon / Wrangler Rubicon	
Flipper Glass Present	Not Set	
Light Load Inflation Pressure Rear Tire	0.0	PSI
Secondary Lock Present	Not Set	
Door Alert Feature Present	Not Set	
Vehicle Brand	Jeep	
Passive Entry Present	Set	
HVAC Configuration	Dual Zone ATC	
Chassis Type	Type 83	
ESCL system present	Not Set	
Paddle Shift Feature Present	Not Set	
Display Outside Temperature Present	Set	
ELV Present	Not Set	
T-Case Type	Transfer Case 246 / Transfer Case 246	
Interior EC Mirror Present	Set	
RKE System Present	Set	
Fuel Capacity	17	gallons
Wheel Base	Long wheel base (140" & 149" Ram Truck) / LONG	
Power Lift Gate Present	Not Set	
FOBIK Safe Enable	Set	
Display Compass Heading Present	Set	
Sunshade Present	Not Set	
Collision Mitigation System present	Set	
Window Express Feature Configuration	Drivers window express only	
Base TPM system present	Not Set	
Power Left Sliding Door Present	Not Set	
Two Fuel Sending Units Present	Not Set	
Auto Headlamp Feature Present	Set	
Auto Park Present	Set	
Forward Collision Warning present	Set	
Keyless Go Present	Set	
Liftgate/Trunk Type	Manual Liftgate	
Sport Mode Present	Not Set	
Premium TPM system present	Set	
Power Right Sliding Door Present	Not Set	

Police Lighting Feature	Not Set	
Adjustable Pedal Feature Present (non-Memory)	Not Set	
Disable Display of Radio Clock	Not Set	
Vehicle is an SRT	Not Set	
High Intensity Discharge Head Lamps	Not Set	
Transfer Case Low Range Reduction Ratio	4.000	
Transfer Case High Ratio	1.000	No Unit
Dynamic Tire Circumference (All or Rear)	98	inch
Axle Ratio	4.100	
Dual Rear Wheel (DRW) Vehicle Present	Not Set	
Steering Ratio at Positive Angle 5	0.0	No Unit
Steering Ratio at zero	0.0	No Unit
Non-Regulated Tire Pressure Information System (TPIS) Present	Not Set	
Steering Ratio at Positive Angle 1	0.0	No Unit
Steering Ratio at Positive Angle 4	0.0	No Unit
Steering Ratio at Positive Angle 2	0.0	No Unit
Steering Ratio at Positive Angle 3	0.0	No Unit
Air Quality System Present	Not Set	
Steering Ratio at Negative Angle 5	0.0	No Unit
Analog Door Sensor Configuration	All Doors have Analog Sensors	
Steering Ratio at Negative Angle 1	0.0	No Unit
Steering Ratio at Negative Angle 3	0.0	No Unit
Steering Ratio at Negative Angle 4	0.0	No Unit
Steering Ratio at Negative Angle 2	0.0	No Unit
Reserved - Pin E21	Not Set	
Park Brake Input Present - Pin E11	Set	
Low Beam Output Present - Pin A3, D2	Set	
Reserved - F21	Not Set	
VTA Warning LED Output Present - Pin G22	Set	
Run-ACC Y Relay #2 Output Present - Pin E9	Set	
Hood Ajar Switch Input Present - Pin A11	Set	
Front Fog Lamps Output Present - Pin A1 & D13	Set	
Rear Park Lamps Output Present - Pin E4 & F32	Set	
Trailer Backup Lamps Output Present - Pin E23	Set	
Rear Fog Lamps Output Present - Pin E39 & F5	Not Set	
Reserved - Pin G12	Not Set	
Reserved - Pin D20	Not Set	
Diesel Cabin Heater #2 Output Present - Pin D9	Not Set	
Reserved - Pin E15	Not Set	
Reserved - Pin E35	Not Set	
Gated Park ZFII Output Present - Pin D-24	Set	
Diesel Cabin Heater #3 Output Present - Pin D10	Not Set	
Left Rear Door Ajar Input Present - Pin F23	Set	
Right Dedicated DRL Lamp Output Present - Pin A22	Set	

Inverter Enable Relay Output Present - Pin F35	Set	
Hard Top Sense Present - Pin E14	Set	
Reserved - Pin F4	Not Set	
Side Markers Output Present - Pin A10 & D5	Set	
Starter Relay Lowside Coil Drive - Pin D7	Not Set	
Foot Well Lamps Output Present - Pin G24	Set	
Passenger Door Ajar Signal Present - Pin G18	Set	
Horn Switch Input Present - Pin F29	Set	
Ambient Temperature Sensor Present - Pin D22	Set	
Reserved - E20	Not Set	
Reserved - Pin E47	Not Set	
Ambient Light Dimmer Wheel Input Present Pin G9	Set	
Diesel Cabin Heater #1 Output Present - Pin D11	Not Set	
Left Dedicated DRL Lamps Output Present - Pin D15	Set	
UGDO Feed Output Present - Pin G15	Set	
Rear Turn Lamps Output Present - Pin E3 & F42	Not Set	
Flipper Glass #2 Output Present	Not Set	
Front Driver Analog Door Ajar Input Present - Pin F9	Set	
Rear Wiper Motor Park Present - Pin E29	Set	
LED Dedicated DRL Present	Set	
DRL Lamp Location	Dedicated	
LED Front Fog Lamps Present	Set	
LED Front Turn Lamps Present	Set	
One Touch Lane Change	Set	
LED Rear Fog Lamps Present	Set	
Horn Chirp Allowed	Set	
LED Tail Lamps Present	Set	
Park Lamp Loadshed Enable	Set	
DRL Dropout Enable	Set	
Wiper Service Position Enabled	Not Set	
Single Element Tail Lamp	Not Set	
Intermittent Wiper States	4 Intermittent Wiper position Switch	
LED High Beam Lamps Present	Set	
Exterior Light Loadshed Enable	Set	
LED CHMSL Lamp Present	Set	
LED Reverse Lamps Present	Set	
Door Lock Switch Signal FT RT Usage (F23)	Reserved	
Reversible Washer Pump Enable	Set	
Military Vehicle Present	Not Set	
Front Wiper Wipes After Wash	2 Wipes	
Door Lock Switch Signal FT LT Usage (F9)	Reserved	
LED Rear Turn Lamps Present	Set	
LED License Lamps Present	Set	
Bi Xenon Headlamps Enable	Not Set	

Side Repeaters Enable	Not Set	
Combined Rear Lighting Enable	Set	
Trailer Tow Present	Set	
Rear Wiper Park Enable	Set	
Front Fog Lamp Dropout Enable	Set	
DRL Configuration	Optional DRL	
Quad Headlamps Enable	Set	
Tip Start Enabled	Set	
Tunnel Detection	Not Set	
LED Front Park/Marker Lamps Present	Set	
Hazard Lamp Configuration	Latching Switch	
LED Low Beam Lamps Present	Set	
Headlamp Washer Low Fluid Shut-Off Enable	Not Set	
Front Wiper Park Enable	Set	
LED Stop Lamps Present	Set	
Headlamp Wash Shot	Single	
Headlamp Wash Interval	wash cycle#11	
Dual Start Relay System Present	Not Set	
Heated Steering Wheel Present	Set	
External Port Type	AUX + USB + extra USB	
SDAR Travel Link Present	Set	
Microphone Tuning Parameter	Absent	
Surround Sound Feature Present	Not Set	
CTP Max AC Present	Not Set	
Radio Display On/Off Softkey Present	Not Set	
Destination	United States of America	
Power Inverter Present	Set	
DTV Side Camera Present	Not Set	
Hill Descent Control Present	Not Set	
Hybrid Electric Powertrain Present	Not Set	
Radio Apps Present	Not Set	
Front Heated Seats Present	Set	
VIN Check Digit Diable	Not Set	
Microphone Type	Peiker 300 mv	
Antenna Type	Passive Primary and no secondary antenna	
Power Door Locks Present	Set	
Rear Camera Present	Set	
CTP Easy Entry Enable	Not Set	
Disable CD Eject	Not Set	
Cabin Equilization Curve Number	JL 4 Door Premium Top On (Alpine 12ch)	
Front Park Assist Present	Not Set	
Splashscreen Type	Vehicle Brand	
DAB Present	Not Set	
CTP Passive Entry Present	Set	

Front Ventilated Seats Present	Not Set	
CTP Auto Lock Disable	Not Set	
Hill Start Assist Customer Setting Option Present	Set	
Tow Haul Present	Not Set	
Vehicle Theft Alarm Present	Not Set	
Audio Steering Wheel Switch Configuration	Core Steering Wheel	
Microphone Configuration	2 Microphones	
DTV Front Camera Present	Not Set	
ERS Available	not available	
AMB Dimmer	not available	
Temperature Celsius for UK	Not Set	
Max Gear	Eighth gear	
IC Config Feature	not available	
Type of Gallons	U.K. Gallons	
PTO Present	not available	
Gear Shift Indicator	Not Set	
Split Shaft Present	not available	
Service Interval	20000 km and 730 days	
Heated Seat Present	not available	
Speedometer Range Max Scale	not available	
Virtual Speedometer Units	not available	
Manual Headlamp Leveling	not available	
Rear Wheel Dually	not available	
AP5 Trunk Lock	Smart Switch	
AP1 Left Front	Smart Switch	
AP4 Right Rear	Not Present	
Airport Scenario Trunk Set	Not Set	
AP3 Left Rear	Not Present	
AP2 Right Front	Smart Switch	
Tip Start Present	Set	
Electro-chromatic driver mirror present	Not Set	
Passenger Memory Mirror Present	Not Set	
Sun Shade	Not Set	
Window Motor Type	Not Set	
Folding mirrors present	Not Set	
Passenger Window Lockout	Set	
Blindspot Mirror Present	Not Set	
Global Up	Not Set	
Puddle Lamp Present	Not Set	
Window Hall Sensors Present	Not Set	
Driver Memory Mirrors Present	Not Set	
Rear Door Pre Short Drop	Not Set	
Global Down	Not Set	
Tow Mirror Present	Not Set	

Frameless Window Present	Not Set	
Electro-chromatic passenger mirror present	Not Set	
Auto Power Folding Mirrors Present	Not Set	
Heated Mirrors Present	Set	
Mirror turn signals present	Not Set	
Heated Wheel Material Type	Wood/Leather	
Heated Seat Material Type	Default	
Tilt/Telescope Steering Present	Not Set	
Memory Adjustable Pedals Present	Not Set	
Memory Seat Present	Not Set	
Rear Vented Seats Present	Not Present	
Heated Steering Wheel Present	Present	
Front Heated Seat Present	Present	
Front Vented Seats Present	Not Present	
Rear Heated Seats Present	Not Present	
Brake System ECU Configuration B	Undefined	
Wheel 18 inch overall ESC Maserati	Not Set	
Brake System ECU Configuration A	value 0	
Dual Alternator Present	Not Set	
ECO Mode Configuration	Remember Previous State with Ignition Key Cycle	
Manual Door Locks Present	Not Set	
CHMSL Lamp Output Disable	Not Set	
Front Fog Voltage	13.6	Volts
Rear Fog Voltage	12.0	Volts
Swing Gate Unlock Present - Pin F33	Set	
Auto High Beam Module Location	IRCM	
Secondary Door Ajar Present - Pin E28	Set	
Swing Gate Lock Present - Pin F30	Set	
Rain Sensor Module #2 Present	Not Set	
Nose Dive Threshold	480 degrees	
Brake Smoothing Threshold	375 Nm	
Brake Smoothing Duration	10 periods	
Acceleration Threshold	1.5 m/s ²	
Brake Smoothing Factor	Filter Off	
Nose Dive Factor	Filter Off	
Average Last Lateral Acceleration Values	Average 1	
Excess Lateral Acceleration Factor	1.5	
Acceleration Factor	Filter Off	
Excess Longitudinal Acceleration Factor	1.5	
Steering Smoothing Factor	Filter Off	
Average Last Longitudinal Acceleration Values	Average 1	
Steering Smoothing Duration	3 periods	
Maximum Longitudinal Change	2.0 degrees	
Steering Smoothing Threshold	150 Degrees	

Maximum Lateral Change	2.6 degrees	
Interior Lighting Night Threshold	4.45147	Volt
PE Auto-Relock Feature Enable	Set	
Horn Chirp Duration	Short	
RKE Auto-Relock Feature Enable	Not Set	
VTA Hood Ajar Monitoring	Not Set	
Pitch and Roll Present	Set	
ASBM Minimum Voltage Time	10 Seconds	
Parking Light Enable	Not Set	
Interior Lighting Day Threshold	4.27498	Volt
ASBM Battery Minimum Voltage	11.8 Volts	
ADR feature Present	Not Set	
Hybrid Type	PHEV	
PTC Present	Not Set	
AGS Feature Present	Not Set	
TPMS Configuration	Logic 1 NHTSA Enable Warning	
Transmission Equipped	Automatic transmission / AUTOMATIC	
Glovebox Control	Not Set	
TSBM Module Present	Not Set	
Temperature Display Resolution	Set	
Glare Free Present	Not Set	
Brake Type	Reserved	
Park Brake Type	Mechanical park brake - hand or foot / MECH	
Suspension Type	Reserved	
Axle Locker Configuration	Front and Rear Axle Locker / FTRR	
Performance shift enable customer settings menu	Not Set	
EPB service mode customer settings menu	Not Set	
Rain sensitive wipers customer settings menu	Not Set	
Electric power steering customer settings menu	Not Set	
Lane departure torque customer settings menu	Not Set	
Auto door lock customer settings menu	Set	
Air suspension warning customer settings menu	Not Set	
Unit set customer settings menu	Set	
Park assist brake customer settings menu	Not Set	
Headlamp off delay customer settings menu	Set	
Auto entry exit mode customer settings menu	Not Set	
Consumption unit customer settings menu	Set	
Park assist front volume customer settings menu	Not Set	
Pressure unit customer settings menu	Set	
Compass variance customer settings menu	Not Set	
Headlamp drop customer settings menu	Not Set	
Power unit customer settings menu	Not Set	
Blind spot alert customer settings menu	Set	
Rear view camera gridlines customer settings menu	Static + Dynamic / Static + Dynamic	

Compass calibration customer settings menu	Not Set	
Power accessory delay customer settings menu	Set	
Lane departure warning customer settings menu	Not Set	
Easy exit seat customer settings menu	Not Set	
Ambient dimmer customer settings menu	Not Set	
Clock display customer settings menu	Set	
Rear camera customer settings menu	Not Set	
Auto high beam customer settings menu	Set	
Auxiliary switches customer settings menu	Switch 1 - 4 Option / Switch 1 - 4 Option	
Power take off customer settings menu	Not Set	
Passive entry customer settings menu	Set	
Headlamps on with wiper customer settings menu	Set	
Auto on driver comfort customer settings menu	Feature 2 - 3 Option / Feature 2 - 3 Option	
Tire jack mode customer settings menu	Not Set	
Automatic aero mode customer settings menu	Not Set	
Illuminated approach customer settings menu	Set	
Park assist customer settings menu	Feature not present / Absent	
Power liftgate chime customer settings menu	Not Set	
Park assist rear volume customer settings menu	Set	
Distance unit customer settings menu	Set	
Auto park customer settings menu	Not Set	
Forward collision warning customer settings menu	Feature 2 - 3 Option / Feature 2 - 3 Option	
Speed unit customer settings menu	Set	
Torque unit customer settings menu	Not Set	
Teen Key Automatic High Beam Customer Settings Menu	Not Set	
RKE unlock customer settings menu	Set	
Tilt mirror in reverse customer settings menu	Not Set	
Rear view camera delay customer settings menu	Set	
Passenger Airbag On/Off Customer Settings Menu	Not Set	
Teen Key Fuel Pop-up Customer Settings Menu	Not Set	
Doors and Engine Off Power Delay Customer Settings Menu	Set	
Forward Collision Warning and Brake Customer Settings Menu	Set	
Surround View Camera On/Off Softkey Present	Not Set	
Trailer Hitch Camera Present	Set	
Auto Dimming Mirror Hard Button Present	Not Set	
DTV Present	Not Set	
Clari-Fi Present	Not Set	
Rear Defrost and Heated Mirrors Present	Both	
Show Phone Information in Cluster	Set	
Automatic Crash Notification Feature Present	Not Set	
Radio Speaker Open Circuit Disable (LR)	Not Set	
Radio Speaker Open Circuit Disable (RR)	Not Set	
Tri-State Comfort Climate Softkey Function Present	Set	
ANC Calibration Parameter Data Set	46594	ms

Radio Speaker Open Circuit Disable (LF)	Not Set	
Drive Mode Version	Version 1	
Radio Speaker Open Circuit Disable (RF)	Not Set	
Park Assist Tuning Set	Sahara	
Siren	Not Set	
Tilt	Not Set	
Ultrasonics	Not Set	
RFH	Set	
IPC	Set	
PCM	Set	
EPS	Set	
OCM	Set	
DPDM	Set	
DTCM	Set	
ESM	Set	
BCM (PT)	Set	
ITBM	Not Set	
TPM	Not Set	
ABS	Not Set	
TCM	Set	
AFLS	Not Set	
ANC	Not Set	
AHLM/AFLS	Not Set	
ORC	Set	
SCCM	Set	
PTS	Set	
SGW	Set	
ASCM	Not Set	
ELSD	Not Set	
ASBS	Set	
Tachometer Type	Tachometer Type 1 / Type 1	
Increasing speed constant	Increasing 0 KPH	
Speedometer Tolerance	0 Percent Tolerance	
Steering C Factor	Type 3	
Rear Defrost Presence	Present	
Heated Mirrors Present	Present	
Engine Displacement	Signal Not Available / SNA	
EVIC Switch Module Present	Set	
VTA System Present	VTA	
Illuminated Approach Interior Lighting Target Percentage	100 (50%)	
Washer Fluid Level Voltage Threshold	4.46 volts	
Manual Trans Present	Not Set	
Compass Mounting Angle	0	Degree
Compass Mounting Orientation	Upside Down	

DC to DC Converter #2 Present	Not Set	
IBS Present	Set	
Illuminated Approach Interior Lighting Ramp Up Time	130(2600ms)	
Panic Enable	Set	
Humidity Sensor Present	Not Set	
Auto Relock Time	60	seconds
ASBMM Present	Set	
Illuminated Approach Taillamp Target Percentage	165 (82.50%)	
DC to DC Converter Present	Not Set	
ASBM Present	Set	
Illuminated Approach Headlamp Target Percentage	165 (82.50%)	
CRVMM Present	Set	
Reserved	Reserved	
2nd Row Seat Airbags Present	False	
Tow Hooks Present	True	
Passenger Kneebag Present	False	
Integrated EPP Present	False	
Driver Kneebag Present	False	
BUX vehicle	False	
Reserved	Reserved	
Curtain Airbags Present	False	
ODS Present	False	
Passive Ped Pro Present	False	
BCM (Interior Bus)	Set	
ITM	Not Set	
HVAC	Set	
PTCM	Not Set	
LBSM	Set	
HSM	Set	
RBSM	Set	
TBM	Not Set	
AMP	Set	
HVAC_R	Not Set	
Radio	Set	
EDM	Not Set	
Right Low Beam Voltage Regulation	13.6 Volts	
Signature Light Present	Present	
Dual Filament Headlamp	Not Present	
Left High Beam Voltage Regulation	13.6 Volts	
Auto Headlamp On Threshold	3.31409	Volt
Left Low Beam Voltage Regulation	13.6 Volts	
Right Front Corner Voltage	13.6 Volts	
Left Rear Corner Voltage	12.8 Volts	
Right High Beam Voltage Regulation	13.6 Volts	

Right Rear Corner Voltage	12.8 Volts	
Auto Headlamp Off Threshold	2.54930	Volt
Front Turn Lamp Diagnostics	Present	
Left Front Corner Voltage	13.6 Volts	
Left Front Lamp Diagnostics Present - Pin F25	Set	
Backup Reverse Lamp Right Present - Pin E1	Set	
Stop/Turn Lamp or Stop Lamp Present Pin E2 & F40	Stop/Turn Lamp	
Right High Beam Present - Pin A2	Set	
Right Front Lamp Diagnostics Present - Pin F28	Set	
Brake Fluid Level Switch Signal Present - Pin D21	Not Set	
Backup Reverse Lamp Left Present - Pin F41	Set	
Left High Beam Present - Pin D1	Set	
Left Rear Turn Lamp Diagnostics Present - Pin F27	Set	
Right Rear Turn Lamp Diagnostics Present - Pin F31	Set	

RADIO CONFIGURATION

NAME	VALUE	UNITS
GPS on the Bus messaging Authorization	Allowed	
Compass on the bus messaging Authorization	Allowed	
Satellite Subscription Status	Subscribed	
Satellite Subscription ID	BW282E0K	
Satellite Subscription Reason Code	00	
Satellite Subscription Suspend Day	01	
Satellite Subscription Suspend Month	01	
Satellite Subscription Suspend Year	46	
Aux Jack	Not Inserted	
SD Card Readers Detected	0	No Unit
Enumerated USB Devices	0	No Unit
USB Hubs Detected	1	No Unit
DTV Short Term Configuration	—	
911 Button	On	
Splash Screen	Jeep	
Cabin EQ Curve Number Currently Used by Radio	B6	
Clock Defeat	Off	
Anti-Theft Enable Status	On	
12/24 Time Selection	12 Hour Time	
Front Seat Video Playback	Enabled	
Automated Loudness	On	
SDARS	True	
Navigation Active	True	
Cellular	True	
Application Framework	True	
Bluetooth	True	
Internal CD Player	False	

FM Diversity	False	
Wi-Fi	True	

LBSS CONFIGURATION

NAME	VALUE	UNITS
Steering (LHD/RHD)	Left Hand Drive/ LHD	
Teen Key	No	
CFG FEATURE	CFG_NONE	

RBSS CONFIGURATION

NAME	VALUE	UNITS
Teen Key	No	
Steering (LHD/RHD)	Left Hand Drive/ LHD	

ABSO CONFIGURATION

NAME	VALUE	UNITS
Trans Type	ZF_8spd	
Drive Configuration	Selectable 4wd	
Displacement	2.0	No Unit
Hybrid Type	PHEV	
Vehicle Line Identification	JL	
Chassis Type	Type 83	
Axle Ratio	4.093	No Unit
Tire Circumference	98	inch

DASM CONFIGURATION

NAME	VALUE	UNITS
Auto High Beam Present	True	
ACC STOP Present	True	
LDW Plus Present	False	
NCC Present	False	
ACC GO Present	False	
ACC Present	False	
FCW Present	True	



VEHICLE SCAN REPORT

Vehicle 2022 JEEP WRANGLER 2.0L I4 DOHC DI TURBO PHEV ENGINE
VIN [REDACTED]

Odometer 1112.6 miles
Publication Date Apr 29, 2022, 11:33:56 AM

ECU SUMMARY INFO

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
TCM	Transmission Control Module	CAN-C	68563825AB	[REDACTED]	[REDACTED]	68563825AB
PCM	Powertrain Control Module	CAN-C	05188195AC			05188195AC
ASBS	Automatic Sway Bar System	CAN-C	68570943AA			68570943AA
ICS	Integrated Center Stack	CAN-I	6SX94DX9AE			6SX94DX9AE
RFH	Radio Frequency Hub	CAN-C	56029925AB			56029925AB
ESM	Electronic Shifter	CAN-C	04670716AD			04670716AD
DTCM	Drive Train Control Module	CAN-C	68547689AB			68547689AB
ORC	Occupant Restraint	CAN-C	68526670AB			68526670AB
EPS	Electric Power Steering	CAN-C	68529427AC			68529427AC
HVAC	Heat, Ventilation and A/C	CAN-I	52080486AB			52080486AB
CSWM	Comfort Seat Wheel Module	CAN-I	68530204AB			68530204AB
AMP	Amplifier	CAN-I	68549084AB			68549084AB
IPC	Instrument Panel Cluster	CAN-C	68525023AA			68525023AA
PTS	Parktronics	CAN-C	68441031AC			68441031AC
SCCM	Steering Column Control Module	CAN-C	68526258AA			68526258AA
BCM	Body Controller	CAN-C	68525356AC			68525355AC
RADIO	Radio	CAN-I	68472587AJ			68472587AJ
OCM	Occupant Classification	CAN-C	68403128AA			68403128AA
LBSS	Left Blind Spot Sensor	CAN-I	68454896AA			68454896AA
RBSS	Right Blind Spot Sensor	CAN-I	68454896AA			68454896AA

BPCM	Battery Pack Control Module	CAN-C	05193168AH		05193168AH
HCP	Hybrid Control Processor	CAN-C	68540073AB		68540073AB
AHCP	Auxiliary Hybrid Control Processor	CAN-C	68540084AB		68540084AB
ABSO	Anti Lock Brakes OBD	CAN-C	68532850AC		68532850AC
SGW	Security Gateway Module	CAN-C	68532299AB		68532299AB
DPDM	Driver Presence Detection Module	CAN-C	68403129AA		68403129AA
DASM	Driver Assistance System Module	CAN-C	04672888AC		04672888AC
IDCM	Integrated Dual Charge Module	CAN-C	05185035AQ		05185035AQ

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	CVNS
TCM	USA / USA	13 05 0E	15 2B 00	4700	5033262D
PCM	USA	1D 47	21 22 00	4928	A51CF452
ASBS	USA	10 01 00	15 0E 01	4500	
ICS	USA	10 1E 00	14 33 00	4802	
RFH	USA / USA	10 17 00	15 1D 00	4604	
ESM	USA	15 18 00	12 2A 00	4322	
DTCM	USA	11 22 00	15 0A 01	4501	
ORC	USA	14 0B 00	14 12 01	4501	
EPS	USA	10 13 00	14 31 DC	4005	
HVAC	USA	13 20 00	15 01 01	4420	
CSWM	USA	11 2A 00	15 06 00	4202	
AMP	USA	21 01 01	15 16 00	4034	
IPC	USA	17 17 01	15 0B 01	4805	
PTS	USA	10 32 01	13 24 03	4401	
SCCM	USA	13 28 00	13 29 00	4301	
BCM	USA	0D 11 00	15 21 50	4630	
RADIO	USA	15 20 14	15 20 14	8205	
OCM	USA	11 31 01	11 07 04	4060	
LBSS	USA	11 23 01	12 25 00	4204	
RBSS	USA	11 23 01	12 25 00	4204	
BPCM	Rest of world / ROW	13 0C 04	15 24 42	5701	49906456
HCP	USA	15 0C 04	15 29 01	5403	6F5143CE 20A924DE 4C99835C
AHCP	USA	15 0C 04	14 33 01	5600	
ABSO	USA	15 26 00	15 22 03	4300	D74722B2
SGW		5	1125	4103	
DPDM	USA	11 31 01	11 0F 04	4510	
DASM	USA	11 0E 00	15 26 01	401C	

IDCM	USA	15 0E 00	15 28 00	4000	
------	-----	----------	----------	------	--

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
TCM	P1DAF-00	Incompatible Limp In Action Requested-	Stored
PCM	U0594	Implausible Data Received From Hybrid Control Module	Stored
PCM	U145D	Implausible Data Received From TCM On D-PT	Stored
PCM	U0402	Implausible Data Received From TCM	Stored
DTCM	U0594-00	Implausible Data Received From Hybrid Control Module "A"-	Stored
RADIO	U0293-00		Stored
HCP	P0C19-00	Drive Motor A Torque Delivered Performance-	Stored
HCP	P1B03-00	Resolver Signal / MCPA Rationality-	Stored
ABSO	U0594-00	Implausible Data Received From Hybrid Control Module "A"-	Stored
ABSO	U0402-00	Implausible Data Received From TCM-	Stored
DASM	C2227-00	ABS Disabled ECU-	Stored
DASM	U0594-00	Implausible Data Received From Hybrid Control Module "A"-	Stored
DASM	U0402-00	Implausible Data Received From TCM-	Stored

ENVIRONMENTAL DATA SUMMARY

TCM | P1DAF-00 | Stored | Incompatible Limp In Action Requested-

NAME	VALUE	UNITS
DTC	1D AF 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	Error	
Original Odometer Value	267295	miles
Most Recent Odometer Value	272049	miles
Frequency Counter	2	
Ignition Cycle Counter	1	

PCM | U0594 | Stored | Implausible Data Received From Hybrid Control Module

NAME	VALUE	UNITS
Number of DTC	1	
DTC	C5 94	
DTC Readiness Flag	Not Complete	
DTC Storage State	Stored	

Warning Indicator Request State	Off	
Odometer	739.7	miles
Accumulation Timer	79	minutes
Ignition Key Cycles	19	
Starts Since Set Counter	13	
Key Cycles Since DTC Last Set Counter	20	
Warm Up Cycles	1	
Good Trip Counter	10	

PCM | U145D | Stored | Implausible Data Received From TCM On D-PT

NAME	VALUE	UNITS
Number of DTC	1	
DTC	D4 5D	
DTC Readiness Flag	Not Complete	
DTC Storage State	Stored	
Warning Indicator Request State	Off	
Odometer	1034.0	miles
Accumulation Timer	0	minutes
Ignition Key Cycles	21	
Starts Since Set Counter	15	
Key Cycles Since DTC Last Set Counter	22	
Warm Up Cycles	1	
Good Trip Counter	11	

PCM | U0402 | Stored | Implausible Data Received From TCM

NAME	VALUE	UNITS
Number of DTC	1	
DTC	C4 02	
DTC Readiness Flag	Not Complete	
DTC Storage State	Stored	
Warning Indicator Request State	Off	
Odometer	1034.0	miles
Accumulation Timer	0	minutes
Ignition Key Cycles	21	
Starts Since Set Counter	15	
Key Cycles Since DTC Last Set Counter	22	
Warm Up Cycles	1	
Good Trip Counter	11	

DTCM | U0594-00 | Stored | Implausible Data Received From Hybrid Control Module "A"-

NAME	VALUE	UNITS
DTC	C5 94 00	
Test Failed	False	
Test Failed This Operation Cycle	False	

Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	False	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number - All	01	
Occurrence flag	Occurrence	
Original Odometer Value	746	miles
Most Recent Odometer Value	746	miles
Frequency Counter	1	
Ignition Cycle Counter	84	

RADIO | U0293-00 | Stored |

NAME	VALUE	UNITS
------	-------	-------

HCP | P0C19-00 | Stored | Drive Motor A Torque Delivered Performance-

NAME	VALUE	UNITS
DTC	0C 19 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
DTC Extended Data Record Number	10	
Occurrence flag	Occurrence	
Original Odometer Value	764.3	miles
Most Recent Odometer Value	1069.2	miles
Frequency Counter	24	
Ignition Cycle Counter	1	
Microcontroller reset reason - Core 0	Power Up	
Microcontroller reset reason - Core 1	Power Up	
Real time clock	952624064	sec
RAM stamps keyOn	225	sec
RAM Stamps	8842	Min
Accelerator Pedal Position	0	%
Engine Coolant Temperature	127	°F
Engine Speed	3446	rpm
Vehicle Speed	57.2098	MPH
HV Battery SOC	67	%
Brake Switch Status	Not Applied	

Battery Feed Voltage 1 Sense	13.032	Volts
Battery Feed Voltage 2 Sense	13.032	Volts
Battery Feed Voltage 3 Sense	13.032	Volts
Internal EPS Voltage Sense A	8.928	Volts
Internal EPS Voltage Sense B	8.928	Volts
Hybrid System State	Propulsion System Active	
Outside Air Temperature	82.4	°F
Ignition State	Reserved	
Propulsion System Active	True	
HV Contactor Status	Closed	
APM Status	Buck CV	
Impact Event	False	
PRND Position Display	D	
Distance Travelled with Light ON	22	miles
HV Battery Sleep Time	0	Days
eMotor A Shutdown History [0]	44-Position Tracking Loss	
eMotor A Shutdown History [1]	37-Motor Torque Security	
eMotor A Shutdown History [2]	0-NO_FAULT	
eMotor A Fault History [0]	0-NO_FAULT	
eMotor A Fault History [1]	0-NO_FAULT	
eMotor A Fault History [2]	0-NO_FAULT	
eMotor A Fault History [3]	0-NO_FAULT	
eMotor A Fault History [4]	0-NO_FAULT	
eMotor A Fault History [5]	0-NO_FAULT	
eMotor B Shutdown History [0]	0-NO_FAULT	
eMotor B Shutdown History [1]	0-NO_FAULT	
eMotor B Shutdown History [2]	0-NO_FAULT	
eMotor B Fault History [0]	0-NO_FAULT	
eMotor B Fault History [1]	0-NO_FAULT	
eMotor B Fault History [2]	0-NO_FAULT	
eMotor B Fault History [3]	0-NO_FAULT	
eMotor B Fault History [4]	0-NO_FAULT	
eMotor B Fault History [5]	0-NO_FAULT	
eMotor A FA Speed or Position Fault Active	False	
eMotor A FA Motor Temperature Fault Active	False	
eMotor A FA inverter Temperature A Fault Active	False	
eMotor A FA inverter Temperature B Fault Active	False	
eMotor A FA inverter Temperature C Fault Active	False	
eMotor A FA DC Current Fault Active	False	
eMotor A FA DC Voltage Fault Active	False	
eMotor A FA Acceleration Fault Active	False	
eMotor A FA Rotor Temperature Fault Active	False	
eMotor A FA Capacitor Temperature Fault active	False	
eMotor A FA Current Sensor A Fault Active	False	

eMotor A FA Current Sensor B Fault Active	False	
eMotor A FA Current Sensor C Fault Active	False	
eMotor A FA Postion Sensor Fault Active	False	
eMotor A FA DC Voltage Out of Range Fault Active	False	
eMotor A FA Reserved	Undefined	
eMotor B FA Speed or Position Fault Active	False	
eMotor B FA Motor Temperature Fault Active	False	
eMotor B FA Inverter Temperature A Fault Active	False	
eMotor B FA Inverter Temperature B Fault Active	False	
eMotor B FA Inverter Temperature C Fault Active	False	
eMotor B FA HV input Current Fault Active	False	
eMotor B FA HV Input Voltage Fault Active	False	
eMotor B FA Acceleration Fault Active	False	
eMotor B FA Rotor Temperature Fault Active	False	
eMotor B FA Capacitor Temperature Fault Active	False	
eMotor B FA Current Sensor A Fault Active	False	
eMotor B FA Current Sensor B Fault Active	False	
eMotor B FA Current Sensor C Fault Active	False	
eMotor B FA Position Sensor Fault Active	False	
eMotor B FA DC Voltage Out of Range Fault Active	False	
eMotor B FA Reserved	Undefined	
eMotor A Current Ia Max	2.60	A
eMotor A Current Ia Min	-3.00	A
eMotor A Current Ib Max	1.25	A
eMotor A Current Ib Min	-1.40	A
eMotor A Current Ic Max	1.85	A
eMotor A Current Ic Min	-1.40	A
eMotor A Current Id Max	1.65	A
eMotor A Current Id Min	-1.75	A
eMotor A Current Iq Max	1.55	A
eMotor A Current Iq Min	-1.50	A
eMotor A Current Sum Max	4.65	A
eMotor A Current Sum Min	-4.50	A
eMotor A HV Input voltage Max	336.98	Volts
eMotor A HV Input voltage Min	334.92	Volts
eMotor A speed max mrads	-2048.0000	rad/s
eMotor A speed min mrads	-2048.0000	rad/s
eMotor B Current Ia Max	389.90	A
eMotor B Current Ia Min	-385.65	A
eMotor B Current Ib Max	395.10	A
eMotor B Current Ib Min	-381.75	A
eMotor B Current Ic Max	391.70	A
eMotor B Current Ic Min	-390.30	A
eMotor B Current Id Max	-85.05	A

eMotor B Current Id Min	-89.90	A
eMotor B Current Iq Max	254.35	A
eMotor B Current Iq Min	244.70	A
eMotor B current Sum Max	6.25	A
eMotor B current sum Min	-4.50	A
eMotor B HV Input Voltage Max	337.30	Volts
eMotor B HV Input Voltage Min	335.42	Volts
eMotor B speed Max mrads	440.3125	rad/s
eMotor B speed Min mrads	436.4375	rad/s
eMotor A Current Ia Offset	-1.45	A
eMotor A Current Ib Offset	-0.60	A
eMotor A Current Ic Offset	0.30	A
eMotor B Current Ia Offset	-1.45	A
eMotor B Current Ib Offset	-0.60	A
eMotor B Current Ic Offset	0.30	A
eMotor A HV Battery Voltages	334.70	Volts
eMotor A HV input Voltages	336.84	Volts
eMotor B HV Battery Voltages	335.60	Volts
eMotor B HV input Voltages	336.74	Volts
eMotor A Motoring Torque Limit	14.20	Ft-Lbs
eMotor A Regenerative Torque Limit	-14.20	Ft-Lbs
eMotor B Motoring Torque Limit	171.99	Ft-Lbs
eMotor B Regenerative Torque Limit	-172.36	Ft-Lbs
eMotor A Torque command	0.00	Ft-Lbs
eMotor A Torque achieved	-0.03	Ft-Lbs
eMotor A speed RPM	8060	rpm
eMotor B Torque command	113.13	Ft-Lbs
eMotor B Torque achieved	111.21	Ft-Lbs
eMotor B Speed RPM	4183	rpm
eMotor A Temperature Stator	104	°F
eMotor A Temperature Inverter Model	32	°F
eMotor A Temperature Inverter 0	95	°F
eMotor A Temperature Inverter 1	95	°F
eMotor A Temperature Inverter 2	99	°F
eMotor A Temperature Coolant Inlet	32	°F
eMotor A Temperature Coolant Outlet	32	°F
eMotor A Temperature PCB	32	°F
eMotor A Temperature Rotor	32	°F
eMotor A OS Runtime Seconds	226	sec
eMotor B OS Runtime Seconds	226	sec
eMotor B Temperature Stator	131	°F
eMotor B Temperature Inverter Model	32	°F
eMotor B Temperature Inverter 0	167	°F
eMotor B Temperature Inverter 1	167	°F

eMotor B Temperature Inverter 2	167	°F
eMotor B Temperature coolant Inlet	32	°F
eMotor B Temperature coolant outlet	32	°F
eMotor B Temperature PCB	32	°F
eMotor B Temperature Rotor	32	°F
eMotor A Lifetime Over Current w/o Over Voltage Events	0	
eMotor A Lifetime Over Current Events	0	
eMotor A Lifetime Over Voltage Events	0	
eMotor A Lifetime Max Voltage	402.70	Volts
eMotor A Lifetime Max Phase Current	568.45	A
eMotor A Lifetime General Retry Events	70	
eMotor A Key Cycle Max Voltage	382.84	Volts
eMotor A Key Cycle Max phase Current	317.90	A
eMotor A Key Cycle General Retry Events	0	
eMotor B Lifetime Over Current w/o Over Voltage Events	0	
eMotor B Lifetime Over Current Events	0	
eMotor B Lifetime Over Voltage Events	0	
eMotor B Lifetime Max Voltage	402.46	Volts
eMotor B Lifetime Max Phase Current	719.10	A
eMotor B Lifetime General retry Events	0	
eMotor B key Cycle max Voltage	383.22	Volts
eMotor B key Cycle max Phase Current	655.85	A
eMotor B key Cycle General Retry Events	0	
eMotor A MTMR Fault Word	00 00 00	
eMotor B MTMR Fault Word	00 00 00	
GPS Date - Year	58887	Year
GPS Date - Month	4	
GPS Date - Day	24	Days
UTC Time - Hours	16	Hours
UTC Time - Minutes	48	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	956	ms

HCP | P1B03-00 | Stored | Resolver Signal / MCPA Rationality-

NAME	VALUE	UNITS
DTC	1B 03 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	

DTC Extended Data Record Number	10	
Occurrence flag	Occurrence	
Original Odometer Value	764.3	miles
Most Recent Odometer Value	1069.1	miles
Frequency Counter	32	
Ignition Cycle Counter	1	
Microcontroller reset reason - Core 0	Power Up	
Microcontroller reset reason - Core 1	Power Up	
Real time clock	952624064	sec
RAM stamps keyOn	225	sec
RAM Stamps	8842	Min
Accelerator Pedal Position	0	%
Engine Coolant Temperature	127	°F
Engine Speed	3941	rpm
Vehicle Speed	53.6078	MPH
HV Battery SOC	67	%
Brake Switch Status	Not Applied	
Battery Feed Voltage 1 Sense	13.032	Volts
Battery Feed Voltage 2 Sense	13.032	Volts
Battery Feed Voltage 3 Sense	13.032	Volts
Internal EPS Voltage Sense A	8.928	Volts
Internal EPS Voltage Sense B	8.928	Volts
Hybrid System State	Propulsion System Active	
Outside Air Temperature	82.4	°F
Ignition State	Reserved	
Propulsion System Active	True	
HV Contactor Status	Closed	
APM Status	Buck CV	
Impact Event	False	
PRND Position Display	D	
Distance Travelled with Light ON	22	miles
HV Battery Sleep Time	0	Days
eMotor A Shutdown History [0]	44-Position Tracking Loss	
eMotor A Shutdown History [1]	37-Motor Torque Security	
eMotor A Shutdown History [2]	0-NO_FAULT	
eMotor A Fault History [0]	461-Isd Current Ripple	
eMotor A Fault History [1]	462-Isq Current Ripple	
eMotor A Fault History [2]	44-Position Tracking Loss	
eMotor A Fault History [3]	37-Motor Torque Security	
eMotor A Fault History [4]	0-NO_FAULT	
eMotor A Fault History [5]	0-NO_FAULT	
eMotor B Shutdown History [0]	0-NO_FAULT	
eMotor B Shutdown History [1]	0-NO_FAULT	
eMotor B Shutdown History [2]	0-NO_FAULT	

eMotor B Fault History [0]	0-NO_FAULT	
eMotor B Fault History [1]	0-NO_FAULT	
eMotor B Fault History [2]	0-NO_FAULT	
eMotor B Fault History [3]	0-NO_FAULT	
eMotor B Fault History [4]	0-NO_FAULT	
eMotor B Fault History [5]	0-NO_FAULT	
eMotor A FA Speed or Position Fault Active	True	
eMotor A FA Motor Temperature Fault Active	False	
eMotor A FA inverter Temperature A Fault Active	False	
eMotor A FA inverter Temperature B Fault Active	False	
eMotor A FA inverter Temperature C Fault Active	False	
eMotor A FA DC Current Fault Active	False	
eMotor A FA DC Voltage Fault Active	False	
eMotor A FA Acceleration Fault Active	True	
eMotor A FA Rotor Temperature Fault Active	True	
eMotor A FA Capacitor Temperature Fault active	True	
eMotor A FA Current Sensor A Fault Active	False	
eMotor A FA Current Sensor B Fault Active	False	
eMotor A FA Current Sensor C Fault Active	False	
eMotor A FA Postion Sensor Fault Active	True	
eMotor A FA DC Voltage Out of Range Fault Active	False	
eMotor A FA Reserved	Undefined	
eMotor B FA Speed or Position Fault Active	False	
eMotor B FA Motor Temperature Fault Active	False	
eMotor B FA Inverter Temperature A Fault Active	False	
eMotor B FA Inverter Temperature B Fault Active	False	
eMotor B FA Inverter Temperature C Fault Active	False	
eMotor B FA HV input Current Fault Active	False	
eMotor B FA HV Input Voltage Fault Active	False	
eMotor B FA Acceleration Fault Active	False	
eMotor B FA Rotor Temperature Fault Active	False	
eMotor B FA Capacitor Temperature Fault Active	False	
eMotor B FA Current Sensor A Fault Active	False	
eMotor B FA Current Sensor B Fault Active	False	
eMotor B FA Current Sensor C Fault Active	False	
eMotor B FA Position Sensor Fault Active	False	
eMotor B FA DC Voltage Out of Range Fault Active	False	
eMotor B FA Reserved	Undefined	
eMotor A Current Ia Max	76.40	A
eMotor A Current Ia Min	-241.75	A
eMotor A Current Ib Max	168.90	A
eMotor A Current Ib Min	-126.75	A
eMotor A Current Ic Max	284.95	A
eMotor A Current Ic Min	-98.75	A

eMotor A Current Id Max	105.05	A
eMotor A Current Id Min	-196.80	A
eMotor A Current Iq Max	297.10	A
eMotor A Current Iq Min	14.05	A
eMotor A Current Sum Max	6.75	A
eMotor A Current Sum Min	-3.85	A
eMotor A HV Input voltage Max	338.02	Volts
eMotor A HV Input voltage Min	331.72	Volts
eMotor A speed max mrads	-2048.0000	rad/s
eMotor A speed min mrads	-2048.0000	rad/s
eMotor B Current Ia Max	388.90	A
eMotor B Current Ia Min	-379.65	A
eMotor B Current Ib Max	387.15	A
eMotor B Current Ib Min	-383.85	A
eMotor B Current Ic Max	386.20	A
eMotor B Current Ic Min	-388.35	A
eMotor B Current Id Max	-78.15	A
eMotor B Current Id Min	-89.25	A
eMotor B Current Iq Max	252.95	A
eMotor B Current Iq Min	233.65	A
eMotor B current Sum Max	6.15	A
eMotor B current sum Min	-4.75	A
eMotor B HV Input Voltage Max	340.54	Volts
eMotor B HV Input Voltage Min	338.34	Volts
eMotor B speed Max mrads	414.9375	rad/s
eMotor B speed Min mrads	409.7500	rad/s
eMotor A Current Ia Offset	-1.50	A
eMotor A Current Ib Offset	-0.80	A
eMotor A Current Ic Offset	0.45	A
eMotor B Current Ia Offset	-1.50	A
eMotor B Current Ib Offset	-0.80	A
eMotor B Current Ic Offset	0.45	A
eMotor A HV Battery Voltages	337.80	Volts
eMotor A HV input Voltages	338.86	Volts
eMotor B HV Battery Voltages	339.20	Volts
eMotor B HV input Voltages	338.94	Volts
eMotor A Motoring Torque Limit	18.88	Ft-Lbs
eMotor A Regenerative Torque Limit	-18.88	Ft-Lbs
eMotor B Motoring Torque Limit	179.93	Ft-Lbs
eMotor B Regenerative Torque Limit	-179.97	Ft-Lbs
eMotor A Torque command	0.00	Ft-Lbs
eMotor A Torque achieved	0.00	Ft-Lbs
eMotor A speed RPM	9415	rpm
eMotor B Torque command	112.85	Ft-Lbs

eMotor B Torque achieved	113.97	Ft-Lbs
eMotor B Speed RPM	3932	rpm
eMotor A Temperature Stator	104	°F
eMotor A Temperature Inverter Model	32	°F
eMotor A Temperature Inverter 0	97	°F
eMotor A Temperature Inverter 1	95	°F
eMotor A Temperature Inverter 2	97	°F
eMotor A Temperature Coolant Inlet	32	°F
eMotor A Temperature Coolant Outlet	32	°F
eMotor A Temperature PCB	32	°F
eMotor A Temperature Rotor	32	°F
eMotor A OS Runtime Seconds	223	sec
eMotor B OS Runtime Seconds	223	sec
eMotor B Temperature Stator	129	°F
eMotor B Temperature Inverter Model	32	°F
eMotor B Temperature Inverter 0	171	°F
eMotor B Temperature Inverter 1	171	°F
eMotor B Temperature Inverter 2	171	°F
eMotor B Temperature coolant Inlet	32	°F
eMotor B Temperature coolant outlet	32	°F
eMotor B Temperature PCB	32	°F
eMotor B Temperature Rotor	32	°F
eMotor A Lifetime Over Current w/o Over Voltage Events	0	
eMotor A Lifetime Over Current Events	0	
eMotor A Lifetime Over Voltage Events	0	
eMotor A Lifetime Max Voltage	402.70	Volts
eMotor A Lifetime Max Phase Current	568.45	A
eMotor A Lifetime General Retry Events	70	
eMotor A Key Cycle Max Voltage	382.84	Volts
eMotor A Key Cycle Max phase Current	317.90	A
eMotor A Key Cycle General Retry Events	0	
eMotor B Lifetime Over Current w/o Over Voltage Events	0	
eMotor B Lifetime Over Current Events	0	
eMotor B Lifetime Over Voltage Events	0	
eMotor B Lifetime Max Voltage	402.46	Volts
eMotor B Lifetime Max Phase Current	719.10	A
eMotor B Lifetime General retry Events	0	
eMotor B key Cycle max Voltage	383.22	Volts
eMotor B key Cycle max Phase Current	655.85	A
eMotor B key Cycle General Retry Events	0	
eMotor A MTMR Fault Word	00 20 00	
eMotor B MTMR Fault Word	00 00 00	
GPS Date - Year	58887	Year
GPS Date - Month	4	

GPS Date - Day	24	Days
UTC Time - Hours	16	Hours
UTC Time - Minutes	48	
UTC Time - Seconds	0	seconds
ECU Time - Milliseconds	469	ms

ABSO | U0594-00 | Stored | Implausible Data Received From Hybrid Control Module "A"-

NAME	VALUE	UNITS
DTC	C5 94 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	
Controller Event	No	
Mirror Memory	No	
Undervoltage Suspected	No	
Original Odometer Value	288	miles
Most Recent Odometer Value	1064	miles
Frequency Counter	89	
Ignition Cycle Counter	15	
Fault Time	214.40	S
Current System Mode	Engine Running	
Previous System Mode	Engine Running	
Wheel Speed Left Front	15.554	MPH
Rotation Direction Left Front	Invalid	
Wheel Speed Right Front	15.554	MPH
Rotation Direction Right Front	Invalid	
Wheel Speed Left Rear	15.798	MPH
Rotation Direction Left Rear	Invalid	
Wheel Speed Right Rear	15.763	MPH
Rotation Direction Right Rear	Invalid	
Steering Wheel Angle	2.00	°
Longitudinal Acceleration	0.52	m/s ²
Yaw Rate	0.00	°/s
Supplier Internal Code	13638	

ABSO | U0402-00 | Stored | Implausible Data Received From TCM-

NAME	VALUE	UNITS
DTC	C4 02 00	

Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	
Controller Event	No	
Mirror Memory	No	
Undervoltage Suspected	No	
Original Odometer Value	1064	miles
Most Recent Odometer Value	1064	miles
Frequency Counter	1	
Ignition Cycle Counter	17	
Fault Time	553.60	S
Current System Mode	Engine Running	
Previous System Mode	Engine Running	
Wheel Speed Left Front	9.262	MPH
Rotation Direction Left Front	Invalid	
Wheel Speed Right Front	9.297	MPH
Rotation Direction Right Front	Invalid	
Wheel Speed Left Rear	9.297	MPH
Rotation Direction Left Rear	Invalid	
Wheel Speed Right Rear	9.332	MPH
Rotation Direction Right Rear	Invalid	
Steering Wheel Angle	3.00	°
Longitudinal Acceleration	-0.05	m/s ²
Yaw Rate	0.49	°/s
Supplier Internal Code	13105	

DASM | C2227-00 | Stored | ABS Disabled ECU-

NAME	VALUE	UNITS
DTC	62 27 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	

Original Odometer Value	736	miles
Most Recent Odometer Value	1064	miles
Frequency Counter	27	
Operation Cycle Counter	15	
Vehicle Speed	35	MPH
Ignition Voltage	13.7	
System Voltage	13.6	Volts

DASM | U0594-00 | Stored | Implausible Data Received From Hybrid Control Module "A"-

NAME	VALUE	UNITS
DTC	C5 94 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	
Original Odometer Value	736	miles
Most Recent Odometer Value	1064	miles
Frequency Counter	40	
Operation Cycle Counter	15	
Vehicle Speed	34	MPH
Ignition Voltage	13.7	
System Voltage	13.7	Volts

DASM | U0402-00 | Stored | Implausible Data Received From TCM-

NAME	VALUE	UNITS
DTC	C4 02 00	
Test Failed	False	
Test Failed This Operation Cycle	False	
Pending DTC	False	
Confirmed DTC	True	
Test Not Completed Since Last Clear	False	
Test Failed Since Last Clear	True	
Test Not Completed This Operation Cycle	False	
Warning Indicator Requested	False	
Occurrence flag	Error	
Original Odometer Value	1064	miles
Most Recent Odometer Value	1064	miles
Frequency Counter	1	
Operation Cycle Counter	17	

Vehicle Speed	32	MPH
Ignition Voltage	13.2	
System Voltage	13.2	Volts

SNAPSHOT DATA SUMMARY

- No Snapshot Data available for P1DAF-00
- No Snapshot Data available for U0594
- No Snapshot Data available for U145D
- No Snapshot Data available for U0402
- No Snapshot Data available for U0594-00
- No Snapshot Data available for U0293-00
- No Snapshot Data available for P0C19-00
- No Snapshot Data available for P1B03-00
- No Snapshot Data available for U0594-00
- No Snapshot Data available for U0402-00
- No Snapshot Data available for C2227-00
- No Snapshot Data available for U0594-00
- No Snapshot Data available for U0402-00