

Vehicle [REDACTED] [REDACTED] [REDACTED] [REDACTED]

ECU	NAME	BUS TYPE	FLASH PART #	CURRENT VIN	ORIGINAL VIN	PART #
-----	------	----------	--------------	-------------	--------------	--------

[illegible]

ABSO	Anti Lock Brakes OBD	CAN-C				

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	SERIAL NUMBER	CVNS
TCM	USA / USA					
PCM	USA					
ICS	USA					
RFH	USA / USA					
ESM	USA					
ORC	USA					
EPS	USA					
HVAC	USA / USA					
CSWM	USA					
IPC	USA					
SCCM	USA					
BCM	USA					
RADIO						
OCM	USA					
BPCM	Rest of world / ROW					
HCP	USA					
DSM	USA / USA					
AHCP	USA					
ABSO	USA					
SGW						
DPDM	USA					
DASM	USA					
IDCM	USA					
TBM2	USA					

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
-----	----------	-----------------	--------

RADIO			Stored
RADIO			Stored
HCP			Stored
HCP			Stored
TBM2			Stored

ENVIRONMENTAL DATA SUMMARY

RADIO | **Stored | Rear Right Audio Speaker Output-Circuit Resistance Below Threshold**

NAME	VALUE	UNITS
DTC		
Test Failed		
Test Failed This Operation Cycle		
Pending DTC		
Confirmed DTC		

RADIO | **Stored | Rear Right Audio Speaker Output-Circuit Open**

NAME	VALUE	UNITS
DTC		
Test Failed		
Test Failed This Operation Cycle		
Pending DTC		
Confirmed DTC		

HCP | **Stored | Drive Motor A Position Sensor Offset Incorrect**

NAME	VALUE	UNITS
DTC		
Test Failed		
Test Failed This Operation Cycle		
Pending DTC		
Confirmed DTC		
Test Not Completed Since Last Clear		
Test Failed Since Last Clear		
Test Not Completed This Operation Cycle		
Warning Indicator Requested		
DTC Extended Data Record Number		
Occurrence flag		
Original Odometer Value		miles
Most Recent Odometer Value		miles
Frequency Counter		
Ignition Cycle Counter		
Microcontroller reset reason - Core 0		
Microcontroller reset reason - Core 1		
Real time clock		sec

INFORMATION REDACTED PURSUANT TO THE FREEDOM OF INFORMATION ACT (FOIA), 5 U.S.C. 552 (B) (6)

RAM stamps keyOn	sec
RAM Stamps	Min
Accelerator Pedal Position	%
Engine Coolant Temperature	°F
Engine Speed	rpm
Vehicle Speed	MPH
HV Battery SOC	%
Brake Switch Status	
Battery Feed Voltage 1 Sense	Volts
Battery Feed Voltage 2 Sense	Volts
Battery Feed Voltage 3 Sense	Volts
Internal EPS Voltage Sense A	Volts
Internal EPS Voltage Sense B	Volts
Hybrid System State	
Outside Air Temperature	°F
Ignition State	
Propulsion System Active	
HV Contactor Status	
APM Status	
Impact Event	
PRND Position Display	
Distance Travelled with Light ON	miles
HV Battery Sleep Time	Days
eMotor A Shutdown History [0]	
eMotor A Shutdown History [1]	
eMotor A Shutdown History [2]	
eMotor A Fault History [0]	
eMotor A Fault History [1]	
eMotor A Fault History [2]	
eMotor A Fault History [3]	
eMotor A Fault History [4]	
eMotor A Fault History [5]	
eMotor B Shutdown History [0]	
eMotor B Shutdown History [1]	
eMotor B Shutdown History [2]	
eMotor B Fault History [0]	
eMotor B Fault History [1]	
eMotor B Fault History [2]	
eMotor B Fault History [3]	
eMotor B Fault History [4]	
eMotor B Fault History [5]	
eMotor A FA Speed or Position Fault Active	
eMotor A FA Motor Temperature Fault Active	
eMotor A FA inverter Temperature A Fault Active	

eMotor A FA inverter Temperature B Fault Active
eMotor A FA inverter Temperature C Fault Active
eMotor A FA DC Current Fault Active
eMotor A FA DC Voltage Fault Active
eMotor A FA Acceleration Fault Active
eMotor A FA Rotor Temperature Fault Active
eMotor A FA Capacitor Temperature Fault active
eMotor A FA Current Sensor A Fault Active
eMotor A FA Current Sensor B Fault Active
eMotor A FA Current Sensor C Fault Active
eMotor A FA Position Sensor Fault Active
eMotor A FA DC Voltage Out of Range Fault Active
eMotor A FA Reserved
eMotor B FA Speed or Position Fault Active
eMotor B FA Motor Temperature Fault Active
eMotor B FA Inverter Temperature A Fault Active
eMotor B FA Inverter Temperature B Fault Active
eMotor B FA Inverter Temperature C Fault Active
eMotor B FA HV input Current Fault Active
eMotor B FA HV Input Voltage Fault Active
eMotor B FA Acceleration Fault Active
eMotor B FA Rotor Temperature Fault Active
eMotor B FA Capacitor Temperature Fault Active
eMotor B FA Current Sensor A Fault Active
eMotor B FA Current Sensor B Fault Active
eMotor B FA Current Sensor C Fault Active
eMotor B FA Position Sensor Fault Active
eMotor B FA DC Voltage Out of Range Fault Active
eMotor B FA Reserved
eMotor A Current Ia Max
eMotor A Current Ia Min
eMotor A Current Ib Max
eMotor A Current Ib Min
eMotor A Current Ic Max
eMotor A Current Ic Min
eMotor A Current Id Max
eMotor A Current Id Min
eMotor A Current Iq Max
eMotor A Current Iq Min
eMotor A Current Sum Max
eMotor A Current Sum Min
eMotor A HV Input voltage Max
eMotor A HV Input voltage Min
eMotor A speed max mrad/s

Volts

Volts

rad/s

eMotor A speed min mrads	rad/s
eMotor B Current Ia Max	
eMotor B Current Ia Min	
eMotor B Current Ib Max	
eMotor B Current Ib Min	
eMotor B Current Ic Max	
eMotor B Current Ic Min	
eMotor B Current Id Max	
eMotor B Current Id Min	
eMotor B Current Iq Max	
eMotor B Current Iq Min	
eMotor B current Sum Max	
eMotor B current sum Min	
eMotor B HV Input Voltage Max	Volts
eMotor B HV Input Voltage Min	Volts
eMotor B speed Max mrads	rad/s
eMotor B speed Min mrads	rad/s
eMotor A Current Ia Offset	
eMotor A Current Ib Offset	
eMotor A Current Ic Offset	
eMotor B Current Ia Offset	
eMotor B Current Ib Offset	
eMotor B Current Ic Offset	
eMotor A HV Battery Voltages	Volts
eMotor A HV input Voltages	Volts
eMotor B HV Battery Voltages	Volts
eMotor B HV input Voltages	Volts
eMotor A Motoring Torque Limit	Ft-Lbs
eMotor A Regenerative Torque Limit	Ft-Lbs
eMotor B Motoring Torque Limit	Ft-Lbs
eMotor B Regenerative Torque Limit	Ft-Lbs
eMotor A Torque command	Ft-Lbs
eMotor A Torque achieved	Ft-Lbs
eMotor A speed RPM	rpm
eMotor B Torque command	Ft-Lbs
eMotor B Torque achieved	Ft-Lbs
eMotor B Speed RPM	rpm
eMotor A Temperature Stator	°F
eMotor A Temperature Inverter Model	°F
eMotor A Temperature Inverter 0	°F
eMotor A Temperature Inverter 1	°F
eMotor A Temperature Inverter 2	°F
eMotor A Temperature Coolant Inlet	°F
eMotor A Temperature Coolant Outlet	°F

INFORMATION REDACTED PURSUANT TO THE FREEDOM OF INFORMATION ACT (FOIA), 5 U.S.C. 552 (B) (6)

eMotor A Temperature PCB	°F
eMotor A Temperature Rotor	°F
eMotor A OS Runtime Seconds	sec
eMotor B OS Runtime Seconds	sec
eMotor B Temperature Stator	°F
eMotor B Temperature Inverter Model	°F
eMotor B Temperature Inverter 0	°F
eMotor B Temperature Inverter 1	°F
eMotor B Temperature Inverter 2	°F
eMotor B Temperature coolant Inlet	°F
eMotor B Temperature coolant outlet	°F
eMotor B Temperature PCB	°F
eMotor B Temperature Rotor	°F
eMotor A Lifetime Over Current w/o Over Voltage Events	
eMotor A Lifetime Over Current Events	
eMotor A Lifetime Over Voltage Events	
eMotor A Lifetime Max Voltage	Volts
eMotor A Lifetime Max Phase Current	A
eMotor A Lifetime General Retry Events	
eMotor A Key Cycle Max Voltage	Volts
eMotor A Key Cycle Max phase Current	A
eMotor A Key Cycle General Retry Events	
eMotor B Lifetime Over Current w/o Over Voltage Events	
eMotor B Lifetime Over Current Events	
eMotor B Lifetime Over Voltage Events	
eMotor B Lifetime Max Voltage	Volts
eMotor B Lifetime Max Phase Current	A
eMotor B Lifetime General retry Events	
eMotor B key Cycle max Voltage	Volts
eMotor B key Cycle max Phase Current	A
eMotor B key Cycle General Retry Events	
eMotor A MTMR Fault Word	
eMotor B MTMR Fault Word	
GPS Date - Year	Year
GPS Date - Month	
GPS Date - Day	Days
UTC Time - Hours	Hours
UTC Time - Minutes	
UTC Time - Seconds	seconds
ECU Time - Milliseconds	ms

HCP | [REDACTED] Stored | Charge Status Indicator Module Internal-

NAME	VALUE	UNITS
DTC	[REDACTED]	

Test Failed	
Test Failed This Operation Cycle	
Pending DTC	
Confirmed DTC	
Test Not Completed Since Last Clear	
Test Failed Since Last Clear	
Test Not Completed This Operation Cycle	
Warning Indicator Requested	
DTC Extended Data Record Number	
Occurrence flag	
Original Odometer Value	miles
Most Recent Odometer Value	miles
Frequency Counter	
Ignition Cycle Counter	
Microcontroller reset reason - Core 0	
Microcontroller reset reason - Core 1	
Real time clock	sec
RAM stamps keyOn	sec
RAM Stamps	Min
Accelerator Pedal Position	%
Barometric Pressure	PSI
Engine Coolant Temperature	°F
Engine Speed	rpm
Vehicle Speed	MPH
HV Battery SOC	%
Brake Switch Status	
Battery Feed Voltage 1 Sense	Volts
Battery Feed Voltage 2 Sense	Volts
Battery Feed Voltage 3 Sense	Volts
Internal EPS Voltage Sense A	Volts
Internal EPS Voltage Sense B	Volts
Hybrid System State	
Actual Torque - Motor A	Ft-Lbs
Actual Torque - Motor B	Ft-Lbs
Available Motor Torque - Motor A	Ft-Lbs
Available Motor Torque - Motor B	Ft-Lbs
Available Regen Torque - Motor A	Ft-Lbs
Available Regen Torque - Motor B	Ft-Lbs
Commanded Torque - Motor A	Ft-Lbs
Commanded Torque - Motor B	Ft-Lbs
Motor A - Inverter Current - phase A	AMP
Motor A - Inverter Current - phase B	AMP
Motor A - Inverter Current - phase C	AMP
Motor B - Inverter Current - phase A	AMP

INFORMATION REDACTED PURSUANT TO THE FREEDOM OF INFORMATION ACT (FOIA), 5 U.S.C. 552 (B) (6)

Motor B - Inverter Current - phase B	AMP
Motor B - Inverter Current - phase C	AMP
Motor A Resolver Angle	Degree
Motor B Resolver Angle	Degree
Motor A Temp Sensor	°F
Motor B Temp Sensor	°F
Outside Air Temperature	°F
Ignition State	
HCP ePT Wake-Up Output	
CBC Wake-Up Input	
EPT LOC Diag Enable	
Propulsion System Active	
HV Contactor Status	
HV Battery Voltage from BPCM	Volts
Electric Motor A Speed	rpm
Electric Motor B Speed	rpm
PIM DC Link Voltage - A	Volts
PIM DC Link Voltage - B	Volts
Inverter A IGBT Temperature for phase A	°F
Inverter A IGBT Temperature for phase B	°F
Inverter A IGBT Temperature for phase C	°F
Inverter B IGBT Temperature for phase A	°F
Inverter B IGBT Temperature for phase B	°F
Inverter B IGBT Temperature for phase C	°F
APM Status	
Impact Event	
PRND Position Display	
HCP System Shutdown Command	
PHEV Charging Status	
Distance Travelled with Light ON	miles
OBCM Operating Mode	
J1772 Prox Detected State	
HV Battery Sleep Time	Days
SW Build Release Version	
HCP SW Version	
High Voltage bus voltage fault status	
HV Battery Voltage	Volts
HV Battery Voltage fault status	
APM HV Voltage	Volts
APM HV Voltage fault status	
ECH HV Voltage	Volts
ECH HV Voltage fault status	
EAC HV Voltage	Volts
EAC HV Voltage fault status	

INFORMATION REDACTED PURSUANT TO THE FREEDOM OF INFORMATION ACT (FOIA), 5 U.S.C. 552 (B) (6)

HV Battery Contactor Status FA

DAP Contactor Open

Air PTC Heater HV Voltage

Volts

Air PTC Heater HV Voltage Fault Status

DBK Heater HV Voltage

Volts

DBK Heater HV Voltage Fault Status

High Voltage Interlock Status

Engine WarmUp Cycle Complete

Charging System Status

Charging Level

High Voltage Contactor Control

GPS Date - Year

Year

GPS Date - Month

GPS Date - Day

Days

UTC Time - Hours

Hours

UTC Time - Minutes

UTC Time - Seconds

seconds

ECU Time - Milliseconds

ms

No Environmental Data available for

SNAPSHOT DATA SUMMARY

RADIO | Stored | Rear Right Audio Speaker Output-Circuit Resistance Below Threshold

Record 0

NAME	VALUE	UNITS
DTC		
Test Failed		
Test Failed This Operation Cycle		
Pending DTC		
Confirmed DTC		

Record 1

NAME	VALUE	UNITS
DTC		
Test Failed		
Test Failed This Operation Cycle		
Pending DTC		
Confirmed DTC		

RADIO | Stored | Rear Right Audio Speaker Output-Circuit Open

Record 0

NAME	VALUE	UNITS
DTC		
Test Failed		

Test Failed This Operation Cycle	[REDACTED]	
Pending DTC		
Confirmed DTC		

Record 1

NAME	VALUE	UNITS
DTC	[REDACTED]	
Test Failed		
Test Failed This Operation Cycle		
Pending DTC		
Confirmed DTC		

No Snapshot Data available for [REDACTED]

No Snapshot Data available for [REDACTED]

No Snapshot Data available for [REDACTED]

INFORMATION REDACTED PURSUANT TO THE FREEDOM OF INFORMATION ACT (FOIA), 5 U.S.C. 552 (B) (6)