



CONFIGURATION REPORT

Vehicle
VIN

) 2.0L I4 DOHC DI TURBO ENGINE

Odometer
Publication Date

29632.5 miles

ECU SUMMARY INFO

ECU	NAME	PLUS	FLASH PART	CURRENT VIN	ORIGINAL VIN	PART #
TCM	Transmission Control Module					
PCM	Powertrain Control Module	CAN-C				
ICS	Integrated Center Stack	CAN-I				
TPM	Tire Pressure Monitor	CAN-C				
RFH	Radio Frequency Hub	CAN-C				
ESM	Electronic Shifter	CAN-C				
DTCM	Drive Train Control Module	CAN-C				
ORC	Occupant Restraint	CAN-C				
EPS	Electric Power Steering	CAN-C				
HVAC	Heat, Ventilation and A/C	CAN-I				
CSWM	Comfort Seat Wheel Module	CAN-I				
AMP	Amplifier	CAN-I				
IPC	Instrument Panel Cluster	CAN-C				
SCCM	Steering Column Control Module	CAN-C				
BCM	Body Controller	CAN-C				
RADIO	Radio	CAN-I				
OCM	Occupant Classification	CAN-C				
BPCM	Battery Pack Control Module	CAN-C				
HCP	Hybrid Control Processor	CAN-C				

	Central vision processing module	CAN-I				
	Auxiliary Hybrid Control Processor	CAN-C				
ABSO	Anti Lock Brakes OBD	CAN-C				
SGW	Security Gateway Module	CAN-C				
DPDM	Driver Presence Detection Module	CAN-C				
IDCM	Integrated Dual Charge Module	CAN-C				

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	SERIAL NUMBER	CVNS
	/	0E				
PCM						
ICS		10 1E 00				
TPM		0E 23 00				
RFH	/	10 31 00				
ESM		13 0C 00				
D		11 22 00				
ORC		12 23 00				
EPS		10 13 00				
HVAC		13 20 00				
CSWM		10 2B 00				
AMP		18 2E 01				
IPC		17 17 01				
SCCM		13 28 00				
		0D 11 00				
RADIO		16 27 13				
		11 31 01				
BPCM	Rest of world / ROW	14 20 05				
HCP		14 26 03				
		11 27 01				
		14 26 03				
ABSO		15 02 00				10
SGW		5				
DPDM		11 31 01				
IDCM		14 1D 00				

CONFIGURATION

CONFIGURATION

NAME	VALUE	UNITS
Autostick/ERS On/Off Switch Equipped		
Paddle-Shift Switches Equipped		
Shifter with Sport Mode Position Equipped		
Shifter with Low Mode Position Equipped		
Sport Mode Switch or Virtual Switch (Non-Terrain) Equipped		
Overdrive Off or Tow Haul Mode Switch or Virtual Switch (Non-Terrain) Equipped		
ECO/Optimizer Switch Equipped		
ERS/Autostick/Tip Non-paddle on Steering Wheel equipped		
ERS/Autostick/Tip Non-paddle on Shifter in D position equipped		
ERS/Autostick/Tip Non-paddle on Shifter in A or M position equipped		
FWD Equipped		
RWD Equipped		
AWD Equipped		
4WD with switchable Lo Range equipped		
Engine Start/Stop equipped		
Polystable E-shift (Cableless without return-to-center) equipped		
Long Learn Enabled		
Short Learn Enabled		

PCM CONFIGURATION

NAME	VALUE	UNITS
AC Equipped		
AC Equipped Over Bus		
Power Steering Switch Equipped		
4 Integrated Cruise Control		
EMAT (Getrag DCT transmission) Equipped		
Vehicle Speed Sensor #1 Calculated from CAN		
Police Package Equipped		
Unleaded Gasoline Fuel		
Unleaded diesel fuel		
Engine		
4 Speed Automatic Transmission Equipped		
Electronic Automatic Transmission (EATX) Equipped		
Vehicle Speed Sensor #1 Calculated by ECU		
Engine		
Engine		
Engine		
Sensorless FFV Enabled		
Electronic Throttle Control Equipped		
Engine		

V6 Engine		
V6 Engine		
V6 Engine		
Engine		
V6 Engine		
V6 Engine		
MTV Solenoid Equipped		
MDS Equipped		
Turbocharger Equipped		
SRV Equipped		
Secondary Air Equipped		
Shift Indicator Lamp Equipped		
Barometric Sensor Equipped		
TIP Equipped		
Battery Temp Sensor Equipped		
Knock Sensor 1 Equipped		
Knock Sensor 2 Equipped		
WI4 Variable Valve Timing Equipped		
Clutch Interlock Switch Equipped		
ESIM Equipped		
Linear Purge Equipped		
Linear EGR Equipped		
Continuous Variable Transmission Equipped		
Direct Injection Equipped		
Secondary Fuel Pump Equipped		
Electronic Coolant Pump Equipped		
O2 Sensor Bank 1 Sensor 1 Equipped		
O2 Sensor Bank 1 Sensor 2 Equipped		
O2 Sensor Bank 1 Sensor 3 Equipped		
O2 Sensor Bank 2 Sensor 1 Equipped		
O2 Sensor Bank 2 Sensor 2 Equipped		
Variable Displacement AC Equipped		
Fixed displacement AC Equipped		
WI4 Intake Flow Control Valve Equipped		
Electric Coolant Valve Equipped		
Engine Oil Heater Cooler Equipped		
Transmission Oil Heater Equipped		
Electric Water Pump Equipped		
Rear Heater Equipped		
Starter Relay 2 Equipped		
Inrush Current Reduction Relay Equipped		
Active Grille Shutter Equipped		

Electronic Vacuum Pump Equipped

Wide Range O2 Sensor Equipped

Wide Range Equipped

MultiAir Equipped

Engine Stop Start Equipped

Viscosity Sensor Equipped

Duty Cycle Purge Valve Equipped

Electric Thermostat Heater Equipped

Exhaust Cam 1 Equipped

Intake Cam 1 Equipped

engine

engine

engine

Engine

Tumble Generator Valve Equipped

Hybrid Electric Vehicle Equipped

Auxiliary Heater Electric Water Pump Equipped

Dual Speed Fuel Pump Equipped

Exhaust Cam 2 Equipped

Intake Cam 2 Equipped

1 Speed Fan Mechanical Relay System Equipped

2 Speed Fan Mechanical Relay System Equipped

2 Speed Fan PWM Relay System Equipped

Linear PWM Fan Relay System Equipped

PWM Fan Motor System Equipped

3 Speed Fan Mechanical Relay System Equipped

Fan Wake Up Relay System Equipped

2 Speed Fan 3 Driver 3 Relay System Equipped

/

/ /

/

VLP Is Learnable Indicator

VLP Equipped Indicator

VFS Actuators Available Indicator

ERS Equipped Indicator

Engine Software In Package

Transmission Software Included

ICC Cruise Equipped

ETC Cruise equipped

Adaptive Cruise Control Equipped

A/C Equipped

Adaptive Cruise Control Hardware Equipped

DUAL_ALTERNATOR_GEN1_LEARNEDCOPY

TOOLCONFIG_OIL_PRESS_ABS_EQUIPPED

Equipped

Equipped

Equipped

Cummins Equipped

Equipped

VMM Equipped

Powernet Equipped

() Equipped

() Equipped

Equipped

Gen Bus Equipped

Constant Heater Temperature Control Valve Equipped

High Side Port Tumble Valve Equipped

CMC Equipped

Turbine Volute Valve Actuator Equipped

Equipped

Active Exhaust Valve Equipped

Active Exhaust Pressure Sensor Equipped

Engine Idle Shutoff Equipped

Aisin RWD Transmission Equipped

Cooled EGR Equipped

Supercharger Equipped

Low Temperature Radiator Coolant Pump Equipped

Mechanical Coolant Pump Heater Equipped

Auxiliary Coolant Pump Heater Equipped

Compressed Natural Gas Equipped

PROXI Write Programming Support Enabled

Active Engine Mount Equipped

ZF 9 Transmission Equipped

HPT Transmission Equipped

Variable Speed Fuel Pump Equipped

Operator Idle Speed Request Equipped

PTO System Equipped

Air Shutoff Valve Bank 1 Control Solenoid 1 Equipped

Air Shutoff Valve Bank 1 Control Solenoid 2 Equipped

Air Shutoff Valve Bank 2 Control Solenoid 2 Equipped

Dual Stage Oil Pump Equipped

Auxiliary Coolant Pump Equipped

Trans Shift Equipped

Trans Reverse Lockout Equipped

Port Flap Valve Equipped

Brushless PWM Fan Equipped

Engine

Primary Lin Alternator Equipped

Coolant On-Off Pump Equipped

Oil Pressure Sensor Enabled

VIN Learning Strategy Equipped

Dual Fuel Tank Equipped

Yaw Rate Sensor ESC Equipped

I3 Engine

Coolant On-Off Valve Equipped

Buffered Crank Output for ANC (Active Noise Cancellation) Equipped

Buffered Crank Output for PHEV Engine Pulse Calculation Equipped

Throttle Inlet Temp Sensor Equipped

Humidity, Temperature and Pressure Sensor (LIN) Equipped

Dual Fuel Pressure Sensor Equipped

Brake Pedal Sensor Equipped

Dual Fuel Tank Equipped

PTO System Equipped

Low Temp Radiator Coolant Pump Equipped

Engine Idle Shutoff Equipped

A/C Relay Powered from Engine Switched Battery

CNG Large Gas Tank Equipped

Cooled EGR Equipped

Supercharger Equipped

Hybrid MEC Shifter Equipped

Dual Alternator Capable

Auxillary Coolant Pump Equipped

Speed Trans Equipped

Trans Equipped

CUSW Cruise Equipped

Power Steering Angle Sensor Mandatory

Throttle Inlet Temp Sensor Equipped

LIN Humidity, Temp, and Pressure Sensor Equipped

Dual Fuel Pressure Sensor Equipped

Brake Pedal Sensor Equipped

Clutch Sensor Equipped

SWAP HARDWIRED SWITCH INPUTS

Mass Airflow System Equipped

Bi-Directional Crank Sensor Equipped

Cruise (LIN) Equipped		
Operator Idle Speed Request Equipped		
02 EQUIPPED		
Cylinder Pressure Sensor Equipped		
Make Up Air Sensor Equipped		
Active Exhaust Pressure Sensor Equipped		
Secondary Mass Airflow Sensor Equipped		
I3 Engine		
Engine		
Variable Valve Lift Equipped		
Coolant On-Off Pump Equipped		
Primary Lin Alternator Equipped		
Electronic Parking Brake Equipped		
Active Exhaust Valve(s) Equipped		
Mechanical Coolant Pump Equipped		
Aux Coolant Pump Heater Equipped		
Heater Temp Control Valve Equipped		
High Side Port Tumble Valve Equipped		
Wastegate HBridge Equipped		
Remote Start Present		
Engine Oil Pressure Sensor Type		None

ICS CONFIGURATION

NAME	VALUE	UNITS
Display Type (Base)		
Display Type (Mid)		
Display Type (High)		

CONFIGURATION

NAME	VALUE	UNITS
System Type		
Tire System		
RSSI Margin Constant Override Setting		
RSSI Margin Constant A		No Unit
RSSI Margin Constant B		No Unit
RSSI Margin Constant C		No Unit
RSSI Margin Constant D		No Unit
Current Gain Mode		
Gain Mode Override Status		
WAL Gain Mode Setting		
High Gain Mode Setting		
Run Flat Tire Present		

SRT Vehicle Present

Base TPM Present

Premium TPM Present

BUX Deactivation Flag

TPM Legislation

RFH CONFIGURATION

NAME	VALUE	UNITS
PIN Successfully Programmed		
VIN Successfully Programmed		
Valid Key In Ignition		
Keyless Go		
Ignition system type connected		
e-shifter present		
Auto Park Present		
Secret Codes Programmed		
Passive Entry		
RKE		
Module Configuration Status		
Remote Start Present		
Programmed by		
Hardware Configuration: Remote Start Antenna		
Hardware Configuration: Front Left Door Handle H/W		
Hardware Configuration: Front Right Door Handle H/W		
Hardware Configuration: Rear Left Door Handle H/W		
Hardware Configuration: Rear Right Door Handle H/W		
Hardware Configuration: Trunk Door Handle H/W		
RFHub Locked		
Fob Location #1 Successfully Programmed		
Fob Location #2 Successfully Programmed		
Fob Location #3 Successfully Programmed		
Fob Location #4 Successfully Programmed		
Fob Location #5 Successfully Programmed		
Fob Location #6 Successfully Programmed		
Fob Location #7 Successfully Programmed		
Fob Location #8 Successfully Programmed		
Back Up Vehicle Config 1		
Back Up Vehicle Config 2		
Back Up Vehicle Config 3		
Back Up Vehicle Config 4		
Back Up Vehicle Config 5		
Back Up Vehicle Config 6		

Back Up Vehicle Config 7		
Back Up ECU Configuration 1		
Back Up ECU Configuration 2		
Back Up ECU Configuration 3		
Back Up ECU Configuration 4		
Back Up ECU Configuration 5		
Back Up ECU Configuration 6		
Back Up ECU Configuration 7		
Back Up ECU Configuration 8		
Back Up ECU Configuration 9		
Back Up ECU Configuration 10		
Back Up ECU Configuration 11		
Back Up ECU Configuration 12		
Back Up ECU Configuration 13		
Back Up ECU Configuration 14		
Back Up ECU Configuration 15		
Back Up ECU Configuration 16		
Back Up ECU Configuration 17		
Back Up Customer Settings Menu 1 ()		
Back Up Customer Settings Menu 2 ()		
Back Up Programmed ECUs: Cabin Network		
Back Up Programmed ECUs: P/T Chassis Network		
Secret Key Sent to Body Controller - Most recent attempt		
Secret Key Sent to Body Controller - Original attempt		

DTCM CONFIGURATION

NAME	VALUE	UNITS
Full-Time T-Case		
Front Locker Present		
Rear Locker Present		
FAD Present		
Mode Switch Present		
Left/Right Hand Drive		
Axle Ratio		
T-Case Type		
SRT Present		

ORC CONFIGURATION

NAME	VALUE	UNITS
Rollover Sensing		
EPPM		
()		

Driver Seatbelt Buckle Switch

Passenger Seatbelt Buckle Switch

Second Row Left seat belt Switch

Center seat belt Switch

Second Row Right seat belt Switch

Driver Seat Track Position Sensor

Passenger Seat Track Position Sensor

Passenger Occupant Detection Sensor

Passenger Airbag Disable Switch

Passenger Airbag Disable Indicator

Driver Frontal Squib 1

Driver Frontal Squib 2

Driver Frontal Squib 3

Passenger Frontal Squib 1

Passenger Frontal Squib 2

Passenger Frontal Squib 3

Driver Knee Bolster Squib

Passenger Knee Bolster Squib

Driver Seatbelt Retractor Pretensioner

Passenger Seatbelt Retractor Pretensioner

Driver Seatbelt Load Limiter

Passenger Seatbelt Load Limiter

Driver Seatbelt Anchor Pretensioner

Passenger Seatbelt Anchor Pretensioner

Driver Seatbelt Buckle Pretensioner

Passenger Seatbelt Buckle Pretensioner

Left Curtain Squib 1

Right Curtain Squib 1

Left Side Seat Squib 1

Right Side Seat Squib 1

Left Seat Side Airbag

Right Seat Side Airbag

Driver Frontal Squib 4

Passenger Frontal Squib 4

Left Up-Front Acceleration Sensor

Right Up-Front Acceleration Sensor

Right B-Pillar Impact Acceleration Sensor

Left B-Pillar Impact Acceleration Sensor

Left C-Pillar Impact Acceleration Sensor

Right C-Pillar Impact Acceleration Sensor

Right D-Pillar Impact Acceleration Sensor

Left D-Pillar Impact Acceleration Sensor

Left Side Door Pressure Sensor

Right Side Door Pressure Sensor

Configuration Column Identifier

CONFIGURATION

NAME	VALUE	UNITS
DualZone ATC Control (Factory)		
DualZone ATC Control		
Dual Zone MTC Control		
Single Zone MTC Control		
MTC With EBL ()		
MTC Without EBL ()		
MTC heater only ()		

AMP CONFIGURATION

NAME	VALUE	UNITS
ANC Calibration Date -		
ANC Calibration Date -		
ANC Calibration Date - Patch	0	
Current ANC Calibration ID - Service		
ANC Status		
Surround Sound Activated		
Door Module - Left Front		
Door Module - Right Front		
Premuim - 1		
Premuim - 2		
Premuim - 3		
Non -ANC		
No Rear Doors		
No Chimes		

IPC CONFIGURATION

NAME	VALUE	UNITS
Main Fuel Tank Gauge - Empty Stop Calibration		
Main Fuel Tank Gauge - Datum Calibration		
Main Fuel Tank Gauge - Datum Calibration		
Main Fuel Tank Gauge - Datum Calibration		
Main Fuel Tank Gauge - Full Stop Calibration		
Sub Fuel Tank Gauge - Empty Stop Calibration		
Sub Fuel Tank Gauge - Datum Calibration		
Sub Fuel Tank Gauge - Datum Calibration		
Sub Fuel Tank Gauge - Datum Calibration		

CONFIGURATION

NAME	VALUE	UNITS
Rear Wiper		
Tilt Telescope		
Paddle Shifter		
Cruise Control / ACC		

BCM CONFIGURATION

NAME	VALUE	UNITS
RBSM		
LBSM		
BCM (Interior Bus)		
HSM		
HVAC		
P		
Radio		
ITM		
AMP		
EDM		
HVAC_R		
TBM		
AHLM/AFLS		
ASCM		
BCM (PT)		
D		
PCM		
EPS		
ESM		
IPC		
ORC		
PTS		
ELSD		
AFLS		
ITBM		
OCM		

DPDM		
SGW		
ASBS		
ANC		
Number of Reprogramming Attempts - Counter #0		
Vehicle Configuration Programmed Status		
Last Programmed Status		
Last Configuration Odometer		miles
Vehicle Configuration Auto Write Counter		
Vehicle Configuration 1 - Write Counter		
Vehicle Configuration 2 - Write Counter		
Vehicle Configuration 3 - Write Counter		
Vehicle Configuration 4 - Write Counter		
Vehicle Configuration 5 - Write Counter		
Vehicle Configuration 6 - Write Counter		
Programmed ECUs: Cabin Network		
Programmed ECUs: P/T Chassis Network		
Programmed Network Configuration - Audio / Telematics Network		
Programmed ECUs: Hybrid LAN Network		
ECU Configuration 1 (CBC Configurable Inputs and Outputs)		
ECU Configuration 2 (CBC Features)		
ECU Configuration 3		
ECU Configuration 4		
ECU Configuration 5 (Wireless)		
ECU Configuration 5 (Doors)		
ECU Configuration 5 (Memory)		
ECU Configuration 6 (Brake)		
ECU Configuration 6 (Suspension)		
ECU Configuration 6 (Powertrain)		
ECU Configuration 6 (Safety)		
ECU Configuration 7 (CBC Exterior Lighting Calibrations)		
ECU Configuration 8 (LIN and Miscellaneous)		
ECU Configuration 9A		
ECU Configuration 9 (ITM)		
ECU Configuration 10		
ECU Configuration 11		
ECU Configuration 12		
ECU Configuration 13		
ECU Configuration 14		
ECU Configuration 15 (CBC Features)		
ECU Configuration 15 (Suspension)		
Vehicle Configuration 7 - Write Counter		

Vehicle Config		
Vehicle Config		
Model Year		
Vehicle Line		
Country Code		
Left/Right Hand Drive		
Remote Start Present		
Drive Configuration		
Emode Present		
Auto Highbeam		
Body Style		
Maximum Vehicle Speed		
Shifter Type		
Performance Pages Present		
Special Packages		
PTS Configuration		
Hill Descent Feature Present		
Select Speed Control Feature Present		
Power Inverter Type		
Thatcham Present		
Rain Sensor Present		
System Present		
Air Conditioning Present		
Cruise Feature is Present		
Flipper Glass Present		
Full Size Spare		
Off Road Capable		
Special Packages		
Max Load Inflation Pressure Rear Tire		
Max Load Inflation Pressure Front Tire		
Light Load Inflation Pressure Rear Tire		
Police Lighting Feature		
Power Lift Gate Present		
Power Right Sliding Door Present		
Power Left Sliding Door Present		
System Present		
Present		
T-Case Type		
Wheel Base		
FOBIK Safe Enable		
ELV Present		
Fuel Capacity		

Window Express Feature Configuration		
Adjustable Pedal Feature Present (non-Memory)		
Auto Headlamp Feature Present		
Door Alert Feature Present		
Present		
Vehicle is an SRT		
Disable Display of Radio Clock		
Chassis Type		
Display Outside Temperature Present		
HVAC Configuration		
Vehicle Brand		
Display Compass Heading Present		
Interior EC Mirror Present		
ESCL system present		
High Intensity Discharge Head Lamps		
Secondary Lock Present		
Liftgate/Trunk Type		
Collision Mitigation System present		
Forward Collision Warning present		
Base system present		
Premium system present		
Paddle Shift Feature Present		
Sport Mode Present		
Auto Park Present		
Passive Entry Present		
Keyless Go Present		
Transfer Case High Ratio		No Unit
Axle Ratio		
Transfer Case Low Range Reduction Ratio		
Dynamic Tire Circumference (All or Rear)		inch
Dual Rear Wheel (DRW) Vehicle Present		
Non-Regulated () Present		
Steering Ratio at		No Unit
Steering Ratio at Positive Angle 1		No Unit
Steering Ratio at Positive Angle 2		No Unit
Steering Ratio at Positive Angle 3		No Unit
Steering Ratio at Positive Angle 4		No Unit
Steering Ratio at Positive Angle 5		No Unit
Analog Door Sensor Configuration		
Air Quality System Present		
Steering Ratio at Negative Angle 1		No Unit
Steering Ratio at Negative Angle 2		No Unit

Steering Ratio at Negative Angle 3		No Unit
Steering Ratio at Negative Angle 4		No Unit
Steering Ratio at Negative Angle 5		No Unit
Ambient Light Dimmer Wheel Input Present Pin G9		
Low Beam Output Present - Pin A3, D2		
Rear Wiper Motor Park Present - Pin		
Left Rear Door Ajar Input Present - Pin		
Front Driver Analog Door Ajar Input Present - Pin		
Reserved - Pin		
Horn Switch Input Present - Pin		
Reserved - Pin		
Hood Ajar Switch Input Present - Pin		
Hard Top Sense Present - Pin		
Reserved -		
Reserved - Pin		
Passenger Door Ajar Signal Present - Pin		
Reserved - Pin		
Reserved - Pin		
Starter Relay Lowside Coil Drive - Pin D7		
Diesel Cabin Heater #2 Output Present - Pin D9		
Diesel Cabin Heater #3 Output Present - Pin D10		
Diesel Cabin Heater #1 Output Present - Pin D11		
Right Dedicated DRL Lamp Output Present - Pin		
Left Dedicated DRL Lamps Output Present - Pin		
Flipper Glass #2 Output Present		
Foot Well Lamps Output Present - Pin G24		
Front Fog Lamps Output Present - Pin A1 &		
Inverter Enable Relay Output Present - Pin		
Reserved -		
Gated Park ZFII Output Present - Pin		
Reserved - Pin		
Rear Fog Lamps Output Present - Pin &		
Rear Park Lamps Output Present - Pin &		
Rear Turn Lamps Output Present - Pin E3 &		
Run-ACC Y Relay #2 Output Present - Pin E9		
Side Markers Output Present - Pin &		
Trailer Backup Lamps Output Present - Pin		
Reserved - Pin F4		
UGDO Feed Output Present - Pin		
VTA Warning LED Output Present - Pin		
Park Brake Input Present - Pin		
Ambient Temperature Sensor Present - Pin		

Tip Start Enabled		
Dual Start Relay System Present		
Wiper Service Position Enabled		
Trailer Tow Present		
Quad Headlamps Enable		
Horn Chirp Allowed		
Bi Xenon Headlamps Enable		
Hazard Lamp Configuration		
Park Lamp Loadshed Enable		
Front Fog Lamp Dropout Enable		
Combined Rear Lighting Enable		
Side Repeaters Enable		
Lane Change		
Exterior Light Loadshed Enable		
Front Wiper Park Enable		
Rear Wiper Park Enable		
Reversible Washer Pump Enable		
Tail Lamp		
DRL Configuration		
DRL Lamp Location		
DRL Dropout Enable		
Tunnel Detection		
Military Vehicle Present		
LED Reverse Lamps Present		
LED Stop Lamps Present		
LED Rear Turn Lamps Present		
LED Tail Lamps Present		
LED Rear Fog Lamps Present		
LED License Lamps Present		
LED Front Turn Lamps Present		
LED Front Fog Lamps Present		
LED Dedicated DRL Present		
LED Low Beam Lamps Present		
LED High Beam Lamps Present		
LED Front Park/Marker Lamps Present		
Door Lock Switch Signal FT LT Usage (F9)		
Door Lock Switch Signal FT RT Usage (F23)		
Headlamp Wash Interval		
Headlamp Wash Shot		
Front Wiper Wipes After Wash		
Headlamp Washer Low Fluid Shut-Off Enable		
Intermittent Wiper States		

LED CHMSL Lamp Present		
Rear Camera Present		
Present		
Front Park Assist Present		
Front Heated Seats Present		
Front Ventilated Seats Present		
Destination		
Cabin Equilization Curve Number		
Hill Start Assist Customer Setting Option Present		
Radio Apps Present		
CTP Easy Entry Enable		
CTP Passive Entry Present		
CTP Auto Lock Disable		
SDAR Travel Link Present		
DAB Present		
Vehicle Theft Alarm Present		
Heated Steering Wheel Present		
VIN Check Digit Diable		
Surround Sound Feature Present		
Power Door Locks Present		
Antenna Type		
CTP Max AC Present		
Hybrid Electric Powertrain Present		
Disable CD Eject		
DTV Front Camera Present		
DTV Side Camera Present		
Tow Haul Present		
Hill Descent Control Present		
Audio Steering Wheel Switch Configuration		
Radio Display On/Off Softkey Present		
Microphone Tuning Parameter		
Microphone Configuration		
Microphone Type		
External Port Type		
Splashscreen Type		
ERS Available		
Rear Wheel Dually		
Max Gear		
Virtual Speedometer Units		
Speedometer Range Max Scale		
IC Config Feature		
Present		

Dimmer		
Heated Seat Present		
Split Shaft Present		
Manual Headlamp Leveling		
Gear Shift Indicator		
Service Interval		
Temperature Celsius for UK		
Type of Gallons		
Tip Start Present		
5 Trunk Lock		
Airport Scenario Trunk Set		
AP1 Left Front		
AP2 Right Front		
Left Rear		
Right Rear		
Global Up		
Global Down		
Sun Shade		
Puddle Lamp Present		
Rear Door Pre Short Drop		
Passenger Window Lockout		
Auto Power Folding Mirrors Present		
Folding mirrors present		
Heated Mirrors Present		
Mirror turn signals present		
Driver Memory Mirrors Present		
Passenger Memory Mirror Present		
Electro-chromatic driver mirror present		
Electro-chromatic passenger mirror present		
Tow Mirror Present		
Blindspot Mirror Present		
Window Motor Type		
Window Hall Sensors Present		
Frameless Window Present		
Memory Adjustable Pedals Present		
Tilt/Telescope Steering Present		
Memory Seat Present		
Rear Heated Seats Present		
Front Vented Seats Present		
Heated Steering Wheel Present		
Heated Seat Material Type		
Heated Wheel Material Type		

Rear Vented Seats Present	
Front Heated Seat Present	
Brake System ECU Configuration A	
Wheel overall ESC Maserati	
Brake System ECU Configuration B	
ECO Mode Configuration	
Dual Alternator Present	
ODS Present	
Driver Kneebag Present	
Passenger Kneebag Present	
Curtain Airbags Present	
Tow Hooks Present	
Passive Ped Pro Present	
2nd Row Seat Airbags Present	
Reserved	
Reserved	
Integrated EPP Present	
BUX vehicle	
Signature Light Present	
Dual Filament Headlamp	
Front Turn Lamp Diagnostics	
Auto Headlamp On Threshold	Volt
Auto Headlamp Off Threshold	Volt
Left Low Beam Voltage Regulation	
Left High Beam Voltage Regulation	
Right Low Beam Voltage Regulation	
Right High Beam Voltage Regulation	
Left Front Corner Voltage	
Right Front Corner Voltage	
Left Rear Corner Voltage	
Right Rear Corner Voltage	
Panic Enable	
Compass Mounting Orientation	
Washer Fluid Level Voltage Threshold	
Present	
M Present	
Humidity Sensor Present	
Manual Trans Present	
DC to DC Converter Present	
M Present	
Auto Relock Time	seconds
System Present	

DC to DC Converter #2 Present		
Illuminated Approach Interior Lighting Target Percentage		
Illuminated Approach Headlamp Target Percentage		
Illuminated Approach Taillamp Target Percentage		
Illuminated Approach Interior Lighting Ramp Up Time		
CRVMM Present		
EVIC Switch Module Present		
Compass Mounting Angle		
Signature Lamps or Mirror Repeater Present - Pin A5 & Pin A7		
Backup Reverse Lamp Left Present - Pin F41		
Backup Reverse Lamp Right Present - Pin		
Stop/Turn Lamp or Stop Lamp Present Pin &		
Left High Beam Present - Pin D1		
Right High Beam Present - Pin A2		
Left Front Lamp Diagnostics Present - Pin F25		
Right Front Lamp Diagnostics Present - Pin		
Left Rear Turn Lamp Diagnostics Present - Pin		
Right Rear Turn Lamp Diagnostics Present - Pin		
Brake Fluid Level Switch Signal Present - Pin		
Siren		
Ultrasonics		
Tilt		
Swing Gate Lock Present - Pin		
Swing Gate Unlock Present - Pin		
Front Fog Voltage		Volts
Rear Fog Voltage		Volts
CHMSL Lamp Output Disable		
Secondary Door Ajar Present - Pin		
Manual Door Locks Present		
Rain Sensor Module #2 Present		
Auto High Beam Module Location		
Average Last Longitudinal Acceleration Values		
Average Last Lateral Acceleration Values		
Excess Longitudinal Acceleration Factor		
Excess Lateral Acceleration Factor		
Brake Smoothing Duration		
Brake Smoothing Factor		
Steering Smoothing Duration		
Steering Smoothing Factor		
Steering Smoothing Threshold		
Brake Smoothing Threshold		
Maximum Longitudinal Change		

Maximum Lateral Change		
Acceleration Threshold		
Acceleration Factor		
Nose Dive Threshold		
Nose Dive Factor		
Auto-Relock Feature Enable		
PE Auto-Relock Feature Enable		
VTA Hood Ajar Monitoring		
Horn Chirp Duration		
Pitch and Roll Present		
Parking Light Enable		
Minimum Voltage Time		
M Battery Minimum Voltage		
Interior Lighting Night Threshold		
Interior Lighting Day Threshold		
Axle Locker Configuration		
Transmission Equipped		
Park Brake Type		
TPMS Configuration		
Hybrid Type		
TSBM Module Present		
ADR feature Present		
AGS Feature Present		
Temperature Display Resolution		
PTC Present		
Glovebox Control		
Glare Free Present		
Brake Type		
Suspension Type		
Park assist customer settings menu		
Park assist brake customer settings menu		
Park assist front volume customer settings menu		
Park assist rear volume customer settings menu		
Electric power steering customer settings menu		
Forward collision warning customer settings menu		
Auto on driver comfort customer settings menu		
Auxiliary switches customer settings menu		
Rear view camera gridlines customer settings menu		
Unit set customer settings menu		
Power accessory delay customer settings menu		
Ambient dimmer customer settings menu		
Tire jack mode customer settings menu		

Air suspension warning customer settings menu		
Automatic aero mode customer settings menu		
Auto high beam customer settings menu		
Auto park customer settings menu		
Blind spot alert customer settings menu		
Clock display customer settings menu		
Compass calibration customer settings menu		
Compass variance customer settings menu		
Consumption unit customer settings menu		
Distance unit customer settings menu		
Auto door lock customer settings menu		
Easy exit seat customer settings menu		
Auto entry exit mode customer settings menu		
EPB service mode customer settings menu		
Headlamp drop customer settings menu		
Headlamp off delay customer settings menu		
Headlamps on with wiper customer settings menu		
Passive entry customer settings menu		
Illuminated approach customer settings menu		
Lane departure torque customer settings menu		
Lane departure warning customer settings menu		
Rear camera customer settings menu		
Rain sensitive wipers customer settings menu		
Power take off customer settings menu		
Pressure unit customer settings menu		
Power unit customer settings menu		
Power liftgate chime customer settings menu		
Performance shift enable customer settings menu		
Rear view camera delay customer settings menu		
RKE unlock customer settings menu		
Speed unit customer settings menu		
Tilt mirror in reverse customer settings menu		
Torque unit customer settings menu		
Teen Key Fuel Pop-up Customer Settings Menu		
Teen Key Automatic High Beam Customer Settings Menu		
Passenger Airbag On/Off Customer Settings Menu		
Forward Collision Warning and Brake Customer Settings Menu		
Doors and Engine Off Power Delay Customer Settings Menu		
Radio Speaker Open Circuit Disable (LF)		
Radio Speaker Open Circuit Disable (RF)		
Radio Speaker Open Circuit Disable (LR)		
Radio Speaker Open Circuit Disable (RR)		

C Calibration Parameter Data Set	[REDACTED]	ms
Surround View Camera On/Off Softkey Present	[REDACTED]	
Drive Mode [REDACTED]		
Rear Defrost and Heated Mirrors Present		
Show Phone Information in Cluster		
Auto Dimming Mirror Hard Button Present		
Clari-Fi Present		
Automatic Crash Notification Feature Present		
Trailer Hitch Camera Present		
Park Assist Tuning Set		
Rear Defrost Presence		
Heated Mirrors Present		
Engine Displacement		
Steering C Factor		
Speedometer Tolerance		
Increasing speed constant		
Tachometer Type		
DTV Present		
Tri-State Comfort Climate Softkey Function Present		

RADIO CONFIGURATION

NAME	VALUE	UNITS
Satellite Subscription ID	[REDACTED]	
Satellite Subscription Status	[REDACTED]	
Satellite Subscription Reason Code		
Satellite Subscription Suspend Day		
Satellite Subscription Suspend Month		
Satellite Subscription Suspend Year		
[REDACTED] Button		
SDARS		
Navigation Active		
Cellular		
Internal CD Player		
Wi-Fi		
Bluetooth		
Application Framework		
FM Diversity		
Clock Defeat		
Automated Loudness		
Anti-Theft Enable Status		
[REDACTED] Selection		
Front Seat Video Playback		

Cabin EQ Curve Number Currently Used by	
Splash Screen	
Compass on the bus messaging Authorization	
GPS on the Bus messaging Authorization	
Hubs Detected	No
SD Card Readers Detected	
Enumerated B Devices	
Aux Jack	
DTV Short Term Configuration	

ABSO CONFIGURATION

NAME	VALUE	UNITS
Vehicle Line Identification		
Displacement		
Hybrid Type		
Trans Type		
Drive Configuration		
Chassis Type		
Axle Ratio		No
Tire Circumference		



VEHICLE SCAN REPORT

Vehicle
VIN

) 2.0L I4 DOHC DI TURBO ENGINE

Odometer
Publication Date

29632.5

ECU SUMMARY INFO

ECU	NAME	PBUS	FLASH PART	CURRENT VIN	ORIGINAL VIN	PART #
TCM	Transmission Control Module					
PCM	Powertrain Control Module	CAN-C				
ICS	Integrated Center Stack	CAN-I				
TPM	Tire Pressure Monitor	CAN-C				
RFH	Radio Frequency Hub	CAN-C				
ESM	Electronic Shifter	CAN-C				
DTCM	Drive Train Control Module	CAN-C				
ORC	Occupant Restraint	CAN-C				
EPS	Electric Power Steering	CAN-C				
HVAC	Heat, Ventilation and A/C	CAN-I				
CSWM	Comfort Seat Wheel Module	CAN-I				
AMP	Amplifier	CAN-I				
IPC	Instrument Panel Cluster	CAN-C				
SCCM	Steering Column Control Module	CAN-C				
BCM	Body Controller	CAN-C				
RADIO	Radio	CAN-				
OCM	Occupant Classification	CAN-C				
BPCM	Battery Pack Control Module	CAN-C				
HCP	Hybrid Control Processor	CAN-C				

	Central vision processing module	CAN-I				
	Auxiliary Hybrid Control Processor	CAN-C				
ABSO	Anti Lock Brakes OBD	CAN-C				
	Security Gateway Module	CAN-C				
DPDM	Driver Presence Detection Module	CAN-C				
	Integrated Dual Charge Module	CAN-C				

ECU SUMMARY INFO (CONT...)

ECU	COUNTRY CODE	HARDWARE VERSION	SOFTWARE VERSION	IDENT	SERIAL NUMBER	CVNS
TCM	/					
PCM						
TPM						
RFH	/					
ESM						
DTCM						
HVAC						
CSWM						
SCCM					S12310573	
RADIO					T	
	Rest of world / ROW					
HCP						
ABSO						
DPDM						

DTC SUMMARY

ECU	DTC CODE	DTC DESCRIPTION	STATUS
-----	----------	-----------------	--------

			Stored
			Stored
			Active
			Stored

ENVIRONMENTAL DATA SUMMARY

Stored

Start Button-General Electrical Failure

NAME	VALUE	UNITS
Test Failed		
Test Failed This Operation Cycle		
Pending DTC		
Confirmed DTC		
Test Not Completed Since Last Clear		
Test Failed Since Last Clear		
Test Not Completed This Operation Cycle		
Warning Indicator Requested		
DTC Extended Data Record Number - All		
Occurrence flag		
Original Odometer Value		
Most Recent Odometer Value		
Frequency Counter		
Ignition Cycle Counter		

RADIO

Stored

Bus Off Performance-

NAME	VALUE	UNITS
DTCTable		
TestFailed		
TestFailedThisMonitoringCycle		
Pending DTC		
Confirmed DTC		
Test Not Completed This Monitoring Cycle		
Warning Indicator Requested		
DTCExtendedDataRecordNumber		
Occurance Flag		
Reserved		
Original Odometer Value		
Most Recent Odometer Value		
Frequency Counter		
Ignition Counter		
RDI		
Event Counter		

Active | Hybrid Battery Pack Voltage Variation-

NAME	VALUE	UNITS
DTC		
Test Failed		
Test Failed This Operation Cycle		
Pending DTC		
Confirmed DTC		
Test Not Completed Since Last Clear		
Test Failed Since Last Clear		
Test Not Completed This Operation Cycle		
Warning Indicator Requested		
Occurrence flag		
Original Odometer Value		
Most Recent Odometer Value		
Frequency Counter		
Ignition Cycle Counter	0	
FoM - for this DTC (lifetime fails)		
FoM - for this DTC (lifetime fails counts on pass)		
FoM - for this DTC (lifetime longest fail on pass)		
Battery Total Time Awake		
Key in Ignition		
EPT -WakeUp		
HCP Contactor Command		
Contactor Status		
Plug in Status		
Balance Mode		
Vehicle Speed		
System (at time of fault		
Battery Lifetime of Charge		
Battery Lifetime of DisCharge		AHr
HVIL Status -Vehicle		
Cycles left to self heal		No Unit
HV Battery Charge Power 2sec		
HV Battery Charge Power 10sec		
HV Battery Discharge Power 2sec		
HV Battery Discharge Power 10sec		
Key - DriveRdy (CAN)		
Battery Lifetime Number Of Closes		
Battery Full Capacity		
Battery Cell Voltage Maximum		
Battery Cell Voltage Minimum		
Battery Cell Voltage Average		

Battery Temperature Maximum Module		°F
Battery Temperature Minimum Module		°F
Battery Temperature Average Module		°F
DTC Extended Data Record Number - All	01	
DTC Extended Data Record Number - 2		
HV Battery Charge Power		watts
HV Battery Discharge Power		watts
Key Position		
SOC		%
HV Bat SOH-R		%
HV Bat SOH-C		%
Cell Impedance Max Discharge		mOhms
Cell Impedance Min Discharge		mOhms
HVIL Status - Battery pack		
HVIL PWM Duty Cycle source - Vehicle		%
HVIL PWM Duty Cycle Source - Battery		%
HVIL PWM Duty Cycle Sink - Battery		%
HVIL PWM Frequency source - Vehicle		Hz
HVIL PWM Frequency Sink - Vehicle		Hz
HVIL PWM Frequency Source - Battery		Hz
HVIL PWM Frequency Sink - Battery		Hz
HVIL Returned current - Vehicle		mA
HVIL Returned current - Battery		mA
Battery Cell Highest Cell number		
Battery Cell Lowest Cell number		
HV Battery Current Sensor Primary		Amps
HV Battery Current Sensor Secondary		Amps
HV Battery Current HVBatCrnt		Amps
HV Battery Voltage (cell sum)		Volts
HV Battery Voltage (Module Sum)		Volts
Battery Temperature Highest Sensor number		
Battery Temperature Lowest Sensor number		
HV Cooling Battery coolant inlet temp		°F
HV Cooling Battery coolant outlet temp		°F
BPCM temperature max		°F
BPCM temperature min		°F
Vehicle Isolation Impedance (Positive side)		Mega Ohms
Vehicle Isolation Impedance (Negative side)		Mega Ohms
Vehicle Isolation Impedance (Equivalent)		Mega Ohms
Battery Isolation Impedance (Positive side)		Mega Ohms

Battery Isolation Impedance (Negative side)		Mega Ohms
Battery Isolation Impedance (Equivalent)		Mega Ohms
Engine Speed	0	rpm
Accelerator position	0.0	%
GPS Date - Year		Year
GPS Date - Month		
GPS Date - Day		Days
UTC Time - Hours		Hours
UTC Time - Minutes		
UTC Time - Seconds		seconds
HCP - System Shutdown Command (CAN)		
HCP - ePT LOC Diagnostics Enable (CAN)		
HCP - Propulsion system active (CAN)		
HV Sensor- Pack Voltage (U BAT P - U BAT M)		Volts
HV Sensor - DC Link Voltage (U DC LINK)		Volts
HV Sensor - main fuse Voltage (U MAIN P - U MAIN M) - U DC LINK		Volts
OBCM Fuse Voltage (U MAIN P - U AUX FUSE)	0.0	Volts
APM Fuse Voltage (U MAIN P - U AUX REL)	0.0	Volts
HV Sensor - Battery Voltage - Positive contactor (U BAT P)	8.0	Volts
HV Sensor - Battery Voltage - Negative contactor (U BAT M)		Volts
HV Sensor - Weld Contactor Voltage - Positive contactor (U MAIN P)		Volts
HV Sensor - Weld Contactor Voltage - Negative contactor (U MAIN M)		Volts
HV Sensor - U AUX FUSE		Volts
HV Battery Total Amp Hour Capacity (CAN)		AHr
HV Battery - Pack Isolation state (CAN)		
HV Battery - Powertrain Isolation state (CAN)		
HV Sensor - Pack Voltage VALIDITY (CAN)		
HV Battery Total Amp Hour Capacity VALIDITY (CAN)		
- MCU Reset Counter		
- RAM Reset Counter		
- ROM Reset Counter		
- Hall current sensor supply voltage ()		Volts
- Precharge Penalty Timer (CAN)		seconds
- RTC Circuit Status		
- HVBat Sleep Time		seconds
- System Mode		No Unit
- HV Battery pack contactor request (CAN)		
- HV Battery Pack contactor Open (CAN)		
- HV Battery pack Contactor welded and impeded opening (CAN)		
- Crash Indication (CAN)		
- Crash Indication VALIDITY (CAN)		

Retention Status		
M - Active weld check type		
Current Category of Wearout Counter		
HV Contactor State - Positive Contactor		
HV Contactor State - Negative Contactor		
HV Contactor State - Precharge Contactor		
CSC Fault - Cn Open		
CSC Fault - Cn Short to SWn		
CSC Fault - Auxiliary channel 1 Open		
CSC Fault - Auxiliary channel 2 Open		
CSC Fault - Measured result difference between Alternative path and Primary path is out of range		
CSC Fault - Balancing Switch Short		
CSC Fault - Balancing Switch Open		
CSC Fault - Alternate reference voltage is out of range		
CSC Fault - Vaa voltage is out of range		
CSC Fault - Level-shift amplifier offset voltage is out of range		
CSC Fault - Stuck ADC output bits verification with		
CSC Fault - Stuck ADC output bits verification with full-scale		
CSC Fault - Multiplexer Open/Short verification with HVMUX test current source		
CSC Fault - Multiplexer Open/Short verification with HVMUX test current sources		
CSC Fault - Measured result difference between Module voltage and Cell voltage summation		
CSC Fault - Vhv < Vhvuv		
CSC Fault - Vhv - Vdcin > Vhvov		
CSC Fault - Die Temperature is over the upper limit		
CSC Fault - Scanning for cell information is not complete		
CSC Fault - ADC Data Path error		
CSC Fault - Packet Error Check		
CSC Fault - Power-on reset event occurred		
CSC Fault - oscillator frequency is not within of its expected value		
CSC Fault - Same as Alrtosc1 (redundant alert)		
CSC Fault - Die Temperature is over the upper limit		
CSC Fault - Module number addressing is fail		
CSC Fault - Alive counter is not matched to the exepected value		
CSC Fault - PEC Bits in Data-check byte error		
CSC Fault - Vhv - V12 is too low		
CSC Fault - Transmit data is not equal to read back data		
CSC Diagnostics - Initialization Status		
CSC Diagnostics - CSC #01 Status	00 00 00 00	
CSC Diagnostics - CSC #02 Status	00 00 00 00	
CSC Diagnostics - CSC #03 Status	00 00 00 00	

CSC Diagnostics - CSC #04 Status	00 00 00 00	
CSC Diagnostics - CSC #05 Status	00 00 00 00	
CSC Diagnostics - CSC #06 Status	00 00 00 00	
CSC Diagnostics - CSC #07 Status	00 00 00 00	
CSC Diagnostics - CSC #08 Status	00 00 00 00	
CSC Diagnostics - Internal Operation Mode		
HVIL PWM Duty Cycle sink - Vehicle		
SBC Status		
Vref UV Flag		
Vref UV State		
5UV count @open	0	
5UV count @close	0	
@open	0	
@close	0	
Pos HSD Feedback Voltage		
Pos HSD Feedback Current		
Neg HSD Feedback Voltage		
Neg HSD Feedback Current		
OCM Value Mon Curr Enrg Val		
Retention Diagnosis Case		
Retention Diagnosis Flag		
Retention Diagnosis Status		

IDCM | Stored | APM HV Battery System Voltage Low-

NAME	VALUE	UNITS
DTC		
Test Failed		
Test Failed This Operation Cycle		
Pending DTC		
Confirmed DTC		
Test Not Completed Since Last Clear		
Test Failed Since Last Clear		
Test Not Completed This Operation Cycle		
Warning Indicator Requested		
DTC Extended Data Record Number - All		
Occurrence flag		
Original Odometer Value		
Most Recent Odometer Value		
Frequency Counter		
Ignition Cycle Counter		
M High Voltage DC Current Set Point		
APM Low Voltage DC Current Set Point		

Commanded APM Operating Mode		
APM High Voltage DC Voltage Set Point		
Low voltage battery voltage from		
APM Low Voltage DC Voltage Set Point		
APM Internal Mode		
APM Wake Up Status		
APM Wake Up Reason		
HV Contactor Status		
HV Battery Voltage from BPCM		
APM Estimated Power		
APM HV side Current Feedback		
APM LV side Current Feedback		
APM Operation Mode Status Reported from APM		
APM HV Side Voltage Feedback		
APM LV Side Voltage Feedback		
APM Current Limit Mode		
APM Power Limit Mode		
APM HV Over V Status		
APM LV High I Status		
APM LV High V Status		
APM LV Low V Status		
CurrentFailSts_APM		
GenericFailSts_APM		
APM Derating Mode Status		
APM Derating Reason		
APM Failure Mode Status		
APM Failure Reason		
APM Temp		°F
APM Temp Cold Plate		°F
APM Temp Two		°F
APM Util Pct of DC/DC		
APM Derating Power		
APM Batt Feed Volt		
APM I DC HV Set P Feedback		
APM LV I Set P Feedback		
APM HV V Set P Feedback		
APM V DC LV Set P Feedback		Volt
APM Input Power		
APM Output Power		
APM_CurrentOperTime		
APM_TotalOperTime		
DTC Extended Data Record Number - Record #2	00	

[REDACTED] Charge Tml	[REDACTED]	
[REDACTED] Idle Time	[REDACTED]	
[REDACTED] C Idle Tml	[REDACTED]	
Watt-[REDACTED] of AC Power	[REDACTED]	
[REDACTED] of Charge the HV Bus	[REDACTED]	
[REDACTED] M Mode	[REDACTED]	
[REDACTED] M Charger Ready		
[REDACTED] M WU Status		
Charge Enable Status		
[REDACTED] ([REDACTED]) Shutdown Command		
[REDACTED] ([REDACTED]) Enable Charge Command		
[REDACTED] ([REDACTED]) [REDACTED] Mode Request		
Generic Fail Sts		
Chrg Fail Sts		
[REDACTED] M Wake Up Reason		
[REDACTED] Control Mth		
[REDACTED] CM Deraing Reason		
Close Chrgr Cntctr		
Chrgr Cntctr Stat		
Chrg Mode		
[REDACTED] M Fault Reason		
EPT LOC Diag Enable		
[REDACTED] Shutdown Command		
HV Battey Contactor Open		
BPCM Request for HV Contactor		
HV Contactor Status		
Ignition on Time for DTC	[REDACTED]	
Module A Primary - PFC Temperature	[REDACTED] °F	
Module A Primary - LLC Temperature	[REDACTED] °F	
Module A Secondary - Buck Temperature	[REDACTED] °F	
Module A Secondary - Ambient Temperature	[REDACTED] °F	
Module A Primary - AC Side Volt	[REDACTED]	
Module A Primary - AC Side Current	[REDACTED]	
Module A Secondary - Battery Side Voltage	[REDACTED]	
Module A Secondary - Battery Side Current	[REDACTED]	
Module A Secondary - Buck Output Voltage	[REDACTED]	
Module B Primary - PFC Temperature	[REDACTED] °F	
Module B Primary - LLC Temperature	[REDACTED] °F	
Module B Secondary - Buck Temperature	[REDACTED] °F	
Module B Secondary - Ambient Temperature	[REDACTED] °F	
Module B Primary - AC Side Volt	[REDACTED]	
Module B Primary - AC Side Current	[REDACTED]	

	- Battery Side Voltage		Volts
Module B	- Battery Side Current		
	- Buck Output Voltage	0.0	Volts
	- HV Over Voltage Protect		
	Aux Over Voltage Protect		
M -	LV Aux Under Voltage Protect		
	Over Voltage Protect		
	Under Voltage Protect		
	- Over Voltage Protect		
M -	Under Voltage Protect		
M - Battery	Under Voltage Protect		
M - Battery	Over Voltage Protect		
	- AC Under Voltage Protect		
	- AC Over Voltage Protect		
	- AC Over Current Protect		
	- HV Voltage Over MaxCal Protect		
	- HV Over Current Protect		
	- Power Stage Over Voltage Protect		
	- Internal Memory Fault		
M -	Over Temperature Protect		
	- HCP Loss of Communication Protect		
	- CAN Bus Off		
M -	Pilot Duty Fault		
	- Loss BPCM Communication Protect		
M -	Prox Range To Low		
M -	Prox Range To High		
	- HV Voltage Under MinCal Protect		
	- SPI Communication Fault		
	- WakeUp Output Stuck Low		
M -	Pilot Short To Battery		
	- WakeUp Output Stuck High		
	- ORC Loss of Communication		
M -	HV Battery Not Contact		
	- Loss Communication Protect		
	- Receive HV Battery Contact Open From BPCM		
	- Aux Over Voltage Protect		
M -	Aux Under Voltage Protect		
M -	Primary Aux Over Voltage Protect		
	- Primary Aux Under Voltage Protect		
	- Stuck Shutdown		
M -	Cycle Shutdown		
M -	HV Under Voltage Protect		

OBCM - Vehicle Impact

OBCM - ARC/CRC Fault

OBCM - AC Contact Welded Fault

Control Pilot Open fault

Prox open fault

OBCM - Internal S2 Switch Low Fault

OBCM - Internal S2 Switch High Fault

OBCM - Pilot Range Fault

OBCM - Prox Range Fault

force shutdown fault

pilot signal wake up issue because of EVSE

HCP stuck low fault

HCP stuck High fault

Plant mode flag

Retry fault flag

Loss SBC communication (SPI)

pilto input short to battery fault in Driver mode detecting

pilot input short to ground fault

pilot short to ground fault in driver mode detecting

Charging ready line open fault

Pilot frequency range fault

OBCM - Internal S2 Switch High Fault in Driver mode detecting

Module A Primary - AC Under Voltage Protect

Module A Primary - PFC Power Limit

Module A Primary - PFC Enable States

Module A Primary - LLC Enable States

Module A Primary - PFC Under Voltage Protect

Module A Primary - PFC Over Voltage Protect

Module A Primary - Over Temperature Protect

Module A Primary - Hot Warning

Module A Primary - AC Present

Module A Primary - PFC Over Temperature Protect

Module A Primary - LLC Over Temperature Protect

Module A Primary - PFC Hot Warning

Module A Primary - LLC Hot Warning

Module A Primary - AC Over Voltage Protect

Module A Primary - Relay Enable States

Module A Primary - Aux Over Voltage Protect

Module A Primary - Aux Under Voltage Protect

Module A Primary - Secondary Micro Enable Command

Module A Primary - AC Vin Lost

Module A Primary - Loss Communication Protect

Module A Primary - Standby Mode		
Module A Primary - Operate Mode		
Module A Primary - Shutdown Mode		
Module A - Aux Enable States		
Module A - HV Enable States		
Module A - Under Voltage Protect		
Module A - Over Voltage Protect		
Module A - HV Over Voltage Protect		
Module A - HV Over Current Protect		
Module A - Over Temperature Protect		
Module A - Hot Warning		
Module A - HV Over Temperature Protect		
Module A - Ambient Over Temperature Protect		
Module A - HV Hot Warning		
Module A - Ambient Hot Warning		
Module A - Aux Over Voltage Protect		
Module A - Aux Under Voltage Protect		
Module A - Loss Primary Communication Protect		
Module A - LV Micro Enable Command		
Module A - Loss LV Communication Protect		
Module A - Primary Turn On States		
Module A - Primary Shutdown States		
Module A - HV Under Voltage Protect		
Module A - Standby Mode		
Module A - Operate Mode		
Module A - Shutdown Mode		
Module A - LV Micro Disable Command		
Module A - High Temperature Derating		
Module A - Low Temperature Derating		
Module A - High Temperature Derating		
Module A - Low Temperature Derating		
Module A - HV High Temperature Derating		
Module A - HV Low Temperature Derating		
Module A - Ambient High Temperature Derating		
Module A - Ambient Low Temperature Derating		
Module A - AC Input Voltage Derating		
Module A - HV Output Voltage Derating		
Module B Primary - AC Under Voltage Protect		
Module B Primary - Power Limit		
Module B Primary - Enable States		
Module B Primary - Enable States		
Module B Primary - Under Voltage Protect		

	Primary - PFC Over Voltage Protect		
	B Primary - Over Temperature Protect		
	Primary - Hot Warning		
	Primary - AC Present		
	Primary - PFC Over Temperature Protect		
	Primary - Over Temperature Protect		
	Primary - PFC Hot Warning		
	Primary - AC Over Voltage Protect		
	Primary - Hot Warning		
	Primary - Relay Enable States		
	B Primary - Aux Over Voltage Protect		
	B Primary - Aux Under Voltage Protect		
	Primary - Micro Enable Command		
	Primary - AC Vin Lost		
	Primary - Loss Communication Protect		
	Primary - Standby Mode		
	Primary - Operate Mode		
	Primary - Shutdown Mode		
	- Aux Enable States		
	- HV Enable States		
	B - Under Voltage Protect		
	B - Over Voltage Protect		
	- HV Over Voltage Protect		
	- HV Over Current Protect		
	- Over Temperature Protect		
	- Hot Warning		
	- HV Over Temperature Protect		
	- Ambient Over Temperature Protect		
	- HV Hot Warning		
	- Ambient Hot Warning		
	B - Aux Over Voltage Protect		
	- Aux Under Voltage Protect		
	- Loss Primary Communication Protect		
	- LV Micro Enable Command		
	- Loss LV Communication Protect		
	- Primary Turn On States		
	- Primary Shutdown States		
	- HV Under Voltage Protect		
	- Standby Mode		
	- Operate Mode		
	B - Shutdown Mode		
	- LV Micro Disable Command		

[REDACTED]	- PFC High Temperature Derating	[REDACTED]	
Module B [REDACTED]	- PFC Low Temperature Derating	[REDACTED]	
[REDACTED]	- [REDACTED] High Temperature Derating		
[REDACTED]	- [REDACTED] Low Temperature Derating		
[REDACTED]	- HV High Temperature Derating		
[REDACTED]	- HV Low Temperature Derating		
[REDACTED]	- Ambient High Temperature Derating		
[REDACTED]	- Ambient Low Temperature Derating		
[REDACTED]	- AC Input Voltage Derating		
[REDACTED]	- HV Output Voltage Derating		
[REDACTED] [REDACTED]			
[REDACTED] State_DF80			
[REDACTED] [REDACTED]			
[REDACTED] [REDACTED]			
[REDACTED] [REDACTED]			
[REDACTED] [REDACTED]			
[REDACTED] [REDACTED]			
GPS Date - Year			Year
GPS Date - Month			
GPS Date - Day			Days
UTC Time - Hours			Hours
UTC Time - Minutes			
UTC Time - Seconds			seconds
ECU Time - Milliseconds			ms

SNAPSHOT DATA SUMMARY

No Snapshot Data available for [REDACTED]

No Snapshot Data available for [REDACTED]

No Snapshot Data available for [REDACTED]00

No Snapshot Data available for [REDACTED]