

- Step 5** Inspect the LP hose for damage. Replace if necessary with KRV # 103593.
- Step 6** Disconnect the copper tubing using a 5/8" backup wrench on the range regulator and remove and discard the old tubing.
- Step 7** Insert the new copper tubing (KRV# 251268) through the grommet and attach the copper tubing to the range regulator using 5/8 wrench as a back up and to the supply hose. See figure 3 and 4.



Figure 3



Figure 4

- Step 8** Connect the range LP supply hose to the quick connect LP supply on the unit. Turn on the shut off valve on the quick connect connection.
- Step 9** Perform Drop Pressure Test.
- Step 10** Replace range cover and install screws and burner control knobs.

WARRANTY REIMBURSEMENT

Note – Either Inspection Only or Repair, not both can be claimed on each vehicle.

Inspection Only - Submit the request on Key Express with **Service Advisory # 07-093** noted in the customer complaint section and use **Flat Rate Code # 7109342K**. The amount of time that will be authorized for this repair is 0.3 hours.

Repair - Submit the request on Key Express with **Service Advisory # 07-093** noted in the customer complaint section and use **Flat Rate Code # 7109342B**. The amount of time that will be authorized for this repair is 0.5 hours.

If you have any questions, please call Keystone RV Customer Service at **(866) 273-1454**.