## DAIMLERCHRYSLER

## SAFETY RECALL G10 – TIRE INFLATION PRESSURE LABELS

Dear: (Name)

This notice is sent to you in accordance with the requirements of the National Traffic and Motor Vehicle Safety Act.

DaimlerChrysler Corporation has decided that some **2007 model year Dodge Ram 2500 Series 4x4 Pick Up truck models** fail to conform to Federal Motor Vehicle Safety Standard (FMVSS) No. 120 – Tire Selection and Rims for Motor Vehicles other than Passenger Cars.

- The problem is...The Certification label, Tire and Loading Information label, and<br/>Supplemental Tire Pressure Information label on your truck<br/>(VIN: xxxxxxxxxxxxx) contain incorrect tire inflation pressure<br/>information. Improper tire inflation pressure can cause tire failure and result in a<br/>crash without warning.
- What you must do to<br/>ensure your safety...~ We ask that you apply the enclosed Certification label overlay, Tire and<br/>Loading Information label overlay, and Supplemental Tire Pressure<br/>Information label so that they cover the original incorrect tire inflation<br/>pressure as described on the reverse side of this letter.
  - If preferred, you may contact your dealer to schedule a service appointment for installation of the labels. The service will be provided free of charge and should only take a few minutes to complete. However, additional time may be necessary depending on service schedules. Bring the enclosed three labels and this letter with you to your dealer. It identifies the required service to the dealer.
- *If you need help...* If you have questions or concerns which your dealer is unable to resolve, please contact DaimlerChrysler at 1-800-853-1403.

Please help us update our records, by filling out the attached prepaid postcard, if any of the conditions listed on the card apply to you or your vehicle. Be sure to print the last eight (8) characters of the VIN (VVVVVVV) and notification code G10 on the postcard.

If your dealer fails or is unable to remedy this noncompliance without charge and within a reasonable time, you may submit a written complaint to the Administrator, National Highway Traffic Safety Administration, 400 Seventh Street, S.W., Washington, DC 20590, or call the toll-free Auto Safety Hotline at 1-888-327-4236.

We're sorry for any inconvenience, but we are sincerely concerned about your safety. Thank you for your attention to this important matter.

(over)

Buckle up for Safety

Customer Services Field Operations DaimlerChrysler Corporation G10

Note to lessors receiving this recall: Federal regulation requires that you forward this recall notice to the lessee within 10 days.

## **Installation Instructions for Tire Pressure Labels**

- 1. Open the driver's door and locate the Certification label on the driver's door as shown in Figure 1.
- 2. Clean the existing Certification label by wiping it with a household cleaner to remove any dirt, oil residue or grease.
- 3. Remove the enclosed Certification label overlay from its paper backing and carefully install it on the Certification label, covering the incorrect tire inflation pressure information (Figure 1). Firmly press and smooth the label to the surface of the Certification label to ensure good adhesion.
- 4. Locate the Supplemental Tire Pressure Information label on the driver's door (Figure 1).
- 5. Clean the existing Supplemental Tire Pressure Information label by wiping it with a household cleaner to remove any dirt, oil residue or grease.
- 6. Remove the enclosed Supplemental Tire Pressure Information label from its paper backing and carefully install it over the original label (Figure 1).
- 7. Locate the Tire and Loading Information label on the "B" pillar (Figure 2).
- 8. Clean the existing Tire and Loading Information label by wiping it with a household cleaner to remove any dirt, oil residue or grease.
- 9. Remove the enclosed Tire and Loading Information label overlay from its paper backing and carefully install it on the original label covering the incorrect tire inflation pressure information (Figure 2).



Figure 2 – Four Door Model Shown