



ProLo Hatch Rear Support Receiver Replacement Instructions

Step 9: Rotate the handle clockwise to secure the receiver to the lid.



Step 10: Using the electric screw driver with Phillips head bit, fasten the four (4) screws into the holes in the receiver. Tighten each until the screw is fully seated. **Do Not Over Tighten Screws**



Step 11: Rotate the handle 90 degrees counter clockwise and guide the metal bracket into the groove on the plastic receiver.



Step 12: Close the lid and rotate the red handle 90 degrees clockwise to secure the lid and ensure proper alignment of the receiver and metal bracket on the lid to the red handle.



Step 13: Verify proper installation. With the lid closed, rotate the red handle counter clockwise 90 degrees. The metal bracket should release slightly from the plastic receiver.



Step 14: Close the lid, guide the metal bracket into the groove on the plastic receiver (as shown in Step 12). Rotate the red handle 90 degrees clockwise to secure the lid (as shown in Step 13). The replacement is complete.



For Technical Support, Email: tech.support@smiglobal.net

Specialty Manufacturing Group, Inc.
10200 Pineville Rd, Pineville, NC 28134
Toll Free 800-951-STOP (7867)
Phone 704-889-7518
Fax 704-889-2760
<http://www.smiglobal.net>

Ω End of Document Ω