



Recall Campaign

NHTSA#: 13V-609

TC#: 2013-431

Job Code: 9901120

Flat Rate: 1 hour

REQUIRES PARTS TO BE ORDERED FROM Starcraft for every unit.

ACTION REQUIRED:

Replace existing tires and spare with ST175/80R13D tires

Replace the following labels:

Federal Certification Label

Tire Label

Canadian Data Sheet (Canada Dealers only)

MODELS / UNITS:

Starcraft AR-ONE Travel Trailer

16BH E28V 5065-5067, 5070-5082, 5084-5094, 5097-5106

KIT CONTENTS

Kit #

13V-609

Note: Kit can only be ordered using the order form included with this bulletin.

- (1) Instruction sheet
- (3) ST175/80R13D tires kits (tire/rim included)

NOTE: Labels are not included with the kit. Labels will be mailed to the the registered owner with the Recall Notification. The owner will be instructed to take them to the Dealer servicing the recall.

TOOLS/MATERIAL REQ.:

Tire chocks
Tire lug wrench
Torque wrench
Floor jack

INSTRUCTIONS

1. Remove and replace both tires/rim on the unit.

NOTE: When you re-install the lug nuts, be sure they are tightened to the appropriate torque range (70-75 ft/lbs)

2. Remove and replace the spare tire/rim.

Tires should not be returned to Starcraft or to the tire vendor

CHANGING THE FEDERAL CERTIFICATION & TIRE LABELS

Remove existing label(s)

1. Locate the label(s) on the outside off door side (road side) front of the unit. Remove the existing Federal Certification and tire label from the unit and discard them.
2. Using isopropyl alcohol and a shop rag, remove any adhesive residue from the surface where the original label had been. Allow the area to dry for at least 30 seconds.

Apply new label(s)

3. Remove the protective back from the new Federal Certification Label. Align the new label in the same location of the original label and apply it to the surface. Remove any air bubbles from the label. Repeat this process for the tire label.

NOTE: Do not attempt to remove or adjust the label once it has come into contact with the surface. Doing so may damage the label or cause it not to adhere properly to the surface. F A LABEL IS DAMAGED OR WILL NOT PROPERLY ADHERE TO THE SURFACE, A NEW LABEL MUST BE ORDERED.

1SABS0BN4C28B5215

RESP MFR: **Starcraft** 09/11
FABRICANT RESP: V.I.N./N.I.V.
GVWR/PNBV KG: 7500 3405

1SABS0BN4C28B5215
SIZE/DIMENSION

GAWR/PNBE KG	TIRE/PNEU	RIMS/JANTE	PRESS./COLD INFL.	PRESS./GONFL FROID
3500 1589 FRONT/DEVANT	ST205/75R15C 15 X 5 JJ		50	345
00000 INT/CENTRAL			50	0000
3500 1589 REAR/ARRIERE	ST205/75R15C15 X 5 JJ		50	0345

TYPE OF VEHICLE/TYPE DE VEHICULE:
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.
FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND
STANDARDS PRESCRIBED UNDER THE CANADIAN
MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT
ON THE DATE OF MANUFACTURE SHOWN ABOVE.

TRAILER/REMORQUE
CE VEHICULE CONFORME A TOUTES LES NORMES QUI
LUI SONT APPLICABLES EN VERTU DU REGLEMENT
SUR LA SECURITE DE VEHICULES AUTOMOBILES
DU CANADA ET DES ETATS UNIS EN VIGUEUR A LA DATE
DE SA FABRICATION CI-DESSUS.

TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should not exceed 732 kg or 1612 lbs.
Le poids du chargement ne doit jamais dépasser 732 kg ou 1612 lb.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID
FRONT AVANT	ST225/75R15D	449 KPA, 65 PSI
REAR ARRIERE	ST225/75R15D	449 KPA, 65 PSI
SPARE DE SECOURS	ST225/75R15D	449 KPA, 65 PSI

SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS

Federal Certification Label

Tire Label

CHANGING THE CANADIAN DATA SHEET (CANADA DEALERS ONLY)

Apply new label

1. Locate the existing Canadian Data Sheet label on the inside of the cabinet door under the kitchen sink. Using a DRY rag, wipe off the surface of the existing label to remove any dust or dirt from the surface. Do not use any wet cleaner on the existing label as it may absorb the liquid adversely affecting the adhesive on the new label.
DO NOT attempt to remove the existing label.

2. Remove the protective back from the new Canadian Data Sheet label. Align the label with the existing label and apply it over the top of the original label.

NOTE: Do not attempt to remove or adjust the label once it has come into contact with the surface. Doing so may damage the label or cause it not to adhere properly to the surface. F A LABEL IS DAMAGED OR WILL NOT PROPERLY ADHERE TO THE SURFACE, A NEW LABEL MUST BE ORDERED.

1. PURPOSE

TO PROVIDE A REFERENCE FOR THE USER TO OBTAIN THE CANADIAN DATA SHEET INFORMATION FOR THE UNIT.

TO PROVIDE A REFERENCE FOR THE USER TO OBTAIN THE CANADIAN DATA SHEET INFORMATION FOR THE UNIT.

TO PROVIDE A REFERENCE FOR THE USER TO OBTAIN THE CANADIAN DATA SHEET INFORMATION FOR THE UNIT.

2. INFORMATION

TO PROVIDE A REFERENCE FOR THE USER TO OBTAIN THE CANADIAN DATA SHEET INFORMATION FOR THE UNIT.

TO PROVIDE A REFERENCE FOR THE USER TO OBTAIN THE CANADIAN DATA SHEET INFORMATION FOR THE UNIT.

TO PROVIDE A REFERENCE FOR THE USER TO OBTAIN THE CANADIAN DATA SHEET INFORMATION FOR THE UNIT.

Canadian Data Sheet