

TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT



TIRE	SIZE	COLD TIRE PRESSURE PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
PNEU	DIMENSIONS			
FRONT	ST22575R15LRD	448 KPA (65 PSI)		
AVANT	ST22575R15LRD	448 KPA (65 PSI)		
REAR	ST22575R15LRD	448 KPA (65 PSI)		
ARRIERE	ST22575R15LRD	448 KPA (65 PSI)		
SPARE	ST22575R15LRD	448 KPA (65 PSI)		

4EZTU2925E5020996

The weight of cargo should never exceed 1,207 kg or 2,660 lbs.
 Le poids du chargement ne doit jamais dépasser 1,207 kg ou 2,660 lb.

RECREATION VEHICLE TRAILER CARGO CARRYING CAPACITY

V.I.N.: 4EZTU2925E5020996
 THE WEIGHT OF CARGO SHOULD NEVER EXCEED
 1207 kg / 2660 lbs

CAUTION:
 A full load of water equals 143 kg or 315 lbs of cargo @ 1 kg/L (8.3 lb/gal)

MANUFACTURED BY/FABRIQUÉ KZRV, L.P. DATE: 02/2014

GVWR/PNBV: 4000 KG (8800 SHIP-SHEWANA, IN

GAWR (EACH AXLE) / PNBE (CHAQUE ESSIEU) 2000 KG (4400 LB) TIRE/PNEU ST22575R15LRD

RIM/JANTE 15 X 6 JJ

COLD INFL. PRESS. /PRESS. DE GONFL. À FROID 448 KPA (65 PSI/LPC)

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE. THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE - CE VÉHICULE EST CONFORME À TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU RÈGLEMENT SUR LA SÉCURITÉ DES

VÉHICULES AUTOMOBILES DU CANADA EN VIGUEUR À LA DATE DE SA FABRICATION.
 V.I.N./N.I.V. 4EZTU2925E5020996 TYPE/TYPE DE VÉHICULE: TRAILER TRAIREM TRA

Dubert