



Recall Campaign

NHTSA #: '16V-305

IC #: 2016-227

Job Code: 9901299

Flat Rate: 0.3 hr

NEW LABELS ARE ENCLOSED WITH THE NOTIFICATION LETTER

ACTION REQUIRED:**Replace the following Labels:**

Federal Cargo Carrying Capacity -ALL affected units(Yellow Label)

Tire Label - ALL affected units -

Federal Certification Label - Canadian Units ONLY

Models/ Units:

2017 Jay Flight Travel Trailer

27BHS

H1TH0051-0080

Parts Kit**Labels are enclosed with the Recall Notification****Supplies**

Isopropyl Alcohol and shop rag

CHANGING THE FEDERAL CERTIFICATION, CCC AND TIRE LABELS

Remove existing label(s)

1. Locate the label(s) on the outside off door side (road side) front of the unit. Remove the existing Federal Certification Label, Tire Label and Cargo Carrying Capacity Label.
2. Using isopropyl alcohol and a shop rag, remove any adhesive residue from the surface where the original label had been. Allow the area to dry for at least 30 seconds.

The labels below do NOT show the correct information for Recall 16V-305 2016-227
They are examples of the different types of labels affected.

Apply new label(s)

- Remove the protective back from the new labels. Align the new label in the same location of the original label and apply it to the surface. Remove any air bubbles from the label.

NOTE: Do not attempt to remove or adjust the label once it has come into contact with the surface. Doing so may damage the label or cause it not to adhere properly to the surface. IF A LABEL IS DAMAGED OR WILL NOT PROPERLY ADHERE TO THE SURFACE, A NEW LABEL MUST BE ORDERED.

* 1UJBJOB [REDACTED] *

RESP MFR: Jayco, Inc. DATE: 08/10
FABRICANT RESP: V.I.N./N.I.V.

GVWR: /PNBV KG 1UJBJOBK2B1J30198
5500 2497

SIZE/DIMENSION PRESS./COLD INFL. PRESS./GONFL FROID

GAWR/PNBE KG	TIRE/PNEU	RIMS/JANTE	PSI/LPC	KPA
2900 1317 FRONT/DEVANT	ST185/80R13C 13 X 4.50	JJ 50	345	
00000 INT/CENTRAL			0000	
2900 1317 REAR/ARRIERE	ST185/80R13C 13 X 4.50	JJ 50	0345	

TYPE OF VEHICLE/TYPE DE VEHICULE: TRAILER/REMORQUE

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

DE VEHICULE CONFORME A TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DE VEHICULES AUTOMOBILES DU CANADA ET DES ETATS UNIS EN VIGUEUR A LA DATE DE SA FABRICATION CI-DESSUS.

**Federal Certification Label
Canadian Units Only**

TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should not exceed kg or lbs.
Le poids du chargement ne doit jamais dépasser 732 kg ou 1612 lb.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID
FRONT AVANT	ST225/75R15D	449 KPA, 65 PSI
REAR ARRIERE	ST225/75R15D	449 KPA, 65 PSI
SPARE DE SECOURS	ST225/75R15D	449 KPA, 65 PSI

SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS

Tire Label

THE

A FULL LOA

THE WEIGH
THE FACTOR
FUEL IF AP

CONSULT Y
ADDITIONA
TOWING GI

Cargo Carrying Capacity Label