



BLUE BIRD

FINAL NOTICE

DATE: JANUARY 30, 2017
TO: BLUE BIRD OWNERS
SUBJECT: RECALL R16YT: PROPANE FUEL LINE ROUTING

According to our records, we have not received confirmation that the above referenced recall dated August 15, 2016, has been completed. A copy of Recall R16YT is attached.

Your buses affected by Recall R16YT are identified by Blue Bird body number and VIN under Section 2 on the enclosed cover sheet.

If this is the first time you received notification of Recall R16YT, please read the enclosed notification carefully and follow the instructions provided. Recall R16YT must be completed, as soon as possible.

If you have already had R16YT performed on your affected buses, please complete and mail the enclosed recall reply sheet to us in the enclosed postage paid pink reply envelope so we may update our recall records. Be sure the reply sheet is filled out properly.

Questions regarding this recall campaign should be directed to me at (478) 822-2242 or lisa.hancock@blue-bird.com

Thank you for your prompt attention to this matter.

Sincerely,

Lisa Hancock
Corporate Recall Administrator
Blue Bird Body Company



R16YT

IMPORTANT SAFETY RECALL NOTICE

NHTSA Recall Number: 16V-542 School Bus
NHTSA Recall Number: 16V-543 Non-School Bus

August 15, 2016

Dear Blue Bird Owner:

Subject: RECALL R16YT, Propane Fuel Line Routing

This important safety recall notice applies to your bus(es) identified by both Blue Bird Body Number and Vehicle Identification Number (VIN) on the enclosed yellow cover sheet.

This notice is sent to you in accordance with the requirements of the National Traffic and Motor Vehicle Safety Act.

Blue Bird Body Company is recalling certain model year 2015-2017 Vision Propane School Buses manufactured from July 3, 2014, through June 24, 2016, and certain model year 2016-2017 Vision Propane Non-School Buses manufactured from September 24, 2015, through May 21, 2016. Certain buses equipped with Ford 6.8L Propane Engines could have incorrect fuel line routing. If operated under this condition, this could cause the fuel lines to rub against each other which could lead to a propane fuel leak. A propane fuel leak in the presence of an ignition source could result in a fire causing injury and/or damage to property.

Buses should be corrected immediately according to the enclosed instructions for Recall R16YT. Owners should have the bus(es) inspected and re-route the fuel lines to prevent future damage. Fuel line(s) should be replaced if damage is found. **Parts are currently available in limited quantities at no cost to you.**

Your Blue Bird bus(es) affected by this recall are identified by both the Blue Bird Body Number(s) and Vehicle Identification Number(s) (VIN) on the enclosed yellow reply sheet. If you no longer own the subject bus(es), please complete the appropriate section of the yellow reply sheet and return to Blue Bird in the enclosed pink postage prepaid envelope.

Blue Bird recommends that you contact your local or nearest Blue Bird Dealer to arrange for this recall to be performed. The Dealer can perform the repairs, or arrange for repairs to be performed by a service repair facility authorized by the Dealer. However, you may elect to perform this recall yourself or pay another independent repair facility to perform this recall. A qualified technician should perform this recall.

If you elect to perform this recall yourself or pay another independent repair facility to perform this recall, complete and submit the Pink Owner's Recall Reply Sheet provided. The Reply Sheet includes a section for the owner to request reimbursement of the owner's labor or to request reimbursement for a labor invoice paid by the owner to an independent repair facility.



Steps and allowable labor times for this campaign:

Step A:

- Inspect, Add Ties, and Reroute Lines:
 - 0.5 hour (30 minutes)

Step B:

- If necessary, purging the system to disconnect line(s) for rerouting (no lines replaced) for additional:
 - 0.5 hour (30 minutes)

Step C:

- If necessary, purging the system to disconnect line(s) for rerouting and replace one line for additional:
 - 1 hour (60 minutes)

Step C+:

- If necessary, purging the system to disconnect line(s) for rerouting and replace additional line for additional:
 - 0.5 hours (30 minutes) for each

When preparing the Pink Reply Sheet for each bus:

- Select "A" or
- Select "A" and "B" or
- Select "A" and enter the number of lines replaced in "C"

Of course, if your Blue Bird Dealer performs the recall or arranged for repairs to be performed by a service facility authorized by the Dealer, the Blue Bird Dealer will notify Blue Bird about the completion of the recall.

Parts to complete Recall R16YT must be obtained from Blue Bird Recall Administration via e-mail at campaignparts@blue-bird.com or return the yellow coversheet to Blue Bird in the pink, self-addressed, postage prepaid envelope to receive parts at no charge. Be sure to provide a valid shipping address as UPS does not deliver to post office boxes. You should retain a copy of the reply sheet for your records. Parts are currently available in limited quantities.

If the modifications directed by this notification were performed on your bus prior to the receipt of this recall notification, attach a copy of the work order/invoice. Mail the documents in the **pink** self-addressed postage prepaid envelope included with the pink reply coversheet to Blue Bird for warranty consideration. Reimbursements will be made in accordance with the requirements of the National Highway Transportation Safety Act, Title 49 Code of Federal Regulations, Parts 573 and 577.

Federal law requires that any vehicle lessor receiving this recall notice must forward a copy of this notice to the lessee within ten days.



Blue Bird Body Company
Page 3

R16YT

If Blue Bird Body Company should fail to or is unable to remedy this condition without charge to you, you may contact:

**ADMINISTRATOR
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
1200 NEW JERSEY AVENUE, SE
WASHINGTON, D.C. 20590**

Or, you may call The National Highway Traffic Safety Administration toll free at:
1-888-327-4236 TTY 1-800-424-9153 or go to: <http://www.safercar.gov>

Questions regarding this recall campaign should be directed to me at (478) 822-2242 or lisa.hancock@blue-bird.com.

Sincerely,

A handwritten signature in dark blue ink, reading "Lisa Hancock" in a cursive script.

Lisa Hancock
Corporate Recall Administrator
Blue Bird Body Company



Propane Fuel Line Routing

RECALL

**Models Affected: Certain 2015 through 2017 Model Year Vision Buses
Equipped with Propane Engines**

ISSUE

Propane fuel lines may be crossed and/or rubbing. Crossed and/or rubbing fuel lines may become damaged from movement and develop a leak.

CORRECTIVE ACTION

Inspect fuel lines and if necessary reroute propane fuel lines to ensure the lines are secured parallel and are not rubbing. Replace any damaged fuel line(s).

INSPECTION

WARNING: Always follow all Federal, State, Local and Shop safety standards and use proper safety equipment, and thoroughly read and understand all instructions before performing these procedures.


1. Park bus on level surface, apply parking brake, turn off ignition, remove key, and chock wheels.
2. Disconnect batteries.
3. Open hood and locate propane fuel lines from Fuel Rail Pressure Control Module (FRPCM) to the rear of the engine.



RECALL CAMPAIGN R16YT




INSPECT FUEL LINE ROUTING BELOW FRPCM



FRPCM

Throttle body and air intake tube

Fuel line damaged from contact with air intake tube



4. Inspect for clearance between the fuel lines and the air intake tube.
5. If the fuel lines are contacting the air intake tube, inspect for damage to the fuel lines and follow reroute instructions.

NOTE: If any lines need replacing, obtain replacement parts before rerouting lines.

6. See Page 6 for help in identifying a good or damaged fuel line. If any fuel lines are damaged, follow replacement instructions.


RECALL CAMPAIGN R I 6 Y T



Propane Fuel Line Routing

RECALL

INSPECT FOR CROSSED AND RUBBING FUEL LINES



Cable tie and heavy duty cable mounts

These are examples of fuel lines routing where the fuel lines may be crossed and/or rubbing. These lines must be rerouted, per instructions on Page 4. Remove existing cable ties from both heavy duty cable mounts.

Note:

Do not remove heavy duty cable mounts just the cable ties.

7. Fuel lines may have been installed where they contact each other. If the lines are rubbing or crossed, then the fuel lines may become damaged. Remove the cable ties from both heavy duty cable mounts and inspect the fuel lines for any damage. If the fuel line has been damaged, follow fuel line replacement instructions.

NOTE: If any lines need replacing, obtain replacement parts before rerouting lines.

RECALL CAMPAIGN R I 6 Y T



Propane Fuel Line Routing

RECALL

REROUTE PROCEDURE

WARNING: Always follow all Federal, State, Local, and Shop safety standards and use proper safety equipment, and thoroughly read and understand all instructions before performing these procedures.

CAUTION: Allow engine and components to cool prior to performing these procedures to prevent risk of severe burns.

WARNING: Technicians working with, or around, fuel systems should be properly trained to utilize extreme care and caution at all times. Failure to exercise extreme caution and care may lead to serious accidents which can result in property damage, personal injury and/or death.

WARNING: LPG is under pressure, wear adequate eye protection. When LPG is discharged into the atmosphere the rapid change in pressure can cause a refrigerant condition in the fuel (quick cooling) and can harm your skin or cause serious burns much like frostbite. Always wear gloves.

WARNING: Liquid propane is cold. The temperature of propane in its liquid state is -44° F (-42° C). Wear eye and ear protection during venting and repair operations. Keep moisture away from the valves. Failure to heed this warning can result in personal injury.

1. Park bus on level surface, apply parking brake, turn off ignition, remove key, and chock wheels.
2. Disconnect batteries.
3. Open hood and locate propane fuel lines from FRPCM to the rear of the engine.
4. **NOTE 1:** Cable ties on both sides of the bracket were cut and removed during the inspection process.

NOTE 2: If any line needs replacing, obtain replacement parts before rerouting lines.

NOTE 3: If the heavy duty cable mounts are missing during the inspection, please contact Blue Bird Recall Administration at campaignparts@blue-bird.com for parts. Parts shown below will be needed before lines can be rerouted because these support the dual clamp ties.

- 00024168 Mount, Heavy Duty CABLE, .25 hole size (2 required)
- 01247709 Washer, Flat, 17/64 ID X 5/8 (1 required)
- 01667773 Capscrew, Hex HD, ¼ - 20 X 1 , Gr 5 (1 required)
- 01339639 Nut, Hex HD, ¼-20, PRVLG Torque, Flange (1 required)

R I G H T

RECALL CAMPAIGN



Propane Fuel Line Routing

RECALL

REROUTE PROCEDURE

5. Using Photo's 1, 2, 3, and 4 in the **Proper Routing and Clamping Section** as your guide, reroute the four fuel lines to be parallel with each other. Install two or three dual clamp ties Part Number 00024043 to maintain separation.
 - a. **NOTE:** It may be necessary to loosen the fuel lines on the bottom of the FRPCM to reroute these fuel lines. Please follow **Roush CLEANTECH Depressurization Procedure** at the end of the document for depressurization procedure (purging) a system prior to loosening fuel lines. If lines need to be disconnected from the FRPCM for rerouting, replace Jiffy Tite Fittings. Roush's description and part numbers for the 1/4 inch fitting is 25031 (2 per FRPCM, as well as, 4 in the fuel lines) and for the 3/8 inch fitting part is 85672 (2 per FRPCM). Please contact **ROUSH CLEANTECH** at Phone Number: **800.59.ROUSH** or e-mail ROUSHcleantech.com with any questions regarding Roush's procedures.
 - b. **Be sure to follow ALL of the Warnings and Cautions in the propane section of Blue Bird Service Manual.**
6. Maintain 1/2 inch minimum clearance between the throttle body/air intake tube and the bottom of the fuel lines (See Photo 1).
7. If any fuel line has been damaged, replace fuel line(s) by following **Roush CLEANTECH Instructions** at the end of this document. See Page 6 on how to identify a good or damaged fuel line. Please contact **ROUSH CLEANTECH** at Phone Number: **800.59.ROUSH** or e-mail ROUSHcleantech.com with any questions regarding Roush's procedures.
8. After all fuel lines have been rerouted, repaired and/or replaced, check for leaks, check all the surrounding components to be sure nothing has been displaced with this rework. Place the bus back into service.


R I 6 Y T
C A M P A I G N



Propane Fuel Line Routing

RECALL

HOW TO IDENTIFY A GOOD OR DAMAGED FUEL LINE/HOSE



Steel braid has been damaged, fuel line **MUST** be replaced.



Witness mark only, Do Not Replace.



Visible fiberglass damage shown on Roush Fuel Line. If the heat sleeve is worn through to the point that the fiberglass is visible like shown, then it is recommended that it be replaced. As long as the line underneath shows no damage to the braid then a replacement sleeve can be installed over the line. Please contact **ROUSH CLEANTECH** at Phone Number: **800.59.ROUSH** or e-mail ROUSHcleantech.com with any questions regarding Roush's procedures.

RECALL CAMPAIGN R I 6 Y T



Propane Fuel Line Routing

RECALL

PROPER ROUTING AND CLAMPING




Photo 1
(Viewed from front of engine)

RECALL CAMPAIGN R I G H T



Propane Fuel Line Routing


RECALL

PROPER ROUTING AND CLAMPING

Note: Ensure there is a minimum of 1/2 inch clearance between hoses.

10022862 Hose Assy., (fuel line return to tank)

10022860 Hose Assy., (fuel line from tank)



10020944 Hose Assy., (fuel return line from engine)

Existing support bracket and two heavy duty cable mounts

00024043 Tie, Clamp, Dual

00024043 Tie, Clamp, Dual

10020943 Hose Assy., (fuel supply line to engine)

Photo 2
(Viewed looking down on top of engine with air brakes)

RECALL CAMPAIGN R I G H T



Propane Fuel Line Routing

RECALL


PROPER ROUTING AND CLAMPING

10020943 Hose Assy., (fuel supply line to engine)

10022860 Hose Assy., (fuel line from tank)

Existing support bracket and two heavy duty cable mounts

10022862 Hose Assy., (fuel line return to tank)



00024043 Tie, Clamp, Dual

10020944 Hose Assy., (fuel return line from engine)

Photo 3
(Viewed from rear of engine looking forward with air brakes)

RECALL CAMPAIGN R16YT



Propane Fuel Line Routing


RECALL

PROPER ROUTING AND CLAMPING

10022862 Hose Assy.,
(fuel line return to tank)

00024043 Tie, Clamp, Dual

10022860 Hose Assy.,
(fuel line from tank)



10020944 Hose Assy.,
(fuel return line from
engine)

Existing support bracket
and two heavy duty
cable mounts

10020943 Hose Assy.,
(fuel supply line to
engine)

Photo 4
(Viewed looking down on top of engine with hydraulic brakes)

RECALL CAMPAIGN R I G H T



Propane Fuel Line Routing

RECALL

PART NUMBER	DESCRIPTION	QUANTITY
00024043	TIE, CLAMP, DUAL	3
10020943	HOSE ASSY, SUPPLY, FUEL RAIL,ROUSH PROPANE	As Required
10020944	HOSE ASSY, SUPPLY, FUEL RAIL,ROUSH PROPANE	As Required
10022860	HOSE ASSY, PROPANE, FRWD FUEL LINE , FEED, ROUSH ,CV	As Required
10022862	HOSE ASSY, PROPANE, FRWD FUEL LINE , FEED, ROUSH ,CV	As Required
00024168	MOUNT, HEAVY DUTY, .25 HOLE SIZE	As Required
01247709	WASHER, FLAT, 17/64 ID X 5/8	As Required
01667773	CAPSCREW, HEX HD, ¼ - 20 X 1 , Gr 5	As Required
01339639	NUT, HEX HD, ¼-20, PRVLG TORQUE, FLANGE	As Required

RECALL CAMPAIGN R16YT

1. Disable 12V power to the fuel pumps by removing the fuel pump fuse from the fuse panel on the vehicle.
2. Fully close the manual shut-off on the tank supply valve.
3. Start the vehicle and let it run until it stalls, this will remove the majority of the liquid from the fuel lines. (Delay period during this start will be extended due to fuel pumps not running and rail pressure not building)
4. Perform the starting procedure a second time to ensure liquid is removed from lines.
5. Locate the fuel line union on the return line near the fuel tank and slowly crack it loose to relieve the lines of the remaining vapor pressure.
6. Turn the ignition to crank and allow the vehicle to attempt to flush the system but do not allow the vehicle to crank (Be sure to turn the ignition off before the vehicle reaches 30 seconds of delay time). This will allow the pressure from the supply side of the system to drain through the return line union. This may have to be done several times until pressure is no longer coming from the return line union.
7. Perform the necessary fuel system repairs.

Fuel Rail Return Line – Replacement

NOTE: Clearing the propane out of the fuel lines (purging) is required before working on any fuel system component. Please follow the fuel system de-pressurization procedure outlined in the ROUSH CleanTech service manual.

WARNING: Liquid propane is cold. The temperature of propane in its liquid state at atmospheric pressure is – 44°F (–42°C). Wear eye and ear protection during venting and repair operations. Keep moisture away from the valves. Failure to heed this warning can result in personal injury.

Remove - Fuel Rail Return Line


1. Close the manual shut-off valve on the tank supply valve..
2. Disconnect the FRPCM wire harness connector at the FRPCM.
3. Connect the supplied bleed harness to the FRPCM.
4. Connect selected bleed harness leads to the battery positive (+) and known good vehicle ground.
5. Allow the FRPCM to bleed completely (minimum of five (5) minutes).
6. Disconnect the supplied bleed harness and leads.
7. Disconnect ground cable from vehicle battery and/or turn off battery switch.
8. Remove the air intake tube from the throttle body.
9. In order to verify that the fuel rail is fully depressurized, slowly loosen one of the Jiffy-Tite fittings in the fuel rail retighten Jiffy-Tite fitting to 20-22 Nm once propane is drained

WARNING: Liquid propane or vapor may vent from the Jiffy-tite fitting when loosened

10. Release the reusable zip tie from the fuel return line. Remove and discard reusable zip tie.
11. Disconnect the fuel return line from the FRPCM using the appropriate Jiffy-Tite tool.
12. Disconnect the fuel return line from the RH and LH fuel rails using the appropriate Jiffy-Tite tool.
13. Disconnect VMV hose from the Intake Manifold.


Welded Bracket Fuel Rail Return Line Only:

- a. Remove and discard (2) fuel return line bracket screws M6 x 1 x 20 and M6 x 1 x 16 as shown below.



100397a


- b. Remove (1) M6 X 1 X 16 screw and save for reuse. Remove the fuel return line from the engine.



100380a

P-Clip Attached Fuel Rail Return Line Only:

14. Remove (2) M6 x 1 x 14 screws and (1) M6 x 1 x 16. Save mounting screws for reuse. Remove the fuel return line from the engine.




100409a

Install – Fuel Rail Return Line

CAUTION: Fuel return line bracket screws must be installed in positions indicated or damage to intake manifold will occur.


15. By hand, slightly spread open the fuel return line bracket assembly (P/N P14BB-10F110-AA) and 1/4" clamps (P/N 11-054-0158). While supporting the fuel return line, install the bracket assembly over the fuel return line. Make sure the rubber portion of the bracket assembly is seated around the fuel return line and is not rolled or pinched. Position the fuel return line bracket assembly against the crimp on the fuel return line.



100407a

16. Position the replacement fuel return line onto the engine and connect the fuel return line to both the RH and LH fuel rails.

17. Loosely install two (2) M6 X 1 X 14 mm fuel return line bracket screws.



100409a


18. Compress the fuel return line bracket assembly around the fuel return line. Align the fuel return line bracket assembly to the fuel supply line support bracket. Ensure that the bracket assembly does not have to be forced into position.



100346a


NOTE: Do NOT bend the fuel return line.

Install the bracket assembly with the previously removed M6 X 1 X 16 mm screw. While tightening, make sure to apply pressure to the back of the bracket assembly to keep it from contacting the intake manifold. Torque to 8-12 Nm and mark the head of the screw after applying specified torque.



100347b

19. Tighten and torque the remaining fuel return line mounting bracket screws in sequence. Torque screw labeled #1 first followed by screw labeled #2. Torque to 8-12 Nm and mark the head of the screw after applying specified torque.
20. Reconnect the VMV hose to the intake manifold and position lock tab. Verify connection by gently pulling on VMV hose.



100408a

23. Replace Jiffy-Tite on FRPCM fuel rail return line fitting
24. Connect fuel rail return line to FRPCM
25. Reconnect the FRPCM to the engine harness.
26. Reconnect battery ground and/or turn on main power switch.
27. Open the manual shutoff valve on the tank and turn the key to the crank position. If the vehicle does not start after the first attempt, turn the key OFF and then turn the key to the crank position a second time. Repeat sequence until vehicle starts.