

CHANGING THE FEDERAL CERTIFICATION AND TIRE LABELS

Remove existing label(s)

1. Locate the label(s) on the outside off door side (road side) front of the unit.
2. Using isopropyl alcohol and a shop rag, remove any adhesive residue from the surface where the original label had been.
Allow the area to dry for at least 30 seconds.

The labels below do NOT show the correct information for Recall 16V671
They are examples of the different types of labels affected.

Apply new label(s)

3. Remove the protective back from the new labels. Align the new label in the same location of the original label and apply it to the surface. Remove any air bubbles from the label.

NOTE: Do not attempt to remove or adjust the label once it has come into contact with the surface. Doing so may damage the label or cause it not to adhere properly to the surface. IF A LABEL IS DAMAGED OR WILL NOT PROPERLY ADHERE TO THE SURFACE, A NEW LABEL MUST BE ORDERED.

* 1UJBJOBK		* *	
RESP MFR: Jayco, Inc.		DATE: 08/10	
FABRICANT RESP:			
V.I.N./N.T.V			
GVMR: /PNBV KG	1UJBJOBK		
5500 2497			
SIZE/DIMENSION		PRESS. /COLD INFL.	
		PRESS. /GONFL FROID	
GAWR/PNBE KG	TIRE/PNEU	RIMS/JANTE	PSI/LPC KPA
2900 1317 FRONT/DEVANT	ST185/80R13C 13 X 4.50	JJ 50	345
00000 INT/CENTRAL			0000
2900 1317 REAR/ARRIERE	ST185/80R13C 13 X 4.50	JJ 50	0345
TYPE OF VEHICLE/TYPE DE VEHICULE:		TRAILER/REMORQUE	
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.		CE VEHICULE CONFORME A TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DE VEHICULES AUTOMOBILES DU CANADA ET DES ETATS UNIS EN VIGUEUR A LA DATE DE SA FABRICATION CI-DESSUS.	



TIRE AND LOADING INFORMATION

RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should not exceed
Le poids du chargement ne doit jamais dépasser

kg ou
732
lbs.
1612

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
FRONT AVANT	ST225/75R15D	449 KPA, 65 PSI	
REAR ARRIERE	ST225/75R15D	449 KPA, 65 PSI	
SPARE DE SECOURS	ST225/75R15D	449 KPA, 65 PSI	

Tire Label

Federal Certification Label

Instructions for Canadian Data Sheet - CSA built Units Only

1. Locate the existing **Canadian Data Sheet** label on the inside of the cabinet door under the kitchen sink. Using a DRY rag, wipe off the surface of the existing label to remove any dust or dirt from the surface. Do not use any wet cleaner on the existing label as it may absorb the liquid adversely affecting the adhesive on the new label.
DO NOT attempt to remove the existing label.
2. Remove the protective back from the new Canadian Data Sheet label. Align the label with the existing label and apply it over the top of the original label.

NOTE: Do not attempt to remove or adjust the label once it has come into contact with the surface. Doing so may damage the label or cause it not to adhere properly to the surface. IF A LABEL IS DAMAGED OR WILL NOT PROPERLY ADHERE TO THE SURFACE, A NEW LABEL MUST BE ORDERED.

[illegible]