

MOTOR HOME OCCUPANT AND CARGO CARRYING CAPACITY

VIN: [REDACTED]

THE COMBINED WEIGHT OF OCCUPANT AND CARGO SHOULD

NEVER EXCEED: 1105 kg or 2437 lbs

Safety belt equipped seating capacity: 5

CAUTION:

A full load of water equals 83 kg or 183 lbs of cargo @ 1 kg/L (8.3 lb/gal) and the tongue weight of a towed trailer counts as cargo

RECREATIONAL VEHICLE TRAILER CARGO CARRYING CAPACITY
Capacité de transport de chargement de caravane de véhicule de récréation

CARGO-CARRYING CAPACITY IS DETERMINED WITH THE FRESH WATER TANKS FULL AND THE WASTE TANKS EMPTY

Capacité de chargement est calculée avec les réservoirs d'eau douce pleins et les réservoirs d'eaux usées vides

Dry weight/Poids Sec:	3798 KG	VIN/NIV:	[REDACTED]
Cargo carrying capacity:	1022 KG	Capacité de transport de chargement:	1022 KG
Calculated with the fresh water tanks full		Calculé avec les réservoirs d'eau douce pleins	
Cold:	72 KG	Froid:	72 KG
Hot:	11 KG	Chaud:	11 KG
Mass of waste water tank		Masses de réservoirs d'eaux usées pleins:	94 KG
	94 KG		



TIRE AND LOADING INFORMATION

Seating Capacity | Total:5 | Front:2 | Rear:3
The combined weight of occupants and Cargo should never exceed 1105 Kgs or 2437 Lbs

TIRE	SIZE	COLD TIRE PRESSURE	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT	LT215/85R16	409 kpa 61 psi	
REAR	LT215/85R16	409 kpa 61 psi	
SPARE	LT215/85R16	409 kpa 61 psi	



RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

Nombre De Places | Total:5 | Avant:2 | Arrière:3
Le poids total des occupants et du chargement ne doit jamais dépasser 1105 Kgs ou 2437 Lbs

PNEU	DIMENSIONS	PRESSION DES PNEUS À FROID	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
AVANT	LT215/85R16	409 kpa 61 lb/po2	
ARRIÈRE	LT215/85R16	409 kpa 61 lb/po2	
DE SECOURS	LT215/85R16	409 kpa 61 lb/po2	

G
A
A
0
0
1
0
0
3



Dry Weight: 8372 lbs



Dry Weight: 8372 lbs

MANUFACTURED BY / FABRIQUE PAR **FOREST RIVER, INC.**

V.I.N./N.I.V. [REDACTED] **GAB24STM**

GVWR/PNBV **5003** KG (**11030** LB) TYPE/TYPE **MH/AC**

DATE **12/16/2015**

DESIG. SEAT CAP./NOMBRE D'ESIGNE' DE PLACES ASSISES **5X68kg=340 kg or 5X150lbs=750 lbs**

GAWR/PNBE	TIRES/PNEU	RIMS/JANTE	COLD INFL. PRESS/PRESS DE GONFL. A FROID
FRONT/AVANT (2000 KG 4410 LB)	LT215/85R16	16X5.5	409 KP SINGLE DUAL (61 PSI/LPC <input checked="" type="checkbox"/> <input type="checkbox"/>
INTERM/INTERM (0 KG 0 LB)			0 KP SINGLE DUAL (0 PSI/LPC <input type="checkbox"/> <input type="checkbox"/>
REAR/ARRIÈRE (3502 KG 7720 LB)	LT215/85R16	16X5.5	409 KP SINGLE DUAL (61 PSI/LPC <input type="checkbox"/> <input checked="" type="checkbox"/>

G
A
A
0
0
1
0
0
3

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE.

CE VEHICULE EST CONFORME A TOUTES LES NORMES QUI UI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICLES AUTOMOBILES DU CANADA EN VIGEUR A LA DATE DE SA FABRICATION.

INC. VEL. MFG. BY: **Mercedes-Benz Canada**