



U.S. Department of Transportation
**National Highway Traffic Safety
Administration**

1200 New Jersey Avenue SE
Washington, DC 20590

February 28, 2019

Mr. David Mihalick
Standards Compliance Manager
Airstream, Inc.
419 West Pike Street
P.O. Box 629
Jackson Center, OH 45334-0629

NEF-150KL
19V-024

Subject: Incorrect Tire Info Printed on Label/FMVSS 110

Dear Mr. Mihalick:

This letter serves to acknowledge Airstream, Inc.'s notification to the National Highway Traffic Safety Administration (NHTSA) of a safety recall which will be conducted pursuant to Federal law for the product(s) listed below. Please review the following information to ensure that it conforms to your records as this information is being made available to the public. If the information does not agree with your records, please contact us immediately to discuss your concerns.

Makes/Models/Model Years:
AIRSTREAM/BASECAMP/2019

Mfr's Report Date: January 3, 2019

NHTSA Campaign Number: 19V-024

Components:
EQUIPMENT:OTHER:LABELS

Potential Number of Units Affected: 189

Problem Description:

Airstream, Inc. (Airstream) is recalling certain 2019 Airstream Basecamp X recreational vehicles. The Federal Certification Label and Tire Placard may have incorrect information stating that the vehicle is equipped with 235/55R18 Load Range D tires needing 80 psi, when the vehicles are actually equipped with 235/75R15 Load Range D tires needing 51 psi. As such, these vehicles fail to comply with the requirements of Federal Motor Vehicle Safety Standard (FMVSS) number 110, "Tire Selection and Rims."

Consequence:

If the information is incorrect, the operator may overinflate the tires, increasing the risk of a crash.

Remedy:

Airstream has notified owners and will send them a new corrected Federal Certification Label and Tire Placard, free of charge. The recall began on February 22, 2019. Owners may contact Airstream customer service at 1-877-596-6505 or 1-937-596-6111 extension 7401 or 7411.

Notes:

Owners may also contact the National Highway Traffic Safety Administration Vehicle Safety Hotline at 1-888-327-4236 (TTY 1-800-424-9153), or go to www.safercar.gov.

NHTSA is missing critical, required information for this safety recall. This information must be supplied through the NHTSA Recalls Portal within 5 working days of confirming its accuracy:

- A statement that the defect or noncompliance can cause a vehicle crash without prior warning; or a description of whatever prior warning may occur, and a statement that if this warning is not heeded, a vehicle crash can occur (49 CFR 577.5 (f)(1)).
- 573 filings must supply the estimated date(s) for which it will notify owners regarding this safety recall. (49 CFR 573.6 (c)(8)(ii)).
- 573 filings must supply the estimated date(s) for which it will notify dealers and/or distributors regarding this safety recall. (49 CFR 573.6 (c)(8)(ii)).

Under 49 U.S.C. § 30112(a), it is illegal for anyone, including a manufacturer, distributor, dealer, or retailer to sell an item of equipment or vehicle that fails to comply with all applicable Federal motor vehicle safety standards.


Please be reminded of the following requirements:

Copies of all notices, bulletins, dealer notifications, and other communications that relate to this recall are required to be submitted to this office no later than 5 days after they are originally sent (if they are sent to more than one manufacturer, distributor, dealer, or purchaser/owner).

As stated in Part 573.7, submission of the first of six consecutive quarterly status reports is required within one month after the close of the calendar quarter in which notification to purchasers occurs. Therefore, the first quarterly report will be due on, or before, 30 days after the close of the calendar quarter.

Your contact for this recall will be Kristin Lepper who may be reached by phone at 202-366-5227, or by email at kristin.lepper@dot.gov. We look forward to working with you.

Sincerely,



Kareem Habib
Acting Chief, Recall Management Division
Office of Defects Investigations
Enforcement