



LOW PROFILE SERIES





LOW PROFILE SERIES

Super Diesel Trailer







GENERAL DIMENSIONS AND WEIGHTS - SKID:

Length: 14.75' (4.5m) (573 Model) Length: 16.4' (5m) (873 Model) Length: 18' (5.5m) (1273 Model)

Height: 82" (208m)

Empty Weight: 5,440lbs (2468kg) (573 Model) Empty Weight: 6,160lbs (2794kg) (873 Model) Empty Weight: 9,250lbs (4,195.7kg) (1273 Model)

Width: 93" (236cm)

Width: 94" (239cm) (1273 Model)

GENERAL DIMENSIONS & WEIGHTS-TRAILER:

Empty Weight: 6,440lbs (573 Model) Empty Weight: 6,670lbs (873 Model) Empty Weight: 8,280lbs (873 Heavy) Empty Weight: 9,680lbs (1273 Model) Length: 19.25' (5.9m) (573 Model) Length: 22.4' (6.8m) (873 Model) Length: 24' (7m) (1273 Model)

Width: 93" (236.2cm)

Width: 100" (254cm) (873 Heavy) Width: 94" (239cm) (1273 Model)

Height: 90" (228.6cm)

Height: 111" (282cm) (1273 Model)

Brake Type: Electric Hitch Type: Pintle

GVWR: 9,995lbs (4,534kg) (573 Lite)

GVWR: 12,000lbs (5,443kg) (573 Model) GVWR: 14,000lbs (6,350kg) (573 Heavy)

GVWR: 14,000lbs (6,350kg) (873 Model) GVWR: 20,000lbs (9,072kg) (873 Heavy)

GVWR: 24,000lbs (10,886.2kg) (1273 Model) Trailer Axles: Tandem dually (1273 Model)

ENGINE 573/873/1273 SDT:

Horsepower: 49 hp (37kW) Yanmar Diesel Tier 4 Final Horsepower: Optional 83hp (61kW) Yanmar Diesel T4I

Enclosure: Yes

Fuel Tank Capacity: 30gal (114L)

WATER TANK:

Water Tank Capacity:
573 Lite: 100gal (379L)
573 Model: 200gal (757L)
573 Heavy: 300gal (1,136L)
873 Model: 200gal (757L)
873 Heavy: 400gal (1,515L)
1273 Model: 300gal (1,136L)

Number of Tanks: 2

High Pressure Pump Flow Rate: 4gpm (15.1 lpm) High Pressure Pump: 4,000psi (275.8 bar) High Pressure Hose Length: 50' (15m)

Low Water Shut Off: Yes

SPOIL TANK:

Spoil Tank Capacity: 500gal (1,893L) (573 Model) Spoil Tank Capacity: 800gal (3,028L) (873 Model) Spoil Tank Capacity: 1,200gal (4542.5L) (1273 Model) Door Type: Hydraulic Tank Lift Type: Hydraulic

VACUUM:

Type of Filters: Cartridge filter 0.5 microns
Hose Length: 30' (9m)
Hose Width: 3" (8cm)
Hose Width Optional: 4" (10cm)
Vacuum: 1,000cfm
Water Trap Capacity: 60gal (227L)

CONTROL PANEL:

Controls: Curbside Gauges: Analog & Digital

Suction Hose Storage: 30' (9m)

OPTIONAL BOOM:

Pick up Hose: 4" (10cm) Reach: 15' (4.6m) Movement: 6-way

OPTIONAL STRONG ARM:

Reach: 15' (4.6m)




CVS FILTRATION HOUSING:

The LP ground level filtration housing also incorporates a 28" (71.1cm) diameter cyclone, four-way valve for reverse pressure, and the largest silencer in the industry for quiet performance. **Patented.**

7 SERIES HYDRAULIC CLAW DOOR:

No fuss, over center locking mechanism for positive lock and unlock.





OPTIONAL BOOM:

Optional six-way hydraulic boom maximizes job performance by supporting the weight of the vacuum hose.

Vac-Tron Equipment, LLC., reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice Shown is for illustrative purposes only, and may display optional accessories or components. Please contact your local Vac-Tron dealer for more information on machine specifications Vac-Tron and the Vac-Tron logo are trademarks of Vac-Tron Equipment.

2017 Vac-Tron Equipment, LLC. All Rights Reserved. Printed in the U.S.A. Please Recycl

