



VAC-TRON[®] EQUIPMENT

The Industry Innovator



CVS FILTRATION
HOUSING



7 SERIES
HYDRAULIC
CLAW DOOR

LP 573/873/1273 XDT:

LOW PROFILE SERIES

Standard Diesel Trailer

LOW PROFILE
SERIES



OPTIONAL
STRONG
ARM



WWW.VACTRON.COM

1-888-VAC-TRON

822-8766



GENERAL DIMENSIONS & WEIGHTS - SKID:

Length: 14.75' (4.5m) (573 Model)
 Length: 16.4' (5m) (873 Model)
 Length: 18' (5.5m) (1273 Model)
 Height: 82" (208.3cm)
 Empty Weight: 5,440lbs (2467.5kg) (573 Model)
 Empty Weight: 6,160lbs (2794.1kg) (873 Model)
 Empty Weight: 9,250lbs (4,195.7kg) (1273 Model)
 Width: 93" (236.2cm)
 Width: 94" (239cm) (1273 Model)

GENERAL DIMENSIONS & WEIGHTS - TRAILER:

Empty Weight: 6,190lbs (573 Model)
 Empty Weight: 7,140lbs (873 Model)
 Empty Weight: 7,880lbs (Heavy)
 Empty Weight: 9,680lbs (1273 Model)
 Length: 19.25' (5.9m) (573 Model)
 Length: 22.4' (6.8m) (873 Model)
 Length: 24' (7m) (1273 Model)
 Width: 93" (236.2cm)
 Width: 94" (239cm) (1273 Model)
 Height: 90" (228.6cm)
 Height: 111" (282cm) (1273 Model)
 Brake Type: Electric
 Hitch Type: Pintle
 GVWR: 9,995lbs (4,534kg) (573 Lite)
 GVWR: 12,000lbs (5,443kg) (573 Model)
 GVWR: 14,000lbs (6,350kg) (573 Heavy)
 GVWR: 14,000lbs (6,350kg) (873 Model)
 GVWR: 20,000lbs (9,072kg) (873 Heavy)
 GVWR: 24,000lbs (10,886.2kg) (1273 Model)
 Trailer Axles: Tandem dually (1273 Model)

ENGINE 573/873/1273 XDT:

Horsepower: 24hp (17.9kW) Kohler Diesel Tier 4 final.
 Enclosure: Yes
 Fuel Tank Capacity: 30gal (114L)

WATER TANK:

Water Tank Capacity:
 573 Standard: 200gal (757L)
 573 Lite: 100gal (379L)
 573 Heavy: 300gal (1,136L)
 873 Standard: 200gal (757L)
 873 Heavy: 400gal (1,515L)
 1273: 300gal (1,136L)
 Number of Tanks: 2
 High Pressure Pump Flow Rate: 4gpm
 High Pressure Pump: 3,500psi
 High Pressure Hose Length: 50' (15.2m)
 Low Water Shut Off: Yes

SPOIL TANK:

Spoil Tank Capacity: 500gal (1,893L) (573 Model)
 Spoil Tank Capacity: 800gal (3,028L) (873 Model)
 Spoil Tank Capacity: 1,200gal (4,542L) (1273 Model)
 Door Type: Hydraulic
 Tank Lift Type: Twin Cylinder

VACUUM:

Type of Filters: Cartridge Filter 0.5 Microns
 Hose Length: 30' (9m)
 Hose Width: 3" (7.9cm)
 Vacuum: 580cfm
 Water Trap Capacity: 60gal (227L)
 Suction Hose Storage: 30' (9m)

CONTROL PANEL:

Controls: Curbside
 Gauges: Analog

OPTIONAL STRONG ARM:

Reach: 15' (4.57m)

OPTIONAL BOOM:

Pickup Hose: 4" (10cm)
 Reach 15' (4.57m)
 Movement: 6-way

LP 573/873/1273 XDT

VAC-TRON LOW PROFILE SERIES





OPTIONAL STRONG ARM:

Optional strong arm to support the weight of the vacuum hose.

7 SERIES HYDRAULIC CLAW DOOR:

No fuss, over center locking mechanism for positive lock and unlock.



CV5 FILTRATION HOUSING:

The LP XDT filtration housing also incorporates a 28" (71.1cm) diameter cyclone, four-way valve for reverse pressure, and the largest silencer in the industry for quiet performance. **Patented.**

Vac-Tron Equipment, LLC., reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice. Shown is for illustrative purposes only, and may display optional accessories or components. Please contact your local Vac-Tron dealer for more information on machine specifications.

Vac-Tron and the Vac-Tron logo are trademarks of Vac-Tron Equipment.

© 2017 Vac-Tron Equipment, LLC. All Rights Reserved. Printed in the U.S.A. Please Recycle.



WWW.VACTRON.COM
 1-888-VAC-TRON