

- For maximum bond, surface must be clean and dry.

2. Ensure that surface is clean and dry.

Install Decal

NOTE

- Apply in ambient temperatures between 21–38 °C (70–100 °F).
- Parts cannot be repositioned after initial installation. Do not remove protective film from adhesive until ready to apply.
- Do not bend emblem to fit contour of mounting surface.
- Allow at least 24 hours after application before exposing the area to vigorous washing, strong water spray or extreme weather.
- The adhesive bond will increase to maximum strength after about 72 hours at normal room temperature.

1. Remove protective film from back of decal.

NOTE

- Protect adhesive from grease, oil, dust, dirt and fingerprints.
- Once applied, do not shift decal.

2. Position decal in center of master cylinder fluid cover relief.

3. Apply even pressure across entire surface. Hold in place for 15 seconds.

4. Wait 20 minutes before touching decal.

5. If needed, repeat steps 1-4 for other master cylinder fluid cover relief.

Credit Procedure

NOTE

Enter bulletin number into comment section of claim.

For each vehicle involved in this recall (involvement of Vehicle Identification Number (VIN) has been verified on h-dnet.com), submit a recall claim per Table 4.

Table 4.

ITEM	DATA
Claim Type	SRC
Problem Part Number	44791-07
Quantity	Leave Blank
Primary Labor Code ⁽¹⁾	2719
Time	0.2 h
Customer Concern Code	0632
Condition Code	9981
<i>(1) Download may be required</i>	

Upon submission of the properly completed claim, you will be credited for 0.2 hours of labor time for performing the procedure, plus appropriate administrative time. Submit campaign events on their own warranty claim. Do not mix them with other warranty events.