

RECALL 23V141 / 2023-111 REMEDY INSTRUCTIONS



Make(s): PALOMINO - SOLAIRE
 Model(s): PAT320TSBH
 Model Year(s): 2020 - 2023

Concern:
 Certain PAT320TSBH models may be missing rearward and forward support for the fresh water tank.

Repair Code: RC-672-03-00-004306
 Allotted Time: 2.00 HRS.
 Inspection Code: N/A
 Allotted Time: N/A

Photo(s) Required: YES, PRE & POST
 Prior Authorization Required: YES
 Part(s) Kit Number: F100393660
 Part(s) Return: N/A

Disconnect the vehicles' battery Positive and Negative, disconnect any House battery(s) Positive and Negative, if equipped with a generator ensure it is off and lastly, ensure the vehicle is disconnected from shore power. Block any tires/wheels to prevent the vehicle from rolling. Failure to do so may result in electrocution, fire or other personal injury, property damage and/or death.

STEP 1: UNFASTEN THE FIRST EIGHT (8') FEET OF UNDERBELLY MATERIAL, BEGINNING AT THE FRONT AND WORKING TOWARDS THE REAR ON THE CURBSIDE AND ROADSIDE. TAKE CARE TO NOT RIP OR TEAR. ROLL THE MATERIAL INTO ITSELF AS YOU WORK REARWARD;

STEP 2: LOCATE THE FRESH WATER TANK, ROUGHLY BETWEEN FOURTY (40") TO FOURTY SIX (46") INCHES;

- DO NOT REMOVE THE CURRENTLY INSTALLED TWO (2) FLOATING CROSS-MEMBERS – LEAVE THEM INSTALLED.

STEP 3: INSTALL ONE OF THE FLOATING CROSS-MEMBERS FROM THE PARTS KIT UNDER THE TANK, ENSURE THIS CROSS-MEMBER IS FLUSH AGAINST THE WELDED IN CROSS-MEMBER. USE TWO SELF DRILLING LAGS PER SIDE ON THIS FLOATING CROSS-MEMBER. SEE FIGURE 1;

- PUSH FRESH WATER HOLDING TANK REARWARDS UNTIL IT CONTACTS THE REAR WELDED IN CROSS-MEMBER AND SITS ON TOP OF THE NEWLY INSTALLED FLOATING CROSS-MEMBER;

FIGURE 1



STEP 4: LOCATE THE FRONT OF THE FRESH WATER HOLDING TANK AND INSTALL THE SECOND FLOATING CROSS-MEMBER;

- CAPTURE THE FRESH WATER TANK WITH THE FLOATING CROSS-MEMBER, THE BOTTOM LEG OF THE ANGLE SHOULD BE UNDER THE FRESH WATER HOLDING TANK, HOLDING THE TANK UP. THE VERTICAL LEG OF THE ANGLE SHOULD BE FLUSH AGAINST THE FORWARD FACE OF THE FRESH WATER HOLDING TANK. SEE FIGURE 2;

FIGURE 2

