



**NHTSA: 23V-270**  
**Winnebago Towable: CAM0000029**

Safety Recall:  
  
MICRO MINNIE SPARE TIRE CARRIER

**Repair, Claim Preparation, and Filing Instructions**

Please submit a warranty claim pre-authorization using the following codes and labor times:

<u>LABOR:</u>	<u>OPERATION CODE</u>	<u>LABOR ALLOWANCE</u>
<b>Inspection only:</b>	44012000	0.10
<b>Remove and Replace:</b>	44012001	0.20

**PARTS:**

**280085 - Replacement Spare Tire Carrier Kit**

Please follow attached repair instructions.

Submit all pre-authorizations and claims through the Dealer Portal. If there are any questions, please call our Warranty Team at 574-825-5250.



**Repair Instructions:**

**MICRO MINNIE SPARE TIRE CARRIER**

**Tools Needed: Torque wrench, Impact gun, 9/16” socket, 13/16” socket.**

**REPAIR INSTRUCTIONS:**

**Using the impact gun and 13/16” socket, remove nuts from spare tire and set tire aside. Remove the tire carrier bolts that attach it to the bumper with 9/16” socket and discard old parts.**

**Hold the new tire carrier into place and attach the U-bolts around the bumper and into the holes on the carrier.**

**Thread the U-bolt nuts onto the bolts enough to prevent the carrier from slipping but also so the carrier can still slide on the bumper.**

**Place spare tire onto the new carrier so that the upper lug goes through the hole and the lower one goes through the center of the rim.**

**Thread the tire nuts onto these bolts. Using the torque wrench, tighten the nuts to 80-90 ft-lbs.**

**Adjust carrier location as to not block taillights or license plate.**

**Once location is set, tighten the U-bolt nuts to 50 ft-lbs.**