MOTOR HOME OCCUPANT AND CARGO CARRYING CAPACITY

THE COMBINED WEIGHT OF OCCUPANT AND CARGO SHOULD NEVER EXCEED: 583 kg or 1286 lbs

Safety belt equipped seating capacity: 5

CAUTION:

A full load of water equals 154 kg or 340 lbs of cargo @ 1 kg/L (8.3 lb/gal) and the tongue weight of a towed trailer counts as cargo.



TIRE AND LOADING INFORMATION

Seating Capacity | Total:5 | Front:2 | Rear:3 The combined weight of occupants and cargo should never exceed 583 kg or 1286 lbs.

TIRE	SIZE	COLD TIRE PRESSURE	SEE OWNER'S
FRONT	LT215/85R16/E	61 psi / 421 kpa	MANUAL FOR
REAR	LT215/85R16/E	58 psi / 400 kpa	ADDITIONAL
SPARE	LT215/85R16/E	61 psi / 421 kpa	INFORMATION



RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

PNEU	DIMENSIONS	PRESSION DES PNEUS À FROID	
-			VOIR LE MANUEL
AVANT			DE L'USAGER
ARRIÈRE			POUR PLUS DE
DE SECOURS			RENSEIGNEMENT



DRY WEIGHT: 9484 LBS RECREATIONAL VEHICLE OVERALL LENGTH 24'11" AS MANUFACTURED.



DRY WEIGHT: 9484 LBS RECREATIONAL VEHICLE OVERALL LENGTH 24'11" AS MANUFACTURED.

MANUFACTURED BY: FOREST RIVER, INC.

DATE: 07/21/2022

PRC24FS

DESIGNATED SEATING CAPACITY 5X68kg=340 kg or 5X150lbs=750 lbs

GVWR: 5003 KG (11030 LB) TIRES GAWR RIMS COLD INFL. PRESS FRONT 2000 KG KPA SINGLE DUAL LT215/85R16/E 16X5.5J V 4410 LB) 61 PSI) INTERM KG KPA SINGLE DUAL LB) PSI) REAR 3502 KG LT215/85R16/E 16X5.5J KPA SINGLE DUAL 7720 LB)

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

TYPE: MH/AC

INCLUDES VEHICLE MFG. BY: MERCEDES-BENZ

PSI)