


RECALL 24V822 / 2024-665 REMEDY INSTRUCTIONS

 FOREST RIVER	Make(s): ALTA Model(s): MANY, SEE BELOW Model Year(s): 2025	Repair Code: RC-003-22-00-004630 Allotted Time: .30 HRS. Inspection Code: RC-003-05-00-004629 Allotted Time: .10 HRS.
	Concern: The inverter may be connected to constant "hot" on the second battery, whereas it should be on a breaker side on the second battery.	Photo(s) Required: NO Prior Authorization Required: YES Part(s) Kit Number: N/A Part(s) Return: N/A

Turn off LP Gas at LPG Tank(s). Disconnect the vehicles' battery Positive and Negative, disconnect any House battery(s) Positive and Negative, if equipped with a generator ensure it is off and lastly, ensure the vehicle is disconnected from shore power. Block any tires/wheels to prevent the vehicle from rolling. Failure to do so may result in electrocution, fire or other personal injury, property damage and/or death.

CERTAIN: 2025 – ALTA – ALT1900MMK, ALT2375KRK, ALT2475KBH, ALT2600KRB, ALT2810KIK & ALT3150KBH

INSPECTION:

STEP 1: LOCATE THE THREE WIRES ON THE "HOT" SIDE OF THE SECOND BATTERY;

- ENSURE THE WIRE FROM THE INVERTOR IS WIRED TO THE BREAKER SIDE OF THE BREAKER;
 - IF THIS IS WIRED THIS WAY, CLAIM THE INSPECTION ONLY;
 - IF THIS IS NOT WIRED THIS WAY, MOVE ON TO THE REMEDY;
- ENSURE THE WIRE FROM THE 4X4 JUNCTION BOX IS WIRED TO THE BREAKER SIDE OF THE BREAKER;
 - IF THIS IS WIRED THIS WAY, CLAIM THE INSPECTION ONLY;
 - IF THIS IS NOT WIRED THIS WAY, MOVE ON TO THE REMEDY;
- ENSURE THE WIRE FROM THE FIRST BATTERY IS WIRED DIRECTLY TO THE "HOT" POST OF THE SECOND BATTERY;
 - IF THIS IS WIRED THIS WAY, CLAIM THE INSPECTION ONLY;
 - IF THIS IS NOT WIRED THIS WAY, MOVE ON TO THE REMEDY;

REMEDY:

STEP 1: MOVE THE FIRST BATTERY IS WIRED DIRECTLY TO THE "HOT" POST OF THE SECOND BATTERY (AS NEEDED);

STEP 2: MOVE THE INVERTOR WIRE TO THE TOP SIDE OF THE BREAKER (SO IT IS PROTECTED AND NOT CONSTANTLY HOT);

STEP 3: MOVE THE 4X4 JUNCTION BOX WIRE TO THE TOP SIDE OF THE BREAKER (SO IT IS PROTECTED AND NOT CONSTANTLY HOT);

STEP 4: ENSURE CONNECTIONS ARE TIGHT;

STEP 5: CLAIM REPAIR CODE.