


RECALL 24V846 / 2024-684 REMEDY INSTRUCTIONS

 FOREST RIVER	Make(s): AURORA & CATALINA Model(s): MANY, SEE BELOW Model Year(s):	Repair Code: RC-720-22-00-004635 Allotted Time: .50 HRS. Inspection Code: RC-720-05-00-004634 Allotted Time: .10 HRS.
	Concern: The solar controller may not be consistently wired to the battery.	Photo(s) Required: NO Prior Authorization Required: YES Part(s) Kit Number: N/A Part(s) Return: N/A

Turn off LP Gas at LPG Tank(s). Disconnect the vehicles' battery Positive and Negative, disconnect any House battery(s) Positive and Negative, if equipped with a generator ensure it is off and lastly, ensure the vehicle is disconnected from shore power. Block any tires/wheels to prevent the vehicle from rolling. Failure to do so may result in electrocution, fire or other personal injury, property damage and/or death.

CERTAIN: 2025 – AURORA: ART24RBS, ART26ATH & ART29QBS

CERTAIN: 2025 – CATALINA: CAT26TH & CAT243RBSLE

CERTAIN: 2024 – 2025 – AURORA: ART28BHS

CERTAIN: 2024 – 2025 – CATALINA: CAT263BHCKLE, CAT283EPIC & CAT293QBCKLE

INSPECT:

STEP 1: LOCATE AND REMOVE/UNSCREW THE SOLOR CONTROLLER IN THE PASS-THROUGH STORAGE;

- LOCATE WHICH WIRE IS BATTERY POSITIVE AND MATCH THIS TO THE TAGGED WIRE WITH THE “BATTERY POSITIVE +” TAG.
- LOCATE WHICH WIRE IS BATTERY NEGATIVE AND MATCH THIS TO THE TAGGED WIRE WITH THE “BATTERY NEGATIVE -” TAG
- IF THIS IS CORRECT THEN NO FURTHER ACTION IS REQUIRED, CLAIM REPAIR CODE.
- REINSTALL THE SOLAR CONTROLLER

REMEDY:

STEP 1: LOCATE AND REMOVE/UNSCREW THE SOLOR CONTROLLER IN THE PASS-THROUGH STORAGE;

STEP 2: LOCATE THE BLACK WIRE WITH THE WHITE STRIPE;
REMOVE IT FROM THE BACK OF THE SOLOR CONTROLLER;

STEP 3: LOCATE THE SOLID WHITE WIRE;
REMOVE IT FROM THE BACK OF THE SOLOR CONTROLLER;

STEP 4: INSERT THE BLACK WIRE WITH THE WHITE STRIPE INTO THE “BATTERY +” SIDE OF THE SOLAR CONTROLLER;
RETIGHTEN SCREW SO THE WIRE HAS SOLID CONNECTION;

STEP 5: INSERT THE SOLID WHITE WIRE INTO THE “BATTERY -” SIDE OF THE SOLAR CONTROLLER;
RETIGHTEN SCREW SO THE WIRE HAS SOLID CONNECTION;

STEP 6: REINSTALL THE SOLAR CONTROLLER AND ENSURE IT IS SECURE;

STEP 7: RETAG THE BLACK WIRE WITH THE WHITE STRIPE WITH THE “SOLAR POSITIVE +” STICKER;

STEP 8: RETAG THE SOLID WHITE WIRE WITH THE “SOLAR NEGATIVE -” STICKER;

STEP 9: CLAIM REPAIR CODE.