


RECALL 24V884/2024-713 REMEDY INSTRUCTIONS

 FOREST RIVER	Make(s): CLIPPER & VIKING Model(s): MANY, SEE BELOW Model Year(s): 2024 - 2025	Repair Code: RC-672-01-00-004648 Allotted Time: .75 HRS. Inspection Code: N/A Allotted Time: N/A
	Concern: The fresh water holding tank support bracket ("floater") may not be the proper steel gauge. It may allow the tank to fall when being filled and/or in travel.	Photo(s) Required: NO Prior Authorization Required: YES Part(s) Kit Number: F100685165 Part(s) Return: NO, FIELD DESTROY

Turn off LP Gas at LPG Tank(s). Disconnect the vehicles' battery Positive and Negative, disconnect any House battery(s) Positive and Negative, if equipped with a generator ensure it is off and lastly, ensure the vehicle is disconnected from shore power. Block any tires/wheels to prevent the vehicle from rolling. Failure to do so may result in electrocution, fire or other personal injury, property damage and/or death.

USE A FLOOR JACK AND LUMBER TO SUPPORT THE FRESH WATER HOLDING TANK IN PLACE WHILE CONDUCTING THE REMEDY – DO NOT COMPRESS THE FRESH WATER TANK

CERTAIN 2024 – 2025 – CLIPPER - CWT9000ROK & CWT12000ROK
CERTAIN 2024 – 2025 – VIKING - VWT9000ROK & VWT12000ROK
CERTAIN 2025 – CLIPPER: CWT11000ROK & CWT13000ROK
CERTAIN 2025 – VIKING: VWT13000ROK

REMEDY:

STEP 1: LOCATE THE STRAPS FROM UNDER THE FRESH WATER HOLDING TANK;

- REMOVE THE STRAPS BY CUTTING, DISCARD;
- DO NOT PUNCTURE THE HOLDING TANK – THIS WILL NOT BE COVERED IN THE RECALL IF YOU DO;

STEP 2: REMOVE THE HOLDING TANKS' FLOATING CROSS-MEMBERS;

- REMOVE THEM BY REMOVING 8 – 3/8" SELF TAPPING TEK SCREWS, 2 PER END, DISCARD;
- DISCARD THE TWO FLOATING CROSS-MEMBERS;

STEP 3: INSTALL THE TWO REPLACEMENT FLOATING CROSS-MEMBERS;

- USE THE 8 – 3/8" SELF TAPPING TEK SCREWS, 2 PER END IN PRE-DRILLED HOLES, FROM THE PARTS KIT;

STEP 4: INSTALL THE 4 STRAPS WITH BUCKLES AROUND THE NEWLY INSTALLED FLOATING CROSS-MEMBERS AND ENCOMPASSING THE FRESH WATER TANK. THIS IS REQUIRED AS A SECONDARY MEANS OF SECUREMENT OF THE FRESH WATER TANK;

- SPACE THE STRAPS EVENLY THE WIDTH OF THE FRESH WATER HOLDING TANK;
- CINCHE THE BUCKLES TIGHTLY ON ALL 4 STRAPS;

STEP 5: CLAIM THE REPAIR CODE.