



## Procedure for Side Reflectors removal and fixing new Reflectors

**Applicable Models :** Classic 350 / Hunter 350 / Meteor 350/ INT 650 / Continental GT 650 / Super Meteor 650/ Himalayan

### **Procedure Side Reflector Removal and Fixing**

**1)** Use masking tape to mark the reflector boundary (Upper & lower side) as shown in Fig (i) & (ii).

Fig(i)



Fig(ii)



**2)** Use measuring scale & marker to mark on the reflector position as shown in Fig(iii)& (iv).

Fig(iii)



Fig(iv)





## Procedure for Side Reflectors removal and fixing new Reflectors

**3)** Gently press and remove the reflector from the fork surface. Clean the surface with microfibre cloth . Ensure surface is free from the dust as shown in Fig (v) & (vi)

Fig(v)



Fig(vi)



**4)** Repeat steps 1 ~ 3 for the other side reflector.

**5)** Take the respective new reflector & remove the adhesive release paper as shown in Fig (vii) & (viii).

Fig(vii)



Fig(viii)





## Procedure for Side Reflectors removal and fixing new Reflectors

6) Affix the reflector on the fork surface and ensure the alignment with marked line . Apply even load on the fork surface by using thumb as shown in Fig (ix) & (x)

Fig(ix)



Fig(x)



7) Remove the masking tape on the fork surface as shown in Fig (xi).

Fig(xi)



Final Image



8) Repeat steps 5 ~ 7 for the other side reflector.



## Procedure for Rear Reflector removal and fixing new Reflector

**Applicable Models :** Meteor 350/ INT 650 / Continental GT 650 / Himalayan.

### **Procedure :**

- 1) Remove the Rear reflector's M8 nut by using ring spanner. As shown in Fig(i)
- 2) Assemble the new reflector on the Rear mudflap & tighten by using ring spanner (Torque - 3 NM). As shown in Fig(iii)&Fig(iv)

