

Service Information

VAS Tester

Number: AVT-12-22

Subject: VAS-PC Audi Brand CD V.19.44.00

Date: Sept 14, 2012

VAS-PC Audi Brand CD V19.44.00, (Technical Literature ordering number **A44.5001.21.21**) is being shipped to all Audi dealers.

Please note the following important points:

Hardware problems during the installation of new Brand CDs are minimized if users regularly perform the Windows hard disc maintenance utility “chkdsk”. If your device has never had hard disc maintenance performed via the Windows “chkdsk” utility, please perform this maintenance **prior to** installation of this Brand update, and ensure that it be performed on a regular basis to ensure reliable software functions. Please refer to Service Information document ATE-10-02 for instructions.

- Brand CD V19.44.00 must only be installed on VAS-PC testers that were previously updated with Base V19.01.01.
- After installation of the Brand CD, all stored Diagnosis Jobs are erased; therefore complete work beforehand if required.
- **DO NOT** install the Brand CD V19.44.00 on VAS 5051A or 5052 testers.

New and Revised Content for CD V.19.44.00

Submitted by	Vehicle/Engines	Issue Description
Technical Assistance Center Centre d'assistance technique	2012 Q5 (8R) 2.0L	The function test for malfunction entry DTC 1299 was fixed.
Elsa Diag. Feedback Rétroaction de diag. d'Elsa	2008 Q7 (4L) 3.6L	The Instrument Cluster replacing function test has been corrected.
Technical Assistance Center Centre d'assistance technique	2012 A7 (4GA) 3.0L	Function test for the 8B – Distance Regulation Control Module have been updated.
Internal Feedback Rétroaction interne	2012 Q5 (8R) 2.0L	Function test added to the 51 – Electro Drive for the Q5 Hybrid.
Technical Field Manager Gestionnaire de champ technique	2012 A6 (4G) 3.0L	The function test for DTC P017D00 has been corrected.
Internal Feedback Rétroaction interne	2011 R8 (42) 4.2L	SVM test has been updated.
Internal Feedback Rétroaction interne	2013 Q5 (8R) 2.0L	The function test for the J934 0 Battery Monitoring Control Module has been added.
Internal Feedback Rétroaction interne	2012 A6 (4G) 2.0L	The Electronic Oil Consumption function test has been corrected.

Service Information

Installation instructions

Requirements:

- VAS-PC connected to A/C power
- **Base V19.01.01 previously installed on tester**
- If an Ethernet (network) cable is connected to the device, disconnect it

Installation procedure:

- Switch ON tester
- Once tester is fully booted, launch the "VAS-PC" application from the Windows desktop
- Allow Consistency Test to run without interruption
- From the VAS-PC main screen, select tester function "Administration"
- Insert Audi Brand CD V19.44.00 into CD/DVD drive
- Select Administration function "Install update" and confirm by answering "Yes" when prompted

End of installation.

Notes:

- The installation could take up to 25 minutes per Brand CD and tester.
- Further installation information can be found in the VAS-PC Operator's manual.
- **No return envelope is included in this shipment, retain all future copies of the Brand CD.**

For Help with VAS-PC software installation or function, please contact:

Software Support at 1 (888) 896-1298 (United States and Canada) from 9:00 AM to 5:00 PM EST Monday through Friday.

For Help with VAS-PC software subscriptions, please contact:

The Audi Technical Literature Ordering Center at www.audi.techliterature.com 24 hours a day / 7 days a week.