


# 2013 PRE-DELIVERY SERVICE CHECK SHEET December 2012

BEFORE INSPI	ECTION		OK Adjust/	repail	UNDER VEH	IICLE (ON HOIST)   5	Adjust/ Repair	
	Se - see page 2					brake anti-rust covers/anti-corrosion	4.2	
02 Install radio antenna*  FUNCTIONAL OPERATION					02 Inspect tires fo			
Apply parking brake and cycle ignition "IG-ON"; place gear selector in reverse; t lights and rear defogger. Unlock doors; release fuel door, and release the back					page 2			
01 Check dome, courtesy, map, and sun visor lights*		urn   urn 	000 000 000 000		04 Install wheel caps*			
07 Check audio/navigation*/backup camera* systems and set clock		1		j	ROAD TEST			
O8 Verify Entune/Navigation software version (Display Audio, Non-HDD Type only)*						helps assure customer satisfaction. Drive vehicle over a es and driving conditions. Check for unusual noise and		
	verride button cover*f*			]	Reading Before Test:			
WALKAROUND INSPECTION				01 Check cold engine operation				
switch, if equipped). Co checking each door and condition, all lights, lugga aim and continue into UN		wise di belts, king he	irection interior eadlight	t	03 Check engine 04 Check hybrid t 05 Check brake a	at normal operating temperature		
01 Check Smart Key System*  02 Check door and door lock operation, including each wireless remote control/theft deterrent system*  03 Check window operation  04 Check that engine starts with all keys		[1 [1			07 Inspect for abnormal noise and vibration			
05 Check that child safety door locks are in normal (unlocked) position*					FINAL INSPE	ECTION AND CLEANING		
06 Check seats and seat belt operation		[1	0 0 0 0 0 0		tags, etc. (Ren to customer) 02 Visually inspec damage, fit, dii 03 Verify floor m retaining clips 04 Remove Rapg 05 Wash and clea	or protective covers, unnecessary labels, nove protective covers just before delivery ct all interior parts for installation, rt, etc. at application and install using s* and clear protective bumper film* an vehicle		
UNDER HOOD					damage, etc	ge sticker on inside of windshield, top		
01 Check engine oil and ATM* fluid levels		[   [   [	8 8 8 8 8 8 8	]     	left corner	or body parts for proper installation, etc		
BATTERY MAINTENANCE						stream Health Check		
01 Perform HV battery check and maintenance								
Completion and retention of this from is required to comply with Toyota's War TECHNICIAN'S SIGNATURE SERVICE M					olicy. ER'S SIGNATURE	on this form have been checke and corrected for proper		
NAME (PLEASE PRINT) NAME (			(PLEASE PRINT)		RINT)	operation as required.		
Date	Dealer Name			D	ealer Code	Vehicle Identification Number (Sticker)		

## D/C CUT FUSE INSTALLATION

The D/C Cut fuse (30 A) has been removed at the assembly plant to reduce parasitic current draw in transit and storage.

Reinstall the D/C Cut fuse to the original location.



- 1 Storage Location
- 2 Installation Location

## TPWS INITIALIZATION

Refer to the Repair Manual for the Initialization procedure. Please note the spare tire does not have a TPWS sensor.

#### **NOTE**

To adjust tire pressure correctly when outside temperature is significantly colder or warmer than shop temperature, follow the procedures outlined in Service Bulletin T-SB-0020-12, "Tire Inflation Pressure Compensation and Adjustment".

### FRONT WHEEL OPENING EXTENSION PAD INSTALLATION


The front wheel opening extension pad set (right and left front wheel opening extension pads and 4 tapping screws) is loaded in the luggage compartment at the assembly plant to avoid damage in transit.

1. Hook the retainers of the front left wheel opening extension pad through the installation holes on the fender liner and temporarily fix it to the installation position.

#### **NOTE**

There is a distinguishable mark on each pad.

- 2. Tighten the 2 tapping screws.
- 3. Repeat for the right side.



## FRONT LICENSE PLATE INSTALLATION


1. Align the installation holes of the front license plate with the dimples on the front bumper.

### **NOTICE**

- Do NOT pre-drill holes into the bumper.
- Do NOT over-tighten the self-tapping screws.
- 2. Using 2 self-tapping screws, install the front license plate by directly screwing the tapping screws into the dimples.

Length: 15.0 — 20.0 mm (0.60 — 0.79 in.)

Diameter: 6.0 mm (0.24 in.)



- 1 Dimples
- 2 License Plate
- 3 Self-tapping Screws