

Q5 - 2013 FLUID CAPACITY CHART

15 Nov 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q5 SUV quattro (8RB52A)	2.0 TFSI 211 hp (CPMA) 4.6 L (4.9 qt) <u>Audi Oil Spec**</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBK/OBL) <u>New Fill:</u> 8.6 L approx. (9.0 qt.) <u>Refill</u> 3.6-4.0 L (3.8-4.2 qt.)	Front F/Drive New Fill: 1.0L (1.1qt) <u>Oil PN</u> G 052 145 S2* Rear F/Drive (OBD) 1.0L (1.1qt) <u>Oil PN</u> G 052 145 S2*	10.0 L (10.5qt)***	Electromechanical	1.0 L (1.1 qt) (approximately) <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a 600g ± 15g (21.1 ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity & PN</u> For Denso 150 cc +/- 10 cc (5.1 ± 0.3 oz.) G 052 300 A2*	4.6 L (4.9 qt.) <u>Fluid PN</u> G 052 164*
Q5 SUV quattro (8RB57A)	3.0L V6 272 hp (CTUC) 6.8 L (7.2 qt.) <u>Audi Oil Spec**:</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	<u>Oil PN</u> G 060 162 A2* Transfer Case 1.0 L (1.1 qt.) <u>Oil PN</u> G 055 145 A2*		12.0 L (12.7qt)***				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

** Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

Q5 Hybrid - 2013 FLUID CAPACITY CHART

15 Nov 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q5 Hybrid quattro (8RB5GA)	2.0 TFSI 245 hp (CHJA) 4.6L (4.9 qt) <u>Audi Oil Spec**</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBWA) <u>New Fill:</u> 8.6 L approx. (9.0 qt.) <u>Refill</u> 4.0L (4.2 qt.) <u>Oil PN</u> G 060 162 A2* Transfer Case 1.0L (1.1 qt.) <u>Refill</u> 0.8 L (0.8 qt.) <u>Oil PN</u> G 055 145 A2*	Front F/Drive New Fill: 1.0L (1.1qt) <u>Refill</u> 0.9 L (0.9 qt.) <u>Oil PN</u> G 052 145 S2* Rear F/Drive (0BC) 0.9L (0.9qt) <u>Oil PN</u> G 052 145 S2*	10.0 L (10.5qt)***	Electromechanical	1.0 L (1.1 qt) (approximately) <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a 840g ± 20g (29.6 ± 0.7 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity & PN</u> For Denso 150 cc +/- 10 cc (5.1 ± 0.3 oz.) G 052 300 A2*	4.6 L (4.9 qt) <u>Fluid PN</u> G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

** Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.