



SERVICE BULLETIN

Classification: ST11-008	Reference: NTB12-030	Date: March 22, 2012
-----------------------------	-------------------------	-------------------------

ALTIMA, MAXIMA; POWER STEERING HOSE SERVICE PART CHANGE

APPLIED VEHICLES: 2007-2011 Altima (C/L32)
2009-2011 Maxima (A35)

SERVICE INFORMATION

If the high pressure hose on an Applied Vehicle needs to be replaced for any reason:

- The hose now comes without the pressure sensor (refer to Figure 1).
- When replacing this hose, reuse the existing pressure sensor. Replace the pressure sensor ONLY IF there is a pressure sensor related issue.
- Do not replace other related hoses unless necessary (i.e., do not replace as a set).
- Do not damage the pressure sensor during removal or installation.
- Always use a new O-ring when installing a new or existing pressure sensor (refer to Figure 1).
- Pressure sensor mounting torque: 19.6 N•m (2.0 kg-m, **14.5 ft lb**)
- If only the pressure sensor needs replacement, do not replace any hoses.
- Always replace both copper washers (mounted at the power steering pump).

CAUTIONS:

- Do not allow dirt or contamination to enter the hydraulic system.
- Always secure the pressure sensor mounting block in a soft jaw vise when removing and installing the pressure sensor. Do not clamp onto the “banjo” end of the hose.
- Refer to the appropriate Electronic Service Manual (ESM) for power steering hose removal, installation, and torque specifications.



Figure 1 (examples only, your hose appearance may be different)

Nissan Bulletins are intended for use by qualified technicians, not 'do-it-yourselfers'. Qualified technicians are properly trained individuals who have the equipment, tools, safety instruction, and know-how to do a job properly and safely. NOTE: If you believe that a described condition may apply to a particular vehicle, DO NOT assume that it does. See your Nissan dealer to determine if this applies to your vehicle.

PARTS INFORMATION

1. Refer to FAST or your electronic parts catalogue to determine the part for your application.
2. Match that part number with the one in the HOSE WITH SWITCH column below.
3. Order the HOSE W/O SWITCH part number that aligns with the HOSE WITH SWITCH number you found in the catalogue.

DESCRIPTION	HOSE WITH SWITCH (DO NOT ORDER)	HOSE W/O SWITCH	QTY
HOSE & TUBE ASSY-PRESS, PS	49720 ZN50A	49720 ZN50B	1
	49720 ZN55A	49720 ZN55B	1
	49720 JA000	49720 JA00B	1
	49720 JA100	49720 JA10B	1
	49720 9N00A	49720 9N00B	1
APPLICATION	DESCRIPTION	PART NUMBER	QTY
ALL	O-RING	49345 6N200	1
ALL	SEN ASSY-PRESS.PS	49763 6N20A	1
A35 AND CL32 W/18" WHEELS	GASKET-CONNECTOR (COPPER WASHER)	49726 Y0100	2
		49726 50W00	2
ALL OTHER VEHICLES (WHERE APPLICABLE)	GASKET-CONNECTOR (COPPER WASHER)	49726 Y0100	2