# HONDA

# sB-10043778-2794 Service Bulletin



Applies To: 2012 Civic 4-Door – ALL

March 20, 2012

# Driver's and Front Passenger's Doors Do Not Unlock in Freezing Weather

#### SYMPTOM

In freezing weather, the driver's and front passenger's doors don't unlock with the remote or the key.

#### **PROBABLE CAUSE**

Moisture in the lock cable freezes.

#### **CORRECTIVE ACTION**

Dry and lubricate the lock cable.

#### **REQUIRED MATERIALS**

Dow Corning 111 Valve Lubricant & Sealant (commercially available)

### WARRANTY CLAIM INFORMATION


The normal warranty applies.

OP#	Description	FRT
8180A2	Dry and lubricate the lock cable on one front door	0.4
A	Add for the other front door	0.4

Failed Part:	P/N 72133-TR0-A01	
Defect Code:	03214	
Symptom Code:	07902	
Skill Level:	Repair Technician	

## **REPAIR PROCEDURE**

 Remove the power window switch panel from the affected door by pulling it upward and forward in the sequence shown, then disconnect the connectors.




© 2012 American Honda Motor Co., Inc. – All Rights Reserved

ATB 47673 (1203)

**CUSTOMER INFORMATION:** The information in this bulletin is intended for use only by skilled technicians who have the proper tools, equipment, and training to correctly and safely maintain your vehicle. These procedures should not be attempted by "do-it-yourselfers," and you should not assume this bulletin applies to your vehicle, or that your vehicle has the condition described. To determine whether this information applies, contact an authorized Honda automobile dealer.




2. Push in the tab, then remove the inner handle cap.




3. Remove the screw, then pull the inner door handle out of the door panel.



4. Remove the screw under the door handle.



5. Carefully release the eight clips holding the door panel in place, and remove the panel by pulling upward.



6. Remove any moisture from the lock cable by blowing compressed air into the cable end at the inner handle.



Blow are here.

- 7. Remove the door latch.
- 8. Clean the cable surface, and remove any potential traces of oxidation with a clean, dry towel.

Clean area with shop towel.



9. Apply DC 111 lubricant to the lock cable as shown.







- 10. Reinstall the door latch.
- 11. Reinstall the door panel.
- 12. Reattach the screw under the door handle.
- 13. Reinstall the door handle and the inner handle cap.
- 14. Reinstall the power window switch panel.