



Classification:

ST11-006

Reference:

ITB12-014

Date:

March 22, 2012

2004 - 2010 QX56; POWER STEERING HOSE SERVICE PART CHANGE

APPLIED VEHICLE: 2004-2010 QX56 (JA60)

SERVICE INFORMATION

If the high pressure hose needs to be replaced for any reason:

- The hose now comes without the pressure sensor (refer to page 2).
- When replacing this hose, reuse the existing pressure sensor. Replace the pressure sensor ONLY IF there is a pressure sensor related issue.
- Do not replace other related hoses unless necessary (i.e., do not replace as a set).
- Do not damage the pressure sensor during removal or installation.
- Always use a new O-ring when installing a new or existing pressure sensor (refer to page 2).
- Pressure sensor mounting torque: 19.6 N•m (2.0 kg-m, 14.5 ft lb)
- If only the pressure sensor needs replacement, do not replace any hoses.
- Always replace both copper washers (mounted at the power steering pump).

CAUTIONS:

- Do not allow dirt or contamination to enter the hydraulic system.
- Always secure the pressure sensor mounting block in a soft jaw vise when removing and installing the pressure sensor. Do not clamp onto the "banjo" end of the hose.
- Refer to the appropriate Electronic Service Manual (ESM) for power steering hose removal, installation, and torque specifications.

PARTS INFORMATION

DESCRIPTION	HOSE WITH SENSOR	HOSE W/O SENSOR	QTY
HOSE & TUBE ASSY-PRESS, PS	49720-7S000	49720-7S00A	1
GASKET-CONNECTOR (copper washer)	49726-Y0100		2
SEAL – O-RING	49345-6N200		1
SEN ASSY-PRESSURE, PS	49763-6N20A		1

Infiniti Bulletins are intended for use by qualified technicians, not 'do-it-yourselfers'. Qualified technicians are properly trained individuals who have the equipment, tools, safety instruction, and know-how to do a job properly and safely. NOTE: If you believe that a described condition may apply to a particular vehicle, DO NOT assume that it does. See your Infiniti dealer to determine if this applies to your vehicle.

