

## 2015 MY Scheduled Maintenance Intervals

Ailes (in thousands)	5/25/45/65/85/105/125	15/55/95/135	35/75/115
(ilometers (in thousands)	8/40/70/100/130/160/190	25/85/145/205	55/115/175
	-		-
ingine Oil/Oil Filter – change oil and replace filter	•		•
AdBlue Fluid – fill completely with fresh fluid (maximum capacity: 24 liters) and adapt earned values for AdBlue tank under guided fault finding after filling fluid	Q5 3.0L TDI, A6 3.0L TDI and A7 3.0L TDI, Q7 3.0L TDI and A8 3.0L TDI only	Q5 3.0L TDI, A6 3.0L TDI and A7 3.0L TDI, Q7 3.0L TDI and A8 3.0L TDI only	Q5 3.0L TDI, A6 3.0L TDI and A7 3.0 TDI, Q7 3.0L TDI and A8 3.0L TDI on
Cooling System – check level, add if necessary		•	•
ingine Compartment – check for leaks		•	•
<b>Dnboard Diagnosis</b> – check	Flex Fuel vehicles only	Flex Fuel vehicles only	Flex Fuel vehicles only
<b>/isual Check</b> – check the chassis for possible paint damage and corrosion, from the nside and outside, with the doors as well as hood and trunk lids open		•	•
<b>Battery</b> – check for clean terminals (no corrosion), properly mounted housing, Ind no damage; replace if necessary. Also, check the acid level of battery Inly if the level can be seen through the housing and fill if necessary		except Q5 hybrid	except Q5 hybrid
Small (12-volt) Side Battery – located in the trunk compartment on left side – check or clean terminals (no corrosion), properly mounted housing and no damage; replace f necessary		Q5 hybrid only	Q5 hybrid only
Dust and Pollen Filter - replace		•	•
Spark Plugs – replace at 35,000 miles (55,000 km) or 6 years, whichever occurs first. Thereafter, every 40,000 miles (60,000 km) or 6 years, whichever occurs first*			<ul> <li>all vehicles with the 4.0L V8 TFSI, A8 W12, all vehicles with 2.0L TFSI (except Flex Fuel engines)</li> </ul>
<ul> <li>replace at 55,000 miles (85,000 km) or 6 years, whichever occurs first.</li> <li>Thereafter, every 60,000 miles (90,000 km) or 6 years, whichever occurs first</li> </ul>		<ul> <li>55K only: vehicles with the 1.8L (A3), 3.0L V6 TFSI, 4.2L V8 FSI and 5.2L V10 FSI engines</li> </ul>	
<ul> <li>replace at 35,000 miles (55,000 km) or 6 years, whichever occurs first.</li> <li>Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first</li> </ul>			<ul> <li>35K only: 2.0L TFSI Flex Fuel engines only</li> </ul>
Power Steering Fluid – check, add if necessary			A8, Q7 only
Nir Cleaner – clean housing, replace filter element		55K only: except RS 5, S6, S7, RS 7, A8 3.0L V6 TFSI, A8 3.0L V6 TDI,	RS 5, S6, S7, A8 3.0L V6 TDI, A8 3 V6 TFSI, A8 4.0L V8 TFSI, TTS and
– clean housing, replace filter element		A8 4.0L V8 TFSI and TTS RS 5 only	RS 7 only
Ribbed V Belt and Tensioner – check condition and replace if necessary		R8 Coupe, R8 Spyder only	R8 Coupe, R8 Spyder only
Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary – replace only the belt for the compressor drive (front belt)		55K only: all vehicles with the	<ul> <li>75K only</li> <li>115K only: all vehicles with the</li> </ul>
		<ul> <li>55K only: all vehicles with the 3.0L V6 TFSI</li> </ul>	<ul> <li>115K only: all vehicles with the 3.0L V6 TFSI</li> </ul>
now Screen for Air Cleaner – clean		A4, S4, allroad, A5, A5 Cabriolet, S5, S5 Cabriolet, Q5, SQ5 and Q5 hybrid only	A4, S4, allroad, A5, A5 Cabriolet, S5, S5 Cabriolet, Q5, SQ5 and Q5 hybrid only
<b>uel Filter</b> – replace		A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, Q5 3.0L TDI and Q7 3.0L TDI only	A6 3.0L TDI, A7 3.0L TDI, A8 3.0L Q5 3.0L TDI and Q7 3.0L TDI only
Diesel Particulate Filter (DPF) – perform after the first 115K miles (USA)/175,000 km Canada) or 110K miles (USA)/165,000 km (Canada) after a Diesel Particulate Filter (DPF) eplacement; check ash loading according to manufacturer's work procedure, replace** f necessary	<ul> <li>USA: 115K only: A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, Q5 3.0L TDI and Q7 3.0L TDI</li> <li>Canada: 175 km only: A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, Q5 3.0L TDI and Q7 3.0L TDI</li> </ul>		
Plenum Panel – remove cover for plenum panel to check water drain and lean if necessary		•	•
ires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS)	•		
<ul> <li>check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS)</li> </ul>		٠	•
ires – rotate, reset TPMS	5K only		
Viper Blades – check condition and replace if necessary (USA only)	•	•	•
Viper Blades – check condition (Canada only)	•	•	•
Viper/Washer/Headlight Washer – check adjustment and function, dd fluid if necessary	٠	•	٠
<b>nterior Lights</b> – check all interior lights, glove box illumination, control lights and MI (if applicable)			•
iront Lighting – check function of parking lights, low beams, high beams, fog lights, linkers and hazard lights		•	•
Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights		•	•
Service Reminder Display - reset	•	•	•
<b>lorn</b> – check function		•	•
Door Hinges and Straps – lubricate		<ul> <li>Q7, TT, TTS, R8 Coupe and R8 Spyder only</li> </ul>	
Doors – lubricate door hinges, straps, locks and hood latch			•
lood Lid Hinges – lubricate		R8 Coupe, R8 Spyder, TT and TTS only	R8 Coupe, R8 Spyder, TT and TTS of the second se

continued **>** 

Audi Service



## 2015 MY Scheduled Maintenance Intervals (continued)

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95/135	35/75/115
Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145/205	55/115/175
All Sunroof Systems – clean quide rails and lubricate with grease		•	
		A3 Cabriolet, A5 Cabriolet and	A3 Cabriolet, A5 Cabriolet and
Front Latch for Cabriolet Roof – lubricate		S5 Cabriolet only	S5 Cabriolet only
Brake System – check for damage, leaks, pad thickness, fluid level	•	•	•
Brake Discs – check thickness			•
<b>Exhaust System</b> – check for damage, leaks		•	•
Front and Rear Axle – check for excessive play, check dust seals on ball joints and ie rod ends		•	•
Drive Shaft Boots – check		•	•
Automatic Transmission and Final Drive – check for leaks		•	•
Manual Transmission and Final Drive – check for leaks		•	•
Continuously Variable Transmission (multitronic) – change ATF			•
<b>DSG/S Tronic</b> ® – change MTF oil for gear box		RS 5 only	RS 5 only
<b>DSG/S Tronic</b> – change ATF oil and replace transmission filter element or clutch hydraulics			<ul> <li>A3, S4, S5, S5 Cabriolet, S6, S7, F TT, TTS, R8 Coupe and R8 Spyder</li> </ul>
Fiptronic Gear Box – change ATF			Q5 hybrid only
Rear Sport Differential – change ATF for clutch hydraulics and differential oil			RS 5 and RS 7 only
Jnderbody – check for damage and leaks		•	•
Road Test – check engine performance, clutch, manual/automatic transmission, braking (including hand and foot brake), steering, wheels, wheel bearings, drive shaft, horn and hybrid vehicles (electric drive for operational readiness)		•	•
Timing Belt - replace at 110K miles (175,000 km) on TTS. Check condition of timing belt tensioning	system, dampening pulleys and idle	r pulleys, and replace if necessar	ry
Brake Fluid – replace every 2 years regardless of mileage			
Cloth Top – check function and rollover protection every 2 years regardless of mileage (A5/S5 Cabrio	let and R8 Spyder only)		
dBlue Fluid – replace every 4 years regardless of miles/kilometers only if AdBlue has not been filled	d within the last 4 years (Q7 3.0L TD	I, A8 3.0L TDI, A6 3.0L TDI, A7 3	3.0L TDI and Q5 3.0L TDI only)
Crash Active Headrest – check function every 2 years regardless of miles/kilometers (A8 only)			
Haldex Clutch – change oil every 3 years regardless of mileage/kilometers (A3, Q3, TT and TTS only)			
*Does not include 2.0L TFSI Flex Fuel engines.			

\*\*If DPF replacement is not necessary, perform check every 20,000 miles (30,000 km) thereafter until replacement becomes necessary. Subsequent DPF replacement interval is a minimum of 120,000 miles (195,000 km) thereafter.

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.