

Routan Perfect Delivery Inspection (PDI) - Technician and Detailer Inspections

Stock No.:	Dealer Number:	R.O. No.:
VIN:		
Technician Inspection		
Initial Inspection (A workshop maintainer/charger mu ☐ Check hood latch and safety catch	st be used):	☐ Check third row operation of folding seat power / manual
☐ Install ignition off-draw fuse		Check doors / exterior locks
☐ Test and auto charge battery with INC-940 using the "48 Hou	r Check" test.	☐ Install Warranty and Maintenance Booklet
Record Midtronics test code		□ Install California Emissions Warranty Booklet □ Install Applicable Tire Warranty Brochure
□ Install front license plate bracket if required		□ Verify child safety lock is set to unlocked position
□ Check engine coolant level (engine off/cold). Do not exceed m	nax fill line (Use	☐ Check proper fuel door operation
only OAT specified coolant MY 2013-2014)	CH. Is	☐ Check proper tailgate operation using the remote and the exterior button
□ Check brake and power steering fluid levels. Do not exceed medical Top-off windshield washer solvent (p/n G 052164M1)	ax till line	\square Place tow hook and wheel lock adapter in tool kit. Discard 2nd tow hook (if
□ Check engine oil level		applicable)
 Adjust tire pressure to specifications on vehicle sticker at "B" Pi 	llar and torque	□ Install rear tow hook cover (if applicable) □ Raise vehicle and perform a visual inspection for leaks and/or under body
wheels to specification. (Do not set until day before delivery)	·	damage
□ Retrieve radio code from ElsaWeb and check for any open Cai	mpaigns and	Remove suspension blocks located in the suspensions coil springs (If
RVUs. Perform if applicable		applicable)
□ Verify vehicle is equipped with spare tire		
Make sure hands and clothing are clean before enteri	na the vehicle	Road Test:
☐ Disable vehicle transport mode	ng me vermee	□ Odometer reading before road test: after:
Check all instrument cluster warning lights by cycling the ignitic	on from off to on	☐ Check engine performance and acceleration
\square Check that all keys and remotes lock, unlock, and start vehicle		☐ Store current tire pressure values for TPMS by pressing the SET button in the
□ Check operation of all exterior lights using a mirror or another	technician	glove box for a minimum of 2 seconds or setting in MFI if applicable
☐ Check front windshield wiper/washer functions		Check all menu settings in cluster for correct compass zone and unit -
☐ Check function of tilt and telescopic features of steering wheel		calibration (if applicable) Check automatic transmission operation, including automatic shift lock and
□ Set clock, date, and year (if applicable) □ Reset inspection/oil service interval		Tiptronic®
□ Verify language and units of measurement (F°) in multi-function	n display and	☐ Check brake system function (including ABS)/Electronic parking brake
Navigation system (if applicable)	r diopidy diffd	operation – engage and disengage
□ Verify radio operates in AM, FM, CD, MP3 and Satellite Radio	modes using	\square Check steering for pulling, vibration and steering wheel alignment
applicable radio buttons and steering wheel controls		☐ Check climate control for mode functions (Defrost/Vent/Floor), air conditioning
\square Set memory preset stations to AM and FM stations with good re	eception quality	operation and heater operation
by using the scan feature	D.	
Check function of all power windows (including sunroof if equi One-Touch feature, and check function of pinch protection fea		After Road Test:
☐ Check seat belts, seat adjusters, heated seats (if applicable)	iore	☐ Verify no warning lights are illuminated
☐ Install Start/Stop button (found in the By-Pack in the third row s	eat area) in the	Retrieve fault memory, correct any DTC's, set readiness code (if necessary).
ignition switch. (Routan SEL only)	,	Save and attach printout to Repair Order
□ Verify jack is installed		
☐ Check power sliding doors		
Remove contents of Trailer Tow Package from factory bag disp	lavina MC)PAR®	

I certify that all operations have been completed and that this vehicle has been prepared in accordance with Volkswagen procedures and quality standards.

□ All product updates have been checked □ Dealer 30-day maintenance process has been initiated

Dealership Authorized Signature:

department. (Routan with Trailer Tow Package only)

logo, discard factory bag, place contents into new bag received from parts

Detailer Process

Exterior:	
☐ Remove RAPGARD protective covering (best removed 60°-80F°)	Interior:
☐ Wash/dry vehicle exterior (convertibles: do not use high pressure washer above door sills or above rear window seals)	☐ Clean all glass, mirrors, and sunroof (if applicable)☐ Remove all trim protection, coverings, stickers, and decals - Do not remove
☐ Check for water leaks	airbag warning triangle/warning labels
☐ Clean alloy wheels/tires, remove any adhesive on wheels	☐ Check upholstery and clean as required
□ Inspect paint surfaces, moldings and glass. Remove any adhesive, tar, or residue. If any defects (scratches/dings/dents/body damage) are found, contact Service Manager to schedule immediate repair.	 □ Check for excessive grease on seat tracks and clean as required □ Check all interior surfaces and compartments (including sun visors and headliner) and clean as required
□ Wax vehicle using 3M Perfect-It [™] Paste Wax or equivalent	☐ Vacuum carpet
☐ Clean all glass and mirrors using 3M Gloss enhancer, cleaner clay or equivalent	☐ Check luggage compartment and vacuum
☐ Wipe door jambs	☐ Install front/rear floor mats (including locking clip / tabs), check color match. If monster mats are installed, please put factory mats in trunk.
Hadaa Haada	

I certify that all operations have been completed and that this vehicle has bee	n prepared in accordance with Volkswagen procedures and quality standards. □ Dealer 30-day maintenance process has been initiated
Dealership Authorized Signature:	Date:

Original – Retain with Repair Order in Service File

 $\hfill\square$ Wipe down engine compartment (no high pressure wash). Stay clear of HV components on Hybrids.

VW.ROUTAN.PDITECHCHECK. 06.13.2013