<b>ΑΤΟΥΟΤ ()</b>		MRY/CAMRY HV		
2014 PRE-DELIVER	Y SE	RVICE CHECK SHEET	August	t 2013
INSPECTION	DK djust/ epair	UNDER VEHICLE (ON HOIST)	N N	djust/ epair

BEFORE INSPECTION	ок	Adjust/ Repair	UNDER VEHICLE (ON HOIST)	OK Adjust/ Repair				
<ul> <li>O1 Install Short Pin* (Hawaii, Puerto Rico, Saipan, Guam, American Samoa)</li> <li>FUNCTIONAL OPERATION</li> <li>Apply parking brake and cycle ignition "IG-ON"; place gear selector in reve turn on lights and rear defogger. Unlock doors; release fuel door.</li> </ul>	erse;		<ul> <li>01 Remove disc brake anti-rust covers/anti-corrosion wheel film*</li> <li>02 Inspect tires for defects/damage</li> <li>03 Verify Tire Pressure Warning System (TPWS) operation (see page 2)</li> <li>04 Install wheel covers/caps/spare tire wheel covers*</li> <li>05 Check hybrid transmission fluid level*</li> </ul>					
<ul> <li>01 Check dome, courtesy, map, and sun visor lights*</li> <li>02 Check warning/indicator lights, gauges, and horn</li> <li>03 Check windshield wipers and washers</li> <li>04 Check headlights, instrument lights, turn signals, emergency flashers, and brake lights</li></ul>			<ul> <li>06 Inspect for fuel, oil, coolant, and other fluid leaks</li></ul>					
<ul> <li>7 Check audio/navigation*/backup camera* systems and set clock</li></ul>			ROAD TEST         A complete road test helps assure customer satisfaction. Drive vehicle ov variety of road surfaces and driving conditions. Check for unusual noise and driving performance.         Enter Odometer Readings         Reading Before Test:					
WALKAROUND INSPECTION Start at left front door. Check window and door lock operation (from mast switch, if equipped). Continue around vehicle in a counterclockwise checking each door and window operation, child door locks, seat belts condition, all lights, luggage compartment contents. Finish by checking h	direc , inte	tion erior	<ul> <li>01 Check cold engine operation</li> <li>02 Check engine operation during warm-up</li> <li>03 Check engine at normal operating temperature</li> <li>04 Check transmission operation</li> <li>05 Check brake and parking brake operation</li> </ul>					
<ul> <li>aim and continue into UNDER HOOD checks.</li> <li>01 Check Smart Key System</li> <li>02 Check door and door lock operation, including each wireless remote control/theft deterrent system*</li> <li>03 Check window operation.</li> <li>04 Check that engine starts with all keys</li> <li>05 Check that child safety door locks are in normal (unlocked) position</li> </ul>			<ul> <li>06 Check steering operation &amp; off-center/vehicle pull/flutter.</li> <li>07 Inspect for abnormal noise and vibration</li></ul>					
<ul> <li>06 Check seats and seat belt operation</li> <li>07 Check rear defogger/rear view mirror defogger*</li> <li>08 Check side marker, tail, backup, and license plate lights</li> <li>09 Check luggage compartment light* and trim appearance</li> <li>10 Adjust spare tire pressure, inspect for damage, and check jack and tool installation</li></ul>			FINAL INSPECTION AND CLEANING 01 Remove interior protective covers, unnecessary labels, tags, etc. (Remove just before delivery to customer) 02 Visually inspect all interior parts for installation, damage, fit, dirt, etc					
UNDER HOOD	<b>—</b>		retaining clips*	00				
01 Check engine oil level         02 Check brake fluid level         03 Check engine coolant level         04 Check inverter coolant level*         05 Check windshield washer fluid level         06 Check battery state-of-charge using Digital Battery         System Analyzer (SOC Reading:%)         07 Inspect for fuel, oil, coolant, and other fluid leaks         BATTERY MAINTENANCE*         01 Perform HV battery check and maintenance			<ul> <li>04 Verify green light is illuminated on SOS (Safety Connect) button*</li> <li>05 Remove Rapgard<sup>™</sup> and clear protective bumper film*</li> <li>06 Wash and clean vehicle</li></ul>					
* Inspect or install when equipped/required.			12 Install front license plate & mounting bracket* (see page 2)					
Completion and retention of this from is required to comply with Toyota's Warranty Policy. We hereby certify that all items								

TECHNICIAN'S SIGNATURE

Date

SERVICE MANAGER'S SIGNATURE

on this form have been checked and corrected for proper operation as required.

NAME (PLEASE PRINT)		NAME (PLEASE PRINT)		
Date	Dealer Name		Dealer Cod	

# TPWS OPERATION VERIFICATION

- 1. Connect Techstream to DLC3.
- 2. Adjust all tires (except the spare tire) to the standard tire inflation pressure, as indicated on the tire and loading information label on the vehicle.

### NOTE

To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using Techstream and select the Compensation Tire Pressure" checkbox. Compensation pressures will be displayed on the Health Check results screen. Adjust the tire pressure when the tires are cold.

- Cycle the ignition switch to the "IG-ON" mode. 3.
- 4. Check the tire pressure of all tires using Techstream. If the tire pressure values cannot be displayed, the system is NOT operating properly. Refer to the Repair Manual.

## FRONT WHEEL OPENING EXTENSION PAD INSTALLATION


The front wheel opening extension pad set (right and left front wheel opening extension pads and 2 tapping screws) is loaded in the luggage compartment at the assembly plant to avoid damage in transit.


- 1. Remove the 2 tapping screws form the engine under cover (the screws will be reused for installation).
- 2. Place the left front wheel opening extension pad on the installation position as shown and tighten the 3 tapping screws.

### NOTE

- There is a distinguishable mark on each pad.
- Do not interchange the tapping screws A and B.
- 3. Repeat steps 1 and 2 for the right side.

**Tapping Screws A:** Nominal Length: 23.0 mm (0.91 in.) Diameter: 6.0 mm (0.24 in.) Washer Outside Diameter: 18.0 mm (0.71 in.) Washer Outside Diameter: 20.0 mm (0.79 in.)





## COMPASS CALIBRATION

Refer to the Repair Manual for the Calibration procedure (Camry / Camry HV) for vehicles equipped with a compass in the rear view mirror.

## NOTE

 Do NOT perform calibration of the compass in a place where the Earth's magnetic field is subject to interference (underground parking, under a steel tower, between buildings, roof parking, near a railroad crossing, near a large vehicle, etc.).

**Tapping Screws B:** 

During calibration, do NOT operate electric systems (moon roof, power windows, etc.) as they may interfere with the calibration.

# FRONT LICENSE PLATE & MOUNTING BRACKET\* INSTALLATION

\*There are two types of brackets. Type A (P/N 52114-06160) for Base, LE and XLE models. Type B (P/N 52114-06170) for SE models. Air Intake Installation Procedure

- 1. Insert the front license plate into the mounting bracket.
- 2. Align the center tab on the mounting bracket with the centerline of the air intake.
- 3. Type A (Base, LE, XLE) P/N 52114-06160 Attach the hooks of the mounting bracket to the second air intake opening and rotate the bracket upwards. Type B (SE) - P/N 52114-06170 Attach the hooks of the mounting bracket to the second air

intake opening and rotate the bracket upwards.

- 4. Align the installation holes on the mounting bracket and front license plate with the dimples on the front bumper.
- 5. Screw in the 2 self-tapping screws directly into the dimples to install the front license plate and mounting bracket.

## NOTICE

- Do NOT pre-drill holes into the bumper.
- Do NOT overtighten the self-tapping screws.



- Hooks 3 Front License Plate
- Mounting Bracket
- 4 Tab 5 Rotate Bracket
- Dimples
- Front License Plate Mounting Bracket
- 3 License Plate
- 4 Self-tapping Screws