TOYOTA VENZA 2014 PRE-DELIVERY SERVICE CHECK SHEET

			July 2013			
BEFORE INSPECTION	OK Adjust/ Repair	UNDER VEHICLE (ON HOIST)	OK Adjust/ Repair			
01 Install antenna		01 Remove disc brake anti-rust covers/anti-corrosion				
FUNCTIONAL OPERATION Apply parking brake and cycle ignition "IG-ON"; place gear selector in reverse;		02 Inspect tires for defects/damage				
 turn on lights and rear defogger. Unlock doors; release fuel door. 01 Check dome, courtesy, map, and sun visor lights* 02 Check warning/indicator lights, gauges, and horn 03 Check windshield wipers and washers 04 Check headlights, instrument lights, turn signals, emergency flashers, and brake lights 05 Check inside/outside rear view mirror operation/ adjustment		 page 2) 04 Install wheel covers/caps/spare tire wheel covers* 05 Inspect for fuel, oil, coolant, and other fluid leaks 06 Inspect under the vehicle for damage, rust, etc. 07 Visually check bolts and nuts on chassis and powertrain for looseness. 08 Install rubber body plugs* (stored in glove box or center console). 				
 07 Check audio/navigation*/backup camera* systems and set clock		A complete road test helps assure customer satisfaction. Drive vehicle ov variety of road surfaces and driving conditions. Check for unusual noise and driving performance. Enter Odometer Readings Reading Before Test: Reading After Test:				
10 Install shift-lock override button cover 11 Check Rear Seat Entertainment System operation* WALKAROUND INSPECTION		01 Check cold engine operation 02 Check engine operation during warm-up				
Start at left front door. Check window and door lock operation (from mast switch, if equipped). Continue around vehicle in a counterclockwise checking each door and window operation, child door locks, seat belts condition, all lights, luggage compartment contents. Finish by checking h aim and continue into UNDER HOOD checks. 01 Check Smart Key System*	direction s, interior headlight	 03 Check engine at normal operating temperature 04 Check automatic transmission operation 05 Check brake and parking brake operation 06 Check steering operation & off-center/vehicle pull/flutter 07 Inspect for abnormal noise and vibration 08 Inspect for squeaks and rattles 09 Check front and rear* heater and A/C operation 10 Check cruise control operation*				
03 Check window operation04 Check that engine starts with all keys05 Check that child safety door locks are in normal		FINAL INSPECTION AND CLEANING				
 (unlocked) position		 01 Remove interior protective covers, unnecessary labels, tags, etc. (Remove just before delivery to customer) 02 Visually inspect all interior parts for installation, damage, fit, dirt, etc				
UNDER HOOD		07 Inspect exterior body parts for proper installation, damage, rust, etc				
01 Check engine oil level 02 Check brake fluid level 03 Check engine coolant level 04 Check windshield washer fluid level 05 Check battery state-of-charge using Digital Battery System Analyzer (SOC Reading:%) 06 Inspect for fuel, oil, coolant, and other fluid leaks		 08 Place oil change sticker on inside of windshield, top left corner 09 Place Owner's Guide & first aid kit portfolio* in glove box 10 Perform Techstream Health Check 11 Install front license plate and mounting bracket* (see page 2) * Inspect or install when equipped/required. 				
Completion and retention of this from is required to comply with Toyota's Warranty Policy.						
TECHNICIAN'S SIGNATURE SERVICE MANAGER'S SIGNATURE We hereby certify that all items on this form have been checked and corrected for proper operation as required.						

NAME (PLEASE PRINT)		NAME (PLEASE	PRINT)	
Date	Dealer Name		Dealer Code	Vehicle Identification Number (Sticker)

TPWS VERIFICATION

- 1. Connect Techstream to DLC3.
- 2. Adjust all tires (except the spare tire) to the standard tire inflation pressure, as indicated on the tire and loading information label on the vehicle.
- 3. Cycle the ignition switch to the "IG-ON" mode.

NOTE

To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using Techstream and select the "Compensation Tire Pressure" checkbox. Compensation pressures will be displayed on the Health Check results screen. Adjust the tire pressure when the tires are cold.

- 4. Check the tire pressure of all tires using Techstream. If the tire pressure values cannot be displayed, the system is not operating properly. Refer to the Repair Manual.
- 5. Remove the ID number labels that are attached to each wheel and discard.

NOTE

If the tire pressure values are not properly displayed (example: showing -14 psi, -100 kPa, etc.) the data from the transmitter has not been received.

COMPASS CALIBRATION

Refer to the Repair Manual for the Calibration procedure for vehicles equipped with a compass in the rear view mirror.

NOTE

- Do NOT perform calibration of the compass in a place where the Earth's magnetic field is subject to interference (underground parking, under a steel tower, between buildings, roof parking, near a railroad crossing, near a large vehicle, etc.).
- During calibration, do NOT operate electric systems (moon roof, power windows, etc.) as they may interfere with the calibration.


FRONT LICENSE PLATE AND MOUNTING BRACKET INSTALLATION*

Front License Plate Bracket: P/N 75101-0T010

- 1. Insert the front license plate into the mounting bracket.
- 2. Align the installation holes on the mounting bracket and front license plate with the dimples on the front bumper.
- 3. Screw in the 2 self-tapping screws directly into the dimples to install the front license plate and mounting bracket.

NOTICE

- Do NOT pre-drill holes into the bumper.
- Do NOT overtighten the self-tapping screws.



- 2 Front License Plate Mounting Bracket
- 3 License Plate
- 4 Self-Tapping Screws