

Front Brake Squeak Noise

Service

Category Brake

Section Brake (front)

Market USA



Applicability

YEAR(S)	MODEL(S)	ADDITIONAL INFORMATION
2010 – 2013	GX460	

Introduction

Some 2010 – 2013 model year GX 460 vehicles may exhibit a front brake squeak noise when coming to a stop from 10 – 0 mph. A new front brake rotor has been made available to address this condition.

Production Change Information

This bulletin applies to vehicles produced **BEFORE** the Production Change Effective VIN shown below.

MODEL	PLANT	PRODUCTION CHANGE EFFECTIVE VIN
GX 460	Tahara	JTJBM7FX#D5050223

Warranty Information

OP CODE	DESCRIPTION	TIME	OFP	T1	T2
473011	R & R Front Disc (One Side) (includes Replacing Pad*)	0.5	43512-60190	36	13
Combo A	R & R Opposite Side, Front Disc	0.2			

^{*} Replace pad only when pad wear is identified. Pad replacement will NOT be covered under warranty.

APPLICABLE WARRANTY

- This repair is covered under the Lexus Comprehensive Warranty. This warranty is in effect for 48 months or 50,000 miles, whichever occurs first, from the vehicle's in-service date.
- Warranty application is limited to occurrence of the specified condition described in this bulletin.

Parts Information

PREVIOUS PART NUMBER	CURRENT PART NUMBER	PART NAME	QTY
43512-60190	43512-60200	Disc, Front	2

L-SB-0015-13 March 13, 2013 Page 2 of 2

Front Brake Squeak Noise

Repair Procedure

- 1. Test drive the vehicle to confirm that the noise is coming from the front brakes.
- 2. Remove and replace the front brake rotors.

NOTE

Please do NOT apply any grease to the pads or shims.

Refer to the Technical Information System (TIS), applicable model and model year Repair Manual:

- 2010 GX 460: Brake – Brake (Front) – "Brake (Front): Front Brake: <u>Removal / Installation</u>"
- 2011 GX 460: Brake – Brake (Front) – "Brake (Front): Front Brake: <u>Removal</u> / <u>Installation</u>"
- 2012 GX 460: Brake – Brake (Front) – "Brake (Front): Front Brake: Removal / Installation"
- 2013 GX 460: Brake – Brake (Front) – "Brake (Front): Front Brake: Removal / Installation"
- 3. Road test the vehicle to confirm repair.